

Potentiometric Surface Map of the Bedrock Aquifers of Huntington County, Indiana

by
Robert K. Schmidt
Division of Water, Resource Assessment Section
May 2013

Huntington County, Indiana is located in the northeastern section of the state and lies within the Upper Wabash River Basin.

The Potentiometric Surface Map (PSM) of the bedrock aquifers of Huntington County was mapped by contouring the elevations of approximately 1040 static water-levels reported on well records received primarily over a 50 year period. These wells are completed in aquifers at various depths, and typically, under confined conditions (bounded by impermeable layers above and below the water bearing formation). However, some wells were completed under unconfined (not bounded by impermeable layers) settings. The potentiometric surface is a measure of the pressure on water in a water bearing formation. Water in an unconfined aquifer is at atmospheric pressure and will not rise in a well above the top of the water bearing formation, in contrast to water in a confined aquifer which is under hydrostatic pressure and will rise in a well above the top of the water bearing formation. The potentiometric contour lines crossing through Salamonie Lake, and J. E. Roush Lake, represent the potentiometric surface of the groundwater in the immediate area, not the water level of the reservoirs, which are man-made features.

Static water-level measurements in individual wells used to construct county PSM's are indicative of the water-level at the time of well completion. The groundwater level within an aquifer constantly fluctuates in response to rainfall, evapotranspiration, groundwater movement and pumpage. Therefore, measured static water-levels in an area may differ due to local or seasonal variations. Because fluctuations in groundwater are typically small, static water-levels can be used to construct a generalized PSM. As a general rule, but certainly not always, groundwater flow approximates the overlying topography and intersects the land surface at major streams.

Universal Transverse Mercator (UTM) coordinates for the water wells were either physically obtained in the field, determined through address geocoding, or reported on water well records; however, the location of the majority of the water well records used to make the PSM were not field verified. Elevation data were either obtained from topographic maps or a digital elevation model. Quality control/quality assurance procedures were utilized to refine or remove data where errors were readily apparent.

Bedrock static water levels in Huntington County range from a high of 829 feet mean sea level (msl) in the southeastern section of the county, to a low of 640 feet msl in the central portion along the Wabash River. Groundwater flow direction in the northern portion of the county is generally to the south toward the Wabash River, and to the north-northwest toward the Wabash River in the southern portion of the county.

The county PSM can be used to define the regional groundwater flow path and to identify significant areas of groundwater recharge and discharge. County PSM's represent overall regional characteristics and are not intended to be a substitute for site-specific studies.