State of Indiana <u>Department of Natural Resources</u> Division of Water

Control Station Descriptions and Elevations

FULTON COUNTY

The staff of the Department of Natural Resources, Division of Water, has developed the layout, surveys, adjustments, and publications of the following second-order area levels. All field survey records and publication procedures in the process of development of this list may be examined at the office of the Department in Indianapolis, Indiana. Requests for specific information pertaining to the surveys in this county, or others in the State, are accepted as a public service.

Fulton County Index of Benchmarks

Station	THIRD	783.102	Elevation	Elevation	28
	THIRD	ORDER	Meters	Feet	28
	THIRD	784.492	NGVD '29	NGVD '29	28
	THIRD	810.899			28
DNR TBM 1-01788	238.690	768.879	237.321	778.61	1
DNR TBM 2-01788	THIRD	destroyed	242.234	794.73	28
DNR TBM 3-01788	239.114	764.846	238.973	784.03	1
DNR TBM 4-01788	247.162	771.629	241.652	792.82	1
DNR TBM 5-01788	234.355	770.701	238.813	783.506	2
DNR TBM 6-01788	destroyed	780.371	239.159	784.64	2
DNR TBM 7-01788	233.126	767.437	239.237	784.896	2
DNR TBM FULCO 1	235.193	766.115	247.299	811.347	3
DNR TBM FULCO 2	234.910		234.501	769.359	3
DNR TBM FULCO 3	237.858	738.304	destroyed	destroyed	3
DNR TBM FULCO 4	233.915	747.624	233.250	765.253	4
DNR TBM FULCO 5	233.512	737.436	235.317	772.035	4
DNR TBM FULCO 6		741.840	235.033	771.104	25
DNR TBM FULCO 7	225.035	741.504	238.005	780.855	26
DNR TBM FULCO 8	227.876	760.587	234.058	767.905	5
DNR TBM FULCO 9	224.771	739.014	233.636	766.520	5
DNR TBM FLK 1	226.113	741.014	242.089	794.253	5
DNR TBM FLK 10	226.011	754.685	225.157	738.703	6
DNR TBM FLK 11	231.827	756.997	227.997	748.022	6
DNR TBM FLK 12	225.252	787.130	224.892	737.835	6
DNR TBM FLK 15	225.870	758.056	226.235	742.241	7
DNR TBM FLK 16	230.029	794.982	226.133	741.905	7
DNR TBM FLK 17	230.733	758.027	231.950	760.989	7
DNR TBM FLK 18	239.918	765.321	225.376	739.422	8
DNR TBM FLK 19	231.056	759.833	225.994	741.449	8
DNR TBM FLK 20	242.311	769.995	230.153	755.093	8
DNR TBM FLK 21	231.047	767.673	230.857	757.405	9
DNR TBM FLK 22	233.270	767.138	240.042	787.537	9
DNR TBM FLK 23	231.598	768.621	231.179	758.461	9
DNR TBM FLK 24	234.695	791.114	242.434	795.386	10
DNR TBM FLK 25	233.987	834.035	231.172	758.436	10
DNR TBM FLK 26	233.824		233.395	765.729	10
DNR TBM FLK 27A	234.276	751.505	231.722	760.240	11
DNR TBM FLK 28	241.132	770.791	234.836	770.458	11
DNR TBM FLK 29	254.214	767.527	234.134	768.155	11
DNR TBM FLK 30			233.977	767.640	24
DNR TBM FLK 31	229.059	730.933	234.425	769.109	12
DNR TBM FLK 33	234.938	728.955	241.255	791.517	12
DNR TBM FLK 34	233.943		254.337	834.438	12
DNR TBM PLK 2			225.390	739.466	24
DNR TBM MILL #1	222.789		229.183	751.910	12
DNR TBM MILL #2	222.186		235.060	771.193	13
DNR TBM MILL #3	Elevation		234.65	767.928	
DNR BM FUL 1	Feet		242.697	796.247	
DNR BM FUL 10	NAVD '88		222.910	731.331	
DNR BM FUL 11			222.307	729.353	
Elevation	ORDER				
Meters	ORDER			Page	
NAVD '88	ORDER				
	ORDER				

DNR BM FUL 14	233.405	737.353	225.352	739.342	15
DNR BM FUL 16	234.466	755.896	224.997	738.178	15
DNR BM FUL 17	233.772	754.585	225.170	738.746	16
DNR BM FUL 20	242.478	772.505	231.840	760.628	16
DNR BM FUL 21	238.489	744.633	230.275	755.493	16
DNR BM FUL 24	782.584	761.122	233.534	766.186	17
DNR BM FUL 26	233.989	732.054	234.612	769.723	17
DNR BM FUL 27	224.746	778.658	233.924	767.466	17
DNR BM FUL 30	230.397	758.561	242.601	795.934	18
DNR BM FUL 32	229.998	812.925	238.612	782.847	18
DNR BM FUL 33	235.460	804.429	237.706	779.875	18
DOT BM FUL L152	226.965	810.979	234.112	768.083	19
DOT BM FUL L211	231.990	740.294	224.867	737.751	19
DOT BM FUL L465	223.130	778.899	230.521	756.301	19
DOT BM L551 FUL	237.335	789.346	230.122	754.992	23
DOT BM FULT L564	231.210	786.157	235.601	772.968	20
DOT BM L582 FULTON	247.780	759.218	227.088	745.038	25
DOT BM FULTON L590	unstable	765.317	232.115	761.531	26
DOT BM FULTON L606	247.188	806.8	223.252	732.453	26
IDOH BM FULTON L701	225.642	804.94	237.457	779.058	20
USC&GS BM E134	237.409	801.335	231.330	758.955	20
USC&GS BM E144	240.593	771.055	247.899	813.315	21
USC&GS BM K176	239.621	736.511	DNR Elev.	804.823	21
USC&GS BM L176	231.410	805.210	247.307	811.373	21
USC&GS BM R176	233.269	779.374	225.765	740.697	24
USC&GS BM Z176	245.91		237.531	779.300	25
USC&GS BM C177	245.347		240.715	789.746	22
USC&GS BM D177	244.247		239.744	786.560	22
USC&GS BM C179	235.018		231.535	759.628	22
USC&GS BM D179	224.489		233.394	765.727	23
USC&GS BM W180 Reset	245.429		246.032	807.191	23
USC&GS BM X180	237.554		245.467	805.336	
USC&GS KELSER			244.371	801.739	
USC&GS TIOSA AZI			235.166	771.540	
USCOE BM Not Stamped			224.611	736.912	
USGS BM			245.552	805.614	
Gaging Station			237.676	779.775	

Note: DNR BM's FUL		
12,13,15,18,19,22,23,25,28,		
29, and 31 were not set.	738.941	
DNR TBM's FLK 13, 14, &	737.775	
32 were set in Marshall	738.343	
County and are published	760.221	
in the D.N.R Marshall	775.087	
County BM Publication.	765.764	
225.230	769.245	13
224.874	766.966	13
225.047	795.531	14
231.716	782.443	14
230.151	779.474	14
	767.680	15

State of Indiana

Department of Natural Resources Division of Water

Control Station Descriptions and Elevations

Fulton County

The staff of the D.N.R. Division of Water has developed the following benchmark descriptions and elevations. Second Order Class II Level lines were incorporated into a Star Lev network adjustment incorporating the level lines from both the Tippecanoe River Ora to Monterey flood plain mapping project and the level lines from the Fulton County Levels project.

INDIANA DEPARTMENT OF NATURAL RESOURCES DIVISION OF WATER

FULTON COUNTY

DNR TBM 5-01788

In Fulton County, Rochester Quad., in the NW ¼ of Sec. 23, T. 30 N., R. 3 E., 2nd PM; approximately 2.0 miles southeast of <u>Rochester</u>; at the intersection of Country Club Road and 400 East Road (Bassmore Road); set in the north side of a 15.0 inch Oak tree, 71.8 feet west of a metal "Yield" sign post, 39.2 feet south of and across the road from a metal "Country Club Road & 400 East Road" sign post, 17.0 feet south of the center line of Country Club Road; a railroad spike driven thru an aluminum tag, stamped "IDNR TBM 5-01788".

783.102 feet NAVD 1988 238.690 meters NAVD 1988 783.506 feet NGVD 1929 238.813 meters NGVD 1929

DNR TBM 7-01788

In Fulton County, Rochester Quad., in the NW ¼ of Sec-14, T.30 N., R.3 E., 2nd PM; approximately 2.5 miles southeast of <u>Rochester</u>; set in the north side of a 24 inch Oak tree that stands alone in the public fishing site, 172.0 feet southeast of the gaging station at the public boat ramp, 123.0 feet north of the centerline of Country Club Drive, 105.8 feet northwest of the northwest corner of a brick building, 32.0 feet south of the top of bank, 1.0 foot above the ground; a railroad spike driven thru an aluminum tag, stamped "IDNR TBM 7-01788".

784.492 feet NAVD 1988 239.114 meters NAVD 1988 784.896 feet NGVD 1929 239.237 meters NGVD 1929

DNR TBM FULCO 1, 1993

In Fulton County, Argos Quad., in the NE ¼ of Sec. 1, T. 31 N., R.3 E., 2nd PM; about 0.6 miles north of <u>Talma</u>; approximately 0.4 mile south along 550 East Road from its intersection with State Road 110 (Fulton-Marshall County Line Road.) to a private drive to the east; set in the west side of power pole #292-457 with a transformer, 83.1 feet south of a steel railroad rail post painted white, 33.3 feet north of the centerline of the private drive (7577 N. 550 E.), 29.8 feet west of a 20.0 inch Sycamore tree, 21.3 feet northwest of a metal flag pole, 12.1 feet east of the centerline of 550 East Road, 1.6 feet above the ground; a railroad spike driven thru an aluminum tag, stamped "FULCO 1, 1993".

810.899 feet NAVD 1988 247.162 meters NAVD 1988 811.347 feet NGVD 1929 247.299 meters NGVD 1929

DNR TBM FULCO 2, 1993

In Fulton County, Argos Quad., in the NE ¼ of Sec. 14, T.31 N., R 3 E., 2nd PM; about 1.3 miles southeast of <u>Talma</u>; at the State Road 25 bridge over an unnamed tributary to the Tippecanoe River; set in the top of the west concrete wingwall of the bridge, 20.8 feet northwest of the centerline of the bridge, 0.9 foot northwest of the northwest face of the concrete handrail of the bridge, 0.7 foot southwest of the north face of the wingwall of the bridge, about level with the road; a chiseled triangle.

768.879 feet NAVD 1988 234.355 meters NAVD 1988 769.359 feet NGVD 1929 234.501 meters NGVD 1929

DNR TBM FULCO 3, 1993

In Fulton County, Rochester Quad., in the East ½ of Sec. 36, T. 31 N., R. 3 E., 2nd PM; approximately 1.3 miles northwest of Rochester; at the "T" road intersection of Oilstone Road and Meridian Road, approximately 300 feet west of the intersection of U.S. 31 and Oilstone Rd.; set in the south side of power pole #CAN, 49.8 feet north of the center line of Oilstone Road, 41.2 feet northwest of a metal "Buckeye Pipeline" sign post, 4.7 feet west of the metal end post of a north-south fence line, 6.5 feet west of the extended centerline of Meridian Road, 1.9 feet above the ground; a railroad spike driven thru an aluminum tag, stamped "IDNR TBM FULCO 3, 1993".

DESTROYED

DNR TBM FULCO 4, 1993

In Fulton County, Pershing Quad., in the NW ¼ of Sec. 26, T. 31 N., R. 2 E., 2nd PM; about 1.5 miles southeast of <u>Anderson Lake</u>; at the "T" road intersection of 375 North Road and 200 West Road, in the northeast quadrant of the intersection; set in the west side of a power pole, 56.0 feet north of the centerline of 375 North Road, 10.5 feet southeast of a mailbox (J&W Johnson), 4.2 feet north-northwest of a metal fence post, 1.5 feet west of a fence line, 1.9 feet above the ground; a railroad spike driven thru an aluminum tag, stamped "INDR TBM FULCO 4, 1993".

764.846 feet NAVD 1988 233.126 feet NAVD 1988 765.253 feet NGVD 1929 233.250 meters NGVD 1929

DNR TBM FULCO 5, 1993

In Fulton County, Pershing Quad., in the SW ¼ of Sec. 22, T. 31 N., R.2 E., 2nd PM; approximately 0.7 mile southeast of <u>Anderson Lake</u>; approximately 0.45 mile west along 450 North Road from its intersection with 200 West Road to a white 1 and 1/2 story residence (#2707) on the south side of 450 North Road; set in the north side of a power pole, 66.5 feet west of the centerline of the private drive (#2707) to the south, 38.4 feet northwest of the northwest corner of the house(#2707), 15.0 feet south of the centerline of the road, 3.0 feet west of the wood mailbox post (#2707W.), 2.0 feet above the ground; a railroad spike driven thru an aluminum tag, stamped "INDR TBM FULCO 5, 1993".

771.629 feet NAVD 1988 235.193 meters NAVD 1988 772.035 feet NGVD 1929 235.317 meters NGVD 1929

DNR TBM FULCO 6, 1993

In Fulton County, Pershing Quad., near the SE. corner of Section 18, T.31 N., R. 2 E., 2nd PM; about 1.9 miles North West of <u>Pershing</u>; at the "T" road intersection of 475 North Road and 500 West Road; set in the southwest side of a power pole with transformer, 16.8 feet north of the centerline of 475 North Road; 51.0 feet northwest of a "stop" sign post, 45.9 feet northeast of road sign post, 46.6 feet west of west end of a stone wall on the north side of 475 West Road 3 feet west of the extended centerline of 500 West Road; 1.4 feet south of an east west fence line, 2.0 feet above the ground; a railroad spike driven thru an aluminum tag, stamped "IDNR TBM FULCO 6, 1993".

770.701 feet NAVD 1988 234.910 meters NAVD 1988 771.104 feet NGVD 1929 235.033 meters NGVD 1929

DNR TBM FULCO 7, 1993

In Fulton County, Argos Quad., in the NE ¼ of Sec. 21, T.31 N., R. 3 E., 2nd PM; approximately 1.7 miles south-southeast of <u>Tiosa</u>; at the intersection of 500 North Road and the Norfolk and Western railroad, in the southwest quarter of the intersection of the intersection; set in the northeast side of a utility pole, 95.0 feet southwest of the centerline of the railroad and the centerline of 500 North Road, 15.5 feet south of the centerline of 500 North Road, 85.0 feet west of the railroad tracks, 1.5 feet north of a fence line, 1.5 feet above the ground; a railroad spike driven thru an aluminum tag, stamped "IDNR TBM FULCO 7, 1993".

780.371 feet NAVD 1988 237.858 meters NAVD 1988 780.855 feet NGVD 1929 238.005 meters NGVD 1929

DNR TBM FULCO 8, 1993

In Fulton County, Rochester Quad., in the SW ¼ of Sec. 21, T.31 N., R. 3 E., 2nd PM; approximately 2.7 miles north-northeast of <u>Rochester</u>; at the Norfolk and Western Railroad bridge over the Chippewanuck Creek; set in the top of the southwest concrete headwall of the bridge, 4.5 feet west of the west rail of the tracks, 0.8 foot south of the north face of the southwest headwall of the bridge, 0.9 foot north of the south face of the concrete headwall, 0.7 foot below the top of the rails of the tracks; a chiseled triangle.

767.437 feet NAVD 1988 233.915 meters NAVD 1988 767.905 feet NGVD 1929 234.058 meters NGVD 1929

DNR TBM FULCO 9, 1993

In Fulton County, Rochester Quad., in the Michigan Road Grant Number 30; approximately 1.0 mile north of <u>Rochester</u>; at the "T" road intersection of (Old US 31) Main Street and Olson Road, in the east quadrant of the intersection; set in the west side of power pole #827-3552, 47.0 feet east of the centerline of Old US 31, 33.5 feet southeast of the south metal "road direction" sign post, 29.5 feet south of the extended centerline of Olson Road, 3.0 feet below the level of Old US 31, 1.7 feet above the ground; a railroad spike driven thru an aluminum tag, stamped "INDR TBM FULCO 9, 1993".

766.115 feet NAVD 1988 233.512 meters NAVD 1988 766.520 feet NGVD 1929 233.512 meters NAVD 1929

DNR TBM FULCO 10, 1994

In Fulton County, Culver Quad., in the NE ¼ of Sec. 9, T.31 N., R. 1 E., 2nd PM; approximately 1.25 mile north of <u>Delong</u>; at the intersection of 700 North Road, in the southwest quarter of the intersection; set in the southwest side of power pole # BCF23 (power pole has a guy pole with a guy wire on the north side of 700 North Road), 125.7 feet west of the centerline of 900 East Road, 85.3 feet west of a metal "stop" sign post, 23.5 feet east of a P K nail 2.0 feet above the ground in the north side of a 8.0 inch pine tree (east most pine tree in a east-west line of pine and spruce trees), 18.0 feet south of the centerline of 700 North Road, 1.0 foot above the ground; a railroad spike driven thru an aluminum tag, stamped "IDNR TBM FULCO 10, 1994"

738.304 feet NAVD 1988 225.035 meters NAVD 1988 738.703 feet NGVD 1929 225.157 meters NGVD 1929

DNR TBM FLK 11, 1994

In Fulton County, Culver Quad., in the NE ¼ of Sec. 7, T. 31 N., R.1 E., 2nd PM; approximately 1.2 miles east-southeast of Monterey; at the "T" road intersection of 1100 West Road and Olson Road; set in the west side of a power pole with a guy wire, 98.0 feet southwest of and across the "T" road intersection from a white and orange plastic PVC buried fiber optic cable marker post, 64.5 feet south of a metal "Olson Rd & 1100 W" road sign post, 64.0 feet south of the extended centerline of Olson Road, 13.5 feet west of the centerline of 1100 West Road, 1.0 foot above the ground; a railroad spike driven thru an aluminum tag, stamped "IDNR TBM FLK 11, 1994".

747.624 feet NAVD 1988 227.876 meters NAVD 1988

748.022 feet NGVD 1929 227.997 meters NGVD 1929

DNR TBM FLK 12, 1994

In Fulton County, Culver Quad., in the NE ¼ of Sec. 8, T.31 N., R. 1 E., 2nd PM; approximately 1.1 miles northwest of <u>Delong</u>; approximately 0.3 mile south along State Road 17 from the State Road 17 bridge over the Tippecanoe River to Olson Road, thence 0.4 mile generally northwest to a bend in the road to the west, and the tbm on the north side of Olson Road; set in the south side of power pole #791-349 with a guy wire, 46.2 feet west of a metal satellite dish support post, 24.7 feet east of a white and orange plastic PVC buried fiber optic cable marker post, 17.0 feet north of the centerline of Olson Road, 10.2 feet west of the centerline of a gravel private drive to the north, 3.2 feet east-northeast of a green metal telephone junction box, 1.0 foot above the ground; a railroad spike driven thru an aluminum tag, stamped "IDNR TBM FLK 12, 1994"

737.436 feet NAVD 1988 224.771 meters NAVD 1988 737.835 feet NGVD 1929 224.892 meters NGVD 1929

DNR TBM FLK 15, 1994

In Fulton County, Culver Quad., in the SE ¼ of Sec. 10, T.31 N., R.1 E., 2nd PM; approximately 0.5 mile northeast of <u>Delong</u>; at the "T" road intersection of 850 West Road and 600 North Road; set in the south side of powerpole #BC 175, in the northwest quadrant of the intersection, 42.2 feet northeast of and across 600 North Road from a metal fence corner post that has two metal supports, 16.0 feet north of the centerline of 600 North Road, 7.3 feet west of the extended centerline of 850 West Road, 7.0 feet west of a metal (850 W. 600 N) road sign post, 1.6 feet east of a gray metal telephone junction box, 1.0 foot above the ground; a railroad spike driven thru an aluminum tag, stamped "IDNR TBM FLK 15, 1994"

741.840 feet NAVD 1988 226.113 meters NAVD 1988 742.241 feet NGVD 1929 226.235 meters NGVD 1929

DNR TBM FLK 16, 1994

In Fulton County, Culver Quad., in the NE ¼ of Sec. 23, T.31 N., R.1 E., 2nd PM; approximately 1.7 miles southeast of <u>Delong</u>; at the "T" road intersection of 500 North Road and 750 West Road, in the southeast quadrant of the intersection; set in the west side of a powerpole #229-520 with a transformer and guy wire, 130.0 feet south of the centerline at 500 North Road, 40.0 feet east of and across 750 West Road from a powerpole with a meter box, 34.5 feet south of a metal "stop" sign post, 20.5 feet east of the centerline of 750 West Road, 1.0 foot above the ground; a railroad spike driven thru an aluminum tag, stamped "IDNR TBM FLK 16, 1994"

741.504 feet NAVD 1988 226.011 meters NAVD 1988 741.905 feet NGVD 1929 226.133 meters NGVD 1929

DNR TBM FLK 17, 1994

In Fulton County, Rutland Quad., in the NW ¼ of Sec. 24, T.31 N., R.1 E., 2nd PM; approximately 3.1 miles west of Anderson Lake; approximately 0.25 mile east along 500 North Road from the "T" road intersection of 675 East Road and 500 North Road to power pole #BCF11 with a transformer and guy wire on the south side of 500 North Road at 6527 West 500 North; set in the north side of powerpole #BCF11, 105.0 feet east of the centerline of the private gravel drive to the south at 6527 West 500 North, 103.0 feet west powerpole #BCF10 with 3 transformers and 3 guy wires, 60.8 feet southwest of and across the road from a 1 and 1/2 foot square 5 feet tall concrete fence corner post with east-west concrete wings, 37.2 feet south of and across 500 North Road from a east-west fence line, 3.1 feet southwest of the guy wire anchor for powerpole #BCF11, 1.3 feet above the ground; a railroad spike driven thru an aluminum tag, stamped "IDNR TBM FLK 17, 1994"

760.587 feet NAVD 1988 231.827 meters NAVD 1988 760.989 feet NGVD 1929 231.950 meters NGVD 1929

DNR TBM FLK 18, 1994

In Fulton County, Pershing Quad., in the NE ¼ Sec. 27, T.31 N., R.2 E., 2nd PM; approximately 5 miles east of Leiters Ford; about 0.4 miles North along 275 West Road (Strawberry Lane) from the intersection of 275 West Road and Olson Road, at the residence at #3756 275 West Road; set in the south side of a power pole, 108.3 feet east of mailbox post at residence (#3756 275 West Road), 85 feet Northeast of the centerline of 275 West Road and the extend centerline of a two car gray garage at the above residence, 40.5 feet southeast of the southeast corner of a gray mini barn, 1.3 feet east of the east most white wooden fence post, 0.9 foot above the ground; a railroad spike driven thru an aluminum tag, stamped "IDNR TBM FLK 18, 1994".

739.014 feet NAVD 1988 225.252 meters NAVD 1988 739.422 feet NGVD 1929 225.376 meters NGVD 1929

DNR TBM FLK 19, 1994

In Fulton County, Pershing Quad., in the NE ¼ Sec. 27, T.31 N., R.2 E., 2nd PM; approximately 5 miles east of Leiters Ford; about 0.2 miles North along 275 West Road (Strawberry Lane) from the intersection of Olson Road and 275 West Road; at the beginning of where 275 West Road loops back on itself; set in the west side of a power pole with a transformer; 103.1 feet northeast of a speed limit sign (25 mph) post, 23.2 feet northerly of the "JC GLEVA" 3715 275 West Road mailbox post, 13 feet south of the centerline of a sand driveway, 35 feet east of the centerline of the north and south bound 275 West Road, 62 feet southwest of a light pole with a meter box, 1.2 feet above the ground; a railroad spike driven thru an aluminum tag stamped "IDNR TBM FLK 19, 1994"

741.041 feet NAVD 1988 225.870 meters NAVD 1988 741.446 feet NGVD 1929 225.994 meters NGVD 1929

DNR TBM FLK 20, 1994

In Fulton County, Pershing Quad., near the center of Sec. 27, T.31 N., R.2 E., 2nd PM; about 5.0 miles east of <u>Lieters Ford</u>; in the northeast ¼ of intersection of Olson Road and 275 West Road (Strawberry Lane); set in the south side of a power pole, 55.3 feet east of a "stop" sign post, 51.2 feet northeast of a street sign post, 40.8 feet north of a power pole, 33.5 feet east of the centerline of 275 West Road, 24.5 feet north of the centerline of Olson Road, 1.0 foot above ground; a railroad spike driven thru an aluminum tag, stamped "IDNR TBM FLK 20, 1994"

754.685 feet NAVD 1988 230.029 meters NAVD 1988 755.093 feet NGVD 1929 230.153 meters NGVD 1929

DNR TBM FLK 21, 1994

In Fulton County, Pershing Quad,. in the SW ¼ Sec. 27, T.31 N., R.2 E., 2nd PM; approximately 5.5 miles east of Leiters Ford; approximately 0.2 miles west along Olson Road from the intersection of 200 W. Road and Olson Road; set in the southerly side of a power pole 60.5 feet westerly of the southwest corner of the Robert Smith residence, 17.1 feet north of the centerline of Olson Road, 36.5 feet northwest of a fence corner post, 48.5 feet northerly from a telephone pole on the south side of Olson Road, 1.1 feet southerly from a fence line, 31.8 feet northwest of a telephone on the north side of Olson Road, 0.5 foot above the ground; a railroad spike driven thru an aluminum tag, stamped "IDNR TBM FLK 21, 1994"

756.997 feet NAVD 1988 230.733 meters NAVD 1988 757.405 feet NGVD 1929 230.857 meters NGVD 1929

DNR TBM FLK 22, 1994

In Fulton County, Pershing Quad., in the SW ¼ Sec. 23, T.31 N., R.2 E., 2nd PM; about 6 miles east of Leiters Ford; in the southeast 1/4 of the intersection of 450 North Road and 200 West Road; set in the west side of a power pole 59 feet south of the centerline of 450 North Road, 15 feet east of the centerline of 200 West Road, 4 feet east of a "stop" sign post, 24.5 feet north of the anchor bolt of the guy wire of a power pole, 1.4 feet west of a fence line, 1.0 foot above the ground; a railroad spike driven thru an aluminum tag, stamped "IDNR TBM FLK 22, 1994".

787.130 feet NAVD 1988 239.918 meters NAVD 1988 787.537 feet NGVD 1929 240.042 meters NGVD 1929

DNR TBM FLK 23, 1994

In Fulton County, Pershing Quad., in the SE ¼ of Sec. 21, T.31 N., R.2 E., 2nd PM; about 4.8 miles east of Leiters Ford; approximately 1.1 miles west along 450 North Road from the intersection of 200 West Road and 450 North Road, to a small white house with a green roof, on the south side of 450 North Road; set in the north side of a power pole with a transformer and a security light 17.5 feet south of the centerline of 450 North Road, 37.5 feet east of a mailbox post, 35.2 feet southerly of a guy pole, 18.4 feet east of the approximate centerline of a private gravel drive, 80.4 feet northeast of a 30 inch tree with a "posted" sign on it, 1.0 foot above the ground; a railroad spike driven thru an aluminum tag, stamped "IDNR TBM FLK 23, 1994"

758.056 feet NAVD 1988 231.056 meters NAVD 1988 758.461 feet NGVD 1929 231.179 meters NGVD 1929

DNR TBM FLK 24, 1994

In Fulton County, Pershing Quad., near the NW ¼ of Sec. 21, T.31 N., R.2 E., 2nd PM; about 4 miles east of Leiters Ford; at the intersection of 475 North Road and 400 West Road; set in the west side of a power pole, 82.2 feet east of a "stop" sign post, 70.5 feet northeast of the northern most vertical railroad track, 61.7 feet northeast of the southern-most vertical railroad track, 14.0 feet east of the centerline of 400 West Road, 4.1 feet north of a concrete fence post, 1.0 foot above the ground; a railroad spike driven thru an aluminum tag, stamped "IDNR TBM FLK 24, 1994"

794.982 feet NAVD 1988 242.311 meters NAVD 1988 795.386 feet NGVD 1929 242.434 meters NGVD 1929

DNR TBM FLK 25, 1994

In Fulton County, Pershing Quad., in the NW ¼ of Sec. 11, T. 30 N., R.2 E., 2nd PM; about 2.7 miles southeast of <u>Pershing</u>; in the southeast 1/4 of the intersection of 100 North Road and 200 West Road; set in the west side of a power pole, 77 feet southeasterly of the centerline centerline intersection of 200 West Road and 100 North Road, 76 feet south of the centerline of 100 North Road, 57 feet southeast of the northeast corner of a concrete fence post in the southwest 1/4 of intersection, 18 feet east of the centerline of 200 West Road, 7.0 feet southerly of "stop" sign post, 0.9 foot above the ground; a railroad spike driven thru an aluminum tag, stamped "IDNR TBM FLK 25, 1994"

758.027 feet NAVD 1988 231.047 meters NAVD 1988 758.436 feet NGVD 1929 231.172 meters NGVD 1929

DNR TBM FLK 26, 1994

In Fulton County, Pershing Quad., in the SW ¼ of Sec. 35, T. 31 N., R. 2 E., 2nd PM; about 2.1 miles east southeast of <u>Pershing</u>; in northeast 1/4 of the intersection of 200 North Road and 200 West Road; set in the west side of a power pole 89 feet northeast of the centerline/centerline intersection of 200 West Road and 200 North Road, 88 feet north of the centerline of 200 North Road, 15 feet east of the centerline of 200 West Road, 42 feet northeast of a road sign post for 200 West Road and 200 North Road, 1.5 feet west of a wire fence line, set 1.0 foot above the ground; a railroad spike driven thru an aluminum tag, stamped "IDNR TBM FLK 26, 1994".

765.321 feet NAVD 1988 233.270 meters NAVD 1988 765.729 feet NGVD 1929 233.395 meters NGVD 1929

DNR TBM FLK 27 A, 1994

In Fulton County, Pershing Quad., in the SW ¼ of Sec. 26, T. 31 N., R. 2 E., 2nd PM; about 2.1 miles east of Pershing; in the southeast 1/4 of the intersection of Olsen Rd. and 200 West Road; set in the west side of a power pole with 3 transformers, 108 feet south of the centerline of Olsen Road, 58.4 feet east of a vertical railroad rail painted silver, 41.9 feet south of a "stop" sign post, 16 feet east of the centerline of 200 West Road, 4 feet west of a fence line, 0.9 foot above the ground; a railroad spike driven thru an aluminum tag, stamped "IDNR TBM FLK 27, 1994"

759.833 feet NAVD 1988 231.598 meters NAVD 1988 760.240 feet NGVD 1929 231.722 meters NGVD 1929

DNR TBM FLK 28, 1994In Fulton County, Rochester Quad, in the NW ¼ Sec 28, T. 31 N., R. 3 E., 2nd PM; approximately 2.7 miles northeast of <u>Rochester</u>; at the intersection of 375 North Road and the Norfolk and Western Railroad, in the northwest quarter of the intersection; set in the south side of a power pole with a guy wire in to the west, 78.7 feet northwest of a wood mailbox post #2486 (Tim Eizenger residence), 35.8 feet northwest of a telephone pole #1014 with a guy wire, 50.8 feet west of a wood railroad crossing sign post, 71.0 feet west of the west rail of railroad and the centerline of the road crossing the railroad, 12.5 feet west of the road crossing the railroad, 12.5 feet west of the extended centerline of a private drive to the north, 93.0 feet north of the centerline of a private drive to the west (#2486 E.), 1.2 feet above the ground a railroad spike driven thru an aluminum tag, stamped "IDNR TBM FLK 28, 1994"

769.995 feet NAVD 1988 234.695 meters NAVD 1988 770.458 feet NGVD 1929 234.836 meters NGVD 1929

DNR TBM FLK 29, 1994

In Fulton County, Rochester Quad., in the NW ¼ of Sec. 27, T. 31 N., R. 3 E., 2nd PM; approximately 2.5 miles north-northeast of <u>Rochester</u>; at the State Road 25 bridge over Chippewanuck Creek; set in the top of the southeast corner of the north concrete bridge approach, 21.5 feet east of the centerline of State Road 25, 1.0 foot west of the north end of the east concrete guardrail of the bridge, 0.7 foot north of the concrete bridge seat, level with the road; a chiseled triangle.

767.673 feet NAVD 1988 233.987 meters NAVD 1988 768.155 feet NGVD 1929 234.134 meters NGVD 1929

DNR TBM FLK 30, 1994

In Fulton County, Rochester Quad., in the North ½ of Sec. 22, T. 31 N., R. 3 E., 2nd PM; approximately 3.5 miles north-northeast of <u>Rochester</u>; at the 350 East Road bridge over the Tippecanoe River; set in the top of the northwest concrete bridge abutment, 16.5 feet west of the centerline of 350 East Road, 1.2 feet northwest of the northwest corner of the northwest concrete guardrail of the bridge, 0.4 foot east of the west face of the concrete bridge abutment, about level with the road; a chiseled triangle.

767.138 feet NAVD 1988 233.824 meters NAVD 1988 767.640 feet NGVD 1929 233.977 meters NGVD 1929

DNR TBM FLK 31, 1994

In Fulton County, Argos Quad., in the SW ¼ of Sec. 14, T. 31 N. R. 3 E., 2nd PM; approximately 2.1 miles southwest of <u>Talma</u>; at the "T" road intersection of 500 North Road and State Road 25, in the northwest quadrant of the intersection; set in the west side of a power pole, 42.0 feet northwest of the centerline of State Road 25, 39.0 feet northeast of a concrete highway right-of-way marker, 36.0 feet north of the extended centerline of 500 North Road, 3.5 feet southwest of a metal telephone pedestal; a railroad spike driven thru an aluminum tag, stamped "IDNR TBM FLK 31, 1994"

768.621 feet NAVD 1988 234.276 meters NAVD 1988 769.109 feet NGVD 1929 234.425 meters NGVD 1929

DNR TBM FLK 33, 1994

In Fulton County, Rochester Quad., in the NE ¼ of Sec. 23, T. 30 N., R. 3 E., 2nd PM; approximately 2.0 miles southeast of <u>Rochester</u>; at the intersection of 500 East Road and 150 South Road, in the northwest quarter of the intersection; set in the south side of a power pole, 59.0 feet west of the centerline of 500 East Road, 55.9 feet southwest of a metal "150S-500E" road sign post, 383. feet north of and across 150 South Road from a metal "stop" sign post, 22.5 feet north of the centerline of 150 South Road, 4.9 feet southwest of a railroad rail set vertically in the ground, 1.1 feet east of a green metal telephone pedestal, 0.9 foot above the ground; a railroad spike driven thru an aluminum tag, stamped "IDNR TBM FLK 33, 1994".

791.114 feet NGVD 1988 241.132 meters NGVD 1988 791.517 feet NGVD 1929 241.255 meters NGVD 1929

DNR TBM FLK 34, 1994

In Fulton County, Rochester Quad., in the NW ¼ of Sec. 36, T. 30 N., R. 3 E., 2nd PM; approximately 4.3 miles southeast of Rochester; at the intersection of 350 South Road and 500 East Road, in the northeast quarter of the intersection; set in the northeast side of a power pole with a guy wire, 275 feet east of the centerline of 500 East Road, 18.0 feet north of the centerline 350 South Road, 51.0 feet west of the extended centerline of a private drive to the south (Scoot and Dawn Holtmeyer residence 5075 East 250 South), 41.8 feet northeast of and across 350 South Road from a green metal telephone pedestal, 20.4 feet east of a metal "caution buried telephone cable" sign post, 1.5 feet above the ground, 0.8 foot south of a fence line; a railroad spike driven thru an aluminum tag, stamped "IDNR TBM FLK 34, 1994".

834.035 feet NAVD 1988 254.214 meters NAVD 1988 834.438 feet NGVD 1929 254.337 meters NGVD 1929

DNR TBM Mill #1, 1990

In Fulton County, Rochester Quad., in the East ½ of Sec. 31, T. 31 N., R. 3 E., 2nd PM; approximately 1.0 mile north-northwest Rochester; approximately 0.2 mile east along Olson Road from the Olson Road bridge over Mill Creek, set in the north side of powerpole #134-770, 45.0 feet southeast of and across Olson Road from a green metal telephone pedestal, 38.0 feet north of a wood gate post with a metal bar gate, 15.0 feet south of the centerline of Olson Road, 15.0 feet west of the extended centerline of a gravel road to the north, 2.0 feet above the ground; a railroad spike driven thru an aluminum tag, stamped "IDNR TBM"

751.505 feet NAVD 1988 229.059 meters NAVD 1988 751.910 meters NGVD 1929 229.183 meters NGVD 1929

DNR TBM Mill #2, 1990

In Fulton County, Rochester Quad., in the Michigan Road Grant #31; at Rochester; at the Fourth Street triple cmp culvert over Mill Creek; set in the south side of a utility pole #175 with an overhead light, 62.0 feet east of the centerline of the center of the culvert, 46.5 feet northeast of the northwest end of the southeast concrete wingwall of the culvert, 37.0 feet west of the extended centerline of an asphalt drive to the north leading to the Water Haven Apartments, 22.0 feet south of the centerline of Fourth Street, 1.5 feet above the ground; a railroad spike.

770.791 feet NAVD 1988 234.938 meters NAVD 1988 771.193 feet NGVD 1929 235.060 meters NGVD 1929

DNR TBM Mill #3, 1990

In Fulton County, Rochester Quad., in the Michigan Road Grant #32; at Rochester; at the Indiana Avenue triple pipe culvert over Mill Creek; set in the southwest side of powerpole #129-207 with a transformer, overhead light, and a guy wire, 60.1 feet southwest of the center of the top bolt of a fire hydrant painted yellow, 36.0 feet northeast of the centerline of the center pipe culvert, 17.0 feet southeast of the centerline of Indiana Avenue, 1.6 feet above the ground; a railroad spike.

767.527 feet NAVD 1988 233.943 meters NAVD 1988 767.928 feet NGVD 1929 234.065 meters NGVD 1929

DNR BM FUL 10, 1993In Fulton County, Culver Quad., in the SW ¼ of Sec. 6, T. 31 N., R. 1 E., 2nd PM; approximately 0.7 mile east-northeast of Monterey; approximately 0.5 mile north along State Road 17 from the State Road 17 bridge over the Tippecanoe River to 700 North Road, thence 1.7 miles generally west to the Monterey Pines Christmas Tree Farm, or 0.2 mile east along 700 North from the Pulaski-Fulton County line to the tbm on the north side of 700 North Road, 25.5 feet north of the centerline of 700 North Road, 20.1 feet southwest of a 48.0 inch Oak tree, 13.9 feet northwest of a metal "school bus turnaround" sign post, 3.8 feet south of a 8 inch square wood fence end post in a north-south fence line, 2.7 feet south of a orange D.N.R. witness post, 0.1 foot below the ground; a Department of Natural Resources brass control station tablet, stamped "FUL 10, 1993".

730.933 feet NAVD 1988 222.789 meters NAVD 1988 731.331 feet NGVD 1929 222.910 meters NGVD 1929

DNR BM FUL 11, 1993

In Fulton County, Culver Quad., in the SW ¼ of Sec 5, T. 31 N., R. 1 E., 2nd PM; approximately 1.3 miles east of Monterey; at the 700 North Road cmp pipe culvert over Thompson Ditch; set in the top of a concrete post, 230 .5 feet west of the centerline of the cmp culvert under the road, 72.7 feet northwest of the northwest corner of a red barn with a field stone foundation, 45.1 feet northeast of the northeast corner of a small barn (tractor shed) with wood siding painted red, 16.2 feet south of the centerline of 700 North Road, 4.5 feet North of a power pole with overhead light and a metal meter box, 3.7 feet north of an orange D.N.R. witness post, 0.3 foot below the ground; a Department of Natural Resources brass control station tablet, stamped "FUL 11, 1993".

728.955 feet NAVD 1988 222.186 meters NAVD 1988

729.353 feet NGVD 1929 222.307 meters NGVD 1929

DNR BM FUL 14, 1993

In Fulton County, Culver Quad., in the NE ¼ of Sec. 15, T. 31 N., R. 1 E., 2nd PM; approximately 1.0 mile east-southeast of <u>Delong</u>; at the "T" road intersection of 800 West Road and 550 North Road, in the northwest quadrant of the intersection; set in the top of a concrete post, 45.5 feet northwest of and across 550 North Road from a metal fence corner post, 34.5 feet west of the centerline of 800 West Road, 29.5 feet southwest of a metal "stop" sign post (on the west side of 800 West Road), 16.5 feet north of the centerline of 550 North Road, 16.0 feet east of a power pole #BC153 with a transformer, 6.1 feet northeast of a wood mailbox post (#B045 W 550 N), 2.0 feet south of an orange DNR witness post, level with the ground; a Department of Natural Resources brass control station tablet, stamped "FUL 14, 1993".

738.941 feet NAVD 1988 225.230 meters NAVD 1988 739.342 feet NAVD 1929 225.352 meters NAVD 1929

DNR BM FUL 16, 1993In Fulton County, Pershing Quad., in the NW ¼ of Sec. 19, T. 31 N., R, 2 E., 2nd PM; approximately miles west of <u>Anderson Lake</u>; at the intersection of 475 North Road and 600 West Road; set in the top of a concrete post, 10.5 feet south of the extended centerline of 475 North Road, 9.0 feet east-northeast of a 8 inch X 8 inch wood fence corner post, 6.5 feet east of the extended centerline of 600 West Road, 32.6 feet southeast of and across a private drive to the west from a 6 inch treated wood gate post, near the centerline of a dim lane to the south, 0.1 foot below the level of the ground; a Department of Natural Resources brass control station tablet, stamped "FUL 16, 1993".

737.775 feet NAVD 1988 224.874 meters NAVD 1988 738.178 feet NGVD 1929 224.997 meters NGVD 1929

DNR BM FUL 17, 1993

In Fulton County, Pershing Quad., in the SW ¼ of Sec. 21, T. 31 N., R. 2 E., 2nd PM; about 1.75 miles northwest of <u>Pershing</u>; at the intersection of 500 West Road and Boicourts Dr/Beaman Ln; set in top of a concrete post, on the north side of the Tippecanoe River, 27 feet west of the centerline of 500 West Road, 28 feet north of the centerline of Beaman Lane, 11.5 feet northwest of a power pole, 10.4 feet northeast of the west guy wire anchor, 19.1 feet southerly of a "stop" sign post, 34.6 feet northeast a "slow, children at play" sign post, level with the ground; a Dept. of Natural Resources brass control station tablet, stamped "FUL 17, 1993".

738.343 feet NAVD 1988 225.047 meters NAVD 1988 738.746 feet NGVD 1929 225.170 meters NGVD 1929

DNR BM FUL 20, 1993

In Fulton County, Pershing Quad., in the NE ¼ of Sec. 35, T. 31 N., R. 2 E., 2nd PM; approximately 2.8 miles east of <u>Pershing</u> approximately 1.05 mile generally east along Olson Road from its intersection with 200 West Road to a farm drive north (Freat Residence); set in the top of a concrete post, 70.5 feet east of the centerline of a private drive to the south, 15.7 feet south of the centerline of Olson Road, 9.7 feet east of a powerpole #43A with 2 guy wires, 5.4 feet southeast of a wood mailbox post (#1170), 3.0 feet north of a fence corner, 2.9 feet north of an orange D.N.R. witness post, on the extended centerline of the farm drive north (Freat Residence); a Department of Natural Resources brass control station tablet, stamped "FUL 20, 1993".

760.221 feet NAVD 1988 231.716 meters NAVD 1988 760.628 feet NGVD 1929 231.840 meters NGVD 1929

DNR BM FUL 21, 1993In Fulton County, Rochester Quad., in the NE ¼ of Sec. 36, T. 31 N., R. 2 E., 2nd PM; approximately 1.8 miles northwest of <u>Rochester</u>; approximately 0.65 mile west and north along Olson Road from its intersection with U.S. 31 to a bend in Olson Road to the west, and a gravel private drive to the north; set in the top of a concrete post, 40.0 feet southeast of and across the private drive from a 12.0 inch Pine tree, 23.8 feet east of the extended centerline of Olson Road from the south, 22.0 feet east of the north end of a steel guardrail, 8.2 feet east of the north leg of a road direction sign, 2.4 feet west of an orange D.N.R. witness post, 0.1 foot below the ground, on the extended centerline of Olson Road to the west; a Department of Natural Resources brass control station tablet, stamped "FUL 21, 1993".

755.087 feet NAVD 1988 230.151 meters NAVD 1988 755.493 feet NGVD 1929 230.275 meters NGVD 1929

DNR BM FUL 24, 1993

In Fulton County, Rochester Quad., in the Michigan Road Grant Number 29, approximately 2.2 miles north of Rochester; at the entrance to the Menominee Public Fishing Site; set in the top of a concrete post, 83.2 Feet northeast of the extended centerline of the east most gravel entrance drive and the centerline of 350 North Road, 65.0 feet east of the centerline of the east most gravel entrance drive, 40.0 feet northwest of a 22.0 inch oak tree, 38.0 feet southwest of a 18.0 inch oak tree, 37.1 feet north of the centerline of 350 North Road, 35.2 feet southeast of a 22.0 inch Oak tree, 28.7 feet south of the centerline of the gravel boat ramp access road, 2.3 feet south of an orange D.N.R. witness post, about level with the ground; a Department of Natural Resources brass control station tablet, stamped "FUL 24 1993".

765.764 feet NAVD 1988 233.405 meters NAVD 1988 766.186 feet NGVD 1929 233.534 meters NGVD 1929

DNR BM FUL 26, 1993

In Fulton County, Rochester Quad., in the NE ¼ of Sec. 21, T. 31 N., R. 3 E., 2nd PM; approximately 3.2 miles north-northeast of <u>Rochester</u>; at the Norfolk and Western Railroad bridge over the Tippecanoe River; set in the top of the northwest concrete headwall of the bridge, 5.4 feet west of the west rail of the tracks, 1.4 feet south of the north face of the headwall, 1.6 feet north of the south face of the headwall, 0.7 foot below the top of the rails of the railroad; a Department of Natural Resources brass control station tablet, stamped "FUL 26 1993".

769.245 feet NAVD 1988 234.466 meters NAVD 1988 769.723 feet NGVD 1929 234.612 meters NGVD 1929

DNR BM FUL 27, 1993In Fulton County, Rochester Quad., in the North ½ of Sec. 22, T. 31 N., R. 3 E., 2nd PM; approximately 3.5 miles north-northeast of <u>Rochester</u>; at the 350 East Road bridge over the Tippecanoe River; set in the southwest concrete bridge abutment, 15.0 feet west of the centerline of 350 East Road bridge, 0.9 foot west of the west face of the concrete guardrail of the bridge, 0.8 foot south of the north face of the abutment, 0.5 foot east of the west face of the abutment, about level with the road; a Department of Natural Resources brass control station tablet, stamped "FUL 27 1993".

766.966 feet NAVD 1988 233.772 meters NAVD 1988 767.466 feet NGVD 1929 233.924 meters NGVD 1929

DNR BM FUL 30, 1993

In Fulton County, Rochester Quad., in the SW ¼ of Sec. 25, T. 30 N., R. 3 E., 2nd PM; approximately 3.0 miles southeast of Rochester, at Wagoner; at the 500 East Road bridge over Rain Creek; set in the top of the third and east most metal and concrete bridge piling on the southeast side of the bridge, 17.1 feet southeast of the centerline of 500 East Road, 9.1 feet east of the east corner of the southeast concrete curb of the bridge, 1.15 feet southwest of the northeast corner of the concrete wingwall of the bridge, 0.65 foot south of the south face of the concrete wingwall of the bridge, 0.3 foot below the level of the road; a Department of Natural Resources brass control station tablet, stamped "FUL 30 1993".

795.531 feet NAVD 1988 242.478 meters NAVD 1988 795.934 feet NGVD 1929 242.601 meters NGVD 1929

DNR BM FUL 32, 1993

In Fulton County, Rochester Quad., in the NW ¼ of Sec. 14, T. 30 N., R. 3 E., 2nd PM; approximately 1.0 mile southeast of <u>Rochester</u>; at the 400 East Road (Bessmore Park Road) bridge over Graham Ditch; set in the top of the southwest concrete abutment of the bridge, 13.8 feet west of the centerline of 400 East Road, 7.4 feet south of the north end of the abutment, 0.55 foot northwest of the northwest corner of a aluminum "I" beam guardrail support post, 0.5 foot north of the south end of the abutment, about level with the road; a Department of Natural Resources brass control station tablet, stamped "FUL 32 1993".

782.443 feet NAVD 1988 238.489 meters NAVD 1988 782.847 feet NGVD 1929 238.612 meters NGVD 1929

DNR BM FUL 33, 1993

In Fulton County, Rochester Quad., in the SE ¼ of Sec. 9, T. 30 N., R. 3 E., 2nd PM; at Rochester; at the concrete outlet dam for Lake Manitou; set in the top of the south concrete headwall of the outlet spillway, 48.7 feet east of the west end of the principle spillway of the dam, 1.7 feet northwest of the southeast end of the concrete headwall of the outlet spillway, 1.1 feet east of the east end of the metal chain link fence end post on the south side of the outlet, 0.6 foot southwest of the northeast face of the headwall, 2.4 feet above the concrete spillway of the dam; a Department of Natural Resources brass control station tablet, stamped "FUL 33 1993".

779.474 feet NAVD 1988 237.584 meters NAVD 1988 779.875 feet NGVD 1929 237.706 meters NGVD 1929

DOT BM FUL L 152

In Fulton County, Rochester Quad., in the South ½ of Sec. 31, T. 30 N., R. 3 E., 2nd PM; at Rochester; at the Main Street (Old US 31) bridge over Mill Creek; set in the top of the southwest concrete wingwall of the bridge, 48.2 feet west of the centerline of Main Street, 3.5 feet northwest of the northwest corner of the north most aluminum "I" beam support post of the southwest aluminum guardrail of the bridge, 0.8 foot west of the west face of the west concrete guardrail of the bridge, 0.65 foot south of the north face of the concrete wingwall of the bridge, about 1.0 foot below the level of the centerline of the road; a State Highway Commission of Indiana Survey Bench Mark tablet, stamped "FUL L152".

767.680 feet NAVD 1988 233.989 meters NAVD 1988 768.083 feet NGVD 1929 234.112 meters NGVD 1929

DOT BM FULT L 211

In Fulton County, Culver Quad., in the NW ¼ Sec. 9, T. 31 N., R. 1 E., 2nd PM; approximately 1.1 miles northwest of <u>Delong</u>; at the State Road 17 bridge over the Tippecanoe River; set in the top of the west concrete sidewalk of the bridge, 16.8 feet west of the centerline of the road, 6.4 feet north of the south end of the concrete sidewalk, 0.6 foot south of the north end of the southwest aluminum guardrail of the bridge, 0.25 foot east of the east face of the concrete handrail of the bridge, 0.7 foot above the level of the road; a State Highway Commission of Indiana Survey Bench Mark tablet, stamped "FULT L211".

737.353 feet NAVD 1988 224.746 meters NAVD 1988 737.751 feet NGVD 1929 224.867 meters NGVD 1929

DOT BM FUL L465In Fulton County, Rochester Quad., in the NW ¼ of Sec. 31, T. 31 N., R. 3 E., 2nd PM; approximately 1.5 miles northwest of <u>Rochester</u>; at the south bound U.S. 31 bridge over the Tippecanoe River; set in the top of the southwest concrete retaining wall of the bridge, 23.5 feet west of the centerline of the south bound lanes of U.S. 31, 11.0 feet south of the north end of the retaining wall, 2.0 feet northwest of the northwest corner of the aluminum "I" beam guardrail support post, the 5th "I" beam north of the south end of the guardrail, 0.95 foot north of the south end of the retaining wall, 0.55 foot east of the west face of the retaining wall, about level with the road; a State Highway Commission of Indiana Survey Bench Mark tablet, stamped "FUL L465".

755.896 feet NAVD 1988 230.397 meters NAVD 1988 756.301 feet NGVD 1929 230.521 meters NGVD 1929

DOT BM L551 FUL

In Fulton County, Pershing Quad., in the SE ¼ of Sec. 27, T. 31 N., R. 2 E., 2nd PM; approximately 1.8 miles southeast of <u>Anderson Lake</u>; at the 200 West Road bridge over the Tippecanoe River; set in the top of the southwest concrete parapet of the bridge, 13.7 feet west of the centerline of 200 West Road, 4.1 feet south of the north end of the parapet (also metal and rubber expansion joint between the bridge and the concrete parapet), 1.3 feet north of the south end of the parapet, 0.85 foot southwest of the southwest corner of an aluminum "I" beam guardrail support post, about level with the road; a State Highway Commission of Indiana Survey Bench Mark tablet, stamped "L551 FUL".

754.585 feet NAVD 1988 229.998 meters NAVD 1988 754.992 feet NGVD 1929 230.122 meters NGVD 1929

DOT BM FULT L564

In Fulton County, Argos Quad., in the NW ¼ of Sec. 12, T. 31 N., R. 3 E., 2nd PM; approximately 0.2 mile west-southwest of <u>Talma</u>; at the 525 East Road bridge over the Tippecanoe River; set in the top of the southwest concrete abutment of the bridge, 13.2 feet west of the centerline of the road, 2.4 feet south of the metal and rubber expansion joint between the bridge and the concrete approach pad, 2.0 feet north of the south end of the concrete abutment, 0.9 foot northwest of the northwest corner of an aluminum "I" beam guardrail support post, 0.6 foot east of the west face of the abutment, about level with the road; a State Highway Commission of Indiana Survey bench mark tablet, stamped "FULT L564".

772.505 feet NAVD 1988 235.460 meters NAVD 1988 772.968 feet NGVD 1929 235.601 meters NGVD 1929

DOT BM L582 FultonIn Fulton County, Pershing Quad., in the SW ¼ of Sec. 21, T. 31 N., R. 2 E., 2nd PM; approximately miles southwest of <u>Anderson Lake</u>; at the 375 West Road bridge over Tippecanoe River; set in the top of the southwest concrete parapet of the bridge, 12.3 feet west of the centerline of the road, 4.4 feet south of the metal and rubber expansion joint between the south end of the bridge and the parapet, 2.5 feet north of the south end of the parapet, 0.6 foot east of the west face of the parapet, 1.0 foot southwest of the southwest corner of an aluminum "I" beam guardrail support post, 0.2 foot above the level of the centerline of the road; a State Highway Commission of Indiana Survey Bench Mark tablet, stamped "L582 FULTON".

744.633 feet NAVD 1988 226.965 meters NAVD 1988 745.038 feet NGVD 1929 227.088 meters NGVD 1929

DOT BM FULTON L590

In Fulton County, Rochester Quad., in the Land Grant Area T. 31 N., R. 3 E., 2nd PM; approximately miles north of <u>Rochester</u>; at the Old U.S. 31 bridge over the Tippecanoe River; set in the top of the southwest retaining wall of the bridge, 1.3 foot northwest of the northwest corner of an aluminum "I" beam guardrail support post, 0.5 foot east of the west face of the concrete retaining wall, level with the road; a State Highway Commission of Indiana Survey Bench Mark tablet, stamped "FULTON L590".

761.122 feet NAVD 1988 231.990 meters NAVD 1988 761.531 feet NGVD 1929 232.115 meters NGVD 1929

DOT BM FULTON L606

In Fulton County, Culver Quad., in the SE ¼ of Sec. 9, T.31 N., R. 1 E., 2nd PM; approximately 0.2 mile north of <u>Delong</u>; at the 900 East Road bridge over the Tippecanoe River; set in the top of the south concrete abutment of the bridge, 13.2 feet west of the centerline of the road, 4.5 feet south of the north end of the abutment, 2.2 feet southwest of the southwest corner of an aluminum "I" beam guardrail post (1st guardrail post south of the expansion joint on the south side of the bridge), 1.0 foot north of the south end of the abutment, 0.6 foot east of the west face of the abutment, about level with the road; a Indiana Department of Highways benchmark tablet, stamped "FULTON L606".

732.054 feet NAVD 1988 223.130 meters NAVD 1988 732.453 feet NGVD 1929 223.252 meters NGVD 1929

DOT BM FULTON L701In Fulton County, Rochester Quad., near the center of Sec. 9, T. 30 N., R. 3 E., 2nd PM; at <u>Rochester</u>; at the State Road 14 and State Road 25 (E. 9th Street) bridge over Mill Creek; set in the top of the north concrete guardrail of the bridge, 30.8 feet north of the centerline road, 1.3 feet east of the west end of the concrete guardrail, 2.9 feet above the level of the concrete bridge deck, 6.6 feet southwest of a wood light pole, 0.35 foot south of the north face of the concrete guardrail; a Indiana Department of Highways benchmark tablet, stamped "FULTON L701".

778.658 feet NAVD 1988 237.335 meters NAVD 1988 779.058 feet NGVD 1929 237.457 meters NGVD 1929

USC & GS BM E144, 1946

In Fulton County, Rochester Quad., in the SE ¼ of Sec. 28, T. 31 N., R. 3 E., 2nd PM; approximately 2.6 miles north of <u>Rochester</u>; approximately 0.9 mile north along old U.S. 31 from the old U.S. 31 bridge over the Tippecanoe River; set vertically in the south face of the southeast corner of a manufacturing building, 1.5 feet west of the southeast corner of the concrete foundation, approximately 0.2 foot above the ground, note: exterior siding has been added to the building that extends out over the disk, now unable to set rod on tablet; a U.S. Coast and Geodetic Survey benchmark tablet, stamped "E 144 1946"

812.925 feet NAVD 1988 247.780 meters NAVD 1988 813.315 feet NGVD 1929 247.899 meters NGVD 1929

USC & GS BM Z 176, 1946

In Fulton County, Rochester Quad., in the NW ¼ of Sec. 9, T. 30 N., R. 3 E., 2nd PM; at Rochester; approximately 0.2 mile southeast along State Road 14 from its intersection with Wabash Avenue to the entrance drive to Lakeview Park; set vertically in the northeast face of the concrete base of a 2 1/2 foot x 2 12 foot brick gate post (gate is gone) west most of 2 gate posts, 159 feet northeast of the centerline of State Road 14, 71.0 feet northeast of the northeast end of the northwest fieldstone headwall of the park entrance drive culvert over a small drain that runs along State Road 14, 18.7 feet southeast of power pole #175/129-508 with two guy wires, in the center of the northeast face of the concrete base, 0.5 foot above the ground; a U.S. Geological Survey benchmark tablet, stamped "Z 176 1946".

778.899 feet NAVD 1988 237.409 meters NAVD 1988 779.300 feet NGVD 1929 237.531 meters NGVD 1929

USC & GS BM C177, 1946In Fulton County, Rochester Quad., in the West ¼ of Sec. 10, T. 30 N., R. 3 E., 2nd PM; at <u>Rochester</u>; on the north side of Lake Manitou, near the Fulton County Airport; at the intersection of State Road 14 and Boulevard Street, 300 feet east of the centerline of Boulevard Street, 63.3 feet southeast of the southeast corner of the Airvac Collection Station Building (brown brick), 40.0 feet north of the centerline of State Road 14, 3.3 feet south of a utility pole, 1.9 feet west of a railroad set vertically in the ground, 1.1 feet south of an orange witness post, about level with the road; a U.S. Coast and Geodetic Survey benchmark tablet, stamped "C177 1946"

789.346 feet NAVD 1988 240.593 meters NAVD 1988 789.746 feet NGVD 1929 240.715 meters NGVD 1929

USC & GS BM D177, 1946

In Fulton County, Rochester Quad., in the SW ¼ of Sec. 11, T. 30 N., R. 3 E., 2nd PM; approximately 1.0 mile east of Rochester; at the northeast side of Lake Manitou; at the intersection of State Road 14 and 400 East Road; set in the top of the northeast concrete headwall of a 14 inch concrete pipe culvert, 143 feet east of the centerline of 400 East Road, 20.0 feet northeast of the centerline of State Road 14, 8.9 feet southwest of a green metal telephone pedestal, 1.0 foot northwest of the southeast end of the headwall, 0.5 foot below the level of the centerline of State Road 14; a U.S. Coast and Geodetic Survey benchmark tablet, stamped "D177 1946".

786.157 feet NAVD 1988 239.621 meters NAVD 1988 786.560 feet NGVD 1929 239.744 meters NGVD 1929

USC & GS BM C179, 1946In Fulton County, Pershing Quad., in the NW corner of Sec. 14, T. 30 N., R. 2 E., 2nd PM: about 3.8 miles west of <u>Rochester</u>; in the southeast 1/4 of the intersection of State Road 14 and 200 West Road; set in the top of a concrete post, 53 feet south of the centerline of State Road 14, 20 feet east of the centerline of 200 West Road, 38 feet easterly of a guy pole in the southwest 1/4 of the intersection, 38.7 feet easterly of a railroad rail set vertically in the southwest 1/4 of the intersection, 4.9 feet east-southeast of the east post of a "stop" sign post, 3.8 feet northeast of the northeast corner of a square brick "chain fence" post with a light on top, 0.3 foot below the ground; a U.S. Coast and Geodetic Survey benchmark tablet, stamped "C179 1946".

759.218 feet NAVD 1988 231.410 meters NAVD 1988

759.628 feet NGVD 1929 231.535 meters NGVD 1929

USC & GS BM D179, 1946In Fulton County, Pershing Quad., in the SE corner of Sec. 11, T. 30 N., R. 2 E., 2nd PM; about 2.8 miles west of <u>Rochester</u>; in the northwest 1/4 of the intersection of State Road 14 and 100 West Road; set in the top of a concrete post, 34.5 feet north of the centerline of State Road 14, 20 feet west of the centerline of 100 West Road, 39.8 feet westerly of a power pole in the northeast 1/4 of the intersection, 2.6 feet northeasterly of a railroad rail set vertically in a fence line, 1.5 feet east of a barb wire fence, 5.2 feet southerly of the west most post of a "stop" sign, level with the ground; a U.S. Coast and Geodetic Survey benchmark, stamped "D179 1946".

765.317 feet NAVD 1988 233.269 meters NAVD 1988 765.727 feet NGVD 1929 233.394 meters NGVD 1929

USC & GS Kesler 1952

In Fulton County, Rutland Quad., near the section line between Sec. 16 & 17, T. 31 N., R. 2 E., 2nd PM; approximately 0.6 mile west-northwest of <u>Anderson Lake</u>, northeast of Moose Woods Lake; 0.1 mile north along from its intersection with 500 North Road to a bend in the road to the west; set in the top of a concrete post, 121.0 feet south of and across the road from a powerpole with a guy wire, 107.7 feet northwest of and across the road from a telephone pole, 82.5 feet southwest of and across from the southwest corner of a two-car garage, 55.0 feet southwest of and across the road from a power pole with a transformer and a guy wire, 43.6 feet west-northwest of the south most corner of a concrete private drive, 32.0 feet west of the centerline of the road, east of an orange witness post, above the level of the road, 0.3 feet above the ground; a U.S. Coast and Geodetic triangulation tablet, stamped "Kesler 1952".

801.335 feet NAVD 1988 244.247 meters NAVD 1988 801.739 feet NGVD 1929 244.371 meters NGVD 1929

USC & GS TIOSA AZI

In Fulton County, Argos Quad., in the SE ¼ of Sec. 14, T. 31 N., R. 3 E., 2nd PM; approximately 1.5 miles southwest of <u>Talma</u>; approximately 0.75 mile southwest along State Road 25 from the Hamlett Cemetery, to the station on the northwest side of State Road 25, near a bend in the Tippecanoe River; set in the top of a concrete post, 40.1 feet northwest of the centerline State Road 25, 12.1 feet west of a guy wire anchor, 2.6 feet south of a power pole, 0.7 foot southeast of a fence line, 0.6 foot southeast of an orange witness post, 0.3 foot above the ground; a U.S. Coast and Geodetic Survey azimuth mark tablet, stamped "TIOSA 1952".

771.055 feet NAVD 1988 235.018 meters NAVD 1988 771.540 feet NGVD 1929 235.166 meters NGVD 1929

COE BM Not Stamped

In Fulton County, Kewanna Quad., in the NE ¼ of Sec. 23, T. 31 N., R. 1 E., 2nd PM; at Leiters Ford; at the River Road steel pony truss bridge over the Tippecanoe River; set in the top of the southeast concrete bridge seat, 13.5 feet southeast of the centerline of the road, 3.3 feet southeast of the south end of the southeast concrete curb of the bridge, 2.1 feet south of the south end of the southeast steel truss, 1.0 foot southwest of the northeast face of the concrete bridge seat, about level with the road; a Corps of Engineers U.S. Army Survey mark tablet, not stamped.

736.511 feet NAVD 1988 224.489 meters NAVD 1988 736.912 feet NGVD 1929 224.611 meters NGVD 1929

USGS BM 132 EOM 1958

In Fulton County, Rochester Quad., in the SW ¼ of Sec. 31, T. 30 N., R. 4 E., 2nd PM; approximately 4.5 miles southeast of Rochester, at Millark Mill pond; at the 350 South Road bridge over Rain Creek; set in the top of the west corner of the south concrete bridge approach, 15.0 feet west of the centerline of 350 South Road, 2.0 feet south of the north face of the concrete bridge approach, 1.75 feet northwest of the northwest corner of a metal "I" beam guardrail support post, 0.7 foot northeast of the northeast end of the southwest concrete and metal wingwall of the bridge, 0.6 foot east of the south corner of a metal plate "FULTON COUNTY BRIDGE NO 80" embedded in the concrete bridge approach, level with the road; a U.S. Geological Survey benchmark tablet, stamped "132 EOM 1958 804".

805.210 feet NAVD 1988 245.429 meters NAVD 1988 805.614 feet NGVD 1929 245.552 meters NGVD 1929

USGS Gaging Station

In Fulton County, Rochester Quad., in the SE ¼ of Sec. 9, T. 30 N., R. 3 E., 2nd PM; at Rochester; at the concrete outlet dam for Lake Manitou; set in the top of the south concrete headwall of the outlet spillway, 35.0 feet west of the east end of the concrete headwall, 32.5 feet west of the east end of the metal chain link fence and post on the south side of the outlet, 15.4 feet east of the west end of the principle spillway of the dam, about 2.8 feet above the level of the concrete spillway of the outlet structure, 1.25 feet north of the chain link fence, 0.5 foot south of the north face of the south concrete headwall; a U.S. Geological Survey gaging station tablet, not stamped.

779.374 feet NAVD 1988 237.554 meters NAVD 1988 779.775 feet NGVD 1929 237.676 meters NGVD 1929

USC& GS BM E134, 1946

In Fulton County, Kewanna Quad., in the SW ¼ Sec. 19, T. 31. N., R. 1 E., 2nd PM; about 7.0 miles north-northwest of Kewanna; 7.0 miles generally north along State Road 17 from its junction with Main Street in Kewanna to an east-west crossroad (400 North Road), thence 2.0 miles west to a T-road north (County Line Road); set in the top of a concrete post in the northeast quarter of the junction, 71 feet east of the centerline of the "T"-road north, 27 feet east from the center line of the east-west road, 3 feet above the roadway, 0.3 foot above the ground; a U.S. Coast and Geodetic Survey bench mark tablet, stamped "E134 1946".

758.56 feet NAVD 1988 231.210 meters NAVD 1988 758.955 feet NGVD 1929 231.3299 meters NGVD 1929

DNR TBM PLK 2, 1977

In Fulton County, Kewanna Quad., in the SW ¼ Sec. 31, T. 31 N., R. 1 E., 2nd PM; about 1.3 miles north of the town of <u>Lake Bruce</u>; at the Pulaski-Fulton County Road steel pipe culvert over Wolf Ditch; set in the east side of an 8-inch Walnut tree on the east side of the road, 142.8 feet south from the centerline of the steel pipe culvert, 15.4 feet east from the centerline of the road, 0.4 foot above the ground; a railroad spike driven thru an aluminum tag, stamped "DNR TBM PLK 2 1977".

739.466 feet NGVD 1929 225.3897 meters NGVD 1929

USC & GS BM W180 RESET 1947

In Fulton County, Macy Quad., in the NE ¼ Sec. 16, T. 29 N., R. 3 E., 2nd PM; about 3.2 miles west of Macy (Miami County); 3.26 miles generally west along 1350 North Road from its junction with 300 West Road in Macy, to a "T"-road south; set in the top of a concrete post, on the north side of the road, on the east side of the extended centerline of the "T"-road, in a north-south fence line, 33 feet north from the centerline of the road, 21.8 feet east-southeast of the southeast corner of a house, level with the ground; a U.S. Coast and Geodetic Survey bench mark tablet, stamped "W180 RESET 1947".

806.8 feet NAVD 1988 245.91 meters NAVD 1988 807.191 feet NGVD 1929 246.0323 meters NGVD 1929

DNR BM FUL 1, 1977In Fulton County, Macy Quad., in the NE ¼ Sec. 21, T. 29 N., R. 3 E., 2nd PM; about 3.5 miles west-southwest of Macy (Miami County), 3.6 miles generally west along 1350 North Road from its junction with 300 West Road in Macy to a north-south crossroad, thence 0.5 mile south to a "T"-road east leading to South Mud Lake, thence 0.3 mile east to a "T"-road southwest, thence 0.15 mile southwest to the end of the road; set in the top of the northeast dam abutment of South Mud Lake, 270 feet southeast from the centerline of the dead end road, 6.0 feet west from the southeast end of the abutment, 2.6 feet above the dam spillway, 1.5 feet above the ground; a Department of Natural Resources brass control station tablet, stamped "FUL 1 1977".

796.247 feet NGVD 1929 242.6966 meters NGVD 1929

DNR TBM FLK 1, 1977

In Fulton County, Macy Quad., in the NE ¼ Sec. 21, T. 29 N., R. 3 E., 2nd PM; about 3.48 miles west-southwest of Macy (Miami County); 3.6 miles generally west along 1350 North Road from its junction with 300 West Road in Macy to a north-south crossroad, thence 0.46 mile south to a T-road east leading to South Mud Lake, thence 0.3 mile east to a T-road southwest, thence 0.15 mile southwest to the end of the road; set in the top of the northeast concrete dam abutment of South Mud Lake, 270 feet southeast from the centerline of the dead end road, 16.5 feet northwest from the dam spillway, 3.6 feet southeast from the northwest end of the abutment; a chiseled triangle.

794.253 feet NGVD 1929 242.0888 meters NGVD 1929

USC & GS BM X 180, 1946

In Fulton County, Macy Quad., in the NE ¼ Sec. 21, T. 29 N., R. 3 E., 2nd PM; 3.7 miles west-southwest of Macy (Miami County); 3.6 miles generally west along 1350 North Road from its junction with 300 West Road in Macy to a north-south crossroad, thence 0.62 mile south to a turn west; set in the top of a concrete post on the north side of the road, 450 feet west from the north-south centerline of the road, 4.5 feet west from a telephone pole, 0.5 foot above the roadway; a U.S. Coast and Geodetic Survey bench mark tablet, stamped "X 180 1946"

804.94 feet NAVD 1988 245.237 meters NAVD 1988 805.336 feet NGVD 1929 245.4669 meters NGVD 1929

USC & GS BM K 176, 1946

In Fulton County, Rutland Quad., in the NE ¼ Sec. 4, T.31 N., R.2 E., 2nd PM, about 0.9 mile south Eddy Lake; 0.05 mile east along State Road 110 from its intersection with South Muckshaw Road to a private drive south; set in the southwest corner of the junction, 62 feet south from the centerline of State Road 110, 16 feet west of the centerline of the private drive, 2 feet below the highway, 2 feet west of a white wooden witness post; a U.S. Coast and Geodetic Survey bench mark tablet, stamped "K176 1946".

POSSIBLY--UNSTABLE--DNR ELEVATION-

804.823 feet NGVD 1929 245.3105 meters NGVD 1929

USC & GS BM L 176, 1946

In Fulton County, Rutland Quad., in the NW ¼ Sec. 5, T.31 N., R.2 E., 2nd PM; about 1.4 miles southwest of Eddy Lake; 0.4 mile west along State Road 110 from its intersection with South Nutmeg Road to an 18 foot steel pipe culvert under the road; set in the top of the east end of the south concrete headwall of the culvert, 22 feet south of the centerline of State Road 110, 1 foot west of the east end of the headwall, about 0.5 foot below the highway; a U.S. Coast and Geodetic Survey bench mark tablet, stamped "L 176 1946".

810.98 feet NAVD 1988 247.188 meters NAVD 1988 811.373 feet NGVD 1929 247.3070 meters NGVD 1929

USC & GS BM R 176, 1946

In Fulton County, Culver Quad., in the NE ¼ Sec. 4, T.31 N., R.1 E., 2nd PM, about 2.6 miles south of <u>Culver</u> (Marshall County); 1.0 mile east along State Road 110 from its intersection with State Road 17 to an east-west crossroad (Old State Road 17), thence 0.5 mile south along Old State Road 17 to power pole #1571 on the west side of the road; set in the top of a concrete post on the west side of the road, 56.2 feet southwest of the power pole, 37.0 feet west of the centerline of the road, 36 feet east of the east rail of an abandoned railroad track, 13.5 feet northeast of a mile post sign, 2.0 feet south of a white wooden witness post, level with the ground; a U.S. Coast and Geodetic Survey bench mark tablet, stamped "R 176 1946".

740.29 feet NAVD 1988 225.642 meters NAVD 1988 740.697 feet NGVD 1929 225.7649 meters NGVD 1929

DNR TBM FLK 10, 1994

In Fulton County, Culver Quad., in the NE ¼ of Sec. 9, T. 31 N., R. 1 E., 2nd PM; approximately 1.25 mile north of Delong; at the intersection of 700 North Road and 900 East Road, in the southwest quarter of the intersection; set in the southwest side of power pole #BCF 23, power pole has a guy pole with a guy wire on the north side of 700 North Road, 125.7 feet west of the centerline of 900 East Road, 85.3 feet west of a metal "stop" sign post, 23.5 feet east of a PK nail, 2.0 feet above the ground, in the north side of a 8.0 inch Pine tree, (east most Pine tree in a east-west line of Pine and Spruce trees), 18.0 feet south of the centerline of 700 North Road, 1.0 foot above the ground; a railroad spike driven thru an aluminum tag, stamped "IDNR TBM FLK 10, 1994".

738.304 feet NAVD 1988 225.035 meters NAVD 1988 738.703 feet NGVD 1929 225.157 meters NGVD 1929

State of Indiana <u>Department of Natural Resources</u> Division of Water

Control Station Descriptions and Elevations

FULTON COUNTY

The staff of the Department of Natural Resources, Division of Water, has developed the layout, surveys, adjustments, and publications of the following third-order area levels. All field survey records and publication procedures in the process of development of this list may be examined at the office of the Department in Indianapolis, Indiana.

DNR TBM 1-01788

In Fulton County, Rochester Quad., in the NE ¼ of SW 1/4 of Sec. 9, t. 30 N., R. 3 E., 2nd PM; approximately 0.3 mile west of the intersection of State Road 14 and State Road 25; set in the south side of a power pole, 85.5 feet south of the centerline of State Road 14; 55.0 feet west of the centerline of a road leading south from State Road 14, 45.5 feet north of a northwest-southeast road centerline; 0.8 foot above the ground; a railroad spike driven thru a stamped aluminum tag.

THIRD ORDER
THIRD ORDER

778.61 feet NGVD 1929 237.321 meters NGVD 1929

DNR TBM 2-01788

In Fulton County, Rochester Quad., in the NE ¼ of Sec. 14, T.30 N., R.3E., 2nd PM; in the southwest quadrant of the intersection of State Road 14 and 500 East Road; set in the north side of a power pole, 50.8 feet south of the centerline of State Road 14; 30.2 feet west of the centerline of 500 East Road, 0.5 foot above the ground; a railroad spike driven thru a stamped aluminum tag.

THIRD ORDER
THIRD ORDER

794.72 feet NGVD 1929 242.231 meters NGVD 1929

DNR TBM 3-01788

In Fulton County, Rochester Quad., in the SW ¼ of NW 1/4 of Sec. 14, T.30 N., R.3E., 2nd PM; at the Public Access Site for Lake Manitou; set in the west side of a 14 inch Willow tree, 76.0 feet southeast from centerline of 400 East Road, 38.5 feet northwest from centerline of the access road to the public access site; 81.7 feet northeast of a 6.3 foot diameter Cottonwood tree; 1.0 foot above the ground; a railroad spike driven thru a stamped aluminum tag.

THIRD ORDER
THIRD ORDER

784.03 feet NGVD 1929 238.973 meters NGVD 1929

DNR TBM 4-01788

In Fulton County, Rochester Quad., in the SW ¼ of SW 1/4 of Sec. 14, T.30 N., R.3E., 2nd PM; in the northwest quadrant of the "T" road intersection of 75 South Road and 400 East Road, 21.2 feet west of the centerline of 400 East Road, 65.7 feet north of the centerline of 75 South Road; 0.5 foot above the ground. set in the northeast side of a power pole; A railroad spike driven thru a stamped aluminum tag.

THIRD ORDER
THIRD ORDER

792.82 feet NGVD 1929 241.652 meters NGVD 1929

DNR TBM 6-01788

In Fulton County, Rochester Quad., in the SE ¼ of the NW 1/4 of Sec. 23, T. 30 N., R. 3 E., 2nd PM; approximately 500 feet northwest along Bassmore Road (400 East Road) from its intersection with 150 South Road; set in the north side of a 26 inch Sycamore tree, 64 feet southwest of the centerline of 400 East Road, 1.6 feet above the ground; a railroad spike.

THIRD ORDER
THIRD ORDER

784.64 feet NGVD 1929 239.159 meters NGVD 1929

DNR TBM FLK 1, 1980

In Fulton County, Akron Quad., in the SE 1/4 of the NW ¼ of Sec. 25, T. 30 N., R. 4 E.,2nd PM; approximately 1.0 mile southwest of <u>Akron</u>; at the County Road culvert over the channel between L Lake and Town Lake; set in the north side of a power pole, 57.5 feet east of the centerline of the culvert, 18.0 feet south of the centerline of the road, 2.5 feet northwest of a fence corner post, 0.5 foot above the ground; a railroad spike driven thru an aluminum tag, stamped "DNR TBM FLK 1, 1980".

THIRD ORDER
THIRD ORDER

843.109 feet NGVD 1929 256.9801 meters NGVD 1929

DNR TBM FLK 2, 1980

In Fulton County, Akron Quad., in the South ½ of Sec. 24, T. 30 N., R. 4 E., 2nd PM; approximately 0.5 mile southwest of Akron; at a 3 foot steel pipe culvert over the inlet channel of Town Lake; set in the top of the north end of the culvert, 11.5 feet east of a "Private Property Stay Out" sign post, 11.5 feet north of the centerline of a private drive, 2.7 feet below the drive, 0.05 foot south of the north end of the culvert; the center of two filed notches.

THIRD ORDER
THIRD ORDER

824.257 feet NGVD 1929 251.2340 meters NGVD 1929

DNR TBM FLK 3, 1980

In Fulton County, Akron Quad., in the NW ¼ of Sec. 25, T. 30 N., R. 4 E., 2nd PM; approximately 1.0 mile southwest of <u>Akron</u>; on the County Road west of the culvert over the channel between L Lake and Town Lake; set in the north side of a power pole, 300 feet west of the centerline of a drive, 16.0 feet south of the centerline of the County Road; a railroad spike driven thru an aluminum tag, stamped "DNR TBM FLK 3".

THIRD ORDER
THIRD ORDER

844.460 feet NGVD 1929 257.3919 meters NGVD 1929

DNR TBM FLK 4, 1980

In Fulton County, Akron Quad., in the NE ¼ of Sec. 26, T. 30 N., R. 4 E., 2nd PM; approximately 1.2 mile southwest of Akron; at the intersection of State Road 19 and a County Road; set in the north side of a power pole, 62.0 feet east of the centerline of State Road 19, 17.5 feet south of the centerline of the County Road, 0.3 foot above the ground; a railroad spike driven thru an aluminum tag, stamped "DNR TBM FLK 4, 1980".

THIRD ORDER THIRD ORDER

850.495 feet NGVD 1929 259.2314 meters NGVD 1929

DNR TBM TOWN 1980

In Fulton County, Akron Quad., in the South ½ of Sec. 24, T. 30 N., R. 4 E., 2nd PM; approximately 0.5 mile southwest of Akron; 0.1 mile north of the inlet channel of Town Lake; set in the west side of a power pole, at the intersection of a driveway west and a private north – south driveway, in the northwest quadrant of the intersection, 100 feet west of the centerline of the north – south private drive, 20.0 feet north of the centerline of the drive west, 0.5 foot above the ground; a 20 penny nail.

THIRD ORDER THIRD ORDER

830.178 feet NGVD 1929 253.0388 meters NGVD 1929