

## INDIANA DEPARTMENT OF LABOR - IOSHA

### TOP-50 INDUSTRIAL SAFETY STANDARDS CITED IN 2006

		TOTAL	SER	WIL	REP	OTH	
1*	1910.303(g)(2)(i) - Uninsulated live electrical parts	120	118	0	0	2	
2*	1910.212(a)(1) - General machine guarding	88	86	0	0	2	
3*	1910.1200(e)(1) - No written Haz Com program	67	20	0	0	47	
4	1910.215(b)(9) - Tongue guard on grinder - >1/4"	63	58	0	0	5	
5*	1910.1200(h)(1) - Employee training in Haz Com	52	19	0	0	33	
6	1910.23(c)(1) - Install standard railing - fall >4 feet	51	50	0	0	1	
7*	1910.1200(f)(5)(i) - Identify the hazardous chemical	46	11	0	0	35	
8	1910.304(f)(4) - Permanent electrical grounding	44	18	0	0	26	
9	1910.1200(f)(5)(ii) - Appropriate hazard warnings	41	10	0	0	31	
10**	22-8-1.1 Section 2 - General Duty Clause	41	41	0	0	0	
11	1910.304(f)(5)(v) - Provide electrical grounding	38	34	0	0	4	
12	1910.219(d)(1) - Guarding of pulleys	34	34	0	0	0	
13*	1910.305(b)(1) - Openings in electrical cabinets	32	5	0	0	27	
14	1910.1200(g)(8) - MSDS not readily accessible	32	3	0	0	29	
15	1910.253(b)(4)(iii) - Oxygen cylinders -20' or 5' high	31	7	0	0	24	
16	1910.242(b) - Compressed air for cleaning - >30 psi	30	3	0	0	27	
17*	1910.1200(g)(1) - MSDS for Haz Com	28	6	0	0	22	
18	1910.151(c) - No Eye/body flushing facilities	25	20	0	1	4	
19**	610 IAC 4-6-14 - Inaccurate OSHA #300, or #300A, or #301	23	0	0	0	23	
20*	1910.212(a)(3)(ii) - Guarding the point of operation	21	20	0	0	1	
21	1910.215(a)(4) - Work rest on grinder - >1/8"	18	16	0	0	2	
22*	1910.305(g)(1)(iii) - Cords & cables may not be used	18	8	0	0	10	
23	1910.22(d)(1) - Posting of floor load capacity	17	3	0	0	14	

24	1910.219(e)(3)(i) - Guarding of vertical and inclined belts	17	17	0	0	0
25	1910.133(a)(1) - Use appropriate eye or face protection	16	15	0	0	1
26*	1910.134(c)(1) - Establish written protection program	16	8	0	0	8
27*	1910.305(b)(2) - Electrical covers approved for the purpose	16	4	0	0	12
28	1910.219(e)(1)(i) - Guarding of horizontal belts	15	15	0	0	0
29	1910.219(f)(3) - Guarding of gears, sprockets, etc.	15	15	0	0	0
30*	1910.303(f) - Mark purpose of electrical disconnect	15	2	0	0	13
31*	1910.147(c)(4)(i) - Establish energy control procedures	14	12	0	0	2
32*	1910.178(p)(1) - Lift truck in need of repair	14	3	0	0	11
33	1910.213(h)(1) - Guarding of radial saw blade	14	14	0	0	0
34*	1910.178(l)(1)(i) - Forklift operator is competent to operate	12	10	0	0	2
35	1910.217(c)(2)(i)(A) - Reach through, over, under, around,	12	11	0	1	0
36	1910.253(b)(2)(ii) - Storage - vent - secure - 20' combustible	12	3	0	0	9
37*	1910.305(g)(2)(iii) - No strain relief for flexible cords	12	2	0	0	10
38*	1910.134(c)(2)(i) - Respirators supplied at employee request	11	0	0	1	10
39*	1910.134(e)(1) - Provide medical evaluation for employee	11	7	0	1	3
40	1910.138(a) - Select and use appropriate hand protection	11	6	0	0	5
41	1910.146(c)(2) - Inform employees of permit confined spaces	11	11	0	0	0
42	1910.303(e) - Mark voltage, current, and other ratings	11	3	0	0	8
43	1910.37(a)(4) - Maintain sprinklers, exit lights, alarms, etc	10	0	0	0	10
44	1910.95(c)(1) - Establish a hearing conservation program	10	9	0	0	1
45	1910.217(e)(1)(i) - Inspections of mechanical power presses	10	7	0	0	3
46	1910.304(a)(2) - Reversed polarity	10	0	0	0	10
47*	1910.147(c)(6)(i) - Annual inspection of the energy control	9	1	0	0	8
48*	1910.212(a)(5) - Unguarded fan blades < 7 feet above floor	9	9	0	0	0
49	1910.253(b)(4)(i) - Oxygen stored near combustible material	9	5	0	0	4
50	1910.22(a)(2) - Maintain floor in clean and dry condition	8	4	0	0	4

\* Recorded on the Federal OSHA September 2006 Top-50 list

\*\* Combined total cited by IOSHA general industry and construction inspections