



		CONSTRAINTS											
ALTERNATIVE WORK ZONE TYPES	LANE CONSTRUCTION (Use part of the shoulder if necessary)			✓	✓					✓			Restripe lanes lines; keep lanes 10 ft. or wider. For freeways and other divided highways, the minimum lane width is 11 ft.
	LANE CLOSURE							✓		✓	✓	✓	Restripe lanes lines; keep lanes 10 ft. or wider. For freeways and other divided highways, the minimum lane width is 11 ft.
	ONE-LANE, TWO-WAY OPERATION			✓	✓		✓						Traffic volume less than 1000 vehicles per hour both directions. (See INDOT computer program "WORK")
	RUNAROUND	✓			✓					✓			Sufficient right-of-way available.
	INTERMITTENT TOTAL CLOSURE	✓				✓				✓			Off-peak hours only.
	USE OF SHOULDER (As a full lane)			✓							✓		May need to upgrade shoulder structure.
	CROSSOVER						✓		✓				
	TWO-WAY TRAFFIC ON DIVIDED FACILITIES						✓		✓				
	DETOUR TO EXISTING ROAD	✓			✓	✓	✓	✓	✓		✓	✓	Reasonable detour route (s) available. Maintain local access.

✓ Feasible Alternatives

CHART FOR IDENTIFICATION OF FEASIBLE WORK ZONE TYPES

Figure 81-2H