

	Total Paved Width ^{1,2,3}	Travel-Lane Width ²	Paved-Shld. Width	Sealed-Agg. Shld. Width
AADT ≥ 5,000	D = 8.4 m M = 7.8 m	D = 3.6 m M = 3.6 m	D = 1.8 m M = 0.3 m	N / A
3,000 ≤ AADT < 5,000	D = 8.4 m M = 7.8 m	D = 3.6 m M = 3.6 m	D = 1.2 m M = 0.3 m	D = 0.9 m M = 0.6 m
400 ≤ AADT < 3,000	D = 8.4 m M = 7.2 m	D = 3.6 m M = 3.3 m	D = 0.6 m M = 0.3 m	D = 0.9 m M = 0.6 m
AADT < 400	D = 7.8 m M = 6.6 m	D = 3.3 m M = 3.0 m	D = 0.6 m M = 0.3 m	D = 0.6 m M = 0.3 m

D = Desirable, M = Minimum.

- ¹ Includes widths of travel lanes and paved shoulders only.
- ² Should be widened on a curve where possible as described in Section 43-2.06.
- ³ For a road with a TWLTL, the total width will be increased by the applicable width of a TWLTL.

PAVEMENT WIDTH FOR RURAL 2-LANE ROAD WITH SHOULDERS

Figure 56-4A