

Design Element			Manual Section	2-Lane					
Design Controls	Design--Year AADT		40-2.01	< 400	400 ≤ AADT < 1000	1000 ≤ AADT < 3000	3000 ≤ AADT < 5000	≥ 5000	
	Design Forecast Period		55-4.01	20 Years (2)					
	*Design Speed (mph)		55-4.01	See Section 55-4.01 (3)					
	Access Control		40-5.0	None					
	Level of Service		40-2.0	Desirable: B; Minimum: D					
Cross-Section Elements	Travel Lane	*Width (4)	55-4.05	Des: 10ft Min: 9 ft (4a)	Des: 11 ft Min: 10 ft (4b)	Des: 11 ft Min: 10 ft (4b)	Des: 12 ft Min: 11 ft	Des: 12 ft Min: 11 ft.(4c)	
		Typical Surface Type		Ch. 52	Asphalt / Concrete				
	Shoulder (5)	*Width Usable		55-4.05	Des: 4 ft Min: 2 ft	Des: 6 ft Min: 2 ft	Des: 6 ft Min: 3 ft	Des: 8 ft Min: 6 ft	Des: 10 ft Min: 8 ft
		*Width Paved		55-4.05	Des: 2 ft Min: 0 ft	Des: 2 ft Min: 0 ft	Des: 4 ft Min: 2 ft	Des: 6 ft Min: 2 ft	Des: 8 ft Min: 2 ft
		Typical Surface Type		Ch. 52	Asphalt / Aggregate / Earth				
	Cross Slope	*Travel Lane (6)		55-4.05	2%-3%				
		Shoulder (7)		55-4.05	Paved Width ≤ 4 ft 2% - 3%; Paved Width > 4 ft: 4%-6% Asphalt; 6%-8% Aggregate; 8% Earth				
	Auxiliary Lane	Lane Width		55-4.06	Des: 10 ft; Min: 9 ft		Des: 11 ft; Min: 10 ft		Des: 12 ft Min: 10 ft
		Shoulder Width			Des: Same as Next to Travel Lane; Min: 2 ft				
	Obstruction-Free-Zone Width			55-5.02	See Section 55-5.02				
	Side Slopes	Cut	Foreslope	55-4.05	2:1 or Flatter (8)				
			Ditch Width		(8)				
Backslope			2:1 or Flatter (8)						
Fill		55-4.05	2:1 or Flatter (8)						
Bridges**	New or Reconstructed Bridge	*Structural Capacity	Ch. 60	HL-93 (8A)					
		*Clear-Roadway Width (9)	55-6.03	Travelway +4 ft	Travelway +6 ft	Travelway +6 ft	Travelway +8 ft	Full Paved Appr. Width	
	Existing Bridge to Remain in Place	*Structural Capacity	Ch. 72	HS-15 (10)					
		*Clear-Roadway Width (11)	55-6.02	22 ft	22 ft	24 ft	28 ft	28 ft	
	*Vertical Clearance, Collector Under	New or Replaced Overpassing Bridge (12)		55-6.0	14.5 ft				
		Existing Overpassing Bridge			14.0 ft				
Vertical Clearance, Collector Over Railroad (13)			Ch. 69	23.0 ft					

Des: Desirable; Min: Minimum.

* Controlling design criterion. ** Selection of cross section and bridge elements is based on design-year traffic volume irrespective of design speed.

GEOMETRIC DESIGN CRITERIA FOR RURAL COLLECTOR, LOCAL-AGENCY ROUTE, 3R PROJECT

Figure 55-3C

Design Element		Manual Section	2-Lane					
Alignment Elements	Design Speed	---	30 mph	35 mph	45 mph	50 mph	55 mph	
	*Stopping Sight Distance, Desirable	55-4.02	200 ft	250 ft	360 ft	425 ft	495 ft	
	Decision Sight Distance	Speed / Path / Direction Change	42-2.0	450 ft	525 ft	675 ft	750 ft	865 ft
		Stop Maneuver		220 ft	275 ft	395ft	460ft	535 ft
	Passing Sight Distance	42-3.0	Existing	Existing	Existing	Existing	Existing	
	Intersection Sight Distance, -3% to +3% (15)	55-4.06	P: 330 ft SUT: 420 ft	P: 390 ft SUT: 490 ft	P: 500 ft SUT: 630 ft	P: 630 ft SUT: 780 ft	P: 730 ft SUT:890 ft	
	*Minimum Radius	55-4.03	See Section 55-4.03					
	*Superelevation Rate	55-4.03	See Section 55-4.03					
	*Horizontal Sight Distance	55-4.03	See Section 55-4.03					
	*Vertical Curvature, K-value	Crest	55-4.04	See Section 55-4.04				
		Sag		See Section 55-4.04				
	*Maximum Grade (14)	Level	55-4.04	9%	9%	8%	8%	7%
		Rolling		11%	10%	9%	9%	8%
Minimum Grade	44-1.03	Desirable: 0.5%; Minimum: 0.0%						

* Controlling design criterion. A deviation from such is a design exception, and is subject to approval. See Section 40-8.0.

An operational or maintenance change, permanent or temporary, exclusive of work-zone traffic control, that in fact creates substandard conditions such as by re-striping to obtain added lane(s) by reducing existing lane widths or shoulders, must be addressed in a design exception, whether or not actual construction or reconstruction is involved.

GEOMETRIC DESIGN CRITERIA FOR RURAL COLLECTOR, LOCAL-AGENCY ROUTE, 3R PROJECT

Figure 55-3C (Continued)

GEOMETRIC DESIGN CRITERIA FOR RURAL COLLECTOR, LOCAL-AGENCY ROUTE, 3R PROJECT

Footnotes to Figure 55-3C

- (1) Applicability. This figure is applicable only to a federal-aid funded project.
- (2) Design Forecast Period. For a partial 3R project, the pavement should be designed for at least a 10-year design life.
- (3) Design Speed. The minimum design speed should equal the anticipated posted speed limit after construction or the legal speed limit, 55 mph, on a non-posted highway.
- (4) Travel Lane, Width. An 11-ft travel lane width should be used where truck volume exceeds 200 trucks per day. In addition, the following will apply:
 - a. Where $V \geq 50$ mph, the minimum width is 10 ft.
 - b. Where $V \geq 50$ mph, the minimum width is 11 ft.
 - c. Where $V \geq 50$ mph, the minimum width is 12 ft.
- (5) Shoulder Width. The following will apply:
 - a. The desirable guardrail offset is 2 ft from the effective usable-shoulder width. See Section 49-5.0 for more information.
 - b. If guardrail is present, the minimum offset from the E.T.L. to face of guardrail should desirably be equal to the shy-line offset distance, but not less than 4 ft (see Section 49-5.0 for shy-line offsets).
 - c. Usable-shoulder width is defined as the distance from the edge of the travel lane to the shoulder break point.
- (6) Cross Slope, Travel Lane. Cross slopes of 1.5% are acceptable on an existing bridge to remain in place.
- (7) Cross Slope, Shoulder. Value is for a tangent section. See Figure 45-1A(1) or Figure 45-1A(2) for more-specific information. See Figure 43-3M or Figure 43-3N for shoulder cross slope on a horizontal curve.
- (8) Side Slopes. Section 55-4.05 provides additional information for side-slope criteria.

GEOMETRIC DESIGN CRITERIA FOR RURAL COLLECTOR, LOCAL-AGENCY ROUTE, 3R PROJECT

Footnotes to Figure 55-3C (Continued)

- (8A) Structural Capacity, New or Reconstructed Bridge. HL-93 loading should be applied. A bridge with an ADTT less than or equal to 1,000 may be designed for HL-93 or HS 20, whichever the LPA elects.
- (9) Width, New or Reconstructed Bridge. See Section 59-1.01(01) for more information. The clear-roadway width is the algebraic sum of the following:
- a. the approach traveled-way width;
 - b. the approach effective usable-shoulder width without guardrail; and
 - c. a bridge-railing offset (see Figure 59-1G).
- (10) Structural Capacity, Existing Bridge to Remain in Place. If the AADT ≤ 50 , an HS-10 loading is acceptable.
- (11) Width, Existing Bridge to Remain in Place. Clear-roadway width should be at least equal to the approach traveled way width or the value, whichever is greater. For a bridge of more than 100 ft in length, the value does not apply. The acceptability of such a bridge will be assessed individually.
- (12) Vertical Clearance, Collector Under. Value includes an additional 6-in. allowance for a future pavement overlay. Vertical clearance applies from usable edge to usable edge of shoulders.
- (13) Vertical Clearance, Collector Over Railroad. See Chapter Sixty-nine for additional information on railroad clearance under a highway.
- (14) Maximum Grade. For a grade of less than 500 ft in length (PVT to PVC), the maximum grade may be 2% steeper than the value. For a road with AADT < 400 , the maximum grade may also be 2% steeper.
- (15) Intersection Sight Distance. For left turn onto a 2-lane road, P = Passenger car; SUT = single unit truck. See Figure 46-10G for value for a combination truck.