




















LEGEND

	Flagger
	Work Area
	Flashing Arrow Sign
	Drum or cone
	Police Car (Optional)
	Construction Sign and Supports
	Minimum Length of Taper
	Low Intensity Construction Warning Light Type A
	Width of Offset
	Temporary Pavement Marking
	Removal of pavement markings and prismatic reflectors
	Temporary bituminous divider with tubular markers
	Typical Sign Standard (Road Closure Sign Assembly)
	Type B Construction Warning Lights
	Type III-A or Type III-B Barricades as required
	Flashing Arrow Sign
	Double Headed Flashing Arrow Sign
	Direction of Traffic

GENERAL NOTES

- ① Distances shown are typical except for minimum distances may be varied based on field conditions.
2. The spacing of drums and cones on tangents shall be as follows:
 - a. Where the posted speed limit is 40 m.p.h. or greater, the spacing shall be 100 ft.
 - b. Where the posted speed limit is less than 40 m.p.h., the spacing shall be 50 ft.
3. The spacing of cones and drums on tapers shall be numerically equal in feet to the posted speed limit in mph.
4. The flashing arrow sign shall not be placed on a sidewalk. The flashing arrow sign shall be placed at a distance of L/3 from the beginning of the taper.
5. For temporary lane closures during daylight hours, cones or tubular markers may be used in lieu of drums.
6. Temporary pavement markings will not be required for temporary daylight lane closures.
7. See Standard Drawing e 801-TCDV-02 for values of L.

INDIANA DEPARTMENT OF TRANSPORTATION									
TRAFFIC CONTROL									
LEGEND AND GENERAL NOTES									
MARCH 2002									
STANDARD DRAWING NO. E 801-TCLG-01									
	<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="border-bottom: 1px solid black; width: 80%;">/s/ Richard L. VanCleave</td> <td style="border-bottom: 1px solid black; width: 20%;">3-01-02</td> </tr> <tr> <td style="font-size: small;">DESIGN STANDARDS ENGINEER</td> <td style="font-size: small;">DATE</td> </tr> <tr> <td style="border-bottom: 1px solid black;">/s/ Richard K. Smutzer</td> <td style="border-bottom: 1px solid black;">3-01-02</td> </tr> <tr> <td style="font-size: small;">CHIEF HIGHWAY ENGINEER</td> <td style="font-size: small;">DATE</td> </tr> </table>	/s/ Richard L. VanCleave	3-01-02	DESIGN STANDARDS ENGINEER	DATE	/s/ Richard K. Smutzer	3-01-02	CHIEF HIGHWAY ENGINEER	DATE
/s/ Richard L. VanCleave	3-01-02								
DESIGN STANDARDS ENGINEER	DATE								
/s/ Richard K. Smutzer	3-01-02								
CHIEF HIGHWAY ENGINEER	DATE								
DESIGN STANDARDS ENGINEER									