


GRADING DETAIL FOR GUARDRAIL END TREATMENT TYPE I



GRADING DETAIL FOR GUARDRAIL END TREATMENT TYPE OS

NOTES:

- ① The required guardrail offset shall be 0 to 600 desirable as specified in The plans. The offset used between the the edge of required shoulder and the face of rail shall also be used to establish the berm width at the end of the guardrail end treatment.
- ② This distance may vary from 0 to 600 desirable.
- ③ These dimensions are based on a 600 guardrail offset and must be adjusted for other offset distances to maintain a 10:1 taper.
- ④ Grading profiles at Section A-A for types OS and type I guardrail end treatments are shown on Standard Drawings 601-GRET-08, and -09.
- ⑤ Limits of compacted aggregate.

All Dimension are in mm unless otherwise specified

INDIANA DEPARTMENT OF TRANSPORTATION	
GRADING AT GUARDRAIL END TREATMENTS	
SEPTEMBER 2002	
STANDARD DRAWING NO. 601-GRET-06	
	/s/ Richard L. VanCleave 9-03-02 DESIGN STANDARDS ENGINEER DATE
	/s/ Richard K. Smutzer 9-03-02 CHIEF HIGHWAY ENGINEER DATE
DESIGN STANDARDS ENGINEER	