


Furnish 2-0.30 \pm thick and 2-0.8 \pm thick shims per post.

SHIM DETAIL



STIFFENER PLATE DETAIL
(See table on Std. Dwg. No. E 802-SNGP-05 for dimensions and weight)





Plate thickness = t_3

Use H.S. bolts with hex head, & hex nut, one flat washer under each bolt head and bevel or flat washer (where required) under nut.


PERFORATED FUSE PLATE DETAIL

(See table on Std. Dwg. No. E 802-SNGP-06 for dimensions and weight)



BASE PLATE DETAIL
(See table on Std. Dwg. No. E 802-SNGP-05 for dimensions and weight)

7/8" bolt diameter



NOTE: The inside diameter of washer is equal to bolt diameter plus 1/8 in.

CLIPPED WASHER DETAIL
(See table for dimensions)

INDIANA DEPARTMENT OF TRANSPORTATION	
SIGN DETAILS	
MAY 2000	
STANDARD DRAWING NO. E 802-SNGP-04	
	/s/ Anthony L. Uremovich 5-01-00 DESIGN STANDARDS ENGINEER DATE
	/s/ Firooz Zandi 5-01-00 CHIEF HIGHWAY ENGINEER DATE
DESIGN STANDARDS ENGINEER	