

August 2, 2013

The following table is to convert a Section 402 HMA mixture to a Section 401 QC/QA HMA mixture. If lay rates are outside the ranges given for the type of course or there are additional questions, contact the Office of Pavement Engineering.

Mixture Type 	402 Type A or B	402 Type C	402 Type D
Lay Rate (lb/syd) 			
Surface			
165	QC/QA-HMA, 2, 64, Surface, 9.5mm	QC/QA-HMA, 3, 70, Surface, 9.5mm	QC/QA-HMA, 4, 70, Surface, 9.5mm
220 or 275	QC/QA-HMA, 2, 64, Surface, 12.5mm	QC/QA-HMA, 3, 70, Surface, 12.5mm	QC/QA-HMA, 3, 70, Surface, 12.5mm
Intermediate			
220	QC/QA-HMA, 2, 64, Intermediate, 12.5mm	QC/QA-HMA, 3, 64, Intermediate, 12.5mm	QC/QA-HMA, 4, 70, Intermediate, 12.5mm
275, 330 or 385	QC/QA-HMA, 2, 64, Intermediate, 19mm	QC/QA-HMA, 3, 64, Intermediate, 19mm	QC/QA-HMA, 4, 70, Intermediate, 19mm
Base			
275, 330 or 385	QC/QA-HMA, 2, 64, Base, 19 mm	QC/QA-HMA, 3, 64, Base, 19mm	QC/QA-HMA, 4, 64, Base, 19mm
440, 495, 550 or 605	QC/QA-HMA, 2, 64, Base, 25 mm	QC/QA-HMA, 3, 64, Base, 25 mm	QC/QA-HMA, 4, 64, Base, 25 mm