

## 107-C-208 USE OF CONES IN LIEU OF DRUMS

*(Adopted 03-30-07)*

SECTION 107, BEGIN LINE 444, DELETE AND INSERT AS FOLLOWS:

Pavements and shoulders having an edge drop of more than 3 in. (75 mm) shall be delineated with drums in accordance with 801.09. Delineation shall be at a maximum spacing of 200 ft (60 m). The use of cones in accordance with 801.08 will be permitted ~~during daylight hours in lieu of drums~~ *as shown on the plans except cones shall not be used for interstate lane restrictions.*

SECTION 801, BEGIN LINE 267, DELETE AND INSERT AS FOLLOWS:

Cones shall be made of a material to withstand impact without damage to striking vehicles. They shall have a substantial base to restrict overturning. Cones and tubular markers shall be as shown on the plans.

Cones shall be used only during temporary activities where portability is advantageous and they remain in place and do not create a hazard to traffic. The use of cones in lieu of drums will be permitted ~~during daylight hours unless otherwise directed~~ *as shown on the plans except cones shall not be used for interstate lane restrictions.*

Tubular markers shall be used for separating 2-lane 2-way traffic as shown on the plans or as directed.

Cones and tubular markers shall be secured in place either by weighting or adhesives. The use of metal bases will not be permitted.

---