

919-R-618 REFLECTIVE SHEETING MATERIAL

(Adopted 07-17-14)

The Standard Specifications are revised as follows:

SECTION 919, BEGIN LINE 86, DELETE AND INSERT AS FOLLOWS:

1. Reflective Sheeting

Reflective sheeting used for signs, channelizing and delineation devices shall be in accordance with ASTM D 4956. Type V *or higher* reflective sheeting ~~may~~ shall be used on delineators, *except for barrier delineators which shall be Type III or higher*. Reboundable reflective sheeting shall be used on plastic drums, flexible delineator posts, and other flexible channelizers.

The reflective sheeting shall include an adhesive backing Class 1 or Class 2 in accordance with ASTM D 4956.

SECTION 926, BEGIN LINE 51, INSERT AS FOLLOWS:

(b) Reflective Sheeting Delineators

Reflective sheeting delineators shall consist of reflective sheeting affixed to an aluminum backing material. The white delineator shall be 3 by 8 in. \pm 1/8 in. The yellow delineator shall be 5 by 5 in. \pm 1/8 in. The backing material shall be in accordance with 919.01(a) except the minimum thickness shall be 0.064 in. Reflective sheeting shall be in accordance with 919.01(b)1.

SECTION 926, BEGIN LINE 89, INSERT AS FOLLOWS:

(d) Temporary Barrier Delineator

Temporary barrier delineators shall consist of a type III *or higher* sheeting in accordance with 919.019(b)1 affixed to a reboundable substrate. The delineator shall be 8 by 12 in. vertically mounted. The mounting bracket used to affix the delineator to the barrier shall not be more than 3 in. vertical.
