801-T-221 BLACK TEMPORARY TAPE

(Adopted 04-19-18)

The Standard Specifications are revised as follows:

SECTION 801, BEGIN LINE 569, INSERT AS FOLLOWS:

Where temporary pavement markings are to be placed on a pavement which has existing markings, the existing markings which conflict with the temporary markings shall be removed in accordance with 808.10. On asphalt pavement, black temporary tape, Type I, may be used to cover conflicting markings. The black temporary tape shall extend at least 1/2 in. beyond the edges of the marking to be covered. Overlapping of temporary tape will not be allowed.

SECTION 801, BEGIN LINE 935, INSERT AS FOLLOWS:

Where temporary pavement markings are to be placed on a pavement which has existing markings, removal of the existing markings which conflict with the temporary markings will be measured in accordance with 808.12. Where conflicting markings are covered with black temporary tape, Type I, the black temporary tape will be measured by the linear foot of markings covered.

SECTION 801, BEGIN LINE 1017, INSERT AS FOLLOWS:

Where temporary pavement markings are to be placed on a pavement which has existing markings, removal of the existing markings which conflict with the temporary markings will be paid for in accordance with 808.13. Where conflicting markings are covered with black temporary tape, Type I, the specified width of black temporary tape will be paid for at the contract unit price per linear foot of temporary pavement marking, removable.

SECTION 923, BEGIN LINE 3, INSERT AS FOLLOWS:

923.01 Temporary Pavement Marking Tape

Temporary pavement marking tape shall be furnished in twothree colors and two types. It shall consist of a white or yellow reflecting film on a conformable backing which is a minimum of 4 in. wide, and is designed for marking either asphalt or concrete pavements. Black temporary pavement marking tape shall consist of a matte film on a conformable backing which is designed for marking asphalt pavement.—The White and yellow temporary pavement marking tape shall be in accordance with ASTM D 4592.

Type I tape shall be selected from the Department's list of approved Temporary Pavement Marking Tape, Type I. Temporary pavement marking tape type I will be placed and maintained on the Department's approved list in accordance with ITM 806, Procedure H.

Type I tape furnished under this specification shall be covered by a type C certification in accordance with 916.