

## 801-C-157 CERTIFICATION OF TEMPORARY TRAFFIC CONTROL DEVICES

(Revised 05-23-13)

**Category I Devices**

The Contractor shall certify that the following temporary traffic control devices to be used do not exceed the maximum values shown in the table below, and are considered crashworthy at Test Level 3 in accordance with NCHRP 350.

Device	Composition	Max. Weight	Max. Height
Single Piece Traffic Cones	Rubber	20 lb	36 in.
	Plastic	20 lb	48 in.
Tubular Markers	Rubber	13 lb	36 in.
	Plastic	13 lb	36 in.
Single Piece Drums	High Density Plastic	77 lb	36 in.
	Low Density Plastic	77 lb	36 in.
Delineators	Plastic, Fiberglass	N/A	48 in.

No lights, signs, flags, or other auxiliary attachments are included in the weight of the devices listed above. Reflective sheeting or reflective buttons are included on delineators. Maximum weights, including ballast, do not exceed the values shown in the table. "Single piece" refers to the construction of the body of the drum exclusive of a separate base, if any.

Type A or type C warning lights in accordance with the following specifications will be allowed on drums if they are firmly attached with vandal resistant 1/2 in. diameter by 4 in. cadmium plated steel bolt with nut and a 1 1/2 in. high cup washer.

1. The weight shall be no more than 5 lb.
2. The lens diameter shall be 7 to 8 in.
3. The height of the light shall be 11 to 14 in.

**Category II Devices**

Category II temporary traffic control devices include type III barricades, vertical panels, portable sign standards, and other light-weight traffic control devices.

Category II temporary traffic control devices shall be in accordance with the NCHRP 350, Test Level 3.

A form will be provided at the preconstruction conference for the Contractor to complete and return to the Engineer prior to the placement of category I or II traffic control devices.

---