

**SAMPLING ASPHALT MATERIALS  
AASHTO T 40**

**APPARATUS**

- Asphalt Material (except Emulsion)
  - Double friction-top can
  - Square can with screw top
  - Small mouth can with screw cap
  
- Emulsion
  - Wide-mouth jar made of glass or plastic
  - Bottle made of glass or plastic

**SAMPLE LOCATION**

- Bulk Storage Tank
  - Approved valve in tank
  - Approved valve in line
  
- Distributor
  - Approved sampling valve
  
- HMA Plant Storage Tank
  - Approved tank valve
  
- Transport
  - Approved sampling valve

**SAMPLE SIZE**

- Asphalt Materials (except Emulsions)
  - 1.0 qt
  
- Emulsions
  - 1/2 gal.

**PROCEDURE**

- At least four quarts are drained from the valve before sample is obtained
- Containers are sealed with clean, dry, tight fitting lids
- Spilled material is wiped from container with a clean, dry cloth that has not been dipped in solvent
- Containers are labeled clearly with a wick labeling pen. Lids are not labeled.

NA - Not Applicable  
X - Requires Corrective Action  
√ - Satisfactory

\_\_\_\_\_  
Acceptance Technician

\_\_\_\_\_  
INDOT

\_\_\_\_\_  
Date

Comments: \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_