

INDOT Gsb list ChangeLog

- All changes from the previous Gsb list will be highlighted in yellow on the latest Gsb list
 - All data will be presented in the following format:
 - Gsb/Absorption (Example: 2.600/1.50)
 - Contact Mary White with questions regarding changes or to request older data at:
 - (317) 610-7251x209 or mwhite@indot.in.gov
-

09/07/2016

- 2362 – IMI Muncie
 - Changed 8s Ledges 1-4 from 2.669/1.38 to 2.620/2.01
 - Changed 11s Ledges 1-4 from 2.634/1.90 to 2.607/2.24

08/16/2016

- 2498 – Rieth-Riley Construction Co., South Bend
 - Added Q/A 24 Man. Sand, values are 2.524/3.24

06/15/2016

- 2359 – IMI Stony Creek, Noblesville
 - Changed 12s Ledges 16-21 from 2.612/2.26 to 2.648/1.75
- 2621 – Mulzer Crushed Stone, Cape Sandy
 - Changed 8s Ledges 603-610 from 2.607/1.64 to 2.653/1.05

05/04/2016

- Added Concrete Gsb values for 8s and sands for use in Concrete Mix Designs
 - Please contact Michael Nelson, Concrete Engineer for further information
 - (317) 610-7251x234 or mnelson@indot.in.gov
- 2232 – Hanson Aggregates, Ft. Wayne
 - Changed note from Ledges 1-7EW to Ledges 1-7E
 - Changed 8s from 2.622/1.91 to 2.596/2.11
 - Changed 11s from 2.626/1.99 to 2.606/2.26
- 2238 – Stone Street Quarries, Ft. Wayne
 - Changed 8s Ledges 5-10, 11-14 from 2.696/1.30 to 2.702/1.15
 - Changed 11s Ledges 5-10, 11-14 from 2.628/2.25 to 2.682/1.58
 - Changed Sand Ledges 5-10, 11-14 from 2.654/2.04 to 2.725/1.28
- 2389 – Martin Marietta Aggregates, Noblesville

- Changed designation 8s and 11s from “Stone” to “Ledges 9-14”
- Changed 11s Ledges 9-14 from 2.633/2.05 to 2.582/2.50

- 2624 – Mulzer Crushed Stone, Tower Quarry, Leavenworth, IN
 - Added values for 8s and 11s for:
 - Ledges 601-602
 - Ledges 801-805
 - Ledge 805
 - Added values for Sand for:
 - Ledges 601-602