| PROFILE WALL POLYVINYL CHLORIDE PIPE HEIGHT OF COVER LIMITS (m) | | |
|---|---|---|
| DIAMETER (mm) | MINIMUM (m) | MAXIMUM (m) |
| 300 | 0.61 | 10.8 |
| 375 | 0.61 | 10.4 |
| 450 | 0.61 | 10.4 |
| 525 | 0.61 | 10.1 |
| 600 | 0.61 | 9.4 |
| 675 | 0.61 | 9.1 |
| 750 | 0.61 | 8.8 |
| 900 | 0.61 | 8.2 |

| SMOOTH WALL POLYVINYL CHLORIDE PIPE HEIGHT OF COVER LIMITS (m) | | | |
|---|---|---|---|
| PAY ITEM DIAMETER (mm) | NOMINAL DIAMETER (mm) | MINIMUM (m) | MAXIMUM (m) |
| 300 | 300 | 0.61 | 19.5 |
| 375 | 375 | 0.61 | 19.5 |
| 450 | 475 | 0.61 | 18.6 |
| 525 | 560 | 0.61 | 18.6 |
| 600 | 630 | 0.61 | 18.6 |
| 675 | 710 | 0.61 | 18.6 |

**NOTE:**

1. The tabulated cover depths shall be measured from the bottom of the concrete or asphalt pavement to the top of the pipe.

2. The pay item diameter reflects the minimum required inside diameter.

All dimensions are in mm unless otherwise specified.

INDIANA DEPARTMENT OF TRANSPORTATION

**PIPE HEIGHT OF COVER LIMITS**

MAY 1999

STANDARD DRAWING NO. **715-PHCL-19**

ANTHONY L. UREMOVICH REGISTERED No. 18095 STATE OF INDIANA PROFESSIONAL ENGINEER

DESIGN STANDARDS ENGINEER

/s/ Anthony L. Uremovich 5-03-99
DESIGN STANDARDS ENGINEER DATE

/s/ Donald W. Lucas 5-03-99
CHIEF HIGHWAY ENGINEER DATE

Source Sheet: NONE