GENERAL NOTES

1. This sign shall be used on expressways, freeways, and other roadways with design speeds of 70 km/h or more.
2. The minimum vertical and horizontal clearances for construction signs shall be as on Standard Drawing 801-TCDV-05.
3. See Standard Drawing 801-TCDV-08 for U-Channel Steel Post Splice Detail.
4. The minimum depth for wood or steel posts shall be 1.10 m.

9. This sign shall be removed, covered, or turned to face away from the roadway during non-working hours.

10. This sign may be ordered to read "500 Ft.", "1000 Ft.", or "1500 Ft." in place of the word "Ahead". Such signs may be used in place of, or in conjunction with, the indicated sign.

All Dimension are in mm unless otherwise specfied

INDIANA DEPARTMENT OF TRANSPORTATION

CONSTRUCTION SIGNS
GENERAL NOTES

SEPTEMBER 2002

STANDARD DRAWING NO. 801-TCSN-11

RICHARD L. VanCLEAVE REGISTERED No. 9750 STATE OF INDIANA PROFESSIONAL ENGINEER

DESIGN STANDARDS ENGINEER

/s/ Richard L. VanCleave 9-03-02
DESIGN STANDARDS ENGINEER DATE

/s/ Richard K. Smulzer 9-03-02
CHIEF HIGHWAY ENGINEER DATE