

STATE OF INDIANA
DEPARTMENT OF NATURAL RESOURCES

John E. Mitchell, Director

BULLETIN NO. 37

OF THE

DIVISION OF WATER

Robert F. Jackson, Chief

WATER RESOURCES OF DELAWARE COUNTY, INDIANA

BY

R. E. Hoggatt - U. S. Geological Survey

J. D. Hunn - U. S. Geological Survey

W. J. Steen - Indiana Department of Natural Resources

Prepared by the
GEOLOGICAL SURVEY
UNITED STATES DEPARTMENT OF THE INTERIOR
and the
STATE OF INDIANA
DEPARTMENT OF NATURAL RESOURCES
DIVISION OF WATER

CONTENTS

	Page
Abstract.....	1
Purpose and scope.....	2
Cooperation and acknowledgements.....	2
Water use.....	3
Physical features affecting water supply.....	4
Climate.....	4
Topography and drainage.....	5
Surficial geology.....	7
Sources of water supply.....	7
Streams.....	7
Application of streamflow data.....	8
Flow duration.....	8
Low-flow frequency.....	11
Base-flow measurements.....	17
Draft-storage requirements.....	17
Summary of low-flow stream characteristics.....	17
Application of techniques of water planning.....	21
Development potential.....	23
Mississinewa River and tributaries.....	23
White River and tributaries.....	24
Glacial deposits.....	25
Sand and gravel aquifers.....	25
Recharge and discharge.....	25
Development and potential.....	30
Principal Pleistocene aquifer.....	30
Deeper sand and gravel aquifers.....	30
Total potential of glacial deposits.....	30
Bedrock formations.....	34
Silurian dolomite.....	34
Water-bearing characteristics.....	34
Recharge and discharge.....	34
Development and potential.....	36
Quality of the water supply.....	39
Chemical and physical quality of the surface water.....	39
Chemical quality of the ground water.....	48
Effects of man's activities on water quality.....	49
Planning water development.....	50
Problems to consider.....	52
Conclusions.....	53
Definitions.....	54
Selected references.....	55

ILLUSTRATIONS

	Page
Plate 1. Map of upper Mississinewa and White River basins embracing Delaware County showing stream runoff for the week of November 11, 1963 at about 90 percent flow duration.....	In Pocket
Figure 1. About one-third of the precipitation that falls on Delaware County runs off in the streams.....	6
2. Duration curves of daily flows at seven gaging stations on the Mississinewa River, White River and Buck Creek.....	10
3. Magnitude and frequency of 7-day low flow at seven gaging stations on the Mississinewa River, White River and Buck Creek.....	16
4. Storage-required graphs for Mississinewa River near Ridgeville and Mississinewa River near Eaton.....	18
5. Storage-required graphs for Buck Creek near Muncie, White River at Anderson and White River at Muncie.....	19
6. Generalized cross section showing aquifers and confining layers.....	26
7. Average recharge and discharge of shallow glacial deposits.....	27
8. Discharge of ground water to streams.....	29
9. Capability of the principal Pleistocene aquifer as a source of water.....	31
10. Depth to the water-bearing zone in the principal Pleistocene aquifer.....	32
11. Known distribution of sand and gravel in and near buried bedrock valleys.....	33

	Page
Figure 12. Average recharge and discharge of the Silurian dolomite and the deeper sand and gravel aquifers.....	35
13. Capability of the Silurian aquifer as a source of water.....	37
14. Map of Delaware County showing approximate depth to bedrock.....	38
15. General raw water criteria for significant chemical constituents for drinking water and several industrial uses.....	40
16. Concentration of chloride in the streams of Delaware County at about 90 percent flow duration (week of November 11, 1963).....	41
17. Concentration of sulfates in the streams of Delaware County at about 90 percent flow duration (week of November 11, 1963).....	42
18. Concentration of total dissolved solids in the streams of Delaware County at about 90 percent flow duration (week of November 11, 1963).....	43
19. Relation of mineral concentration to river discharge.....	44
20. Variation in approximate average water temperature during year for Mississinewa River near Eaton, White River at Muncie and Buck Creek near Muncie.....	45
21. Quality of ground water in Delaware County.....	46
22. Concentration of synthetic detergents (ABS) in the Mississinewa and White Rivers in Delaware County during week of November 11, 1963 at about 90 percent flow duration.....	51
23. Concentration of dissolved oxygen in the Mississinewa and White Rivers in Delaware County during week of November 11, 1963 at about 90 percent flow duration.....	52

TABLES

	Page
Table 1. Estimates of water use in millions of gallons per day, for 1964 and 1980.....	3
2. Average monthly, annual, and seasonal (April through September) precipitation and temperature of east-central Indiana.....	5
3. List of stream-gaging stations, partial-record stations, and miscellaneous sites used in this report.....	9
4. Discharge of equal percent flow duration as taken from gaging station flow-duration curves and computed for intervening areas.....	12
5. Selected low-flow frequency and flow-duration data for partial-record stations and miscellaneous sites in the upper Mississinewa and White River basins embracing Delaware County.....	13
6. Low-flow frequency as taken from gaging station low-flow frequency curves.....	14
7. Average discharge, instantaneous minimum, and lowest two minimum average flows for 1-, 3-, 7-, 14-, 30-, and 60-day consecutive periods for gaging stations on the Mississinewa River, White River and Buck Creek.....	22
8. Summary of water quality in Delaware County...	47

WATER RESOURCES OF DELAWARE COUNTY, INDIANA

By R. E. Hoggatt, J. D. Hunn,

and W. J. Steen

ABSTRACT

In Delaware County, Indiana, water of sufficient quantity and quality is available with proper development in the streams and in the aquifers for the expected increase of most agricultural, domestic, industrial, and municipal uses in the foreseeable future.

Water use in Delaware County totals about 18.5 mgd (million gallons per day) of which 63 percent is from surface water and 37 percent from ground water. Muncie uses about 80 percent of the total water used in the county.

The White River at Muncie yields a natural flow (after adjustment for diversion) of more than 20 cfs (cubic feet per second) (13 mgd) 90 percent of the time from a drainage area of 242 square miles. Low flow in White River is augmented by releases from Prairie Creek Reservoir for the Muncie water supply.

The Mississinewa River offers good development potential, although the low flow is not as well sustained as in the White River. By way of comparison, the Mississinewa River 3 miles upstream from Eaton, drainage area 304 square miles, yields more than 8 cfs (5 mgd) 90 percent of the time.

Many small streams in the northern half of the county frequently go dry, while most streams in the southern half of the county, regardless of size, yield more than 0.013 mgd per square mile 90 percent of the time. Buck Creek has the highest low-flow yield of all the small streams in the county. At the stream-gaging station on Buck Creek near Muncie, drainage area 36.7 square miles, the flow exceeds 10 cfs (6.5 mgd) 90 percent of the time.

Nearly all the available ground water occurs within 400 feet of the land surface. Wells utilizing all available water-bearing zones could probably yield as much as 1,000 gpm (gallons per minute) in the south central and southeastern parts of the county.

The upper 100 feet of dolomite of Silurian Age, at the bedrock surface, is one of the two principal aquifers in the county. It underlies the entire county at depths ranging from 0 to about 300 feet. The most permeable parts of this aquifer could yield as much as 500 gpm to individual wells.

Sand and gravel in and near buried valleys yield water for domestic and industrial use. The areal extent and potential of this unit are not well known.

The principal Pleistocene aquifer is composed chiefly of glacio-fluvial sand and gravel up to 80 feet thick and underlies most of the county at depths of 0 to about 140 feet. The thicker parts of this aquifer could yield as much as 500 gpm to individual wells.

The surface and ground waters in Delaware County are generally a calcium bicarbonate type with moderate amounts of sulfate and hardness. The ground water may contain objectionable concentrations of iron. The chemical quality of the ground water is similar in all important aquifers in the county. The quality of the streams at about 90 percent flow duration approximates that of the ground water except where activities of man have increased the mineralization of the streams.

PURPOSE AND SCOPE

The purpose of this report is to describe for those concerned with water development and use in Delaware County (1) the sources of available water for current and future uses, (2) the quantity, distribution, and quality of the resource, and (3) some of the significant relations in the hydrologic system between precipitation, geology, ground water, surface water, and water quality.

This purpose was accomplished by analyzing information based on (1) well data and aquifer characteristics collected from drillers, water works superintendents, industries and others, (2) streamflow data based on 7 stream-gaging station records, 4 partial-record station measurements and base-flow measurements at miscellaneous sites, (3) quality-of-water data based on samples collected from the streams during low flows, from wells, and at water quality monitoring stations, and (4) field investigation of the surficial geology of the county.

This report provides information that will be useful in planning the development, control, and utilization of surface and ground waters in Delaware County. Some of the problems to be considered by the water user in the development of the resource are discussed.

COOPERATION AND ACKNOWLEDGEMENTS

This report was prepared as part of a cooperative program between the Indiana Department of Natural Resources, Division of Water and the U. S. Geological Survey, Water Resources Division. The work was done under the general guidance of the Indiana Council, Water Resources Division, U. S. Geological Survey.

The authors thank all persons and State Agencies who contributed time, information, and assistance during the preparation of this report. We especially thank the well drillers who furnished well logs and other

information, as well as the Muncie Water Works Company, industries, firms, and water works superintendents who contributed information. The Indiana State Highway Commission supplied locations and logs of test borings and the Indiana State Board of Health and Stream Pollution Control Board furnished water-quality data at monitoring stations on the Mississinewa and White Rivers.

WATER USE

Water use in Delaware County is presently about 18.5 mgd (million gallons per day) or 155 gpd (gallons per day) per person. Water use has been increasing at the rate of about 2 gallons per person per year since 1950. It is estimated that by 1980 the requirements will be nearly 190 gpd per person or a total of 31.5 mgd for the county.

An inventory of municipal and industrial water consumption was made in order to obtain information on present water use in the county and to outline future water needs. These data and records, obtained from water users, the Indiana Public Service Commission, Indiana State Board of Health, and other sources, were utilized in formulating an estimate of the amount of water used in the county.

A compilation of these data along with projected estimates of water use in 1980 are shown in table 1. The estimates for 1980 are made on the assumption that the use of surface water and ground water will have the same ratio as at the present time and that Muncie will be the only surface water user. A small amount of surface water has been used in time past for irrigation, probably less than 0.1 mgd. A larger amount will probably be used in the future when climatic factors are unfavorable during the growing season. As water used for irrigation is such a nebulous figure to estimate in Delaware County, no estimate has been entered in table 1 for either 1964 or 1980.

Table 1. Estimates of water use in Delaware County in millions of gallons per day, for 1964 and 1980.

Source and use	1964	1980
Surface Water		
Industrial	5.8	9.8
Municipal	5.9	10.0
Self-supplied domestic	0	0
Total	11.7	19.8
Ground Water		
Industrial	3.7	6.4
Municipal	.6	1.0
Self-supplied domestic	2.5	4.3
Total	6.8	11.7
Grand Total	18.5	31.5

Water use today is the highest in the history of Delaware County, and the trend has been upward for many years with no indication of leveling off. Of the 18.5 mgd used at present, industry uses about one-half, with the remaining part divided between municipal (Albany, Eaton, Gaston, Muncie and Yorktown) and self-supplied domestic use (table 1). Most municipal and industrial use is not consumptive, and used water is disposed of in the streams usually after treatment.

Industrial and municipal use is concentrated in the Muncie area, where the combined use is about 14.7 mgd, or 80 percent of the total water used in the county. This 14.7 mgd includes water taken from White River, Prairie Creek Reservoir, Buck Creek, and wells. Of the total used in the county, about 11.7 mgd, or 63 percent, is taken from surface water sources, with the remainder, 37 percent, being obtained from numerous municipal, industrial and domestic ground-water supplies.

Population trends have likewise been progressing upward. With an expected increase in population from 120,000 (estimated) in 1964 to about 167,000 by 1980 (Hannaford, 1960, p. 7), water consumption is expected to increase from the present 155 gpd per person (18.5 mgd) to about 190 gpd per person (31.5 mgd). Of this estimated total volume, about 19.8 mgd will probably be taken from surface water sources, primarily White River, Prairie Creek Reservoir and Buck Creek, and the remainder from well supplies.

PHYSICAL FEATURES AFFECTING WATER SUPPLY

Climate

Precipitation, temperature, and wind are climatic factors directly affecting surface and ground-water supplies. Precipitation adds water to the streams and ground-water reservoirs causing water levels to rise. During dry periods water used or flowing out of an area is not replenished, and water levels fall. High temperature and wind cause water levels to fall by increasing the amount of water returned to the atmosphere by evaporation (from exposed water surfaces) and transpiration (from plants). High temperatures likewise cause water levels to fall by increasing the withdrawals by man for both his personal comfort and industry.

In east-central Indiana, which embraces Delaware County, precipitation averages about 39 inches per year, with monthly averages ranging from 2.37 inches for February to 4.50 inches for June. Much of the precipitation that replenishes the ground-water supply occurs during the early spring and late fall months. Although precipitation is slightly less during these periods, recharge is greater than during the growing season, when monthly precipitation averages are higher. During the growing season, the evaporation and the transpiration losses are large and percolation of precipitation to the ground-water reservoirs is greatly decreased. The average monthly, annual, and seasonal (April through September) precipitation and temperature of east-central Indiana for the period 1931-60 are shown in table 2.

Table 2. Average monthly, annual, and seasonal (April through September) precipitation and temperature of east-central Indiana, 1931-60.

Month	Average Precipitation (inches)	Average Temperature (°F)
January	3.03	29.4
February	2.37	30.9
March	3.35	38.8
April	3.78	50.5
May	4.13	60.9
June	4.50	70.7
July	3.60	74.2
August	2.98	72.5
September	3.31	65.5
October	2.77	54.5
November	2.93	41.1
December	2.52	31.1
Annual	39.27	51.7
April through September	22.30	65.7


From U. S. Weather Bureau Data

The annual runoff of the White River at Muncie, adjusted to natural flow, is compared with the annual precipitation of east-central Indiana for the period of 1931-62 in figure 1. The similarity between the two graphs (A of fig. 1) is apparent, with the lowest annual flows in White River generally coinciding with periods of lowest precipitation. The ratio of runoff to precipitation is not constant, however, (B of fig. 1) varying from 0.08 in 1941 to 0.50 in 1950. Soil moisture, amount of precipitation, intensity of precipitation, distribution of precipitation throughout the year, and water levels in ground-water aquifers, as well as other factors, have their effect on the proportion of precipitation that runs off into the stream by either overland or underground flow.


Topography and Drainage

The topography of Delaware County is flat to gently rolling with a dendritic drainage pattern.

Land elevations are highest in the southeastern part of the county where the maximum is about 1,100 feet above mean sea level. The land slopes downward gradually from this area towards the northwest and west. The lowest elevation is 835 feet above mean sea level in the northwestern part where the Mississinewa River flows from the county. Maximum local relief of approximately 80 feet occurs near the south-central edge of the county.



A. The lowest annual flow in White River generally coincides with the lowest annual precipitation



B. The ratio between rainfall and runoff is not constant

Figure 1.—About one-third of the precipitation that falls on Delaware County runs off in the streams.

Delaware County lies within the White River and Mississinewa River drainage basins. Of the 392 square miles of area in the county, approximately two-thirds is drained by the White River system which includes Prairie, Buck, York Prairie, Killbuck and Pipe Creeks. The Mississinewa River and its tributaries drain the northeastern part of the county.

The White River flows generally westward through the county, and the Mississinewa flows in a northwesterly direction. The slopes of the stream channels are about 3.3 and 3.9 feet per mile for the Mississinewa and White Rivers, respectively, as they flow through the county. Several of the smaller streams have been dredged to improve the surface drainage.

Surficial Geology

The land surface of Delaware County is almost entirely covered by a relatively impermeable layer of glacial till and some silt. This deposit limits the amount of ground-water recharge and the amount of ground-water discharge to streams. The unit helps prevent the direct contamination of aquifers by man-made wastes.

Differences in base flow of the streams of Delaware County are caused by: (1) the unequal distribution and hydraulic properties of sand and gravel deposits beneath the surface till, (2) variations in thickness and permeability of the till, and (3) variations of the heights of the piezometric surfaces of the till and of the underlying saturated material above or below the level of the streams. The pick up of base flow in the streams compared with the size of the drainage area indicates the relative availability of ground water in the drift upstream from the points of measurement.

SOURCES OF WATER SUPPLY

The major sources of water in Delaware County are the streams, the upper 400 feet of the glacial drift, and the bedrock. The streams supply the largest amount of water and this amount could be increased by impoundments. The rocks generally provide adequate amounts of water and this amount could be increased by additional wells.

Streams

The average annual precipitation for the county is 39 inches. Of this amount about 12 inches, or 82 billion gallons, drains out of the county through the stream system. The quantity of water in the streams at any given time varies considerably from flood to drought. The amount that can be obtained as a dependable supply is highly variable from stream to stream, as well as at different locations on the same stream.

Application of Streamflow Data

The water available in the streams without impoundment has been evaluated by three techniques: (1) flow duration, (2) low-flow frequency, and (3) base-flow discharge measurements. The water that would be available by impoundment in the vicinity of the stream-gaging stations has been evaluated by a fourth technique: determination of draft-storage requirements. The first two techniques are statistical studies based on records of daily discharges collected at stream-gaging stations. The third technique is the comparison of base-flow (ground-water runoff) increase or decrease from various streams by obtaining discharge measurements when there is no overland runoff into the streams. The fourth technique is based on the low-flow frequency analysis and is used as a design tool. The two statistical studies were developed for a common time interval of 1924-63 by correlation of short-term with long-term water discharge records. A common reference period tends to equalize or make homogeneous climatic experiences.

These studies were based on records from 7 stream-gaging stations and measurements at 4 partial-record stations and 69 miscellaneous sites (including some observations of no flow) in the upper Mississinewa and White River basins embracing Delaware County. A list of the stations and sites is given in table 3, and the location of each is shown on plate 1.

The works of man have greatly altered the discharge of some streams or certain reaches of the channels. Most of these man-made effects are much more pronounced during low flows. At these times a considerable percentage of the total flow may be man supplied through waste or sanitary systems and reservoir releases, or man deleted or detained, through water supplies including reservoir storage. Adjustments have been made to some of the observed data to approach natural flow. Where observed data have been adjusted, this has been noted on the figures and in the tables.

Flow duration. Flow characteristics of a stream throughout its range in discharge may be shown by the flow-duration curve. A flow-duration curve shows the percentage of time discharges have been equaled or exceeded during a given period without regard to the sequence of occurrence. If the period upon which the curve is based represents a long-term flow of a stream, the curve may be used to estimate distribution of future flows for water supply and pollution studies. The slope of the duration curve is a quantitative measure of the variability of the streamflow and a flat slope on the lower end depicts well sustained flow.

The variation in flow at the 7 gaging stations is illustrated in figure 2. These flow-duration curves have been expressed in cubic feet per second per square mile (cfs/m) so that they might be compared on a unit basis.

Table 3.--List of stream-gaging stations, partial-record stations, and miscellaneous sites used in this report and shown on Plate 1

Reference no.	Stream and location	Drainage area (sq mi)	Type of collection point	Reference no.	Stream and location	Drainage area (sq mi)	Type of collection point
1	Mississinewa River near Salem	25.0	M. S.	41	Cunningham ditch near New Burlington	1.95	M. S.
2	Harshman Creek near Salem	13.2	M. S.	42	Prairie Creek near Muncie (Reservoir release)	17.0	M. S.
3	Mississinewa River near Ridgeville	130	S. G. S.	43	Medford drain near Muncie	2.14	M. S.
4	Bear Creek near Ridgeville	15.0	M. S.	44	White River tributary near Muncie	3.83	M. S.
5	Platt Nibarger ditch near Redkey	5.81	M. S.	45	Muncie Creek near Desoto	3.82	M. S.
6	Mississinewa River near Albany	228	M. S.	46	Muncie Creek near Muncie	5.50	M. S.
7	Mud Creek near Albany	11.7	M. S.	47	White River at Muncie	242	S. G. S.
8	Halfway Creek near Albany	21.8	M. S.	48	White River near Yorktown	246	M. S.
9	Campbells Creek near Parker City	10.2	M. S.	49	Buck Creek near Oakville	27.1	M. S.
10	Campbells Creek near Desoto	20.4	M. S.	50	Buck Creek near Muncie	36.7	S. G. S.
11	Mississinewa River tributary near Albany	2.35	M. S.	51	Buck Creek near Yorktown	48.5	M. S.
12	Mississinewa River tributary near Royerton	.93	M. S.	52	Bell Creek near Cross Roads	16.0	M. S.
13	Bosman ditch near Albany	3.12	M. S.	53	Williams Creek near Cross Roads	11.7	M. S.
14	Bosman ditch tributary near Albany	1.56	M. S.	54	No Name Creek near Progress	7.55	M. S.
15	Bosman ditch near Eaton	6.10	M. S.	55	Little No Name Creek near Progress	2.63	M. S.
16	Mississinewa River near Eaton	304	S. G. S.	56	York Prairie Creek near Muncie	3.43	M. S.
17	Rees ditch near Dunkirk	6.43	M. S.	57	York Prairie Creek near Cammack	9.70	M. S.
18	Rees ditch near Millgrove	8.07	M. S.	58	York Prairie Creek near Yorktown	16.2	M. S.
19	Rees ditch near Eaton	13.5	M. S.	59	White River near Daleville	383	M. S.
20	Mississinewa River near Wheeling	348	M. S.	60	White River at Anderson	401	S. G. S.
21	Big Lick Creek near Hartford City	32.9	M. S.	61	Killbuck Creek near Anthony	7.35	M. S.
22	Big Lick Creek near Wheeling	76.4	P. R. S.	62	Mud Creek near Anthony	6.52	M. S.
23	Studebaker ditch near Wheeling	10.5	M. S.	63	Killbuck Creek near Bethel	26.1	M. S.
24	Hayden ditch near Wheeling	4.45	M. S.	64	Thurston ditch near Bethel	1.63	M. S.
25	Hedgeland ditch near Wheeling	2.76	M. S.	65	Jakes Creek near Cammack	8.64	M. S.
26	Pike Creek at Wheeling	21.5	M. S.	66	Eagle Branch near Cammack	5.01	M. S.
27	Hoppas ditch at Matthews	8.14	M. S.	67	Jakes Creek near Bethel	18.5	M. S.
28	Lake Branch near Upland	9.15	M. S.	68	Pleasant Run Creek near Gilman	4.91	M. S.
29	Barren Creek near Upland	20.7	M. S.	69	Killbuck Creek near North Anderson	74.4	M. S.
30	Mississinewa River near Upland	515	M. S.	70	Killbuck Creek near Anderson	98.0	P. R. S.
31	Mississinewa River at Marion	677	S. G. S.	71	White River at Perkinsville	557	M. S.
32	White River near Harrisville	21.3	P. R. S.	72	Pipe Creek at Gaston	1.30	M. S.
33	White River at Winchester	34.1	M. S.	73	Yeager, Finley, Manard ditch near Gaston	7.43	M. S.
34	White River tributary near Maxville	1.15	M. S.	74	Steel ditch near Gaston	.67	M. S.
35	Eightmile Creek near Maxville	8.06	M. S.	75	Pipe Creek near Gaston	18.3	M. S.
36	White River near Farmland	84.5	M. S.	76	Pipe Creek near Alexandria	44.7	P. R. S.
37	Stoney Creek near Blountsville	18.7	M. S.	77	Pipe Creek near Frankton	108	M. S.
38	Stoney Creek tributary near Blountsville	1.03	M. S.	78	White River near Noblesville	814	S. G. S.
39	White River near Selma	179	M. S.	79	Fall Creek near Cross Roads	4.97	M. S.
40	Mud Creek near Selma	6.27	M. S.	80	Brandon ditch near Middleton	5.42	M. S.

S. G. S. - Stream-gaging station P. R. S. - Partial-record station M. S. - Miscellaneous site




Figure 2-Duration curves of daily flows at seven gaging stations on the Mississinewa River, White River and Buck Creek (adjusted to period, 1924-1963)

Discharges of equal percent duration for the lower half of the flow-duration curves, which contain larger percentages of ground-water runoff as the flow decreases, have been tabulated and shown both in terms of cubic feet per second (cfs) and cfsm in table 4. As a means of comparing the inflow between gaging stations, table 4 also contains computed runoff figures for the intervening drainage areas.

To supplement the flow-duration data for the stream-gaging stations, the 90 and 95 percent flow-duration discharges at 4 partial-record stations and 11 miscellaneous sites have been estimated by correlation and are tabulated in table 5.

Low-flow frequency. Since the flow-duration curve does not show the frequency with which any given discharge can be expected to occur on the average, it is necessary to know more about low-flow characteristics of the stream. The low-flow frequency curve is an excellent tool for estimating how frequently a certain average low-flow discharge for a given period of consecutive days will occur. It can also be used in the analysis of storage requirements. The shapes of low-flow frequency curves, like the flow duration curves, reflect the hydrogeologic and hydraulic characteristics of the upstream basin.

Low-flow frequency data for the 3-, 7-, 14-, 30-, 60-, 120-, 183-, and 274-day consecutive periods are presented in table 6 for the same 7 stream-gaging stations for which flow-duration data are tabulated and illustrated. The 7-day low-flow frequency curve for each of these stream-gaging stations is illustrated in figure 3. These low-flow frequency curves have been expressed in cfsm so that they might be compared on a unit basis.

To avoid misuse of these data it might be well to discuss recurrence interval (frequency), as used in this study. By definition, the recurrence interval, given in years, is the long-term average interval between annual minimum discharges equal to or less than the given minimum. For example, inference should not be made that the 3-day 10-year minimum will occur once, and only once during a 10-year period. It may occur in any year or successive years, but its chance of occurring as an annual 3-day minimum in any year is 1 in 10, or 10 percent.

To supplement the low-flow frequency data for the stream-gaging stations, the 7-day 2-year and 7-day 10-year low-flow have been estimated for the 4 partial-record stations and 11 miscellaneous sites where several base-flow measurements have been made and tabulated in table 5.

As with flow-duration studies, estimates of average low-flow frequency are based on records of past events and it is impossible to foresee what the future works of man will do to alter the natural flow.

Table 4.--Discharge of equal percent flow duration as taken from stream-gaging station flow-duration curves and computed for intervening areas (adjusted to the period 1924-63)

Reference no.	Gaging station and intervening areas	Drainage area (sq mi)	Discharge of indicated percent time duration (cubic feet per second, over cubic feet per second per square mile)									
			99.5	99	98	95	90	80	70	60	50	
3	Mississinewa River near Ridgeville	130	0.2	0.4	0.7	1.3	2.2	4.2	7.8	13	22	.169
			.002	.003	.005	.010	.017	.032	.060			
16	Intervening - Ridgeville to Eaton	174	2.1	2.3	2.8	4.0	5.8	10.8	17.2	25	36	.207
			.012	.013	.016	.023	.033	.062	.099			
31	Mississinewa River near Eaton	304	2.3	2.7	3.5	5.3	8.0	15	25	38	58	.191
			.008	.009	.012	.017	.026	.049	.082			
31	Intervening - Eaton to Marion	373	20.7	23.3	26.5	31.7	37	47	60	82	117	.314
			.055	.062	.071	.085	.099	.126	.161			
47	Mississinewa River at Marion (adjusted for low flow regulation)	677	23	26	30	37	45	62	85	120	175	.258
			.034	.038	.044	.055	.066	.092	.126			
50	White River at Muncie (adjusted to natural flow by adding diversion for water supply)	242	7.6	9.0	11	15	20	29	42	59	80	.331
			.031	.027	.045	.062	.083	.120	.174			
60	Buck Creek near Muncie	36.7	4.5	5.3	6.2	8.0	10	13	16	19	22	.599
			.23	.144	.69	.218	.272	.354	.436			
78	Intervening - Muncie to Anderson excluding Buck Creek	122	18	20	21	25	30	38	47	57	73	.598
			.148	.164	.172	.205	.246	.311	.385			
60	White River at Anderson (adjusted to natural flow by correlation with White River near Noblesville)	401	30	34	38	48	60	80	105	135	175	.436
			.075	.085	.095	.120	.150	.200	.262			
78	Intervening - Anderson to Noblesville	413	29	31	35	42	50	60	80	110	155	.375
			.070	.075	.085	.102	.121	.145	.194			
78	White River near Noblesville	814	59	65	73	90	110	140	185	245	330	.405
			.072	.080	.090	.111	.135	.172	.227			

Table 5.--Selected low-flow frequency and flow-duration data for partial-record stations and miscellaneous sites in the upper Mississinewa and White River basins embracing Delaware County (Data adjusted to period 1924-63 on basis of correlation with stream-flow records at stream-gaging stations).

Reference no.	Stream and location	Drainage area (sq mi)	Annual low-flow, in cfs, for indicated period of consecutive days and for indicated recurrence interval, in years			Flow, in cfs, which was equaled or exceeded for indicated percent of time	
			7 day			90	95
			2 yr	10 yr	10 yr		
10	Campbells Creek near Desoto	20.4	0.2	0	0.3	0.2	
19	Rees ditch near Eaton	13.5	1.1	.5	1.0	.8	
22	Big Lick Creek near Wheeling ^{1/2/}	76.4	3.2	1.4	4.0	3.0	
23	Studebaker ditch near Wheeling	10.5	.2	0	.1	.1	
32	White River near Harrisville ^{1/}	21.3	.5	.2	.5	.3	
37	Stoney Creek near Blountsville	18.7	1.4	.6	1.4	.9	
41	Cunningham ditch near New Burlington	1.95	.6	.4	.6	.5	
52	Bell Creek near Cross Roads	16.0	1.2	.6	1.2	.8	
53	William Creek near Cross Roads	11.7	.6	.2	.6	.3	
54	No Name Creek near Progress	7.55	.2	0	.2	.1	
57	York Prairie Creek near Cammack	9.70	2.6	1.8	2.4	2.0	
63	Killbuck Creek near Bethel	26.1	2.0	.8	1.8	1.2	
67	Jakes Creek near Bethel	18.5	.5	0	.5	.2	
70	Killbuck Creek near Anderson ^{1/}	98.0	14	5.7	13	9.5	
76	Pipe Creek near Alexandria ^{1/}	44.7	3.6	1.6	3.4	2.4	

^{1/} Partial-record station

^{2/} Adjusted to natural flow

Table 6.--Low-flow frequency as taken from stream-gaging station low-flow frequency curves (adjusted to the period 1924-63)

Reference no.	Station	Drainage area (sq mi)	Consecutive days	Recurrence Interval in Years																
				2		5		10		20		30		40						
				cfs	cfsm	cfs	cfsm	cfs	cfsm	cfs	cfsm	cfs	cfsm	cfs	cfsm					
3	Mississinewa River near Ridgeville	130	3	1.1	0.003	0.3	0.002	0.2	0.002	0.2	0.002									
				7	1.4	.011	.4	.003	.3	.002	.2	.002								
				14	1.6	.012	.5	.004	.3	.002	.2	.002								
				30	2.3	.018	.8	.006	.5	.004	.4	.003								
				60	4.1	.032	1.3	.010	.7	.005	.5	.004								
				120	9.0	.069	2.8	.022	1.6	.012	1.0	.008								
				183	18	.138	5.9	.045	3.3	.025	2.0	.015								
				274	50	.385	18	.138	10	.077	6.3	.048								
				16	Mississinewa River near Eaton	304	3	4.6	.015	2.1	.007	1.5	.005	1.3	.004					
								7	5.5	.018	2.5	.008	1.8	.006	1.5	.005				
14	6.4	.021	2.8					.009	2.0	.007	1.7	.006								
30	7.9	.026	3.4					.011	2.5	.008	2.0	.007								
60	11	.036	4.5					.015	3.0	.010	2.3	.008								
120	23	.076	8.7					.029	5.7	.019	4.1	.013								
183	47	.155	16					.053	9.7	.032	6.6	.022								
274	120	.395	47					.155	28	.092	18	.059								
31	Mississinewa River at Marion (adjusted for low-flow regulation)	677	3					36	.053	25	.037	21	.031	19	.028	18	0.026	17	0.025	
								7	38	.056	27	.040	22	.032	20	.030	19	.028	18	.026
				14	41	.060	29	.043	24	.035	21	.031	20	.030	19	.028				
				30	47	.069	33	.049	28	.041	24	.035	22	.032	21	.031				
				60	61	.090	39	.058	32	.047	26	.038	24	.035	23	.034				
				120	96	.142	54	.080	42	.062	35	.052	32	.047	31	.046				
				183	135	.199	70	.103	54	.080	44	.065	39	.058	37	.055				
				274	300	.443	140	.207	96	.142	74	.109	64	.095	59	.087				
				47	White River at Muncie (adjusted to natural flow by adding diversions for water supply)	242	3	17	.070	11	.045	8.3	.034	6.7	.028	5.9	.024	5.4	.022	
								7	18	.074	11	.045	8.8	.036	7.0	.029	6.2	.026	5.7	.024
14	20	.083	12					.050	9.3	.038	7.4	.031	6.5	.027	6.0	.025				
30	22	.091	14					.058	11	.045	8.6	.036	7.6	.031	7.0	.029				
60	27	.112	17					.070	13	.054	10	.041	9.3	.038	8.6	.036				
120	40	.165	24					.099	19	.078	15	.062	14	.058	13	.054				
183	59	.244	33					.136	25	.103	20	.083	18	.074	17	.070				
274	110	.454	57					.236	42	.174	34	.140	31	.128	29	.120				

Table 6.--Low-flow frequency as taken from stream-gaging station low-flow frequency curves (adjusted to the period 1924-63)

Reference no.	Station	Drainage area (sq mi)	Consecutive Days	Recurrence Interval in Years															
				2		5		10		20		30		40					
				cfs	cfsm	cfs	cfsm	cfs	cfsm	cfs	cfsm	cfs	cfsm	cfs	cfsm				
50	Buck Creek near Muncie	36.7	3	10	0.272	8.1	0.221	7.0	0.191	6.4	0.174								
				7	.300	8.4	.229	7.4	.202	6.7	.183								
				14	.300	8.8	.240	7.8	.212	7.0	.191								
				30	.327	9.6	.262	8.4	.229	7.6	.207								
				60	.354	10	.272	9.0	.245	8.2	.223								
				120	.436	12	.327	10	.272	9.5	.259								
				183	.490	14	.382	12	.327	11	.300								
				274	.654	16	.436	13	.354	12	.327								
				60	White River at Anderson (adjusted to natural flow by correlation with White River near Noblesville)	401	3	54	.135	38	.095	32	.080	28	.070				
								7	.145	41	.102	34	.085	29	.072				
								14	.152	43	.107	36	.090	30	.075				
								30	.167	48	.120	39	.097	33	.082				
								60	.192	54	.135	44	.110	38	.095				
								120	.249	68	.170	56	.140	48	.120				
183	.324	80	.200					64	.160	54	.135								
274	.549	125	.312					91	.227	72	.180								
78	White River near Noblesville	814	3					99	.122	68	.084	56	.069	48	.059	44	0.054	42	0.052
								7	.129	73	.090	60	.074	51	.063	47	.058	44	.054
								14	.135	76	.093	62	.076	53	.065	49	.061	46	.056
								30	.154	85	.104	70	.086	59	.072	53	.065	50	.061
								60	.172	97	.119	79	.097	66	.081	60	.074	57	.070
								120	.221	115	.141	95	.117	82	.101	75	.092	71	.087
				183	.295	145	.178	115	.141	99	.122	91	.112	86	.106				
				274	.504	230	.282	165	.203	130	.160	120	.147	110	.135				




Figure 3—Magnitude and frequency of 7-day low flow at seven gaging stations on the Mississinewa River, White River, and Buck Creek (adjusted to period, 1924-62)

Base-flow measurements. The third technique used to analyze the quantity of water available in the streams and also to define areas of good or poor ground water possibilities is the base-flow measurement run. In this technique numerous discharge measurements are made over a short period of time throughout an area so that comparisons of flow in streams may be made at approximately equal flow durations. This method is useful in assessing the relative yields of different drainage basins. A word of caution is needed. Because there is only one measurement of flow made at one particular time, there is the possibility that the discharge may be affected by some temporary or permanent work of man. This may be in the form of diversions, depletions, or regulations of the streamflow, or addition to the flow by sewage effluents. Such alterations are not always readily apparent in a reconnaissance type survey which involves collection of base-flow measurements. Also, streams in a certain area may be severely affected by a series of extreme hydrologic events.

A group of 73 base-flow measurements were made the week of November 11, 1963, when the base flow throughout the study area was very close to the 90 percent flow duration. Although most measurements were made within Delaware County, they were not limited to this political unit. Measurements were made in the entire drainage system embracing the county. The measured discharges have been shown on plate 1, as well as the flow in cfs/m of areas between the measured sites.

Draft-storage requirements. The natural flow of a stream during low flow is often not sufficient to meet all the demands of water supply. It then becomes necessary to search out other ways of overcoming the deficiency. One solution to the problem is storing water during periods of excess flow and releasing it during times of deficient flow. In order to determine the amount of storage necessary to maintain certain draft rates, storage-required graphs for various frequency recurrence intervals have been computed from the low-flow frequency data and shown as figures 4 and 5 for the following gaging stations: Mississinewa River near Ridgeville, Mississinewa River near Eaton, White River at Muncie, White River at Anderson and Buck Creek near Muncie.

In using the storage-required frequency curves for estimates of storage, it must be kept in mind that such graphs have not been corrected for reservoir seepage and evaporation.

Summary of Low-flow Stream Characteristics

Results obtained by use of flow duration and low-flow frequency analyses and base-flow discharge measurements show that the low-flow yield per square mile of the Mississinewa and White Rivers generally increases progressively downstream as they pass through Delaware County. Also, low flow is better sustained in the White River than in the Mississinewa River. The low flows of tributary streams are variable at about 90 percent flow duration and range from no flow for most streams in the northern half of the county having less than 10 square miles of drainage area, including the headwaters of larger streams, to the





Figure 4.-- Storage-required graphs for 2, 5, 10 and 20-year recurrence intervals for the Mississinewa River near Ridgeville and Mississinewa River near Eaton. (Storage is uncorrected for reservoir seepage and evaporation)






Figure 5 .-- Storage-required graphs for 2, 5, 10, 20 and 40-year recurrence intervals for the White River at Muncie and 2, 5, 10 and 20-year recurrence intervals for Buck Creek near Muncie and White River at Anderson. (Storage is uncorrected for reservoir seepage and evaporation.)

excellent sustained flow of 0.26 cfsm (0.17 mgd per square mile) for the upper part of Buck Creek (Plate 1).

The flow-duration and low-flow frequency data for the 7 stream-gaging stations show Buck Creek near Muncie to have the highest sustained low-flow yield per square mile and the Mississinewa River near Ridgeville to have the lowest. The relatively flat slopes of the duration and frequency curves, with the exception of that for the Ridgeville station, indicate that a considerable quantity of ground-water discharge is available to sustain low flow.

At the 90 percent flow duration, the flow in the Mississinewa River at Marion is 2.5 times as great per square mile as that upstream near Eaton, and 3.9 times as great as that further upstream near Ridgeville. The spread is even larger at the 95 and 98 percent duration values. Data in table 4 indicate that the flow from the intervening area between the gages at Marion and near Eaton at 90 percent flow duration is 3.0 times as great as the intervening area between the gages near Eaton and near Ridgeville and 5.8 times as great as the area upstream from the near Ridgeville gage.

Carrying the comparison to the White River at 90 percent flow duration, the natural (adjusted) flow per square mile of the White River at Muncie is 3.2 times as great as the Mississinewa River near Eaton, but 0.8 as large as the flow from the intervening area between the Eaton and Marion gages. The 90 percent flow duration from the intervening area between the White River at Anderson and the White River at Muncie, excluding the area above the Buck Creek near Muncie gage, is 3.0 times the flow contributed from the area above the Muncie gage, but 0.9 times the flow from the area above the Buck Creek near Muncie gage. Although the drainage area for the stream-gaging station on Buck Creek near Muncie equals only 15 percent of the drainage area above the stream-gaging station on White River at Muncie, the discharge is 50 percent as large at 90 percent flow duration.

The low-flow characteristics at the 7 stream-gaging stations may be examined further by analyzing the minimum observed flows that have occurred during their period of record. Table 7 shows the instantaneous minimum flow, and the lowest two minimum average flows for 1-day, 3-day, 7-day, 14-day, 30-day and 60-day consecutive periods with the beginning month of the period. The values in this table when compared with the low-flow frequency data in table 6 make it possible to estimate the severity of the observed low flows during the period of records, excepting for the stream-gaging stations that have pronounced regulation or diversion. Example: The lowest 3-day average flow on the Mississinewa River near Eaton during the period from 1952-63 is 2.1 cfs (table 7). This flow will occur on the average 1 time in every 5 years (table 6).

In reviewing the low-flow characteristics it is interesting to compare the runoff map (Plate 1) with the shape of the piezometric water surfaces in the glacial drift (fig. 8) and bedrock (fig. 13). Where contours on the piezometric surface are parallel to the streams, flow is sustained by ground-water discharge. It is possible that some of the

flow does not appear in the streams but rather occurs as underflow beneath the stream channels. This may be the case in the reach of the White River from Yorktown to Daleville.

Application of Techniques to Water Planning

Application of the four foregoing techniques to water planning is demonstrated by the following hypothetical example. A new industrial plant desires to locate on the Mississinewa River at Eaton, where the drainage area is about 310 square miles. It is determined that the water supply obtainable from the town of Eaton's wells is more than adequate to meet anticipated future needs. However, in the absence of a sewage disposal plant at Eaton, it will be necessary to have a minimum flow of 6 cfs, or 3.9 mgd, for dilution of plant waste products as predetermined by the Indiana Stream Pollution Control Board.

Observed minimum flows (at the gage upstream near Eaton) (table 7) are less than the required flows; therefore, it is necessary to know the probable percent of time there will be a shortage of water. From figure 2, it is determined that the flow of 6 cfs, or 0.02 cfs, will be available about 93 percent of the time, or about 7 percent of the time the flow would be less than that required for dilution.

A management decision could be made at this point as to whether or not plant operation can be economically reduced or shut down 7 percent of the time.

If management decides that plant operation cannot be shut down 7 percent of the time, then arrangements for storage or a supplemental supply must be considered and planned.

To assist further in the water planning, the low-flow frequency data for the gaging station near Eaton indicates the frequency at which the discharge falls below 6 cfs. Table 6 shows that on the average, about once every 2 years for a 14-day consecutive period, or once every 10 years for a 120-day consecutive period, or once every 20 years for a 183-day consecutive period, the average natural flow in the Mississinewa River would be less than that needed for plant operations. To continue the plant in operation during these periods of insufficient streamflow, it would be necessary to supplement the natural streamflow with dilution water from a standby facility such as private wells, the Eaton water supply system, or upstream surface storage on the Mississinewa River or on one of its tributaries.

The base flow measurements would be used to determine which of the Mississinewa River tributaries might offer the best potential for off channel storage should it be decided to go to a small storage dam to supplement the natural flow of the Mississinewa River. An examination of plate 1 indicates that both Bosman and Rees ditches offer good possibilities for low-flow yield in their lower reaches.

Table 7.--Average discharge, instantaneous minimum, and lowest two minimum average flows for 1-, 3-, 7-, 14-, 30-, and 60-day consecutive periods for stream-gaging stations on the Mississippi River, White River, and Buck Creek

Reference no.	Station	Drainage area (sq mi)	Period of record	Average discharge (cfs)	Instantaneous minimum (cfs)	1-day (cfs)	3-day (cfs)	7-day (cfs)	14-day (cfs)	30-day (cfs)	60-day (cfs)
3	Mississinewa River near Ridgeville	130	Aug. 1946 to Sept. 1963	132	0.1 (10/24/46)	0.1 (10/46)	0.2 (10/46)	0.2 (10/46)	0.3 (10/46)	0.6 (9/54)	0.9 (9/46)
						.3 (9/54)	.3 (9/54)	.3 (9/54)	.5 (9/54)	1.0 (9/46)	1.7 (9/53)
16	Mississinewa River near Eaton	304	Mar. 1952 to Sept. 1963	282	2.0 (9/23, 27/54)	2.0 (9/54)	2.1 (9/54)	2.2 (9/54)	2.3 (9/54)	2.3 (9/54)	4.3 (8/53)
						2.2 (10/53)	2.2 (10/53)	2.5 (9/53)	2.5 (9/53)	2.9 (9/53)	6.8 (8/54)
31	Mississinewa River at Marion	677	Sept. 1923 to Sept. 1963	641	1.1 (4/17/59)	3.8 (10/40)	5.1 (10/43)	8.4 (10/40)	12.0 (11/28)	16.4 (10/28)	20.2 (9/28)
						3.8 (10/43)	5.4 (10/40)	12.0 (11/28)	18.9 (10/40)	21.7 (8/40)	22.8 (8/40)
47	White River at Muncie	242	Nov. 1930 to Sept. 1963	217 ^b	.6 (9/16/37)	1.1 (9/54)	1.1 (9/54)	1.2 (9/54)	1.2 (9/54)	1.5 (9/54)	2.9 (9/56)
						1.1 (10/56)	1.3 ^d	1.4 (8/34)	1.4 (7/34)	2.2 (9/56)	3.8 (8/40)
50	Buck Creek near Muncie	36.7	Oct. 1954 to Sept. 1963	35.9	-----	5.8 (9/56)	6.1 (9/56)	7.3 (12/62)	8.0 (9/60)	9.1 (9/56)	9.8 (9/56)
						6.0 (12/62)	6.3 (12/62)	7.7 (9/60)	8.6 (9/56)	9.4 (8/60)	10.3 (8/60)
60	White River at Anderson	401	July 1925 to Sept. 1926, Oct. 1931 to Sept. 1963	375	8.8 (9/24/40)	9.1 (9/40)	12.3 (9/41)	13.0 (9/41)	13.9 (9/41)	20.5 (9/40)	22.1 (8/41)
						12.0 (9/41)	13.0 (9/40)	15.7 (9/40)	18.9 (9/40)	20.8 (9/41)	22.2 (8/40)
78	White River near Noblesville	814	May 1915 to Sept. 1926, Oct. 1928 to Sept. 1963	803	36 (9/25/41)	39 (9/41)	41.3 (9/41)	42.0 (9/41)	43.9 (9/41)	55.1 (9/41)	59.8 (8/41)
						46 (9/40)	51.0 (9/40)	53.1 (9/40)	53.1 (9/40)	57.2 (9/40)	62.6 (8/40)

- a Regulated
- b Adjusted for diversion after September 1937
- c Diversion for water supply above gage, returned to stream through sewage treatment plant below gage
- d 8/34 and 10/56
- e Ice effect

To determine the approximate amount of storage necessary to maintain a 6 cfs draft rate from a channel-storage reservoir on the Mississinewa River itself, storage-required frequency curves for the near Eaton gage as presented in figure 4 may be used. A reservoir of 16 million cubic feet, or 120 million gallons, capacity would be needed to maintain a 6 cfs flow for a 10-year frequency recurrence interval. To maintain this draft rate to overcome a 20-year frequency drought, 23 million cubic feet, or 172 million gallons, of storage would be necessary. Additional storage would be necessary to overcome water loss by seepage and evaporation.

Development Potential

The available water supply potentials of the several streams in Delaware County are an index of their development potential. Many of the streams flow with fairly well sustained low flows during dry weather. An excellent example of development is Prairies Creek, a tributary to White River, which was put to use in 1961 for water supply by the Muncie Water Works Company by construction of a 7.2 billion gallon reservoir.

The variation in low flow is illustrated by plate 1. The color lines along the streams indicate the range of flow into which the measured discharges fell during the week of November 11, 1963, at about 90 percent flow duration. The color lines between the measured locations are estimates based on flows at measured points.

From a practical standpoint, the low flow available 90 percent of the time may be considered the maximum dependable supply that can be obtained without storage in reservoirs. The other 10 percent of the time the flow is less than this amount.

The average discharges for the period of record at each of the 7 stream-gaging stations are included in table 7. The average discharge divided by the drainage area equals about 1 cfs/mi at each gage. The average discharge represents the absolute limit of the potential surface-water supply available, if it were possible to store in reservoirs and release at uniform rate the total water that flows from the area above the gage. To carry this reasoning one step further to ungaged sites, an estimate of the absolute limit of the potential surface-water supply available on any stream in Delaware County, regardless of size, would be the product of the drainage area, in square miles, times 1 cfs/mi.

Mississinewa River and tributaries. The flow in the Mississinewa River increases from a yield of 0.008 cfs/mi at the Ohio-Indiana state line, to 0.03 cfs/mi, at about 90 percent flow duration before it leaves Delaware County (pl. 1). On the basis of the streamflow data, the Mississinewa River offers a better development potential downstream from about the mouth of Campbells Creek than it does above this point. This increase in base flow is due to better yields of ground-water discharge from (1) the till and (2) probably the valley train and outwash plain sediments beginning on the main channel a little upstream from Eaton and continuing downstream. Another feature of the surficial

geology in the area of increased base flow yields is the presence of large sand and gravel deposits in the forms of kames and eskers in the till.

A large user of water considering the Mississinewa River as a supply will have to depend on an impoundment if his activity requires 9 mgd or more, more than 90 percent of the time.

The tributaries in Delaware County offer various development potentials at about 90 percent flow duration. Mud Creek, Halfway Creek, the upper reaches of Bosman ditch, Rees ditch, Pike Creek, as well as a few smaller unnamed tributaries, were either dry or contained very little flow during the week of November 11, 1963. Some of these streams had excellent amounts of flow for their size in their lower reaches.

Most of the tributaries having less than 10 square miles of drainage area, including the headwaters of larger streams, go dry frequently. Impoundments would be necessary if these sources were developed. If a supply of 0.6 mgd, or more, was required more than 90 percent of the time from any of the aforementioned tributaries, an impoundment would be necessary.

White River and tributaries. The flow in the White River increases from a yield of 0.03 cfs in its headwaters in Randolph County to 0.10 cfs in Delaware County at about 90 percent flow duration (pl. 1). This increase in base flow is due to better yields of ground-water discharge from (1) the till and (2) probably the valley train and outwash plain sediments, beginning on the main channel of White River at about Mud Creek and continuing downstream.

Below Muncie, the White River meanders through the outwash sediments, and although the flow in the reach from below Muncie to the county line nearly doubles at 90 percent flow duration, the increase is due largely to the entrance of Buck Creek and York Prairie Creek. The White River from below Mud Creek to the mouth of Buck Creek would offer the best potential development under natural flow conditions. However, the flow in this reach is altered by the water supply for the city of Muncie. Water is taken out above Muncie and sewage effluent is returned below Muncie.

A large user of water considering the White River as a supply will have to depend on an impoundment if his activity requires 25 mgd or more, more than 90 percent of the time.

The tributaries in Delaware County offer various development potentials at about 90 percent flow duration. The upper portions of Muncie Creek, and some of the small tributaries of Killbuck and Pipe Creek were either dry or contained practically no flow during the week of November 11, 1963. Flows in Stoney Creek, Mud Creek, Medford drain, the middle portion of Muncie Creek, Bell Creek, the upper portions of Killbuck Creek and Pipe Creek are fairly well sustained. The tributaries of the White River offering the best potential development are Cunningham ditch (tributary to Prairie Creek Reservoir and thus already used in water

supply development), Buck Creek (used for water supply by the Muncie Water Works Company without impoundment), York Prairie Creek and Brandon ditch (tributary to Fall Creek).

Most of the tributaries in the northern half of the county having less than 10 square miles of drainage area, including the headwaters of larger streams, go dry frequently. Impoundments would be necessary if these sources were developed. Most of the tributaries in the southern half of the county, regardless of size, can be depended on to yield more than 9 gpm (0.013 mgd) per square mile 90 percent of the time. Buck Creek, in the upper part of its basin, can be depended on to yield more than 120 gpm (0.170 mgd) per square mile 90 percent of the time.

Glacial Deposits

Delaware County is underlain by glacial drift that ranges in thickness from 0 to about 300 feet. The principal sources of ground water in the drift are two sand and gravel aquifers (fig. 6). Nearly all the ground water in these deposits must percolate through the confining layer that covers almost the entire land surface of the county (fig. 6). Some water can be recovered by dug wells in the surficial confining layer, but usually these wells are not adequate even for domestic supplies.

Sand and Gravel Aquifers

One of the two important water-bearing zones underlies nearly the entire county and is referred to as the "principal Pleistocene aquifer" (fig. 6). The other zone lies beneath the principal Pleistocene aquifer, usually within or near buried bedrock valleys and is referred to as the "deeper sand and gravel aquifers".

The principal Pleistocene aquifer consists chiefly of sand and gravel as much as 80 feet thick, with some areas of sand alone. It extends beyond the boundaries of Delaware County, and is an important aquifer in surrounding areas. The aquifer is artesian except for a few scattered areas of water-table conditions in the central part of the county. Its stratigraphic position is shown on figure 6.

The deeper sand and gravel aquifers occur principally in the southern third of the county in the thicker parts of the glacial drift. The thickness and configuration of these aquifers are not well known.

Recharge and Discharge

Most of the inflow to the shallow glacial deposits of Delaware County is derived from precipitation within the county. Some water enters the county by underground flow, most of which occurs along the eastern and southern boundaries. Average inflow and outflow in the shallow glacial deposits are symbolized by figure 7. Recharge and discharge of the deeper sand and gravel aquifers are illustrated along with the Silurian Dolomite (p. 34).

EXPLANATION

	Symbol on cross section	Lithology	Thickness (feet)	Areal extent	Importance for water supply
QUATERNARY Pleistocene and Recent, undifferentiated		Clay and silt; sandy, gravelly, calcareous, brown to yellowish-brown, occasionally blue. Mostly till	0-110	Underlies entire county except for a few very small isolated areas	A few dug wells for livestock. Limits recharge to aquifers and ground-water discharge to streams
		Sand and gravel; silty, often clayey, tan to brown	0-40	Underlies most of the county. Cannot be distinguished from principal Pleistocene aquifer where the till below is missing	Some domestic and stock wells
		Clay; silty, sandy, gravelly, usually brown or blue. Till	0-100	Same as above unit	Confining layer for part of principal Pleistocene aquifer
		Sand and gravel; silty, often clayey	0-100	Underlies the entire county (fig. 9)	Principal Pleistocene aquifer. Domestic and industrial use
		Clay; silty, sandy, gravelly, usually blue or brown, sometimes red in lower part; with occasional sand and gravel lenses. Till	0-240	Underlies most of the county. Missing on bedrock highs	Confining layer for most of the Silurian Dolomite
		Sand and gravel; often interbedded with clay	0-70 +	Occurs in and near most buried valleys (fig. 11)	Domestic and industrial use
SILURIAN		Mostly dolomite. Drillers occasionally report shale and, rarely, sandstone	200-500	Underlies the entire county	Domestic, industrial, and municipal use





Figure 6.—Generalized cross section showing aquifers and confining layers of Delaware County. Line of cross section is shown on figure 9.

OUTFLOW

INFLOW



	Average amount (mgd)
Increase of streamflow	about 225
Evapotranspiration	about 508 ¹
Underflow	about 4
Total	about 738

¹ By subtraction. Includes consumptive use by man

	Average amount (mgd)
Precipitation	about 730
Underflow	about 8 ²
Total	about 738

² See text

Figure 7.—Average recharge and discharge of the shallow glacial deposits.