


POTENTIOMETRIC SURFACE MAP OF THE BEDROCK AQUIFERS OF HARRISON COUNTY, INDIANA



Harrison County is located in southern Indiana and is bounded by the counties of Crawford, Washington, and Floyd to the west, north and east. The Ohio River borders the county to the south.


The potentiometric surface is a measure of the pressure on groundwater in a water bearing formation. Wells are completed in aquifers at various depths, and typically, under confined conditions (bounded by impermeable layers above and below the water bearing formation). However, some wells are completed under unconfined (not bounded by impermeable layers) settings. Water in a confined aquifer, which is under hydrostatic pressure, will rise in a well above the top of the water bearing formation. In contrast, groundwater in an unconfined aquifer, which is at atmospheric pressure, will not rise in a well above the top of the water bearing formation.

Static water-level measurements obtained from individual wells used to construct potentiometric surface maps are indicative of the water-level at the time of well completion. The groundwater level within an aquifer constantly fluctuates in response to rainfall, evapotranspiration, groundwater movement and pumping. Therefore, measured static water-levels in an area may differ due to local or seasonal variations. Because fluctuations in groundwater are typically small, static water-levels can be used to construct a generalized potentiometric surface map. As a general rule, but certainly not always, groundwater flow approximates the overlying topography and intersects the land surface at major streams.




The potentiometric surface map of the bedrock aquifers was mapped by contouring the elevations of 516 static water-levels reported on well records received primarily over a 50 year period. Universal Transverse Mercator (UTM) coordinates, used in locating the water wells, were either physically obtained in the field, determined through address geocoding, or reported on water well records. The location of the majority of the water well records used to make this map were field verified. Elevation data were obtained from a digital elevation model. Quality control/quality assurance procedures were utilized to refine or remove data where errors were readily apparent.

Potentiometric surface elevations range from a high of 830 feet mean sea level (msl) in the northeastern section of the county southwest of the town of Bradford, to a low of 380 feet msl in the southwestern portion along the Ohio River near the towns of New Amsterdam and Mauckport. Groundwater flow direction within the majority of the county is generally southward towards the Ohio River and its major tributaries. However, in the western portions of the county, groundwater generally appears to flow toward the Blue River. Potentiometric contours have not been extended through portions of the county that are lacking in data and/or covered by more prolific unconsolidated deposits which limits the necessity to complete wells in the bedrock.

The county potentiometric surface map can be used to define the regional groundwater flow path and to identify significant areas of groundwater recharge and discharge. These maps represent overall regional characteristics and are not intended to be a substitute for site-specific studies.



Digital Elevation Model of Harrison County, Indiana



EXPLANATION	
— 670 —	Line of equal elevation, in feet above mean sea level
—	Potentiometric Contour interval 10 feet
—	Stream
—	County Road
—	State Road
—	US Highway
—	Interstate
—	Municipal Boundary
—	State Managed Property
—	Lake & River
—	No Aquifer Material or Limited Data

Map Use and Disclaimer Statement

We request that the following agency be acknowledged in products derived from this map: Indiana Department of Natural Resources, Division of Water. This map was compiled by staff of the Indiana Department of Natural Resources, Division of Water using data believed to be reasonably accurate. However, a degree of error is inherent in all maps. This product is distributed "as is" without warranties of any kind, either expressed or implied. This map is intended for use only at the published scale.

This map has been created from several existing shapefiles. Township and Range Lines of Indiana (line shapefile, 20020621), Land Survey Lines of Indiana (polygon shapefile, 20020621), and County Boundaries of Indiana (polygon shapefile, 20020621) are from the Indiana Geological Survey and based on a 1:24,000 scale. Roads (TIGER and INDOT) (line shapefile, 2005) is from the Indiana Department of Transportation and based on a 1:24,000 scale. Incorporated Boundaries in Indiana (polygon shapefile, 20060501) is from the Graphics and Engineering Section Indiana Department of Transportation. Hydrography, Streams (NH0) (line shapefile, 20081218), Rivers (NH0) (polygon shapefile, 20081218), and Lakes (NH0) (polygon shapefile, 20081218) are from the U.S. Geological Survey and based on a 1:24,000 scale. Basin boundaries are modified from the Watershed Boundary Dataset (polygon shapefile, 2008) developed by the Natural Conservation Service and based on a 1:24,000 scale. Managed Lands (DNR) (polygon shapefile, 20100920) is from the Indiana Department of Natural Resources and based on a 1:24,000 scale. Digital Elevation Model image is derived from the Indiana OrthoLIDAR Statewide Collection Program (2013). Harrison County Bedrock No Aquifer Material or Limited Data (polygon shapefile, Schmidt, 2018), and Potentiometric Surface Map of the Bedrock Aquifers of Harrison County, Indiana (line shapefile, Schmidt, 2018) are based on a 1:24,000 scale.

Potentiometric Surface Map of the Bedrock Aquifers of Harrison County, Indiana

by
Robert K. Schmidt
Division of Water, Resource Assessment Section
March 2018

Map generated by Robert K. Schmidt
Indiana Department of Natural Resources
Division of Water, Resource Assessment Section