

# **Potentiometric Surface Map of the Unconsolidated Aquifers of Jennings County, Indiana**

By

Kristiana E. Cox

Division of Water, Resource Assessment Section

December 2018

Jennings County is located in the southeastern portion of Indiana, and is bounded by the counties of Bartholomew, Decatur, Ripley, Jefferson, Scott, and Jackson to the northwest, northeast, east, southeast, southwest, and west, respectively. The entire county lies within the East Fork White River Basin.

The potentiometric surface is a measure of the pressure on groundwater in a water bearing formation. Wells are completed in aquifers at various depths, and typically, under confined conditions (bounded by impermeable layers above and below the water bearing formation). However, some wells are completed under unconfined (not bounded by impermeable layers) settings. Water in a confined aquifer, which is under hydrostatic pressure, will rise in a well above the top of the water bearing formation. In contrast, groundwater in an unconfined aquifer, which is at atmospheric pressure, will not rise in a well above the top of the water bearing formation.

The Potentiometric Surface Map (PSM) of the unconsolidated aquifers of Jennings County was mapped by contouring the elevations of 82 static water-levels reported on well records received primarily over a 50 year period. Universal Transverse Mercator (UTM) coordinates for the water wells were either physically obtained in the field, determined through address geocoding, or reported on water well records. The location of the majority of the water well records used to make the PSM were field verified. Elevation data were obtained from a digital elevation model. Quality control/quality assurance procedures were utilized to refine or remove data where errors were readily apparent.

Static water-level measurements in individual wells used to construct county PSM's are indicative of the water-level at the time of well completion. The groundwater level within an aquifer constantly fluctuates in response to rainfall, evapotranspiration, groundwater movement and pumpage. Therefore, measured static water-levels in an area may differ due to local or seasonal variations. Because fluctuations in groundwater are typically small, static water-levels can be used to construct a generalized PSM. As a general rule, but certainly not always, groundwater flow approximates the overlying topography and intersects the land surface at major streams.

Potentiometric surface elevations range from a high of 580 feet mean sea level (msl) in the west-central portion of the county near Little Mutton and Mutton creeks, to a low of 550 feet msl in the southwest portion of the county near Gum Lick and Cana creeks. Localized groundwater flow direction in the southwest area of the county is to the west-northwest towards Vernon Fork of the Muscatatuck River and to the west-southwest towards the Muscatatuck River. In the west-central area of the county, groundwater flow direction is to the southwest towards Mutton Creek.

The county PSM can be used to define the regional groundwater flow path and to identify significant areas of groundwater recharge and discharge. County PSM's represent overall regional characteristics and are not intended to be a substitute for site-specific studies.