

INDIANA

DEPARTMENT
OF
TRANSPORTATION

STANDARD
SPECIFICATIONS

2022

ERIC HOLCOMB
GOVERNOR

**INDIANA
DEPARTMENT OF TRANSPORTATION**

Joe McGuinness
COMMISSIONER

STANDARDS COMMITTEE

CHAIRMAN

Greg Pankow, Construction Management Director

MEMBERS

David Boruff, Traffic Engineering

Kumar Dave, Pavement Engineering

Louis Feagans, Statewide Technical Services

Michael Koch, Fort Wayne District Construction

Joe Novak, State Construction Engineer

Mark Orton, Engineering Standards and Policy

Kurt Pelz, Construction Technical Support

Jim Reilman, Materials and Test

Elena Veksler, Highway Design and Technical Support

John Wooden, Contract Administration

SECRETARY

Scott Trammell, Construction Specifications Engineer

Lana Podorvanova, Specifications Coordinator

MEASUREMENTS

The first two paragraphs of 109.01, Measurement of Quantities reads as follows:

(a) General Requirements

All measurements of work completed under the contract will be according to the English System unless otherwise specified.

The standard measures shown in this publication are primarily in the English System of Units such as feet and inches, pounds, gallons, and acres. Any metric equivalents, shown in parentheses, are intended only for those contracts in which they are specified, or to maintain consistency with industry standards. No guarantee is provided, explicit or implicit, that the units are accurate conversions.

The following table and general notes are provided to assist you in becoming familiar with the metric system.

SI UNITS AND CONVERSION FACTORS

MEASUREMENT	ENGLISH UNIT	ENGLISH UNIT SYMBOL	MULTIPLIER FOR CONVERSION FROM ENGLISH UNIT TO SI UNIT (*)	SI UNIT	SI SYMBOL
Acceleration	foot per second squared mile per hour squared	ft/sec ² mi/h ²	0.304 8 exactly 1.060 93	meter per second squared kilometer per hour squared	m/s ² km/h ²
Area	square inch square foot square yard acre square mile	sq in sq ft sq yd ac sq mi	645.16 exactly 0.092 9 0.836 1 0.404 7 2.59	square millimeter square meter square meter hectare square kilometer	mm ² m ² m ² ha km
Density	pound per cubic foot	lb/cu ft	16.018 46	kilogram per cubic meter	kg/cu m
Energy	foot-pound force kilowatt hour	ft lbf kW h	1.355 8 3 600 000. exactly	joule joule	J J
Force/Weight (Gravity of Force)	pound force kilopound force ton	lbf kip t	4.448 2 4.448 2 8.896 4	newton kilonewton kilonewton	N kN kN
Length	inch foot yard mile	in. ft yd mi	25.4 exactly 0.304 8 exactly 0.914 4 exactly 1.609 3	millimeter meter meter kilometer	mm m m km
Mass	ounce pound mass ton mass	oz lbm t	28.349 5 0.453 6 0.907 2	gram kilogram megagram	g kg Mg
Power	horsepower (550 ft·lbf/s)	hp	745.669 9	watt	W
Pressure/Stress	pound per square inch pound per square foot kilopound per square inch	lb/sq in lb/sq ft kip/sq in	6.894 8 0.047 88 6.894 8	kilopascal kilopascal megapascal	kPa kPa MPa
Speed/Velocity	foot per second mile per hour	ft/s mph	0.304 8 exactly 1.609 3	meter per second kilometer per hour	m/s km/h

Temperature	degree Fahrenheit	°F	(°F -32)/1.8(**) exactly	degree Celsius	°C
Volume, Fluid	cubic inch	cu in	16.387 1	milliliter	mL
	fluid ounce	fl oz	29.573 4	milliliter	mL
	gallon	gal.	3.785 4	liter	L
	1000 gallons	kGAL.	3.785 4	kiloliter	kL
Volume, Solid	cubic inch	cu in	16.387.06 exactly	cubic millimeter	mm ³
	cubic foot	cu ft	0.028 32	cubic meter	m ³
	bushel	bu	0.035 24	cubic meter	m ³
	cubic yard	cu yd	0.764 6	cubic meter	m ³
	1000 feet board measure	MFBM	2.359 7	cubic meter	m ³

(*) Conversion from SI unit to English unit may be made by dividing the SI unit by the conversion factor shown in this column.

(**) This is a formula, and not a multiplier. The Fahrenheit temperature is substituted for °F in the formula to attain the Celsius temperature. Conversion from Celsius temperature to Fahrenheit temperature may be made by substituting the Celsius temperature for °C in the formula $(1.8 \times ^\circ\text{C}) + 32$. This is an exact conversion.

1A.

Angles will continue to be measured in degrees, minutes, and seconds instead of radians.

GENERAL NOTES

1. The SI unit of millimeter shall be used to convert inches to millimeters.
2. The SI unit of Mass is the Kilogram (Kg) which shall be used for smaller masses expressed in pounds. The megagram (Mg) shall be used for larger masses expressed in tons.
3. All units peculiar to the various cgs systems (measurement systems constructed by using the centimeter, gram and second as base units) shall be avoided.
4. In commercial and everyday use, the term weight nearly always means mass; thus, when one speaks of a person's weight, the quantity referred to is mass. In Science and Technology, the term weight of a body has usually meant the force that, if applied to the body, would give it an acceleration equal to the local acceleration of free fall g (acceleration of gravity). When the term is used, it is important to know whether mass or force is intended and to use SI Units properly, by using Kilograms for Mass or Newtons for Force. The use of force of gravity (mass times acceleration of gravity) instead of weight with this meaning is recommended. Because of the dual use of the term weight as a quantity, this term shall be avoided in technical practice except under circumstances in which its meaning is completely clear.
5. The term load means either mass or force, depending on its use. A load that produces a vertically downward force because of the influence of gravity acting on a mass may be expressed in mass units. Any other load is expressed in force units.
6. A quantity stated as limits, such as "not more than" or "maximum", shall be handled so that the stated limit is not violated.
7. Conversion of quantities shall be handled with careful regard to the implied correspondence between the accuracy of the data and the given number of digits. In all conversions, the number of significant digits retained shall be such that accuracy is neither sacrificed nor exaggerated. For example, a length of 125 ft converts exactly to 38.1 m. If however, the 125 ft length has been obtained by rounding to the nearest 5 ft, the conversion shall be given as 38 m. The proper conversion procedure is to multiply a value by a conversion factor that is more accurate than is required, the result is then rounded to the appropriate number of significant digits.
8. For calculation of results, avoid rounding of intermediate quantities. For reporting results, the rule for addition and subtraction is that the answer shall contain no significant digits farther to the right than occur in the least precise number. The rule for multiplication and division is that the product or quotient shall contain no

more significant digits than are contained in the number with the fewest significant digits used in the multiplication.

9. When a figure is to be rounded to fewer digits than the total number available, the standard “5” up procedures shall be used as follows:
 - (a) When the first digit discarded is less than 5, the last digit retained shall not be changed. For example, 3.46325, if rounded to three digits, would be 3.463; if rounded to two digits, would be 3.46.
 - (b) When the first digit discarded is 5 or greater, the last digit retained shall be increased by one unit. For example, 8.37652, if rounded to three digits, would be 8.377; if rounded to two digits would be 8.38.
10. Refer to ASTM SI10 American National Standard for Use of the International System of Units (SI) for other conversion factors.
11. This specification book uses the word “shall” to describe the Contractor’s responsibilities. The word “will” is used to describe the Department’s responsibilities. The words “shall” and “will” are not required to be followed by the words “by the Contractor” or “by the Department” to retain these meanings.