




# REHABILITATION RETROFITTS

Michael Wenning, PE  
GAI Consultants, Inc.

INDOT Bridge Conference | February 16, 2017



Rehabilitation Retrofits – Mike Wenning, PE | ©2017

# Link Slabs



Rehabilitation Retrofits – Mike Wenning, PE | ©2017

### LINK SLABS

- Purpose to eliminate problematic joints.
- Stephanie discussed currently preferred joints to use
- Lifespan less than rehabilitation cycle of 20± years.
- Jeremy discussed preferred integral and semi-integral end bent details.
- Works at end bents only.



Rehabilitation Reports – Mike Worning, PE | ©2017



### LINK SLABS

- I-64 over Captain Frank Road
- Built 1965
- Simple Span Prestressed I-beam bridge
- Reconstructed 1992
- Overlay and joint elimination




Rehabilitation Reports – Mike Worning, PE | ©2017



**LINK SLABS**

- I-64 over Captain Frank Road
- Removed Deck and Diaphragms over Piers
- Also widened superstructure and overlaid deck.




Rehabilitation Reports – Mike Worning, PE | ©2017



gal consultants

**LINK SLABS**

- I-64 over Captain Frank Road
- Removed Deck and Diaphragms over Piers
- Poured New Capwidth Diaphragm
- Added #6 Bars in Deck over old Joint
- Now “Continuous” for LL
- No need to worry about RES moments due to age of beams



Rehabilitation Reports – Mike Worning, PE | ©2017



gal consultants

## LINK SLABS

- I-64 over Captain Frank Road
- From 11/19/2015 SI&A

A. INVESTIGATION OF CRACKING  
 The following table summarizes the results of the investigation of cracking in the deck slabs. The table includes the location of the crack, the length of the crack, the width of the crack, and the orientation of the crack. The table also includes a description of the crack and a photograph of the crack.

Location	Length (ft)	Width (in)	Orientation	Description	Photo
Deck Slab 1	10	0.001	Vertical	Crack in deck slab	
Deck Slab 2	15	0.002	Vertical	Crack in deck slab	
Deck Slab 3	20	0.003	Vertical	Crack in deck slab	
Deck Slab 4	25	0.004	Vertical	Crack in deck slab	
Deck Slab 5	30	0.005	Vertical	Crack in deck slab	
Deck Slab 6	35	0.006	Vertical	Crack in deck slab	
Deck Slab 7	40	0.007	Vertical	Crack in deck slab	
Deck Slab 8	45	0.008	Vertical	Crack in deck slab	
Deck Slab 9	50	0.009	Vertical	Crack in deck slab	
Deck Slab 10	55	0.010	Vertical	Crack in deck slab	



Rehabilitation Reports – Mike Worning, PE |©2017



gal consultants

## LINK SLABS

- Behavior and Design of Link Slabs for Jointless Bridge Decks, PCI Journal May-June 1998, Caner and Zia
- Investigated both concrete and steel beam link slabs.
- Developed simplified equation for predicting cracks in deck for link slabs.
  - $\omega = 0.076 \beta f_s (d_c A)^{1/3}$
  - $\omega$  = surface crack width in units of 0.001 in.
  - $\beta$  = ratio of distances to neutral axis from extreme fiber to centroid of main reinforcement.
  - $f_s$  = Reinforcement stress (ksi)
  - $d_c$  = concrete cover (in)
  - $A$  = effective area per bar (sq. in.)


Rehabilitation Reports – Mike Worning, PE |©2017



gal consultants

**LINK SLABS**

- Behavior and Design of Link Slabs for Jointless Bridge Decks
- Some Details used by other DOT's:
  - Control Joints in Slabs
  - Reduced Reinforcing through Joint
  - Bond Break and no Composite action near Joint
- Separating Diaphragm from Beam with Roofing Felt




Rehabilitation Retrofits – Mike Worring, PE |©2017



gal consultants

**LINK SLABS**

- Recent Experiments:
  - SR 64 over SR 37, B-35006



Rehabilitation Retrofits – Mike Worring, PE |©2017




gal consultants

## LINK SLABS

### Recent Experiments:

- SR 64 over SR 37, B-35006
- Only made deck continuous. Did not replace diaphragms.



Rehabilitation Reports – Mike Worring, PE | ©2017




gal consultants

## LINK SLABS

### Recent Experiments:

- Owensville Road over I-64, B-35003



Rehabilitation Reports – Mike Worring, PE | ©2017




gal consultants

**LINK SLABS**

➤ **Recent Experiments:**

- Owensville Road over I-64, B-35003
- **2 Span Continuous Steel Beam with Concrete Girder End Spans**
- **Only Deck Continuous**



Rehabilitation Reports – Mike Worning, PE | ©2017



# Rocker Bearing Replacement

Rehabilitation Reports – Mike Worning, PE | ©2017



### ROCKER BEARINGS

- Found throughout Indiana on Steel Beam / Girder Bridges.




Rehabilitation Reports – Mike Worning, PE |©2017



gal consultants

### ROCKER BEARINGS

- INDOT Used Pintles top and bottom.
- No Pins typically used



Rehabilitation Reports – Mike Worning, PE |©2017



gal consultants



### ELASTOMERIC BEARINGS


- Elastomeric Bearings don't rust
- Low Profile
- Less Expensive
- Easy to Install



Rehabilitation Reports – Mike Worring, PE | ©2017




### BEARING REPLACEMENTS



Rehabilitation Reports – Mike Worring, PE | ©2017



## BEARING REPLACEMENTS



Rehabilitation Reports – Mike Wanning, PE | ©2017




# Zinc Anodes

Rehabilitation Reports – Mike Wanning, PE | ©2017



### ZINC ANODES



Rehabilitation Reports – Mike Wenning, PE | ©2017



### ZINC ANODES

- Amount of zinc dependent on a number of factors such as current, rebar density, etc
- Normally pucks spaced 18-24" are sufficient for decks and most areas
- See presentation from 2016 conference for more information



Rehabilitation Reports – Mike Wenning, PE | ©2017



## ZINC ANODES

- Bid price about \$25 each
- Cheap insurance against premature corrosion
- If there's corrosion on epoxy coated steel deck then coating is compromised
- Bridge Asset Managers' input...



Rehabilitation Reports – Mike Worring, PE | ©2017



## Concrete Patching

Rehabilitation Reports – Mike Worring, PE | ©2017



## CONCRETE PATCHING

- Not all patching is created equal.
- Class A Patching Spec getting a major overhaul today.



Rehabilitation Retrofits – Mike Worring, PE |©2017



## CONCRETE PATCHING

- New Pay Items
  - Patching Concrete Structures, Horizontal Surface SFT
  - Patching Concrete Structures, Overhead Surface SFT
  - Patching Concrete Structures, Vertical Surface SFT
- Each one will have different preapproved materials.
- Since no bid history exists, approximate with low, medium and high values.
  - Horizontal \$50 per SFT
  - Overhead \$400 per SFT
  - Vertical \$100 per SFT

Rehabilitation Retrofits – Mike Worring, PE |©2017



## CONCRETE PATCHING

- **Pneumatically Placed Mortar**
  - “Stickier” than Class A Patching and sometimes works better.
  - More Expensive due to equipment mobilization.
  - \$100 - \$200 per SFT, higher for small quantities.
  - Rule of thumb, don't use for under 500 SFT areas.
  - Don't forget WW Mesh
- **INDOT knows the current specifications do not represent the best current practices and intend to update them in the future.**



Rehabilitation Retrofits – Mike Worring, PE | ©2017



## Drain Sealing

Rehabilitation Retrofits – Mike Worring, PE | ©2017



## DRAIN SEALING

- The Problem:
  - Water and Chlorides Leak around PVC joint
    - Concrete Shrinkage
    - Differential Expansion
  - Chlorides Collect Near Bottom Reinforcing
  - Corrosion and Spalling around Drain





Rehabilitation Reports – Mike Worring, PE | ©2017



## DRAIN SEALING

- Some Solutions:
  - Make sure water can flow to drain
    - Sitting water can wick behind PVC
  - Add Waterstop around Pipe
    - Interrupt water flow
    - Coupler intended to hold drain in place but doesn't act as waterstop
  - Add bead of silicone caulk around outside of Pipe on top of deck



SECTION THRU FLOOR DRAIN  
FLOOR DRAIN DETAIL  
Scale: 3/4\"/>


Rehabilitation Reports – Mike Worring, PE | ©2017



IN CLOSING

# INNOVATIONS

- Notice problems that aren't solved by Standard Details, Specs or Pay Items.
- Try Something.
  - Vet ideas with PM, Bridge Asset Manager, etc.
- Do No Harm
  - Even if your solution doesn't work it will seldom make the situation worse
  - ...and may make it better.



Rehabilitation Reports – Mike Worring, PE | ©2017



# Questions?

Rehabilitation Reports – Mike Worring, PE | ©2017

