


# Bridge Deck Overhang Design

Robert J. Frosch, PhD, PE, FACI

Professor of Civil Engineering  
Senior Associate Dean of Facilities & Operations




## Overhang Design




- Case 1
- Case 2
- Case 3

## Overhang Design for TL-4 Barrier



## Yield Line Analysis



$$W_{INT} = W_{EXT}$$


$$F \cdot \Delta = \sum M\theta$$

$$F = R_w \text{ (nominal railing resistance)}$$

## Barrier Design Forces

Design Forces and Designations	Railing Test Levels					
	TL-1	TL-2	TL-3	TL-4	TL-5	TL-6
$F_t$ Transverse (kips)	<b>13.5</b>	<b>27.0</b>	<b>54.0</b>	<b>54.0</b>	<b>124.0</b>	<b>175.0</b>
$F_L$ Longitudinal (kips)	4.5	9.0	18.0	18.0	41.0	58.0
$F_v$ Vertical (kips) Down	4.5	4.5	4.5	18.0	80.0	80.0
$L_t$ and $L_L$ (ft)	4.0	4.0	4.0	3.5	8.0	8.0
$L_v$ (ft)	18.0	18.0	18.0	18.0	40.0	40.0
$H_e$ (min) (in.)	18.0	20.0	24.0	32.0	42.0	56.0
Minimum $H$ Height of Rail (in.)	27.0	27.0	27.0	32.0	42.0	90.0

## Barrier Resistance



- Barrier overdesign
  - more reinforcement required in overhangs
- Overhang must resist larger moments and axial forces


## Reducing Collision Forces

- AASHTO procedure requires more reinforcement ( $\sim 3 \times F_t$ )
  - Design for barrier capacity
- Past practice required less reinforcement
  - Lower design forces
- INDOT and other states reduce collision force ( $1.25 \times F_t$ )
  - Design for transverse force
- What is the appropriate design procedure?


## Research Objective

- Investigate appropriate design procedure
- Determine failure mechanism in overhang specimens
- Improve design assumptions


## Schematic Design



## 15ft Specimen Design



## Experimental Setup




## Specimen #1 Cracking




## Specimen #2 Cracking



## Vertical Displacement




## 3' Strip Specimens





- 5 full scale INDOT Type FC specimens
- 2 half scale specimens

## Full-Scale Specimen Design



### Test Variables:


- Top Transverse Bar Size
  - #5 and #6
- End Condition
  - Straight and Hook
- Bar Coating
  - Epoxy coat and black



## Experimental Setup

Jack w/ Load Cell

Horizontal Pot.



Full Scale



Half Scale

## Full-Scale Cracking Behavior

#5 Epoxy @ 3.5" Straight  
14 kips#6 Epoxy @ 4.75" Straight  
14 kips

## Full-Scale Cracking Behavior



#5 Epoxy @ 3.5" Hooked  
15 kips



#5 Black @ 3.5" Straight  
15 kips

## Full-Scale Cracking Behavior



#6 Black @ 4.75" Straight  
14 kips



Typical Specimen Failure Plane

## Half-Scale Cracking Behavior




#3 @4.5" Hooked  
8 kips




#3 @ 4.5" Straight  
6 kips

## 27ft Specimens



### Objectives

- Form Barrier Mechanism
- Refine Distribution Length



## Experimental Setup



Specimen #1L Loading



Specimen #2L Loading

## Behavior at Ultimate Load



Specimen #1L at 29.2 kips



## Behavior at Ultimate Load

Specimen #2L at 23.7 kips





## Lower Punching Shear



## Upper Punching Shear



## Nonsymmetrical Failure



## Conclusions

- Diagonal tension joint failure (15ft and 3ft strip specimens)
  - Concrete failure rather than reinforcement anchorage in overhang
  - Only applicable for short bridge lengths (< 30 ft)
- Punching shear failure (27ft specimens)
  - Punching controls prior to forming barrier mechanism (110 kips vs 150 kips)
  - Consistent with actual failures
- Research suggests overhang reinforcement not critical
  - Punching shear governs design
  - Large distribution length ( $10L_t$ )
  - Reinforcement can be reduced in overhang

## Recommendations

- Design overhang for vertical loads (Case 2 and 3)
- If lateral force considered:
  - Design for lesser of:
    - Punching Shear Strength
    - Yield Line Strength
  - Consider distribution length as  $10L_t$

## Questions?

