


# MULTI-LANE DIVIDED HIGHWAY

Median Shoulder



Outside Shoulder \* =

\* =

Work  
Zone


450 m

450 m min.


300 m

300 m min.

150 m



XW20-5 (R)  
(R or L)



XW4-2-(R)

## GENERAL NOTES

- Distances shown are approximate and may be adjusted as directed.
- Strobe lights will be required on all vehicles.

## LEGEND

→ Flashing Arrow Sign

\* High intensity flashing light type B.

Truck with truck mounted attenuator  
(24,000 GVW required)

▲ Cone

3.



WATCH  
FOR STOPPED  
TRAFFIC

XW103-1

Optional sign to be  
placed when directed.


- Lane closure length shall be a maximum of 5 km as directed by Engineer to meet field conditions.

All dimensions are in mm unless otherwise specified.

INDIANA DEPARTMENT OF TRANSPORTATION  
MAINTENANCE OF TRAFFIC FOR  
RPM CASTING INSTALLATION

MAY 2000

STANDARD DRAWING NO. 801-TCTC-06



/s/ Anthony L. Uremovich 5-01-00  
DESIGN STANDARDS ENGINEER DATE

/s/ Firooz Zandi 5-01-00  
CHIEF HIGHWAY ENGINEER DATE