


**GENERAL NOTES**


- ① The Detour Arrow sign shall be used only when a detour route has been signed.
- ② Barricades shall be supported on driven posts in areas outside of the pavement or sidewalk, where side slopes are 3 to 1 or flatter.
- 3. See standard drawing 801-TCSN-11 for additional notes.



**(HALF PLAN WITH SHOULDER SECTION)**

**(HALF PLAN WITH CURB SECTION)**

**PLAN VIEW**



**(HALF ELEVATION WITH SHOULDER SECTION)**

**(HALF ELEVATION WITH CURB SECTION)**

**ELEVATION**

**TYPICAL APPLICATIONS OF TYPE III BARRICADES  
ROAD CLOSED TO ALL TRAFFIC**


All dimensions are in mm unless otherwise specified.

INDIANA DEPARTMENT OF TRANSPORTATION

**TYPE III BARRICADE  
TYPICAL APPLICATIONS**

SEPTEMBER 1997

STANDARD DRAWING NO. 801-TCDV-07



/s/ Anthony L. Uremovich 9-01-97  
DESIGN STANDARDS ENGINEER DATE

/s/ Donald W. Lucas 9-01-97  
CHIEF HIGHWAY ENGINEER DATE

Source Sheet: Det 2A