


### GENERAL NOTES

1. All friction fuse bolts shall be tightened following an approved method.
2. Tightening shall be to such a degree as to obtain the above minimum initial tension in each bolt.
3. The turn-of-nut method of obtaining the required tension will be permitted only to  $\frac{3}{4}$ " bolt diameter.

FOUNDATION DATA				
Post Size	Stub Length	Dia.	Depth	Max. P
W6 x 9	2'-0	20"	5'	4"
W8 x 10	2'-0	20"	5'	4"
W8 x 13	2'-0	20"	5'	4"
W8 x 15	2'-6	24"	6'	4"
W8 x 18	2'-6	24"	6'	4"
W10 x 19	2'-6	24"	7'	4"

INDIANA DEPARTMENT OF TRANSPORTATION									
SIGN DATA TABLES									
MAY 2000									
STANDARD DRAWING NO.E 802-SNGP-07									
	<table><tr><td>/s/ Anthony L. Uremovich</td><td>5-01-00</td></tr><tr><td>DESIGN STANDARDS ENGINEER</td><td>DATE</td></tr><tr><td>/s/ Firooz Zandi</td><td>5-01-00</td></tr><tr><td>CHIEF HIGHWAY ENGINEER</td><td>DATE</td></tr></table>	/s/ Anthony L. Uremovich	5-01-00	DESIGN STANDARDS ENGINEER	DATE	/s/ Firooz Zandi	5-01-00	CHIEF HIGHWAY ENGINEER	DATE
/s/ Anthony L. Uremovich	5-01-00								
DESIGN STANDARDS ENGINEER	DATE								
/s/ Firooz Zandi	5-01-00								
CHIEF HIGHWAY ENGINEER	DATE								
DESIGN STANDARDS ENGINEER									