



REINFORCEMENT DETAILS




SECTION A-A ①

NOTES :

- ① Section A-A shows reinforcement with welded wire fabric.
- ② Hex nut may be tack welded to bottom spacer to facilitate installation and removal. Bolts shall be torqued only to tight condition. Clearance between the spacer and the ends of the barrier shall permit angular deflection at the joints to permit flare rate 11 : 1 or flatter.
- ③ Top spacer TS 4" x 2" x  $\frac{5}{16}$ " x 10" long
- ④ Bottom spacer TS 4" x 2" x  $\frac{5}{16}$ " x 1'-4" long
- 5 Where necessary to meet short radius curving alignment, the shorter top spacer (10") may be substituted for the standard bottom spacer (16").
- 6 For additional connection details see Standard Drawing E 801-TCCB-01.
- ⑦ Where very short radius curving alignment is encountered, spacers may be TS 3" x 2" x  $\frac{1}{4}$ " x the appropriate length as shown above.



FRONT VIEW  
CONNECTION DETAIL



INDIANA DEPARTMENT OF TRANSPORTATION	
TEMPORARY CONCRETE BARRIER DETAILS	
MARCH 2004	
STANDARD DRAWING NO. E 801-TCCB-02	
	/s/ Richard L. VanCleave DESIGN STANDARDS ENGINEER
	3-01-04 DATE
	/s/ Richard K. Smutzer CHIEF HIGHWAY ENGINEER
	3-01-04 DATE