


**GENERAL NOTES**

1. Nut shall be tightened sufficiently so that the sign is held firmly against the post. However, there shall be no deformation of aluminum sheeting or twisting or damage to the reflective sheeting.
2. Signs shall be fastened to the posts with bolts, metal and nylon washers and locknut.
3. A nylon washer and a metal washer shall be placed between each bolt head and the face of the sign.
4. Flanged channel posts are as specified and as shown on the plans.
5. The sheet signs shall be punched or drilled for mounting such that the vertical hole spacing is in equal increments of millimeters.
6. See Std. Dwg. No. E 802-SNPL-02 for mounting height and lateral locations of signs.
7. Splicing of flanged channel post will not be permitted.
8. Bolt can either be stainless steel or galvanized steel bolt.

INDIANA DEPARTMENT OF TRANSPORTATION	
<b>MISC. SIGN DETAILS</b> <b>GENERAL NOTES</b> MAY 1999	
<b>STANDARD DRAWING NO. E 802-SNGS-08</b>	
 <p>ANTHONY L. UREMOWICH REGISTERED No. 18095 STATE OF INDIANA PROFESSIONAL ENGINEER</p>	DETAILS PLACED IN THIS FORMAT 11-15-99
	/s/ Anthony L. Uremovich 11-15-99 DESIGN STANDARDS ENGINEER DATE
	/s/ Firooz Zandi 11-15-99 CHIEF HIGHWAY ENGINEER DATE
	DESIGN STANDARDS ENGINEER ORIGINALLY APPROVED 5-03-99