


GENERAL NOTES

1. Nut shall be tightened sufficiently so that the sign is held firmly against the post. However, there shall be no deformation of aluminum sheeting or twisting or damage to the reflective sheeting.
2. Signs shall be fastened to the posts with bolts, metal and nylon washers and locknut.
3. A nylon washer and a metal washer shall be placed between each bolt head and the face of the sign.
4. Flanged channel posts are as specified and as shown on the plans.
5. The sheet signs shall be punched or drilled for mounting such that the vertical hole spacing is in equal increments of millimeters.
6. See Std. Dwg. No. E 802-SNPL-02 for mounting height and lateral locations of signs.
7. Splicing of flanged channel post will not be permitted.
8. Bolt can either be stainless steel or galvanized steel bolt.

INDIANA DEPARTMENT OF TRANSPORTATION	
MISC. SIGN DETAILS	
GENERAL NOTES	
MAY 1999	
STANDARD DRAWING NO. E 802-SNGS-08	
	DETAILS PLACED IN THIS FORMAT 11-15-99 /s/ <i>Anthony L. Uremovich</i> 11-15-99 <small>DESIGN STANDARDS ENGINEER DATE</small>
DESIGN STANDARDS ENGINEER	/s/ <i>Firooz Zandi</i> 11-15-99 <small>CHIEF HIGHWAY ENGINEER DATE</small>
ORIGINALLY APPROVED 5-03-99	