

R 6 S 6 Strap (#6 bar shown) Hook bolts shall be located 9"± 3" from the end of pipe 3 -#6 1/2 Span Conc class A G 6 6 - #6

ANCHOR FOR STRUCTURAL PLATE PIPE-ARCH PARTIAL ELEVATION

GENERAL NOTES

- Anchor straps shall be used at both upstream and downstream ends of all structural plate pipes and pipe-arches.
- See Standard Drawing E 715-PASD-01 for anchor strap details.
- 3. Hook bolts and anchor straps shall be used for all structural plate pipes and pipe-arches with a diameter or span of 84" or greater.
- 4. See Standard Drawing E 715-PAHB-01 for hook bolt details.
- 5. Riprap shall be placed at the ends of pipe structures when shown on the plans.
- 6 For dimension, enter chart on Standard Drawings E 717-ANCH-01 or E 717-ANCH-02 with known dimension D or span and rise.

INDIANA DEPARTMENT OF TRANSPORTATION

MULTIPLE PIPE CONCRETE ANCHOR

JANUARY 1998

STANDARD DRAWING NO.E 717-MPCA-02

No. 18095 RESTATE OF THE PROPERTY OF THE PROPE

DETAILS PLACED IN THIS FORMAT 7-27-99

/s/ Anthony L. Uremovich 7-27-99
DESIGN STANDARDS ENGINEER DATE

/s/ Firooz Zandi 7-27-99
CHIEF HIGHWAY ENGINEER DATE

DESIGN STANDARDS ENGINEER

ORIGIANLLY APPROVED