

ARCHIVED

Design Element			Manual Section	Rural	Urban
Design Controls	Design Forecast Year	40-2.02		20 Years	20 Years
	*Design Speed (km/h)	40-3.0		110	80-110 (1)
	Access Control	40-5.0		Full Control	Full Control
	Level of Service	40-2.0		Desirable: B Minimum: C	Desirable: B Minimum: C (2)
Cross Section Elements	Travel Lane	*Width	45-1.01	3.6 m	3.6 m
		Surface Type(3)	Ch. 52	Asphalt / Concrete	Asphalt / Concrete
	Shoulder	*Right Width(4)	45-1.02	Usable: 3.3 m Paved: 3.0 m	Usable: 3.3 m Paved: 3.0 m
		*Left Width(5)		2 Ln: D 2.4, M 1.2 m Paved; 3 Ln: 3.0 m Paved	2 Lanes: 1.2 m Paved 3 Lanes: 3.0 m Paved
		Surface Type(3)	Ch. 52	Asphalt / Concrete	Asphalt / Concrete
	Cross Slope	*Travel Lane (6)	45-1.01	2%	2%
		Shoulder (6A)	45-1.02	Paved Width ≤ 1.2 m: 2% Paved Width > 1.2 m: 4%	Paved Width ≤ 1.2 m: 2% Paved Width > 1.2 m: 4%
	Auxiliary Lanes	*Lane Width	45-1.03	3.6 m	3.6 m
		*Shoulder Width		Right: 3.0 m (7) Left: 1.2 m	Right: 3.0 m (7) Left: 1.2 m
	Median Width	Depressed	45-2.0	Desirable: 25 m Minimum: 18 m	Desirable: 18 m Minimum: 7.9 m
		Flush (CMB)		Minimum: 8.0 m	Minimum: 8.0 m
	Clear Zone		49-2.0	(8)	(8)
	Side Slopes (9)	Cut	Foreslope	6:1 (10)	6:1 (10)
			Ditch Width	1.2 m (11)	1.2 m (11)
			Backslope	4:1 (12)	4:1 (12)
		Fill	45-3.0	6:1 to Clear Zone; 3:1 max. to Toe	6:1 to Clear Zone; 3:1 max. to Toe
	Median Slopes		45-2.02	Desirable: 8:1 Maximum: 5:1	Desirable: 8:1 Maximum: 5:1
Bridges	New or Reconstructed Bridge	*Structural Capacity	Ch. 60	HS-25 & Alternate Military Loading (13)	HS-25 & Alternate Military Loading (13)
		*Clear Roadway Width (14)	45-4.01	Full Paved Approach Width	Full Paved Approach Width
	Existing Bridge to Remain in Place	*Structural Capacity	Ch. 72	HS-20	HS-20
		*Clear Roadway Width	45-4.01	Travelway Plus 3.0 m Rt. & 1.2 m Lt. Shoulders	Travelway Plus 3.0 m Rt. & 1.2 m Lt. Shoulders
	*Vertical Clearance (Freeway Under) (15c)	New or Replaced Overpassing Bridge (15a)		5.05 m	5.05 m (15b)
		Existing Overpassing Bridge	44-4.0	4.90 m	4.90 m (15b)
		Sign Truss / Pedestrian Bridge (15a)		New: 5.35 m; Existing: 5.20 m	New: 5.35 m; Existing: 5.20 m
	Vertical Clearance (Freeway over Railroad) (16)		Ch. 69	7.00 m	7.00 m

\* Controlling design criteria (see Section 40-8.0).

## GEOMETRIC DESIGN CRITERIA FOR FREEWAY

### (New Construction or Complete Reconstruction)

Table 53-1

Design Element		Manual Section	Rural	Urban			
Alignment Elements	Design Speed	---	110 km/h	80 km/h	90 km/h	100 km/h	110 km/h
	*Stopping Sight Distance	42-1.0	220 m	130	160 m	185 m	220 m
	Decision Sight Distance (17)	42-2.0	235 m	315	360 m	400 m	430 m
	*Minimum Radii (e=8%)	43-2.0	502 m	230	305 m	395 m	505 m
	*Superelevation Rate	43-3.0	e <sub>max</sub> =8% (18)	e <sub>max</sub> =8% (18)			
	*Horizontal Sight Distance	43-4.0	(19)	(19)			
	*Vertical Curvature (K-values)	Crest 44-3.0 Sag	74 55	26 30	39 38	52 45	74 55
	*Maximum Grade (20)	Level 44-1.02 Rolling	3% 4%	4% 5%	3.5% 4.5%	3% 4%	3% 4%
	Minimum Grade	44-1.03	Desirable: 0.5% Minimum: 0.0%	Desirable: 0.5% Minimum: 0.0%			

\* Controlling design criteria (see Section 40-8.0).

These standards are for use on a freeway including that on the National Highway System. They are to be used for each project that is classified as new construction or reconstruction regardless of funding source. Deviations from controlling design criteria should be covered by an approved design exception.

Design exception requests are required for Level One design criteria for each project type as follows:

- Non-exempt federally-funded project on the Interstate system requires FHWA approval.
- Exempt federally-funded project on the Interstate system requires Chief, Design Division approval.
- Non-federally-funded project on the Interstate system requires Chief, Design Division approval with an information copy sent to FHWA.
- Project not on the Interstate system requires Chief, Design Division approval.

## GEOMETRIC DESIGN CRITERIA FOR FREEWAY (New Construction or Complete Reconstruction)

**Table 53-1 (Continued)**

## **GEOMETRIC DESIGN CRITERIA FOR FREEWAY** **(New Construction or Complete Reconstruction)**

### **Footnotes to Table 53-1**

- (1) Design Speed. An 80-km/h design speed may be considered in a restrictive urban area.
- (2) Level of Service. A minimum Level of Service of D may be used for urban reconstruction.
- (3) Surface Type. The pavement type selection will be determined by the Materials and Tests Division's pavement design engineer.
- (4) Shoulder Width (Right). The following will apply:
  - a. The shoulder is paved to the face of guardrail. The desirable guardrail offset is 0.6 m from the effective usable shoulder width. See Section 49-5.0 for more information.
  - b. Where the number of trucks exceeds 250 DDHV, a 3.6-m right shoulder should be used. If the 3.6-m shoulder is used, the usable shoulder width will be 3.9 m.
  - c. Usable shoulder width is defined as the distance from the edge of the travel lane to the shoulder break point.
- (5) Shoulder Width (Left). The following will apply:
  - a. Typically, the usable shoulder width is equal to the paved shoulder width. The desirable guardrail offset is 0.6 m from the usable shoulder width. See Section 49-5.0 for more information.
  - b. Where there are 3 or more lanes in one direction and the volume of trucks exceed 250 DDHV, a 3.6-m left shoulder should be used.
  - c. For a left shoulder greater than 1.2 m, the usable shoulder width will be 0.3 m more than the paved shoulder width.
- (6) Cross Slope (Travel Lane). Cross slopes of 1.5% are acceptable on an existing bridge to remain in place.
- (6A) Cross Slope (Shoulder). See Figure 45-1A(1) or Figure 45-1A(2) for more-specific information.
- (7) Auxiliary Lane Shoulder Width (Right). On a reconstruction project, a 1.8-m right shoulder may be used.
- (8) Clear Zone. The clear zone will vary according to design speed, traffic volumes, side slopes, and horizontal curvature. See Section 49-2.0.
- (9) Side Slopes. Values in the tables are for new construction. See Section 45-3.0 and section 45-8.0 for more information. For a reconstruction project, see Section 49-3.0.
- (10) Foreslope. See Sections 49-2.0 and 49-3.0 for the lateral extent of the foreslope in a ditch section.

- (11) Ditch Width. A V-ditch should be used in a rock cut. See Section 45-8.0.
- (12) Backslopes. For an earth cut greater than 3.0 m in height, the first horizontal 6.0 m of the backslope should be sloped at a rate of 4:1 and the remainder should be sloped at 3:1 to the natural ground line. See Section 45-3.0 and the INDOT *Standard Drawings*. The backslope for a rock cut will vary according to geotechnical factors and the height of cut. See the INDOT *Standard Drawings* for typical rock cut sections.
- (13) Structural Capacity (New or Reconstructed Bridge). Other loadings will apply to the Toll Road or an Extra Heavy Duty Highway. See Chapter Sixty for more information.
- (14) Width (New or Reconstructed Bridge). See Section 59-1.0 for more information on bridge width.
- (15) Vertical Clearance (Freeway Under). The following will apply:
  - a. Table values include an additional 150 mm allowance for a future overlay.
  - b. A 4.3-m clearance may be used in an urban area where an alternate freeway facility with a 4.9-m clearance is available.
  - c. Vertical clearances apply from usable edge to usable edge of shoulders.
- (16) Vertical Clearance (Freeway Over Railroad). See Chapter Sixty-nine for additional information on railroad clearance under a highway.
- (17) Decision Sight Distance. Table values are for the avoidance maneuver (speed/path/direction change). See Section 42-2.0.
- (18) Superelevation Rate. See Section 43-3.0 for values of superelevation based on design speed and radii.
- (19) Horizontal Sight Distance. For a given design speed, the necessary middle ordinate will be determined by the radius and the sight distance. The SSD values for trucks should sometimes be considered. See the discussion in Section 43-4.0.
- (20) Maximum Grade. A grade 1% steeper than that shown in the table may be used in a restricted urban area where development precludes the use of a flatter grade. A grade 1% steeper than that shown in the table may also be used for a one-way downgrade.
- (21) For a bridge longer than 60 m that is to remain in place, the minimum widths of both shoulders may be 1.2 m. This requirement does not apply to a bridge deck replacement.

Design Element			Manual Section	2-Lane			Multi-Lane			
Design Controls	Design Year Traffic	AADT	40-2.01	< 400	400 ≤ AADT < 2000	≥ 2000	**Undivided	Divided		
	Design Forecast Year		40-2.02	20 Years			20 Years			
	*Design Speed (km/h) (1)		40-3.0	Level: 100-110; Rolling: 80-100			100	110		
	Access Control		40-5.0	Partial Control / None			Partial Control / None			
	Level of Service		40-2.0	Desirable: B; Minimum: C			Desirable: B; Minimum: C			
Cross Section Elements*	Travel Lane	*Width	45-1.01	3.6 m			3.6 m			
	Typical Surface Type (2)		Ch. 52	Asphalt / Concrete			Asphalt / Concrete			
	Shoulder (3)	*Width Usable	45-1.02	1.8 m	2.4 m	3.3 m (3b)	3.3 m (3b)	Right: 3.3 m (3b) Left: 1.2 m (3e)		
		*Width Paved	45-1.02	1.2 m	1.8 m	3.0 m (3b)	3.0 m (3b)	Right: 3.0 m (3b) Left: 1.2 m (3e)		
	Typical Surface Type (2)		Ch. 52	Asphalt / Concrete			Asphalt / Concrete			
	Cross Slope	*Travel Lane (4)	45-1.01	2%			2%			
		Shoulder (4A)	45-1.02	Paved Width ≤ 1.2 m: 2% Paved Width > 1.2 m: 4%			Paved Width ≤ 1.2 m: 2% Paved Width > 1.2 m: 4%			
	Auxiliary Lanes	Lane Width (5)	45-1.03	Desirable: 3.6 m; Minimum: 3.3 m			Desirable: 3.6 m; Minimum: 3.3 m			
		Shoulder Width (6)	45-1.03	Same as That Next to Travel Lane			Same as That Next to Travel Lane			
	Median Width		45-2.0	N/A			0.0 m	Desirable: 25.0 m Minimum: 4.8 m (7)		
	Clear Zone		49-2.0	(8)			(8)			
	Side Slopes (9)	Cut	Foreslope	6:1 (10)			6:1 (10)			
				1.2 m (11)			1.2 m (11)			
		Fill	Backslope	4:1 for 6.0 m; 3:1 Max. to Top (12)			4:1 for 6.0 m; 3:1 Max. to Top (12)			
				6:1 to Clear Zone; 3:1 Max. to Toe			6:1 to Clear Zone; 3:1 Max. to Toe			
	Median Slopes		45-2.02	N/A			Desirable: 8:1; Maximum: 5:1			
Bridges**	New or Reconstructed Bridge	*Structural Capacity	Ch. 60	HS-25 (13)						
		*Clear Roadway Width(14)	45-4.01	Full Paved Approach Width						
	Existing Bridge Bridge to Remain in Place	*Structural Capacity	Ch. 72	HS-20						
		*Clear Roadway Width	45-4.01	Travelway Plus 0.6 m on Each Side						
	Vertical Clearance (Arterial Under)	New or Replaced Overpassing Bridge (15)	44-4.0	5.05 m						
		Existing Overpassing Bridge		4.30 m						
		Sign Truss / Pedestrian Bridge (15)		New: 5.35 m; Existing: 5.20 m						
	Vertical Clearance (Arterial Over Railroad) (16)		Ch. 69	7.00 m						

Controlling design criteria (see Section 40-8.0). \*\* A multi-lane arterial on a new locations should be designed as Divided.

\*\*\* Selection of the cross section and bridge elements is based on the design-year traffic volume irrespective of the design speed.

## GEOMETRIC DESIGN CRITERIA FOR RURAL ARTERIAL (New Construction or Reconstruction)

Table 53-2

Design Element		Manual Section	Rural Arterial			
Alignment Elements	Design Speed	---	80 km/h	90 km/h	100 km/h	110 km/h
	*Stopping Sight Distance	42-1.0	130 m	160	185 m	220 m
	Decision Sight Distance	42-2.0	230 m	270	315 m	330 m
			140 m	170 m	200 m	235 m
	Passing Sight Distance	42-3.0	540 m	615 m	670 m	730 m
	Intersection Sight Distance, -3% to +3% (20)	46-10.0	P: 190 m; SU: 235 m	P: 230 m; SU: 280 m	P: 265 m; SU: 320 m	P: 310 m; SU: 370 m
	*Minimum Radii (e=8%)	43-2.0	230 m	305 m	395 m	505 m
	*Superelevation Rate	43-3.0	emax = 8% (17)			
	*Horizontal Sight Distance	43-4.0	(18)			
	*Vertical Curvature (K-values)	44-3.0	26	39	52	74
			30	38	45	55
	*Maximum Grade (19)	44-1.02	4%	3.5%	3%	3%
			5%	4.5%	4%	4%
Minimum Grade		44-1.03	Desirable: 0.5%; Minimum: 0.0%			

\* Controlling design criteria (see Section 40-8.0).

These standards are for use on a Rural Arterial including that on the National Highway System. They are to be used for each project that is classified as new construction or reconstruction regardless of funding source. Deviations from controlling design criteria should be covered by an approved design exception.

Design exception requests are required for Level One design criteria for each project type as follows:

- Non-exempt federally-funded project on the Interstate system requires FHWA approval.
- Exempt federally-funded project on the Interstate system requires Chief, Design Division approval.
- Non-federally-funded project on the Interstate system requires Chief, Design Division approval with an information copy sent to FHWA.
- Project not on the Interstate system requires Chief, Design Division approval.

## GEOMETRIC DESIGN CRITERIA FOR RURAL ARTERIAL (New Construction or Reconstruction)

**Table 53-2 (Continued)**

## GEOMETRIC DESIGN CRITERIA FOR RURAL ARTERIAL (New Construction or Reconstruction)

### Footnotes to Table 53-2

(1) Design Speed. The minimum design speed should equal the minimum value from the table or the anticipated posted speed limit after construction, whichever is greater. The state legal limit is 60 mph on a non-posted highway.

(2) Surface Type. The pavement type selection will be determined by the Materials and Tests Division's pavement design engineer.

(3) Shoulder. The following will apply:

- a. If there are 3 or more lanes in each direction and there is a median barrier, a 3.0 m paved shoulder and a 0.6 m offset is required.
- b. On a reconstruction project, the usable shoulder width may be 3.0 m, and the paved width may be 2.4 m.
- c. The shoulder is paved to the face of guardrail. The desirable guardrail offset is 0.6 m from the effective usable shoulder width. See Section 49-5.0 for more information.
- d. Usable shoulder width is defined as the distance from the edge of the travel lane to the shoulder break point.
- e. If there are three or more lanes in each direction, a full-width shoulder, 3.3 m usable and 3.0 m paved, is desirable.

(4) Cross Slope (Travel Lanes). Cross slopes of 1.5% are acceptable on an existing bridge to remain in place. Where three or more lanes are sloped in the same direction, each successive pair of lanes may have an increased sideslope.

(4A) Cross Slope (Shoulder). See Figure 45-1A(1) or Figure 45-1A(2) for more-specific information.

(5) Auxiliary Lane (Lane Widths). The width of a truck climbing lane should be 3.6 m.

(6) Auxiliary Lane (Shoulder Width). At a minimum, a 0.6-m shoulder may be used adjacent to an auxiliary lane. At a minimum, a shoulder adjacent to a truck climbing lane should be 1.2 m.

(7) Median Width (Flush). Values in the table are for new construction. A median of less than 7.5 m should be avoided at an intersection. A median width of greater than 18 m is undesirable at a signalized intersection or an intersection that may become signalized in the foreseeable future. On a reconstruction project, the minimum flush median width is 4.2 m for a roadway with a left-turn lane and 6.6 m for a roadway with a median barrier.

(8) Clear Zone. The clear zone will vary according to design speed, traffic volumes, side slopes, and horizontal curvature. See Section 49-2.0.

(9) Side Slopes. Values in the tables are for new construction. See Section 45-3.0 and Section 45-8.0 for more information. For a reconstruction project, see Section 49-3.0.

(10) Foreslope. See the Sections 49-2.0 and 49-3.0 for the lateral extent of the foreslope in a ditch section.

(11) Ditch Widths. A V-ditch should be used in a rock cut. See Section 45-8.0.

(12) Backslopes. The backslope for a rock cut will vary according to geotechnical factors and the height of the cut. See Section 45-8.0 for typical rock cut sections.

(13) Structural Capacity (New or Reconstructed Bridge). The following will apply:

- a. Each bridge on a facility with greater than 600 trucks per day should be checked using the Alternate Military loading.
- b. Each State highway bridge within 25 km of a Toll Road gate must be designed for Toll Road Loading.
- c. Each bridge on an Extra Heavy Duty Highway must be designed for the Michigan Train truck loading configuration.
- d. See Chapter Sixty for additional information on the loading configurations.

(14) Width (New or Reconstructed Bridge). See Section 59-1.0 for more information on bridge width.

(15) Vertical Clearance (Arterial Under). Table values include an additional 150 mm allowance for a future pavement overlay. Vertical clearances apply from usable edge to usable edge of shoulders.

(16) Vertical Clearance (Arterial Over Railroad). See Chapter Sixty-nine for additional information on railroad clearance under a highway.

(17) Superelevation Rate. See Section 43-3.0 for values of superelevation based on design speed and radii.

(18) Horizontal Sight Distance. For a given design speed, the necessary middle ordinate will be determined by the radius and the sight distance which applies at the site. The SSD values for trucks should sometimes be considered. See the discussion in Section 43-4.0.

(19) Maximum Grades. A grade 1% steeper than that shown in the table may also be used for a one-way downgrade.

(20) Intersection Sight Distance. For left turn onto a 2-lane road. P = Passenger car; SU = single unit truck. See Figure 46-10G for values for combination trucks.

Design Element			Manual Section	2-Lane						
Design Controls	Design Year Traffic	AADT	40-2.01	< 400	400 ≤ AADT < 1500	1500 ≤ AADT < 2000	> 2000			
	Design Forecast Year		40-2.02	20 Years						
	*Design Speed (km/h) (2)	Level	40-3.0	60 - 90	80 - 90	80 - 90	100			
		Rolling		60 - 90	60 - 90	60 - 90	80 - 90			
	Access Control		40-5.0	None						
Level of Service			40-2.0	Desirable.: B; Minimum: C						
Cross Section Elements**	Travel Lane	*Width		45-1.01	D: 3.6 m; M: 3.3 m	D: 3.6 m; M: 3.3 m	D: 3.6 m; M: 3.3 m (20) 3.6 m			
		Typical Surface Type (3)		Ch. 52	Asphalt / Concrete					
	Shoulder (4)	*Width Usable		45-1.02	1.2 m	1.8 m	2.4 m 3.0 m			
		*Width Paved		45-1.02	0.6 m	1.2 m	1.8 m 2.4 m			
	Typical Surface Type (3)		Ch. 52	Asphalt / Concrete						
	Cross Slope	*Travel Lane (5)		45-1.01	2%					
		Shoulder (5A)		45-1.02	Paved Width ≤ 1.2 m: 2%; Paved Width > 1.2 m: 4%					
	Auxiliary Lane	Lane Width		45-1.03	Des: Same as Through Lanes; Min: 3.3 m		Desirable: 3.6 m Minimum: 3.3 m			
		Shoulder Width (6)			Same as Next to Travel Lane					
	Clear Zone		49-2.0	(7)						
	Side Slopes (8)	Cut	Foreslope	45-3.0	Des: 6:1; Max: 4:1 (9)					
			Ditch Width		1.2 m (10)					
		Backslope			4:1 for 6.0 m; 3:1 Max. to Top (11)					
		Fill		45-3.0	Des: 6:1 to Clear Zone; Max: 3:1 to Toe					
Bridges**	New or Reconstructed Bridge	*Structural Capacity		HS-25 (12)						
		*Clear Roadway Width (13)		Full Paved Approach Width						
	Existing Bridge to Remain in Place	*Structural Capacity		HS-15						
		*Clear Roadway Width (14)		45-4.01	6.6 m	6.6 m	7.2 m 8.4 m			
	*Vertical Clearance (Collector Under)	New or Replaced Overpassing Bridge (15)		44-4.0	4.45 m					
		Existing Overpassing Bridge			4.30 m					
	Vertical Clearance (Collector Over Railroad) (16)			Ch. 69	7.00 m					

\* Controlling design criteria (see Section 40-8.0).

D or Des: Desirable; M or Min: Minimum

\*\* Selection of the cross section and bridge elements is based on the design-year traffic volumes irrespective of the design speed.

## GEOMETRIC DESIGN CRITERIA FOR STATE RURAL COLLECTOR (New Construction or Reconstruction)

Table 53-3

n Element		Manual Section	2-Lane				
Alignment Elements	Design Speed		60 km/h	70 km/h	80 km/h	90 km/h	100 km/h
	*Stopping Sight Distance	42-1.0	85 m	105 m	130 m	160 m	185 m
	Decision Sight Distance	Speed / path / direction change	170 m	200 m	230 m	270 m	315 m
			95 m	115 m	140 m	170 m	200 m
	Passing Sight Distance	42-3.0	410 m	485 m	540 m	615 m	670 m
	Intersection Sight Distance, -3% to +3% (21)	46-10.0	P: 125 m SU: 160 m	P: 150 m SU: 185 m	P: 190 m SU: 235 m	P: 230 m SU: 280 m	P: 265 m SU: 320 m
	*Minimum Radii (e=8%)	43-2.0	125 m	180 m	230 m	305 m	395 m
	*Superelevation Rate	43-3.0	e <sub>max</sub> = 8% (17)				
	*Horizontal Sight Distance	43-4.0	(18)				
	*Vertical Curvature (K-values)	Crest	11	17	26	39	52
			18	23	30	38	45
	*Maximum Grade (19)	Level	7%	6.5%	6%	5.5%	5%
		Rolling	8%	7.5%	7%	6.5%	6%
Minimum Grade		44-1.03	Desirable: 0.5%   Minimum: 0.0%				

\* Controlling design criteria (see Section 40-8.0).

These standards are to be used for each project on a state rural collector that is classified as new construction or reconstruction regardless of funding source. Deviations from controlling Level One design criteria should be covered by a design exception approved by the Chief, Design Division.

### GEOMETRIC DESIGN CRITERIA FOR STATE RURAL COLLECTOR (New Construction or Reconstruction)

**Table 53-3 (Continued)**

## **GEOMETRIC DESIGN CRITERIA FOR STATE RURAL COLLECTOR** **(New Construction or Reconstruction)**

### **Footnotes to Table 53-3**

- (1) (Note deleted.)
- (2) Design Speed. The minimum design speed should equal the minimum value from the table or the anticipated posted speed limit after construction, whichever is greater. The state legal limit is 55 mph on a non-posted highway.
- (3) Surface Type. The pavement type selection will be determined by the Materials and Tests Division's pavement design engineer.
- (4) Shoulder Width. The following will apply:
  - a. The shoulder is paved to the face of guardrail. The desirable guardrail offset is 0.6 m from the effective usable shoulder width. See Section 49-5.0 for more information.
  - b. Usable shoulder width is defined as the distance from the edge of the travel lane to the shoulder break point.
- (5) Cross Slope (Travel Lanes). Cross slopes of 1.5% are acceptable on an existing bridge to remain in place.
- (5A) Cross Slope (Shoulder). See Figure 45-1A(1) or Figure 45-1A(2) for more-specific information.
- (6) Auxiliary Lane (Shoulder Width). At a minimum, a 0.6-m shoulder may be used adjacent to an auxiliary lane.
- (7) Clear Zone. The clear zone will vary according to design speed, traffic volumes, side slopes, and horizontal curvature. See Section 49-2.0.
- (8) Side Slopes. Values in the tables are for new construction. See Section 45-3.0 and Section 45-8.0 for more information. For a reconstruction project, see Section 49-3.0.
- (9) Foreslope. See Sections 49-2.0 and 49-3.0 for the lateral extent of the foreslope in a ditch section.
- (10) Ditch Widths. A V-ditch should be used in a rock cut. See Section 45-8.0.
- (11) Backslopes. The backslope for a rock cut will vary according to geotechnical factors and the height of the cut. See Section 45-8.0 for typical rock cut sections.

(12) Structural Capacity (New or Reconstructed Bridge). The following will apply:

- a. Each bridge on a facility with greater than 600 trucks per day should be checked using the Alternate Military loading.
- b. Each State highway bridge within 25 km of a Toll Road gate must be designed for Toll Road Loading.
- c. Each bridge on an Extra Heavy Duty Highway must be designed for the Michigan Train truck loading configuration.
- d. See Chapter Sixty for additional information on the loading configurations.

(13) Width (New or Reconstructed Bridge). Minimum clear roadway width will be 9.4 m. See Section 59-1.0 for more information on bridge width.

(14) Width (Existing Bridge to Remain in Place). Clear width will be at least equal to the approach traveled way width or the table values, whichever is greater.

(15) Vertical Clearance (Collector Under). Table values include an additional 150 mm allowance for a future pavement overlay. Vertical clearances apply from usable edge to usable edge of shoulders.

(16) Vertical Clearance (Collector Over Railroad). See Chapter Sixty-nine for additional information on railroad clearance under a highway.

(17) Superelevation Rate. See Section 43-3.0 for values of superelevation based on design speed and radii.

(18) Horizontal Sight Distance. For a given design speed, the necessary middle ordinate will be determined by the radius and the sight distance which applies at the site. See Section 43-4.0.

(19) Maximum Grades. For a grade of less than 150 m in length (PVT to PVC), a one-way downgrade, or a grade on a road with  $AADT < 400$ , the maximum grade may be up to 2% steeper than the table value.

(20) Use 3.6 m if  $V = 90$  km/h.

(21) Intersection Sight Distance. For left turn onto a 2-lane road. P = Passenger car; SU = single unit truck. See Figure 46-10G for values for combination trucks.

Design Element			Manual Section	2-Lane			
Design Controls	Design Year Traffic	AADT	40-2.01	< 400	400 ≤ AADT < 1500	1500 ≤ AADT < 2000	≥ 2000
	Design Forecast Year		40-2.02		20 Years		
	*Design Speed (km/h) (3)	Level	40-3.0	60 - 90	80 - 90	80 - 90	100
		Rolling		50 - 90	60 - 90	60 - 90	80 - 90
	Access Control		40-5.0	None			
	Level of Service		40-2.0	Desirable: B; Minimum: C			
Cross Section Elements*	Travel Lane	*Width (4)	45-1.01	3.0 m (4a)	3.3 m	3.3 m (4b)	3.6 m
		Typical Surface Type	Ch. 52	Asphalt / Concrete			
	Shoulder	*Width Usable	45-1.02	Des: 1.2 m Min: 0.6 m (5)	Des: 1.8 m Min: 1.2 m	Des: 2.4 m Min: 1.8 m	Des: 3.0 m Min: 2.4 m
		*Width Paved (optional)	45-1.02	0.6 m	1.2 m	1.8 m	2.4 m
		Typical Surface Type	Ch. 52	Asphalt / Aggregate / Earth			
	Cross Slope	*Travel Lane (6)	45-1.01	2%			
		Shoulder (6A)	45-1.02	Paved Width ≤ 1.2 m: 2%; Paved Width > 1.2 m: 4% - 6% Asphalt; 6%-8% Aggregate; 8% Earth			
	Auxiliary Lanes	Lane Width	45-1.03	3.0 m		Desirable: 3.3 m Minimum: 3.0 m	Desirable: 3.6 m Minimum: 3.0 m
		Shoulder Width		Desirable: Same as Next to Travel Lane; Minimum: 0.6 m			
	Clear Zone		49-2.0	(7)			
	Side Slopes (8)	Cut	Foreslope Ditch Width Backslope	Des: 6:1; Max: 4:1 (9)			
				1.2 m (10)			
				4:1 for 6.0 m; 3:1 Max. to Top (11)			
		Fill	45-3.0	Des: 6:1 to Clear Zone; Max: 3:1 to Toe			
Bridges**	New or Reconstructed Bridge	*Structural Capacity	Ch. 60	HS-25 (11a)			
		*Clear Roadway Width (12)	45-4.01	Travelway + 1.2 m	Travelway + 1.8 m	Travelway + 2.4 m	Full Paved Approach Width
	Existing Bridge to Remain in Place	*Structural Capacity	Ch. 72	HS-15			
		*Clear Roadway Width (13)	45-4.01	6.6 m	6.6 m	7.2 m	8.4 m
	*Vertical Clearance (Collector Under)	New or Replaced Overpassing Bridge (14)	44-4.0	4.45 m			
		Existing Overpassing Bridge		4.30 m			
	Vertical Clearance (Collector Over Railroad) (15)		Ch. 69	7.00 m			

\* Controlling design criteria (see Section 40-8.0).

Des: Desirable; Min: Minimum.

\*\* Selection of the cross section and bridge elements is based on the design-year traffic volumes irrespective of the design speed.

## GEOMETRIC DESIGN CRITERIA FOR LOCAL AGENCY RURAL COLLECTOR<sup>(1)</sup> (New Construction or Reconstruction)

Table 53-4

Design Element		Manual Section	2-Lane					
Alignment Elements	Design Speed	---	50 km/h	60 km/h	70 km/h	80 km/h	90 km/h	100 km/h
	*Stopping Sight Distance	42-1.0	65 m	85 m	105 m	130 m	160 m	185 m
	Decision Sight Distance	42-2.0	145 m	170 m	200 m	230 m	270 m	315 m
			70 m	95 m	115 m	140 m	170 m	200 m
	Passing Sight Distance	42-3.0	345 m	410 m	485 m	540 m	615 m	670 m
	Intersection Sight Distance, -3% to +3% (19)	46-10.0	P: 105 m SU: 135 m	P: 125 m SU: 160 m	P: 150 m SU: 185 m	P: 170 m SU: 235 m	P: 230 m SU: 280 m	P: 265 m SU: 320 m
	*Minimum Radii (e=8%)	43-2.0	85 m	125 m	180 m	230 m	305 m	395 m
	*Superelevation Rate	43-3.0	emax = 8% (16)					
	*Horizontal Sight Distance	43-4.0	(17)					
	*Vertical Curvature (K-values)	44-3.0	7	11	17	26	39	52
			13	18	23	30	38	45
	*Maximum Grade (18)	44-1.02	7%	7%	6%	6%	5.5%	5%
			9%	8%	7%	7%	6.5%	6%
Minimum Grade		44-1.03	Desirable: 0.5%; Minimum: 0.0%					

\* Controlling design criteria (see Section 40-8.0).

These standards are to be used for each federal-aid funded project on a local agency rural collector that is classified as new construction or reconstruction. Deviations from controlling Level One design criteria should be covered by a design exception approved by the Chief, Design Division.

## GEOMETRIC DESIGN CRITERIA FOR LOCAL AGENCY RURAL COLLECTOR <sup>(1)</sup> (New Construction or Reconstruction)

Table 53-4 (Continued)

**GEOMETRIC DESIGN CRITERIA FOR LOCAL AGENCY RURAL COLLECTOR**  
**(New Construction or Reconstruction)**

**Footnotes to Table 53-4**

- (1) Applicability. This table is only applicable to a federal-aid funded project.
- (2) (Blank)
- (3) Design Speed. The minimum design speed should equal the minimum value from the table or the anticipated posted speed limit after construction, whichever is greater. The state legal limit is 55 mph on a non-posted highway.
- (4) Travel Lane Width. The following will apply:
  - a. Use a 3.3-m width if the design speed is 90 km/h.
  - b. Use a 3.6-m width if the design speed is 90 km/h.
- (5) Shoulder Width. The following will apply:
  - a. If guardrail is present, the minimum shoulder width is 1.2 m.
  - b. Usable shoulder width is defined as the distance from the edge of the travel lane to the shoulder break point.
- (6) Cross Slope (Travel Lanes). Cross slopes of 1.5% are acceptable on an existing bridge to remain in place.
- (6A) Cross Slope (Shoulder). See Figure 45-1A(1) or Figure 45-1A(2) for more-specific information.
- (7) Clear Zone. The clear zone will vary according to design speed, traffic volumes, side slopes, and horizontal curvature. See Section 49-2.0.
- (8) Side Slopes. Values in the tables are for new construction. See Section 45-3.0 and Section 45-8.0 for more information. For a reconstruction project, see Section 49-3.0.
- (9) Foreslope. See Sections 49-2.0 and 49-3.0 for the lateral extent of the foreslope in a ditch section.
- (10) Ditch Widths. A V-ditch should be used in a rock cut. See Section 45-8.0
- (11) Backslopes. Backslopes for a rock cut will vary according to geotechnical factors and the height of the cut. See Section 45-8.0 for typical rock cut sections.
- (11a) Structural Capacity (New or Reconstructed Bridge). A bridge with design year average daily truck traffic (ADTT) greater than 1,000 should be designed for HS 25 live loads. A bridge with an ADTT less than or equal to 1,000 may be designed for HS 25 or HS 20, whichever the LPA elects.

(12) Width (New or Reconstructed Bridge). The following will apply:

- a. Where the approach roadway width (travelway plus shoulders) is surfaced, that surfaced width will be carried across the structure.
- b. The width each bridge of more than 30 m in length will be analyzed individually. At a minimum, the roadway width of such a bridge will be the width of travel lanes plus a 0.9-m right shoulder and 0.9-m left shoulder for a highway with  $AADT > 400$ .
- c. See Section 59-1.0 for more information on bridge width.

(13) Width (Existing Bridge to Remain in Place). Clear width will be at least equal to the approach traveled way width or the table values, whichever is greater. For a bridge of more than 30 m in length, the values in the table do not apply. The acceptability of such a bridge will be assessed individually.

(14) Vertical Clearance (Collector Under). Table values include an additional 150 mm allowance for a future pavement overlay. Vertical clearances apply from usable edge to usable edge of shoulders.

(15) Vertical Clearance (Collector Over Railroad). See Chapter Sixty-nine for additional information on railroad clearance under a highway.

(16) Superelevation Rate. See Section 43-3.0 for values of superelevation based on design speed and radii.

(17) Horizontal Sight Distance. For a given design speed, the necessary middle ordinate will be determined by the radius and the sight distance which applies at the site. See Section 43-4.0.

(18) Maximum Grades. For a grade less than 150 m in length (PVT to PVC), a one-way downgrade, or a grade on a road with  $AADT < 400$ , the maximum grade may be up to 2% steeper than the table value.

(19) Intersection Sight Distance. For left turn onto a 2-lane road. P = Passenger car; SU = single unit truck. See Figure 46-10G for values for combination trucks.

Design Element			Manual Section	2-Lane								
Design Controls	Design Year Traffic	AADT	40-2.01	< 50	50 ≤ AADT < 250	250 ≤ AADT < 400	400 ≤ AADT < 1500	1500 ≤ AADT < 2000	≥ 2000			
	Design Forecast Year		40-2.02	20 years								
	*Design Speed (km/h) (3)	Level	40-3.0	50 - 90	50 - 90	60 - 90	80 - 90	80 - 90	80 - 90			
		Rolling		50 - 90	50 - 90	50 - 90	60 - 90	60 - 90	60 - 90			
	Access Control		40-5.0	None								
Level of Service			40-2.0	Desirable: B; Minimum: D								
Cross Section Elements*	Travel Lane	*Width	45-1.01	3.0 m	3.0 m	3.0 m (4a)	3.3 m	3.3 m(4b)	3.6 m			
		Typical Surface Type	Ch. 52	Asphalt / Concrete / Aggregate								
	Shoulder	*Width Usable	45-1.02	0.6 m	0.6 m	0.6 m	1.8 m (5)	1.8 m	2.4 m			
		Typical Surface Type	Ch. 52	Asphalt / Aggregate / Earth								
	Cross Slope	*Travel Lane (6)	45-1.01	2%-3% Asphalt / Concrete; 6% Aggregate								
		Shoulder (6A)	45-1.02	Paved Width ≤ 1.2 m: 2% - 3%; Paved Width > 1.2 m: 4% - 6% Asphalt/Concrete; 6%-8% Aggregate; 8% Earth								
	Auxiliary Lanes	Lane Width	45-1.03	Same as Travel Lane			Des: Same as Travel Lane; Min: 3.0 m					
		Shoulder Width		Desirable: 1.2 m; Minimum: 0.6 m								
	Clear Zone		49-2.0	(7)								
	Side Slopes	Cut	Foreslope	4:1 (V > 60) (8); 3:1 (V # 60) (8)								
				Des: 1.2 m; Min: 0.0 m								
				4:1 (V > 60); 3:1 (V # 60) (9)								
		Fill	0-9 m Height	45-3.0	Desirable: 4:1; Maximum: 3:1			3:1				
Bridges**	New or Reconstructed Bridge	*Structural Capacity	Ch. 60	HS-25 (9a)								
		*Clear Roadway Width (10)	45-4.01	Travelway + 1.2 m			Travelway + 1.8 m		Full Paved Approach Width			
	Existing Bridge to Remain in Place	*Structural Capacity	Ch. 72	HS-10	HS-15							
		*Clear Roadway Width (11)	45-4.01	6.0 m	6.6 m	7.2 m	8.4 m					
	*Vertical Clearance (Local Road Under)	New or Replaced Overpassing Bridge (12)	44-4.0	4.45 m								
		Existing Overpassing Bridge		4.30 m								
	Vertical Clearance (Local Road Over Railroad) (13)		Ch. 69	7.00 m								

\*Controlling design criteria (see Section 40-8.0). \*\* Selection of the cross section and bridge elements is based on the design-year traffic volumes irrespective of the design speed.  
Des: Desirable. Min: Minimum.

## GEOMETRIC DESIGN CRITERIA FOR LOCAL RURAL ROAD <sup>(1)</sup>

(New Construction or Reconstruction)

Table 53-5

Design Element		Manual Section	2-Lane						
Alignment Elements	Design Speed	---	30 km/h	40 km/h	50 km/h	60 km/h	70 km/h	80 km/h	90 km/h
	*Stopping Sight Distance	42-1.0	35 m	50 m	65 m	85 m	105 m	130 m	160 m
	Decision Sight Distance	42-2.0	90 m	120 m	145 m	170 m	200 m	230 m	270 m
			40 m	50 m	70 m	95 m	115 m	140 m	170 m
	Passing Sight Distance	42-3.0	200 m	270 m	345 m	410 m	485 m	540 m	615 m
	Intersection Sight Distance	46-10.0	65 m	85 m	105 m	150 m	150 m	170 m	190 m
	*Minimum Radii (e=8%)	43-2.0	30 m	55 m	85 m	125 m	180 m	230 m	305 m
	*Superelevation Rate	43-3.0	emax=8% (14)						
	*Horizontal Sight Distance	43-4.0	(15)						
	*Vertical Curvature (K-values)	44-3.0	2	4	7	11	17	26	39
			6	9	13	18	23	30	38
*Maximum Grade	Level	44-1.02	8%	7%	7%	7%	7%	6%	5.5%
	Rolling		11%	11%	10%	9%	9%	8%	7%
Minimum Grade		44-1.03	Desirable: 0.5%; Minimum: 0.0%						

\* Controlling design criteria (see Section 40-8.0).

These standards are to be used for each federal-aid funded project agency rural local road classified as new construction or reconstruction. Deviations from controlling Level One design criteria should be covered by a design exception approved by the Chief, Design Division.

## GEOMETRIC DESIGN CRITERIA FOR RURAL LOCAL ROAD<sup>(1)</sup> (New Construction or Reconstruction)

Table 53-5 (Continued)

## GEOMETRIC DESIGN CRITERIA FOR RURAL LOCAL ROAD (New Construction or Reconstruction)

### Footnotes to Table 53-5

- (1) Applicability. This table is only applicable to a federal-aid project.
- (2) (Blank).
- (3) Design Speed. The minimum design speed should equal the minimum value from the table or the anticipated posted speed limit after construction, whichever is greater. The state legal limit is 55 mph on a non-posted highway.
- (4) Travel Lane Width. The following will apply:
  - a. Use 3.3 m lanes where  $V \geq 90$  km/h.
  - b. Use 3.6 m lanes where  $V \geq 90$  km/h.
- (5) Shoulder Width. The following will apply:
  - a. For  $400 \leq \text{AADT} < 1500$ , the shoulder width may be 1.2 m.
  - b. Usable shoulder width is defined as the distance from the edge of the travel lane to the shoulder break point.
- (6) Cross Slope (Travel Lanes). Cross slopes of 1.5% are acceptable on an existing bridge to remain in place.
- (6A) Cross Slope (Shoulder). See Figure 45-1A(1) or Figure 45-1A(2) for more-specific information.
- (7) Clear Zone. The clear zone will vary according to design speed, traffic volumes, side slopes, and horizontal curvature. See Section 49-2.0. For a design speed lower than 80 km/h, a 3.0 m clear zone may be used.
- (8) Foreslope. See Sections 49-2.0 and 49-3.0 for the lateral extent of the foreslope in a ditch section.
- (9) Backslopes. Backslopes for a rock cut will vary according to geotechnical factors and the height of the cut.
- (9a) Structural Capacity (New or Reconstructed Bridge). A bridge with design year average daily truck traffic (ADTT) greater than 1,000 should be designed for HS 25 live loads. A bridge with an ADTT less than or equal to 1,000 may be designed for HS 25 or HS 20, whichever the LPA elects.
- (10) Width (New or Reconstructed Bridge). The width of each bridge of more than 30 m in length will be analyzed individually. At a minimum, the roadway width of such a bridge will be the width of travel lanes plus a 0.9-m right shoulder and 0.9-m left shoulder for a highway with  $\text{AADT} > 2000$ . Where shoulders are paved, it is desirable to provide the full approach roadway width. See Section 59-1.0 for more information on bridge width.
- (11) Width (Existing Bridge to Remain in Place). A minimum clear width that is 0.6 m narrower may be used on a road with few trucks. The clear roadway width should be at least the same width as the approach travelway. For a one-lane bridge, the width may be 5.4 m. For a bridge of more than 30 m in length, the values in the table do not apply. The acceptability of such a bridge will be assessed individually.

- (12) Vertical Clearance (Local Road Under). Table values include an additional 150 mm allowance for a future pavement overlay. Vertical clearances apply from usable edge to usable edge of shoulders.
- (13) Vertical Clearance (Local Road Over Railroad). See Chapter Sixty-nine for additional information on railroad clearance under a highway.
- (14) Superelevation Rate. See Section 43-3.0 for values of superelevation based on design speed and radii.
- (15) Horizontal Sight Distance. For a given design speed, the necessary middle ordinate will be determined by the radius and the sight distance which applies at the site. See Section 43-4.0.

ARCHIVED

Design Element			Manual Section	Design Values (By Type of Area)		
Design Controls	Design Forecast Year		40-2.02	Suburban	Intermediate	Built-Up
	*Design Speed (km/h) (1)		40-3.0	Curbed: 70-90 Uncurbed: 80-100	Curbed: 60-80 Uncurbed: 80-90	Curbed: 50-60
	Access Control		40-5.0	Partial Control / None	None	None
	Level of Service		40-2.0	Des: B; Min: C	Des: C; Min: D	Des: C; Min: D
	On-Street Parking		45-1.04	None	Optional (2)	Optional (2)
	Travel Lane	*Width (3)	45-1.01	Curbed: 3.6 m Uncurbed: 3.6 m	Curbed: Des.: 3.6 m; Min.: 3.3 m Uncurbed: Des.: 3.6 m; Min.: 3.3 m	Curbed: Des.: 3.6 m; Min.: 3.0 m
Cross Section Elements		Typical Surface Type (4)	Ch. 52	Asphalt / Concrete	Asphalt / Concrete	Asphalt / Concrete
*Curb Offset (5)		45-1.02	0.6 m	0.6 m	0.6 m	
Shoulder	*Paved Width (6)	45-1.02	Curbed, Rt. Des: 3.0 m; Min 0.6 m Curbed, Lt. Des: 1.2 m; Min 0.6 m Uncurbed, Rt.: 3.0 m; Lt.: 1.2 m	Curbed, Rt. Des: 2.4 m; Min 0.6 m Curbed, Lt. Des: 1.2 m; Min 0.6 m Uncurbed, Rt.: 2.4 m; Lt.: 1.2 m	Right: 1.8 m; Left: 1.2 m	
	Typical Surface Type (4)	Ch. 52	Asphalt / Concrete	Asphalt / Concrete	Asphalt / Concrete	
Cross Slope	*Travel Lane (7)	45-1.01	2%	2%	2%	
	Shoulder (7A)	45-1.02	Paved Width ≤ 1.2 m: 2%; Paved Width > 1.2 m: 4%	Paved Width ≤ 1.2 m: 2%; Paved Width > 1.2 m: 4%	Paved Width ≤ 1.2 m: 2%; Paved Width > 1.2 m: 4%	
Auxiliary Lanes	Lane Width	45-1.03	Des: 3.6 m; Min: 3.3 m	Des: 3.6 m; Min: 3.3 m	Des: 3.6 m; Min: 3.0 m	
	Curb Offset (8)		0.3 m	0.3 m	0.3 m	
	Shoulder Width		Des: 3.0 m; Min: 0.6 m	Des: 2.4 m; Min: 0.6 m	Des: 1.8 m; Min: 0.6 m	
	Typical Surface Type (4)		Asphalt / Concrete	Asphalt / Concrete	Asphalt / Concrete	
TWLTL Lane Width		46-5.0	Des: 4.8 m; Min: 4.2 m	Des: 4.8 m; Min: 4.2 m	Des: 4.2 m; Min: 3.6 m	
Parking Lane Width		45-1.04	N/A	Des: 3.6 m; Min: 3.0 m (9)	Des: 3.6 m; Min: 3.0 m (9)	
Median Width	Depressed	45-2.0	8.0 m - 15.0 m	N/A	N/A	
	Raised Island		Des: 5.4 m; Min: 3.9 m (10)	Des: 5.4 m; Min: 1.2 m (10)	Des: 5.4 m; Min: 1.2 m (10)	
	Flush / Corrugated		Des: 4.8 m; Min: 3.9 m (10)	Des: 4.8 m; Min: 1.2 m (10)	Des: 4.8 m; Min: 1.2 m (10)	
Sidewalk Width (11)		45-1.06	1.5 m with 1.5 m Buffer (Des)	1.5 m with 1.5 m Buffer (Des)	Varies; 1.8 m Min	
Bicycle Lane Width (12)		51-7.0	Curbed: 1.5 m Uncurbed: Shld Width +1.2 m	Curbed: 1.5 m Uncurbed: Shld Width +1.2 m	Curbed: 1.5 m	
Clear Zones		49-2.0	(13)	(13)	(13)	
Typical Curbing Type (where used) (14)		45-1.05	Sloping / Vertical	Sloping / Vertical	Sloping / Vertical	
Side Slopes (Uncurbed) (15)	Foreslope	45-3.0	6:1 (16)	6:1 (16)	N/A	
	Cut		1.2 m (17)	1.2 m (17)	N/A	
	Ditch Width		4:1 for 6.0 m; 3:1 Max. to Top (18)	4:1 for 6.0 m; 3:1 Max. to Top (18)	N/A	
	Backslope		6:1 to Clear Zone; 3:1 Max. to Toe	6:1 to Clear Zone; 3:1 Max. to Toe	N/A	
Side Slopes (Curbed)	Fill	45-3.0	(19)	(19)	(19)	
	Cut (Backslope)		12:1 for 3.6 m; 3:1 Max. to Toe	12:1 for 3.6 m; 3:1 Max. to Toe	12:1 for 3.6 m; 3:1 Max. to Toe	
Median Slopes (Depressed)		45-2.0	Des: 8:1; Max: 5:1	N/A	N/A	

\*Controlling design criteria (see Section 40-8.0). Des: Desirable. Min: Minimum.

**GEOMETRIC DESIGN CRITERIA FOR MULTI-LANE URBAN ARTERIAL**  
(New Construction or Reconstruction)

Table 53-6

Design Element		Manual Section	Design Values (By Type of Area)					
			Suburban	Intermediate	Built-Up			
Bridges	New or Reconstructed Bridge	*Structural Capacity (20)	Ch. 60	HS-25	HS-25	HS-25		
		*Clear Roadway Width(21)	45-4.01	Uncurbed: Full Paved Approach Width Curbed: Full Approach Curb-to-Curb Width				
	Existing Bridge to Re-main in Place	*Structural Capacity	Ch.72	HS-20	HS-20	HS-20		
		*Clear Roadway Width	45-4.01	Uncurbed: Travelway Plus 0.6 m on Each Side; Curbed: Full Approach Curb-to-Curb Width				
	*Vertical Clearance (Arterial Under) (22)	New or Replaced Overpassing Bridge (22a)	44-4.0	5.05 m	5.05 m (22b)	5.05 m (22b)		
		Existing Overpassing Bridge		4.30 m	4.30 m	4.30 m		
		Sign Truss / Pedestrian Bridge (22a)		New: 5.35 m; Existing: 5.20 m	New: 5.35 m; Existing: 5.20 m	New: 5.35 m; Existing: 5.20 m		
	Vertical Clearance (Arterial over Railroad) (23)		Ch. 69	7.00 m				
Alignment Elements	Design Speed			50 km/h	60 km/h	70 km/h	80 km/h	90 km/h
	*Stopping Sight Distance		42-1.0	65 m	85 m	105 m	130 m	160 m
	Decision Sight Distance	Speed / Path / Direction Change	42-2.0	U: 195 m SU: 170 m	U: 235 m SU: 205 m	U: 275 m SU: 235 m	U: 315 m SU: 270 m	U: 360 m SU: 315 m
		Stop Maneuver		155 m	195 m	235 m	280 m	325 m
	Intersection Sight Distance, -3% to +3% (28)		46-10.0	P: 105 m SU: 135 m	P: 125 m SU: 160 m	P: 150 m SU: 185 m	P: 190 m SU: 235 m	P: 230 m SU: 280 m
	*Minimum Radii for $e_{max} = 4\% / 6\%$		43-2.0	80 m / 75 m (24a)	130 m/120 m (24a)	185 m/170 m (24a)	230 m (24b)	305 m (24b)
	*Superelevation Rate (25)		43-3.0	Up to $e_{max} = 6\%$			$e_{max}=8\%$	
	*Horizontal Sight Distance		43-4.0	(26)				
	*Vertical Curvature (K-values)	Crest	44-3.0	7	11	17	26	39
		Sag		13	18	23	30	38
	*Maximum Grade (27)	Level	44-1.02	8%	7%	6.5%	6%	5.5%
		Rolling		9%	8%	7.5%	7%	6.5%
	Minimum Grade		44-1.03	Desirable: 0.5% Minimum: 0.3% (Curbed); 0.0% (Uncurbed)				

\* Controlling design criteria (see Section 40-8.0).

U: Urban; SU: Suburban

Refer to note at bottom of Table 53-2 for approval authority for Level One design exceptions.

## GEOMETRIC DESIGN CRITERIA FOR MULTI-LANE URBAN ARTERIAL (New Construction or Reconstruction)

Table 53-6 (Continued)

GEOMETRIC DESIGN CRITERIA FOR MULTI-LANE URBAN ARTERIAL

(New Construction or Reconstruction)

Footnotes to Table 53-6

(1) Design Speed. The minimum design speed should equal a) the minimum value from the table, b) the anticipated posted speed limit after construction, or c) the state legal limit on a non-posted highway. The legal limit in an urban district is 50 km/h. Based on an engineering study, these speeds may be raised to an absolute max. of 90 km/h.

(2) On-Street Parking. In general, on-street parking is discouraged.

(3) Travel Lane Width. For an arterial on the National Truck Network, the right lane must be 3.6 m in width.

(4) Surface Type. The pavement type selection will be determined by the INDOT Pavement Design Engineer.

(5) Curb Offset. The curb offset (for both left and right) should be 0.6 m. Vertical curbs introduced intermittently should be offset 0.6 m

(6) Shoulder Width. The table values apply to paved shoulder widths. The following will also apply:

- For an uncurbed section, the shoulder is paved to the face of guardrail. The desirable guardrail offset is 0.6 m from the effective usable shoulder width. See Section 49-5.0 for more information.
- For an uncurbed section, a desirable additional 0.3 m of compacted aggregate will be provided.
- For a curbed section, the curb offset is included in the paved shoulder width.

(7) Cross Slope (Travel Lane). Cross slopes of 1.5% are acceptable for an existing bridge to remain in place.

(7A) Cross Slope (Shoulder). See Figure 45-1A(1) or Figure 45-1A(2) for more-specific information.

(8) Curb Offset for Auxiliary Lane. In a curbed section, the offset may be zero.

(9) Parking Lane. Where the parking lane will be used as a travel lane during peak hours or may be converted to a travel lane in the future, the width should be equal to the travel lane width plus a 0.3 m offset to the curb (if present). The cross slope for a parking lane is typically 1% steeper than the adjacent travel lane.

(10) Minimum Median Width. The criteria in the table assume the presence of a mountable curb with a 0.0-m curb offset.

(11) Sidewalk Width. A buffer of less than 0.6 m wide is not permitted. If no buffer is provided, the sidewalk width should be 1.8 m.

(12) Bicycle Lane Width. The widths in the table are in addition to the width of a parking lane, if present. See Section 51-7.0 for additional details.

(13) Clear Zones. The following will apply:

- Facility with Vertical Curbs. The clear zone will be measured from the edge of travel lane or will be to the right-of-way line, whichever is less. No clear zone is required where there is 24-hour parking.
- Facility with Sloping Curbs or without Curbs. The clear zone will vary according to design speed, traffic volumes, side slopes and horizontal curvature.
- Curbed Facility. There should be an appurtenance-free area as measured from the gutter line of any curb.

d. Values. See Section 49-2.0 for specific clear zone values.

Footnotes to Table 53-6 continued

(14) Curbing Type. Vertical curbs may only be used with design speed lower than 80 km/h.

(15) Side Slopes (Uncurbed). Values in the table are for new construction. See Section 45-3.0 and Section 45-8.0 for more information. For a reconstruction project, see Section 49-3.0.

(16) Foreslope. See Sections 49-2.0 and 49-3.0 for the lateral extent of the foreslope in a ditch section.

(17) Ditch Widths. In rock cuts, a V ditch should be used. See Section 45-8.0.

(18) Backslopes. Backslopes for rock cuts will vary according to the height of the cut and geotechnical factors. See Section 45-8.0 for typical rock cut sections.

(19) Side Slopes (Curbed) Cut. Typically, a shelf or sidewalk will be present immediately behind the curb before the toe of the backslope. The minimum width of a shelf will be 1.8 m. Where a sidewalk is present, the toe of the backslope will typically be 0.3 m beyond the edge of sidewalk. See Section 45-3.0 for more information.

(20) Structural Capacity (New or Reconstructed Bridge). The following will apply:

- Each bridge on a facility with greater than 600 trucks per day should be checked using the Alternate Military loading.
- Each State highway bridge within 25 km of a Toll Road gate must be designed for Toll Road Loading.
- Each bridge on an Extra Heavy Duty Highway must be designed for the Michigan Train truck loading configuration.
- See Chapter Sixty for additional information on the loading configurations.

(21) Width (New or Reconstructed Bridge). See Section 59-1.0 for more information on bridge widths.

(22) Vertical Clearance (Arterial Under Railroad). The following will apply:

- Table values include an additional 150-mm allowance for future pavement overlays.
- In a highly urbanized area, a minimum clearance of 4.30 m may be provided if there is at least one route with a 4.90-m clearance.
- Vertical clearances apply from usable edge to usable edge of shoulder.

(23) Vertical Clearance (Arterial Over Railroad). See Chapter Sixty-nine for additional information on railroad clearance under a highway.

(24) Minimum Radii. The following will apply:

- Based on  $e_{max} = 4\%$  or  $6\%$  and low-speed urban street conditions.
- Based on  $e_{max} = 8\%$  and open-road conditions.

(25) Superelevation Rate. See Section 43-3.0 for values of superelevation based on design speed and radii. See Section 43-3.0 and the INDOT *Standard Drawings* for information on superelevation requirements.

(26) Horizontal Sight Distance. For a given design speed, the necessary middle ordinate will be determined by the radius and the sight distance which applies at the site. Sometimes the SSD values for trucks will apply. See the discussion in Section 43-4.0.

(27) Where adjacent sidewalks are present, the maximum desirable grade is 5%.

(28) Intersection Sight Distance. For left turn onto a 2-lane road. P = Passenger car; SU = single unit truck. See Figure 46-10G for values for combination trucks.

Design Element		Manual Section	Design Values (By Type of Area)		
			Suburban	Intermediate	Built-up
Design Controls	Design Forecast Year	40-2.02	20 Years	20 Years	20 Years
	*Design Speed (km/h) (1)	40-3.0	Curbed: 60-90 Uncurbed: 70-90	Curbed: 60-80 Uncurbed: 70-80	Curbed: 50-60
	Access Control	40-5.0	Partial Control / None	None	None
	Level of Service	40-2.0	Des: B; Min: C	Des: C; Min: D	Des: C; Min: D
	On-Street Parking	45-1.04	None	Optional (2)	Optional (2)
Cross Section Elements	Travel Lane	*Width (3)	45-1.01	Curbed: 3.6 m Uncurbed: 3.6 m	Curbed: Des.: 3.6 m; Min.: 3.3 m Uncurbed: 3.6 m
		Typical Surface Type (4)	Ch. 52	Asphalt / Concrete	Asphalt / Concrete
	*Curb Offset (5)		45-1.02	0.6 m	0.6 m
	Shoulder	*Paved Width (6)	45-1.02	Curbed: Des: 3.0 m; Min. 0.6 m Uncurbed: 3.0 m	Curbed: Des: 2.4 m; Min: 0.6 m Uncurbed: 2.4 m;
		Typical Surface Type (4)	Ch 52.	Asphalt / Concrete	Asphalt / Concrete
	Cross Slope	*Travel Lane (7)	45-1.01	2%	2%
		Shoulder (7A)	45-1.02	4%	4%
	Auxiliary Lanes	Lane Width	45-1.03	Des: 3.6 m; Min: 3.3 m	Des: 3.6 m; Min: 3.3 m
		Curb Offset (8)		0.3 m	0.3 m
		Shoulder Width		Des: 3.0 m; Min: 0.6 m	Des: 1.8 m; Min: 0.6 m
		Typical Surface Type (4)	Ch. 52	Asphalt / Concrete	Asphalt / Concrete
	TWLTL Lane Width		46-5.0	Des: 4.8 m; Min. 4.2 m	Des: 4.8 m; Min: 4.2 m
	Parking Lane Width		45-1.04	N/A	Des: 3.6 m; Min: 3.0 m (9)
	Sidewalk Width (10)		45-1.06	1.5 m with 1.5 m Buffer (Des)	1.5 m with 1.5 m Buffer (Des)
	Bicycle Lane Width (11)		51.7.0	Curbed: 1.5 m Uncurbed: Shld. Width +1.2 m	Curbed: 1.5 m Uncurbed: Shld. Width +1.2 m
	Clear Zones		49-2.0	(12)	(12)
	Typical Curbing Type (where used) (13)		45-1.05	Sloping / Vertical	Sloping / Vertical
Side Slopes (Uncurbed) (14)	Cut	Foreslope	45-3.0	6:1 (15)	6:1 (15)
		Ditch Width		1.2 m (16)	1.2 m (16)
		Backslope		4:1 for 6.0 m; 3:1 Max. to Top (17)	4:1 for 6.0 m; 3:1 Max. to Top (17)
		Fill		6:1 to Clear Zone; 3:1 Max. to Toe	6:1 to Clear Zone; 3:1 Max. to Toe
Side Slopes (Curbed)	Cut (Backslope)		45-3.0	(18)	(18)
	Fill			12:1 for 3.6 m; 3:1 Max. to Toe	12:1 for 3.6 m; 3:1 Max. to Toe
					12:1 for 3.6 m; 3:1 Max. to Toe

\*Controlling design criteria (see Section 40-8.0). Des: Desirable; Min. Minimum.

### GEOMETRIC DESIGN CRITERIA FOR TWO-LANE URBAN ARTERIAL (New Construction or Reconstruction)

Table 53-7

Design Element		Manual Section	Design Values (By Type of Area)					
			Suburban	Intermediate	Built-Up			
Bridges	New or Reconstructed Bridge	*Structural Capacity (19)	Ch. 60	HS-25	HS-25	HS-25		
		*Clear Roadway Width(20)	45-4.01	Uncurbed: Full Paved Approach Width Curbed: Full Approach Curb-to-Curb Width				
	Existing Bridge to Re-main in Place	*Structural Capacity	Ch. 72	HS-20	HS-20	HS-20		
		*Clear Roadway Width	45-4.0	Uncurbed: Travelway Plus 0.6 m on Each Side; Curbed: Full Approach Curb-to-Curb Width				
	*Vertical Clearance (Arterial Under) (21)	New or Replaced Overpassing Bridge (21a)	44-4.0	5.05 m	5.05 m (21b)	5.05 m (21b)		
		Existing Overpassing Bridge		4.30 m	4.30 m	4.30 m		
		Sign Truss / Pedestrian Bridge (21a)		New: 5.35 m; Existing: 5.20 m	New: 5.35 m; Existing: 5.20 m	New: 5.35 m; Existing: 5.20 m		
	Vertical Clearance (Arterial over Railroad) (22)		Ch. 69	7.00 m				
Alignment Elements	Design Speed		50 km/h	60 km/h	70 km/h	80 km/h	90 km/h	
	*Stopping Sight Distance		42-1.0	65 m	85 m	105 m	130 m	160 m
	Decision Sight Distance	Speed / Path / Direction Change	42-2.0	U: 195 m SU: 170 m	U: 235 m SU: 205 m	U: 275 m SU: 235 m	U: 315 m SU: 270 m	U: 360 m SU: 315 m
		Stop Maneuver		155 m	195 m	235 m	280 m	325 m
	Intersection Sight Distance, -3% to +3% (27)		46-10.0	P: 105 m SU: 135 m	P: 125 m SU: 160 m	P: 150 m SU: 185 m	P: 190 m SU: 235 m	P: 230 m SU: 280 m
	*Minimum Radii for $e_{max} = 4\% / 6\%$		43-2.0	80 m / 75 m (23a)	130 m / 120 m (23a)	185 m / 170 m (23a)	230 m (23b)	305 m (23b)
	*Superelevation Rate (24)		43-3.0	Up to $e_{max}=6\%$			$e_{max}=8\%$	
	*Horizontal Sight Distance		43-4.0	(25)				
	*Vertical Curvature (K-values)	Crest	44-3.0	7	11	17	26	39
		Sag		13	18	23	30	38
	*Maximum Grade	Level	44-1.02	8%	7%	6.5%	6%	5.5%
		Rolling		9%	8%	7.5%	7%	6.5%
	Minimum Grade (26)		44-1.03	Desirable: 0.5% Minimum: 0.3% (Curbed); 0.0% (Uncurbed)				

\* Controlling design criteria (see Section 40-8.0).

U: Urban; SU: Suburban.

See notes at bottom of Table 53-2 for approval authority for Level One design exception requests.

## GEOMETRIC DESIGN CRITERIA FOR TWO-LANE URBAN ARTERIAL (New Construction or Reconstruction)

Table 53-7 (Continued)

**GEOMETRIC DESIGN CRITERIA FOR TWO-LANE URBAN ARTERIAL**  
**(New Construction or Reconstruction)**  
**Footnotes to Table 53-7**

- (1) **Design Speed.** The minimum design speed should equal a) the minimum value from the table, b) the anticipated posted speed limit after construction or c) the state legal limit on a non-posted highway. The legal limit in an urban district is 50 km/h. Based upon an engineering study, these speeds may be raised to an absolute maximum of 90 km/h.
- (2) **On-Street Parking.** In general, on-street parking is discouraged.
- (3) **Travel Lane Width.** For an arterial on the National Truck Network, lane widths must be 3.6 m.
- (4) **Surface Type.** The pavement type selection will be determined by the INDOT Pavement Design Engineer.
- (5) **Curb Offset.** The curb offset should be 0.6 m. Vertical curbs introduced intermittently should be offset 0.6 m.
- (6) **Shoulder Width.** The table values apply to paved shoulder widths. The following will also apply:
  - a. For an uncurbed section, the shoulder is paved to the face of guardrail. The desirable guardrail offset is 0.6 m from the effective usable shoulder width. See Section 49-5.0 for more information.
  - b. For an uncurbed section, a desirable additional 0.3 m of compacted aggregate will be provided.
  - c. For a curbed section, the curb offset is included in the paved shoulder width.
- (7) **Cross Slope (Travel Lane).** Cross slopes of 1.5% are acceptable on an existing bridge to remain in place.
- (7A) **Cross Slope (Shoulder).** See Figure 45-1A(1) or Figure 45-1A(2) for more-specific information.
- (8) **Curb Offset for Auxiliary Lane.** In a curbed section, the offset may be zero.
- (9) **Parking Lane.** Where the parking lane will be used as a travel lane during peak hours or may be converted to a travel lane in the future, the width should be equal to the travel lane width plus a 0.3 m offset to the curb (if present). The cross slope for a parking lane is typically 1% steeper than the adjacent travel lane.
- (10) **Sidewalk Width.** A buffer of less than 0.6 m wide is not permitted. If no buffer is provided, the sidewalk width should be 1.8 m.
- (11) **Bicycle Lane Width.** The widths in the table are in addition to the width of a parking lane, if present. See Section 51-7.0 for additional details.
- (12) **Clear Zones.** The following will apply:
  - a. **Facility with Vertical Curbs.** The clear zone will be measured from the edge of travel lane or will be to the right-of-way line, whichever is less. No clear zone is required where there is 24-hour parking.
  - b. **Facility with Sloping Curbs or without Curbs.** The clear zone will vary according to design speed, traffic volumes, side slopes and horizontal curvature.
  - c. **Curbed Facility.** There should be an appurtenance-free area as measured from the gutter line of any curb.
  - d. **Values.** See Section 49-2.0 for specific clear zone values.

(13) Curbing Type. Vertical curbs may only be used with design speed lower than 80 km/h.

(14) Side Slope (Uncurbed). Values in the table are for new construction. See Section 45-3.0 and Section 45-8.0 for more information. For a reconstruction project, see Section 49-3.0.

(15) Foreslope. See Sections 49-2.0 and 49-3.0 for the lateral extent of the foreslope in a ditch section.

(16) Ditch Width. In a rock cut, a V ditch should be used. See Section 45-8.0.

(17) Backslope. The backslope for a rock cut will vary according to the height of the cut and geotechnical factors. See Section 45-8.0 for typical rock cut sections.

(18) Side Slope (Curbed) Cut. Typically, a shelf or sidewalk will be present immediately behind the curb before the toe of the backslope. The minimum width of a shelf will be 1.8 m. Where a sidewalk is present, the toe of the backslope will typically be 0.6 m beyond the edge of sidewalk. See Section 45-3.0 for more information.

(19) Structural Capacity (New or Reconstructed Bridge). The following will apply:

- Each bridge on a facility with greater than 600 trucks per day should be checked using the Alternate Military loading.
- Each State highway bridge within 25 km of a Toll Road gate must be designed for Toll Road Loading.
- Each bridge on an Extra Heavy Duty Highway must be designed for the Michigan Train truck loading configuration.
- See Chapter Sixty for additional information on the loading configurations.

(20) Width (New or Reconstructed Bridge). See Section 59-1.0 for more information on bridge width.

(21) Vertical Clearance (Arterial Under Railroad). The following will apply:

- Table values include an additional 150 mm allowance for future pavement overlays.
- In a highly urbanized area, a minimum clearance of 4.30 m may be provided if there is at least one route with a 4.90-m clearance.
- Vertical clearances apply from usable edge to usable edge of shoulder.

(22) Vertical Clearance (Arterial Over Railroad). See Chapter Sixty-nine for additional information on railroad clearance under a highway.

(23) Minimum Radii. The following will apply:

- Based on  $e_{max} = 4\%$  or  $6\%$  and low-speed urban street conditions.
- Based on  $e_{max} = 8\%$  and open-road conditions.

(24) Superelevation Rate. See Section 43-3.0 for values of superelevation based on design speed and radius. See Section 43-3.0 and the INDOT *Standard Drawings* for information on superelevation requirements.

(25) Horizontal Sight Distance. For a given design speed, the necessary middle ordinate will be determined by the radius and the sight distance which applies at the site. Sometimes the SSD values for trucks will apply. See the discussion in Section 43-4.0.

(26) Where adjacent sidewalks are present, the maximum desirable grade is 5%.

(27) Intersection Sight Distance. For left turn onto a 2-lane road. P = Passenger car; SU = single unit truck. See Figure 46-10G for values for combination trucks.

Design Element		Manual Section	Design Values (By Type of Area)		
Design Controls	Design Forecast Year	40-2.02	Suburban	Intermediate	Built-Up
	*Design Speed (km/h) (2)	40-3.0	Curbed: 50-80 Uncurbed: 50-80	Curbed: 50-70 Uncurbed: 50-70	Curbed: 50-60
	Access Control	40-5.0	None	None	None
	Level of Service	40-2.0	Desirable: C; Minimum: D	Desirable: C; Minimum: D	Desirable: C; Minimum: D
	On-Street Parking	45-1.04	Optional (3)	Optional (3)	Optional (3)
Alignment Elements	Travel Lane	*Width (4)	45-1.01	Curbed: Des: 3.6 m; Min: 3.3 m Uncurbed: Des: 3.6 m; Min: 3.3 m	Curbed: Des: 3.6 m; Min: 3.3 m Uncurbed: Des: 3.6 m; Min: 3.3 m
		Typical Surface Type (5)	Ch. 52	Asphalt / Concrete	Asphalt / Concrete
	*Curb Offset (6)		45-1.02	0.6 m	0.6 m
	Shoulder	*Paved Width (7)	45-1.02	Curbed: Des: 2.4 m; Min: 0.6 m Uncurbed: 2.4 m	Curbed: Des: 1.8 m; Min: 0.6 m Uncurbed: 1.8 m
		Typical Surface Type (5)	Ch. 52	Asphalt / Concrete	Asphalt / Concrete
	Cross Slope	*Travel Lane (8)	45-1.01	2%	2%
		Shoulder (8A)	45-1.02	4%	4%
	Auxiliary Lanes	Lane Width		Des: 3.6 m; Min: 3.3 m	Des: 3.6 m; Min: 3.0 m
		Curb Offset	45-1.03	Des: 0.3 m; Min: 0.0 m	Des: 0.3 m; Min: 0.0 m
		Shoulder Width		Des: 2.4 m; Min: 0.6 m	Des: 1.8 m; Min: 0.6 m
		Typical Surface Type (5)	Ch. 52	Asphalt / Concrete	Asphalt / Concrete
	TWLTL Lane Width		46-5.0	Des: 4.8 m; Min: 3.6 m	Des: 4.2 m; Min: 3.6 m
	Parking Lane Width (1)		45-1.04	Des: 3.0 m; Min: 2.4 m	Des: 3.0 m; Min: 2.4 m
	Median Width	Raised Island	45-2.0	Des: 5.4 m; Min: 1.2 m (9)	Des: 5.4 m; Min: 1.2 m (9)
		Flush / Corrugated		Des: 4.8 m; Min: 1.2 m (9)	Des: 4.8 m; Min: 1.2 m (9)
	Sidewalk Width (10)		45-1.06	1.5 m with 1.5 m Buffer (Des)	1.5 m with 1.5 m Buffer (Des)
	Bicycle Lane Width (11)		51-7.0	Curbed: 1.5 m Uncurbed: Shld. Width +1.2 m	Curbed: 1.5m Uncurbed: Shld. Width +1.2 m
	Clear Zones		49-2.0	(12)	(12)
	Typical Curbing Type (where used) (13)		45-1.05	Sloping / Vertical	Sloping / Vertical
	Side Slopes (Uncurbed) (14)	Cut		Des: 6:1; Max: 4:1 (15)	Des: 6:1; Max: 4:1 (15)
				1.2 m (16)	1.2 m (16)
			45-3.0	4:1 for 1.2 m; 3:1 Max. to Top (17)	4:1 for 1.2 m; 3:1 Max. to Top (17)
		Fill		Des: 6:1 to Clr Zone; 3:1 Max to Toe Max: 4:1 to Clr Zone; 3:1 Max to Toe	Des: 6:1 to Clr Zone; 3:1 Max to Toe Max: 4:1 to Clr Zone; 3:1 Max to Toe
	Side Slopes (Curbed)	Cut(Backslope)	45-3.0	(18)	(18)
		Fill (19)		12:1 for 3.6 m; 3:1 Max to Toe	12:1 for 3.6 m; 3:1 Max to Toe

\* Controlling design criteria (see Section 40-8.0).

Des: Desirable; Min: Minimum.

## GEOMETRIC DESIGN CRITERIA FOR URBAN COLLECTOR (New Construction or Reconstruction)

Table 53-8

Design Element			Manual Section	Design Values (By Type of Area)		
				Suburban	Intermediate	Built-Up
Bridges	New or Reconstructed Bridge	*Structural Capacity (20)	Ch. 60	HS-25	HS-25	HS-25
		*Clear Roadway Width(21)	45-4.01	Uncurbed: Full Paved Approach Width Curbed: Full Approach Curb-to-Curb Width		
	Existing Bridge to Remain in Place	*Structural Capacity	Ch. 72	HS-20	HS-20	HS-20
		*Clear Roadway Width	45-4.01	Uncurbed: Travelway Plus 0.6 m on Each Side Curbed: Full Approach Curb-to-Curb Width		
	*Vertical Clearance (Collector) (22)	New or Replaced Overpassing Bridge (22)	44-4.0	4.45 m	4.45 m	4.45 m
		Existing Overpassing Bridge		4.30 m	4.30 m	4.30 m
	Vertical Clearance (Collector over Railroad) (23)		Ch. 69	7.00 m		
	Design Speed			50 km/h	60 km/h	70 km/h
	*Stopping Sight Distance		42-1.0	65 m	85 m	105 m
	Decision Sight Distance	Speed / Path / Direction Change	42-2.0	U: 195 m SU: 170 m	U: 235 m SU: 205 m	U: 275 m SU: 235 m
		Stop Maneuver		155 m	195 m	235 m
Alignment Element	Intersection Sight Distance, -3% to +3% (28)		46-10.0	P: 105 m SU: 135 m	P: 125 m SU: 160 m	P: 150 m SU: 185 m
	*Minimum Radii for $e_{max} = 4\% / 6\%$		43-2.0	80 m/75 m (24a)	130 m/120 m (24a)	185 m/170 m (24a)
	*Superelevation Rate (25)		43-3.0	Up to $e_{max} = 6\%$		$e_{max} = 8\%$
	*Horizontal Sight Distance		43-4.0	(26)		
	*Vertical Curvature (K-values)	Crest	44-3.0	7	11	17
		Sag		13	18	23
	*Maximum Grade (27)	Level	44-1.02	9%	9%	8%
		Rolling		11%	10%	9%
	Minimum Grade		44-1.03	Desirable: 0.5% Minimum: 0.3% (Curbed); 0.0% (Uncurbed)		

\* Controlling design criteria (see Section 40-8.0).

U: Urban; SU: Suburban.

See note at bottom of Table 53-3 for Level One design criteria exception approval authority for a state urban collector.

See note at bottom of Table 53-4 for Level One design criteria exception approval authority for a federally-funded local agency urban collector.

## GEOMETRIC DESIGN CRITERIA FOR URBAN COLLECTOR (New Construction or Reconstruction)

Table 53-8 (Continued)

## GEOMETRIC DESIGN CRITERIA FOR URBAN COLLECTOR

(New Construction or Reconstruction)

Footnotes to Table 53-8

(1) **Parking Lane.** In a residential area, a parallel parking lane from 2.1 to 2.4 m in width should be provided on one or both sides of the street. In a commercial or industrial area, parking lane widths should range from 2.4 to 3.3 m, and should usually be provided on both sides of the street. Where a curb-and-gutter section is used, the gutter pan width may be considered as part of the parking lane width. Where practical, the parking lane width should be in addition to the gutter pan width.

(2) **Design Speed.** The minimum design speed should equal a) the minimum value from the table, b) the anticipated posted speed limit after construction, or c) the state legal limit on a non-posted highway. The legal limit in an urban district is 50 km/h. Based upon an engineering study, these speeds may be raised to an absolute maximum of 90 km/h.

(3) **On-Street Parking.** In general, on-street parking is discouraged.

(4) **Travel Lane Width.** In an industrial area, a 3.6-m travel lane should be used. Where right-of-way is restricted, 3.0-m lanes can be used in a residential area, and 3.3-m lanes can be used in an industrial area. On a multi-lane facility in a built-up area, the minimum width is 3.0 m.

(5) **Surface Type.** The pavement type selection will be determined by the INDOT Pavement Design Engineer for a State highway.

(6) **Curb Offset.** The curb offset should be 0.6 m. Vertical curbs introduced intermittently should be offset 0.6 m.

(7) **Shoulder Width.** The table values apply to paved shoulder widths. The following will also apply:

- a. For an uncurbed section, the shoulder is paved to the face of guardrail. The desirable guardrail offset is 0.6 m from the effective usable shoulder width. See Section 49-5.0 for more information.
- b. For an uncurbed section, a desirable additional 0.3 m of compacted aggregate will be provided.
- c. For a curbed section, the curb offset is included in the paved shoulder width.

(8) **Cross Slope (Travel Lane).** Cross slopes of 1.5% are acceptable on an existing bridge to remain in place.

(8A) **Cross Slope (Shoulder).** See Figure 45-1A(1) or Figure 45-1A(2) for more-specific information.

(9) **Minimum Median Width.** The criteria in the table assume the presence of mountable curbs with a 0.0-m curb offset.

(10) **Sidewalk Width.** A buffer of less than 0.6 m wide is not permitted. If no buffer is provided, the sidewalk width should be 1.8 m.

(11) **Bicycle Lane Width.** The widths in the table are in addition to the width of a parking lane, if present. See Section 51-7.0 for additional details.

(12) **Clear Zones.** The following will apply:

- a. **Facility with Vertical Curbs.** The clear zone will be measured from the edge of travel lane or will be to the right-of-way line, whichever is less. No clear zone is required where there is 24-hour parking.
- b. **Facility with Sloping Curbs or without Curbs.** The clear zone will vary according to design speed, traffic volumes, side slopes and horizontal curvature.
- c. **Curbed Facility.** There should be an appurtenance-free area as measured from the gutter line of any curb.
- d. **Values.** See Section 49-2.0 for specific clear zone values

(13) Curbing Type. Vertical curbs may only be used with a design speed lower than 80 km/h.

(14) Side Slopes (Uncurbed). Values in the table are for new construction. See Section 45-3.0 and Section 45-8.0 for more information. For a reconstruction project, see Section 49-3.0.

(15) Foreslope. See Sections 49-2.0 and 49-3.0 for the lateral extent of the foreslope in a ditch section.

(16) Ditch Width. In a rock cut, a V ditch should be used. See Section 45-8.0.

(17) Backslope. The backslope for a rock cut will vary according to the height of the cut and geotechnical factors. See Section 45-8.0 for typical rock cut sections.

(18) Side Slope (Curbed) Cut. Typically, a shelf or sidewalk will be present immediately behind the curb before the toe of the backslope. The minimum width of a shelf will be 1.8 m. Where a sidewalk is present, the toe of the backslope will typically be 0.3 m beyond the edge of sidewalk. See Section 45-3.0 for more information.

(19) Side Slope (Curbed) Fill. If no sidewalks are present or planned, the lateral extent of the 12:1 slope may be reduced to 1.2 m.

(20) Structural Capacity (New or Reconstructed Bridge). The following will apply:

- Each bridge on a facility with greater than 600 trucks per day should be checked using the Alternate Military loading.
- Each State highway bridge within 25 km of a Toll Road gate must be designed for Toll Road Loading.
- Each bridge on an Extra Heavy Duty Highway must be designed for the Michigan Train truck loading configuration.
- See Chapter Sixty for additional information on the loading configurations.

(21) Width (New or Reconstructed Bridge). See Section 59-1.0 for more information on bridge width.

(22) Vertical Clearance (Collector Under Railroad). Table values include an additional 150-mm allowance for future pavement overlays. Vertical clearances apply from usable edge to usable edge of shoulder.

(23) Vertical Clearance (Collector Over Railroad). See Chapter Sixty-nine for additional information on railroad clearance under a highway.

(24) Minimum Radii. The following will apply:

- Based on  $e_{max} = 4\%$  or  $6\%$  and low-speed urban street conditions.
- Based on  $e_{max} = 8\%$  and open-road conditions.

(25) Superelevation Rate. See Section 43-3.0 for values of superelevation based on design speed and radii. See Section 43-3.0 and the INDOT *Standard Drawings* for information on superelevation requirements.

(26) Horizontal Sight Distance. For a given design speed, the necessary middle ordinate will be determined by the radius and the sight distance which applies at the site. See the discussion in Section 43-4.0.

(27) Maximum Grades. For a grade less than 150 m in length (PVT to PVC), a one-way downgrade, or a street with  $AADT < 400$ , the maximum grade may be 2% steeper than table value. Where adjacent sidewalks are present, the maximum desirable grade is 5%.

(28) Intersection Sight Distance. For left turn onto a 2-lane road. P = Passenger car; SU = single unit truck. See Figure 46-10G for values for combination trucks.

Design Element		Manual Section	Design Values (By Type of Area)		
			Suburban	Intermediate	Built-Up
Design Controls	Design Forecast Year	40-2.02	20 Years	20 Years	20 Years
	*Design Speed (km/h) (2)	40-3.0	Curbed: 50-60 Uncurbed: 50-70	Curbed: 50-60 Uncurbed: 50-60	Curbed: 40-60
	Access Control	40-5.0	None	None	None
	Level of Service	40-2.0	Desirable: C; Minimum: D	Desirable: C; Minimum: D	D
	On-Street Parking	45-1.04	Optional (3)	Optional (3)	Optional (3)
Cross Section Elements	Travel Lane	*Width (4)	45-1.01	Curbed: 3.3 m Uncurbed: 3.3 m	Curbed: 3.0 m Uncurbed: 3.3 m
		Typical Surface Type	Chp. 52	Asphalt / Concrete	Asphalt / Concrete
	*Curb Offset (5)		45-1.02	0.6 m	0.6 m
	Shoulder	*Usable Width	45-1.02	Curbed: Des: 1.2 m; Min: 0.6 m Uncurbed: Des: 1.2 m; Min: 0.6 m	Curbed: Des: 1.2 m; Min: 0.6 m Uncurbed: Des: 1.2 m; Min: 0.6 m
		Typical Surface Type	Chp. 52	Asphalt / Concrete / Aggregate / Earth	Asphalt / Concrete / Aggregate / Earth
	Cross Slope	*Travel Lane (6)	45-1.01	2%	2%
		Shoulder	45-1.02	2%-6% Asph. / Conc.; 6%-8% Aggr.; 8% Earth	2%-6% Asph. / Conc.; 6%-8% Aggr.; 8% Earth
	Auxiliary Lanes	Lane Width	45-1.03	Des: 3.3 m; Min: 3.0 m	Des: 3.3 m; Min: 3.0 m
		Curb Offset		Des: 0.3 m; Min: 0.0 m	Des: 0.3 m; Min: 0.0 m
		Shoulder Width		Des: 1.2 m; Min: 0.6 m	Des: 1.2 m; Min: 0.6 m
		Typical Surface Type	Chp. 52	Asphalt / Concrete / Aggregate / Earth	Asphalt / Concrete / Aggregate / Earth
	Parking Lane Width (1)		45-1.04	Des: 2.7 m; Min: 2.4 m	Des: 2.7 m; Min: 2.4 m
	Sidewalk Width (7)		45-1.06	1.5 m with 1.5 m Buffer (Des)	1.5 m with 1.5 m Buffer (Des)
	Bicycle Lane Width (8)		51-7.0	Curbed: 1.5 m Uncurbed: Shld. Width +1.2 m	Curbed: 1.5 m Uncurbed: Shld. Width +1.2 m
	Clear Zones		49-2.0	(9)	(9)
	Typical Curbing Type (where used) (9c)		45-1.05	Sloping / Vertical	Sloping / Vertical
Side Slopes (Uncurbed)	Cut	Foreslope	45-3.0	3:1 Max	3:1 Max
		Ditch Width		Des: 1.2 m; Min: 0.0 m	N/A
		Backslope		3:1 Max (10)	N/A
		Fill		3:1 Max	N/A
Side Slopes (Curbed)	Cut (Backslope)	45-3.0	(11)	(11)	(11)
	Fill (12)		12:1 for 3.6 m; 3:1 Max to Toe	12:1 for 3.6 m; 3:1 Max to Toe	12:1 for 3.6 m; 3:1 Max to Toe

\* Controlling design criteria (see Section 40-8.0).

\*\* Table applies only to projects with Federal-aid funds.

Des: Desirable; Min: Minimum.

## GEOMETRIC DESIGN CRITERIA FOR URBAN LOCAL STREET \*\*

### (New Construction or Reconstruction)

Table 53-9

Design Element		Manual Section	Design Values (By Type of Area)					
			Suburban	Intermediate	Built-Up			
Bridges	New or Reconstructed Bridge	*Structural Capacity	Ch. 60	HS-25(12a)	HS-25(12a)	HS-25(12a)		
		*Clear Roadway Width	45-4.01	Curbed: Full Approach Curb-to-Curb Width Uncurbed: (13)				
	Existing Bridge to Remain in Place	*Structural Capacity	Ch. 72	HS-20	HS-20	HS-20		
		*Clear Roadway Width	45-4.01	Existing Width (14)				
	*Vertical Clearance (Local Under) (15)	New or Replaced Overpassing Bridge (15)	44-4.0	4.45 m	4.45 m	4.45 m		
		Existing Overpassing Bridge		4.30 m	4.30 m	4.30 m		
Vertical Clearance (Local over Railroad) (16)		Ch. 69	7.00 m					
Alignment Elements	Design Speed		30 km/h	40 km/h	50 km/h	60 km/h	70 km/h	
	*Stopping Sight Distance	Desirable	42-1.0	35	50 m	65 m	85 m	105 m
	Decision Sight Distance	Speed / Path / DirectionChange	42-2.0	U: 120 m SU: 100 m	U: 160 m SU: 130 m	U: 195 m SU: 170 m	U: 235 m SU: 205 m	U: 275 m SU: 235 m
		Stop Maneuver		90 m	130 m	155 m	195 m	235 m
	Intersection Sight Distance, -3% to +3% (22)		46-10.0	P: 65 m SU: 80 m	P: 85 m SU: 110 m	P: 105 m SU: 135 m	P: 125 m SU: 160 m	P: 150 m SU: 185 m
	*Minimum Radii		43-2.0	20 m (17)	45 m (17)	80 m (17)	130 m (17)	185 m (17)
	*Superelevation Rate (18)		43-3.0	$e_{max} = 4\%$				
	*Horizontal Sight Distance		43-4.0	(19)				
	*Vertical Curvature (K-values)	Crest	44-3.0	2	4	7	11	17
		Sag		6	9	13	18	23
*Maximum Grade (20)	Level	44-1.02	10%	10%	10%	9%	8%	
	Rolling		15%	11%	11%	10.5%	10%	
Minimum Grade		44-1.03	Desirable: 0.5%; Minimum: 0.3% (Curbed) (21) 0.0% (Uncurbed)					

\* Controlling design criteria (see Section 40-8.0).

U: Urban; SU: Suburban.

\*\* Table applies only to a project with federal-aid funds.

See note at bottom of Table 53-4 for Level One design criteria exception approval authority for a federally-funded urban local street.

## GEOMETRIC DESIGN CRITERIA FOR URBAN LOCAL STREET \*\* (New Construction or Reconstruction)

Table 53-9 (Continued)

**GEOMETRIC DESIGN CRITERIA FOR URBAN LOCAL STREET**  
**(New Construction or Reconstruction)**  
**Footnotes to Table 53-9**

- (1) **Parking Lanes**. In a residential area, the minimum width is 2.1 m. In a commercial or industrial area the minimum is 2.4 m. Where curb and gutter sections are used, the gutter width should be considered part of the parking lane width.
- (2) **Design Speed**. The minimum design speed should equal a) the minimum value from the table, b) the anticipated posted speed limit after construction, or c) the state legal limit on non-posted highways. The legal limit in an urban district is 50 km/h. Based upon an engineering study, these speeds may be raised to an absolute maximum of 90 km/h.
- (3) **On-Street Parking**. In general, on-street parking is discouraged.
- (4) **Travel Lane Width**. In a restricted area and where there are few trucks, travel lanes 0.3 m narrower may be used but may not be less than 3.0 m. In an industrial area, a 3.6-m travel lane should be used. In many residential areas, an 8.0-m roadway (curb face to curb face) consisting of one 3.6-m lane and two 2.2-m parking lanes is used. In an industrial area, 3.6-m lanes are desirable and 3.3-m lanes are minimum.
- (5) **Curb Offset**. The curb offset should be 0.6 m. For a curbed section, the curb offset is included in the paved shoulder width.
- (6) **Cross Slope (Travel Lane)**. Cross slopes of 1.5% are acceptable on an existing bridge to remain in place.
- (7) **Sidewalk Width**. A buffer of less than 0.6 m wide is not permitted. If no buffer is provided, the sidewalk width should be 1.8 m.
- (8) **Bicycle Lane Width**. The widths in the table are in addition to the width of a parking lane, if present. See Section 51-7.0 for additional details.
- (9) **Clear Zones**. The following will apply:
  - a. **Facility with Vertical Curbs**. The clear zone will be measured from the edge of travel lane or will be to the right-of-way line, whichever is less. No clear zone is required where there is 24-hour parking.
  - b. **Facility with Sloping Curbs or without Curbs**. The clear zone will vary according to design speed, traffic volumes, side slopes, and horizontal curvature.
  - c. **Curbed Facility**. There should be an appurtenance-free area as measured from the gutter line of any curb. Vertical curbs may only be used with design speed lower than 80 km/h.
  - d. **Values**. See Section 49-2.0 for specific clear zone values.
- (10) **Backslope**. The backslope for a rock cut will vary according to the height of the cut and geotechnical factors. See INDOT *Standard Drawings* for typical rock cut sections.
- (11) **Side Slope (Curbed) Cut**. Typically, a shelf or sidewalk will be present immediately behind the curb before the toe of the backslope. The minimum width of a shelf will be 1.8 m. Where a sidewalk is present, the toe of the backslope will typically be 0.3 m beyond the edge of sidewalk. See Section 45-3.0 for more information.

(12) Side Slope (Curbed) Fill. If no sidewalks are present or planned, the lateral extent of the 12:1 slope may be reduced to 1.2 m.

(12a) Structural Capacity (New or Reconstructed Bridge). A bridge with design year average daily truck traffic (ADTT) greater than 1,000 should be designed for HS 25 live loads. A bridge with an ADTT less than or equal to 1,000 may be designed for HS 25 or HS 20, whichever the LPA elects.

(13) Width (New or Reconstructed Bridge) Uncurbed. The following will apply:

<u>Volume</u>	<u>Minimum Clear Width</u>
0 < AADT < 400	Travelway +0.6 m each side
400 $\leq$ AADT < 2000	Travelway +0.9 m each side
AADT $\geq$ 2000	Approach Roadway Width (Travelway Plus Shoulders)

(14) Width (Existing Bridge to Remain in Place). If the width of an existing bridge is less than the approach travelway width, consideration should be given to widening the bridge. For such a bridge of length greater than 60 m, the minimum shoulder width on the right and the left may be 1.1 m.

(15) Vertical Clearance (Local Street Under Railroad). Table values include an additional 150-mm allowance for future pavement overlays. Vertical clearances apply from usable edge to usable edge of shoulder.

(16) Vertical Clearance (Local Street Over Railroad). See Chapter Sixty-nine for additional information on railroad clearance under a highway.

(17) Minimum Radii. This is based on  $e_{max}=4\%$  and low-speed urban street conditions.

(18) Superelevation Rate. See Section 43-3.0 for values of superelevation based on design speed and radii. See Section 43-3.0 for information on superelevation requirements.

(19) Horizontal Sight Distance. For a given design speed, the necessary middle ordinate will be determined by the radius and the sight distance which applies at the site. See the discussion in Section 43-4.0.

(20) Maximum Grades. In a residential area, the maximum grade should not exceed 15%. In an industrial or commercial area, the maximum grade should not exceed 8%.

(21) Flat Terrain. In very flat terrain and where no drainage outlet is available, gutter grades as low as 0.2% may be used.

(22) Intersection Sight Distance. For left turn onto a 2-lane road. P = Passenger car; SU = single unit truck. See Figure 46-10G for values for combination trucks.

ARCHIVED

## 54-2.0 TABLE OF 3R/PARTIAL 4R FREEWAY GEOMETRIC DESIGN VALUES

Figure 54-2A, Geometric Design Criteria for Freeways (3R / Partial 4R Projects) presents the Department's criteria for the design of 3R/partial 4R freeway projects for both rural and urban areas. The designer should consider the following in the use of the table.

1. **Manual Section References.** These tables are intended to provide a concise listing of design values for easy use. However, the designer should review the appropriate section references for greater insight into the design elements.
2. **Footnotes.** The tables include many footnotes, which are identified by a number in parentheses (e.g., (6)). The information in the footnotes is critical to the proper use of the design tables.
3. **Controlling Design Criteria.** The 3R/partial 4R table of geometric design criteria provides an asterisk to indicate controlling design criteria. The designer will evaluate the proposed design against the criteria presented in Table 54-2A and elsewhere in this Chapter.
4. **Design Exceptions.** These standards are for use on existing freeways including those on the National Highway System. They are to be used for all projects that are classified as 3R or partial reconstruction regardless of funding source. In other words, any 3R or partial reconstruction work, whether Federal-aid funded or not, must meet these standards. Deviation from controlling design criteria should be covered by an approved design exception. Also, any operational or maintenance changes, permanent or temporary, exclusive of work zone traffic control that in fact create substandard conditions such as by re-striping to obtain added lane(s) by reducing existing lane widths and/or shoulders, must be covered by design exceptions whether or not actual construction or reconstruction is involved.

Design exception requests for Level One design criteria on the following:

- a) Non-Exempt FHWA Funded Projects on the NHS require FHWA Approval.
- b) Exempt FHWA funded Projects on the NHS require Chief, Division of Design approval.
- c) Non-FHWA Federally Funded Projects on the NHS require Chief, Division of Design approval with an information copy sent to FHWA.
- d) Projects not on the NHS require Chief, Division of Design approval

Design Element			Manual Section	Rural	Urban
Design Controls	Design Forecast Year	54-3.01	20 Years (1)	20 Years (1)	
	*Design Speed (km/h)	54-3.01	Min: Original Design Speed	Min: Original Design Speed (2)	
	Access Control	40-5.0	Full Control	Full Control	
	Level of Service	40-2.04	Desirable: B; Minimum: C	Desirable: B; Minimum: D	
Cross Section Elements	Travel Lane	*Width	54-3.03	3.6 m	3.6 m
		Surface Type(3)	Chp. 52	Asphalt / Concrete	Asphalt / Concrete
	Shoulder	*Right Width(4)	54-3.03	Usable: 3.3 m; Paved: 3.0 m	Usable: 3.3 m; Paved: 3.0 m
		*Left Width(5)		2 Lanes: 1.2 m Paved. 3 Lanes: 3.0 m Paved	2 Lanes: 1.2 m Paved. 3 Lanes: 3.0 m Paved
	Cross Slope	Surface Type(3)	Chp. 52	Asphalt / Concrete	Asphalt / Concrete
		*Travel Lane (6)	45-1.01	2%	2%
	Auxiliary Lanes	Shoulder (6A)	45-1.02	Paved Width ≤ 1.2m: 2%; Paved Width > 1.2 m: 4%	Paved Width ≤ 1.2m: 2%; Paved Width > 1.2 m: 4%
		*Lane Width	45-1.03	3.6 m	3.6 m
	Median Width	*Shoulder Width		Left or Right: Des: 3.6 m; Min: 1.8 m	Left or Right: Des: 3.6 m; Min: 1.8 m
		Depressed		Existing	Existing
	Clear Zone	Flush (CMB)	54-3.03	Existing	Existing
			49-2.0	(8)	(8)
	Side Slopes (9)	Cut	54-3.03	2:1 or Flatter	2:1 or Flatter
				Existing	Existing
		Back Slope		2:1 or Flatter	2:1 or Flatter
		Fill	45-3.0	2:1 or Flatter	2:1 or Flatter
	Median Slopes			Desirable: 8:1; Maximum: 4:1	Desirable: 8:1; Maximum: 4:1
Bridges	New and Reconstructed Bridges	*Structural Capacity	Chp. 60	HS-25 & Alt. Military Loading (10)	HS-25 & Alt. Military Loading (10)
		*Clear Roadway Width(11)	54-5.0	Full Paved Approach Width	Full Paved Approach Width
	Existing Bridges to Remain in Place	*Structural Capacity	Chp. 72	HS-20	HS-20
		*Clear Roadway Width	54-5.0	Travelway Plus 3.0 m Rt. & 1.2 m Lt. Shoulders (7)	Travelway Plus 3.0 m Rt. & 1.2 m Lt. Shoulders (7)
	*Vertical Clearance (Freeway Under) (12a)	New and Replaced Overpassing Bridges (12b)	54-5.0	5.05 m	5.05 m (12c)
		Existing Overpassing Bridges		4.90 m	4.90 m (12c)
		Sign Truss / Pedestrian Bridges		New: 5.35 m; Existing: 5.20 m	New: 5.35 m; Existing: 5.20 m
	Vertical Clearance (Freeway over Railroad) (13)			7.00 m	7.00 m

\* Controlling design criteria (see Section 40-8.0).

**GEOMETRIC DESIGN CRITERIA FOR FREEWAY  
(3R or Partial 4R Project)**

Table 54-2A

Design Element		Manual Section	Rural	Urban		
Alignment Elements	Design Speed		110 km/h	90 km/h	100 km/h	110 km/h
	*Stopping Sight Distance	42-1.0	220 m	160 m	185 m	220 m
	*Minimum Radii	43-2.0	Existing (14)	Existing (14)		
	*Superelevation Rate (15)	43-3.0	$e_{max} = 8\%$	$e_{max} = 8\%$		
	*Horizontal Sight Distance	43-4.0	See Section 43-4.0	See Section 43-4.0		
	*Vertical Curvature (K-values)	44-3.0	Existing (14)	Existing (14)		
			Existing (14)	Existing (14)		
	*Maximum Grade	54-3.02	Existing (14)	Existing (14)		
			Existing (14)	Existing (14)		
Interchange Elements	Minimum Grade	44-1.03	Desirable: 0.5%; Minimum: 0.0%	Desirable: 0.5% Minimum: 0.0%		
	Traveled Way	48-5.02	4.9 m	4.9 m		
		Chp. 52	Asphalt / Concrete	Asphalt / Concrete		
	Shoulder	48-5.02	Usable: 3.3 m. Paved: Des: 2.4 m; Min: 2.3 m	Usable: 3.3 m. Paved: Des: 2.4 m; Min: 2.3 m		
			Usable: 2.1 m. Paved: Des: 1.2 m; Min: 0.8 m	Usable: 2.1 m. Paved: Des: 1.2 m; Min: 0.8 m		
	Cross Slope	48-5.02	Asphalt / Concrete	Asphalt / Concrete		
			2%	2%		
	Superelevation	48-5.03	$e_{max} = 8\%$	$e_{max} = 4\%, 6\%, \text{ or } 8\% (18)$		
	Maximum Grade	48-5.04	3% - 5%	3% - 5%		
			4% - 6%	4% - 6%		

\* Controlling design criteria (see Section 40-8.0).

## GEOMETRIC DESIGN CRITERIA FOR FREEWAY (3R or Partial 4R Project)

Table 54-2A (Continued)

## GEOMETRIC DESIGN CRITERIA FOR FREEWAY (3R or Partial 4R Project)

### Footnotes to Table 54-2A

- (1) Design Forecast Year. Resurfaced pavements may have a 10-year design life.
- (2) Design Speed. The existing posted speed limit may be used in restricted urban conditions, but not less than 80 km/h on Interstate highways.
- (3) Surface Type. The pavement type selection will be determined by the Pavement Design Engineer.
- (4) Shoulder Width (Right). The following will apply:
  - a. The shoulder is paved to the face of guardrail. The desirable guardrail offset is 0.6 m from the effective usable shoulder width. See Section 49-5.0 for more information.
  - b. When the number of trucks exceeds 250 DDHV, a 3.6-m right shoulder should be considered. If the 3.6-m shoulder is used, the usable shoulder width will be 3.9 m.
  - c. Usable shoulder width is defined as the distance from the edge of the travel lane to the shoulder break point.
- (5) Shoulder Width (Left). The following will apply:
  - a. Typically, the effective usable shoulder width is equal to the paved shoulder width. The desirable guardrail offset is 0.6 m from the effective usable shoulder width. See Section 49-5.0 for more information.
  - b. When there are 3 or more lanes in one direction, a 3.6-m left shoulder should be provided if practical.
  - c. Usable shoulder width is defined as the distance from the edge of the travel lane to the shoulder break point. Usable width is typically 0.3 m wider than the paved shoulder width.
- (6) Cross Slope (Travel Lane). Cross slopes of 1.5% are acceptable on existing bridges to remain in place.
- (6A) Cross Slope (Shoulder). See Figure 45-1A(1) or Figure 45-1A(2) for more-specific information.
- (7) Shoulders for Bridge to Remain in Place. For such a bridge of length  $> 60$  m, the minimum width for both shoulders may be 1.2 m. This requirement does not apply to a bridge deck replacement.
- (8) Clear Zone. The clear zone will vary according to design speed, traffic volumes, side slopes and horizontal curvature. See Section 49-2.0.

## GEOMETRIC DESIGN CRITERIA FOR FREEWAY (3R or Partial 4R Project)

### Footnotes to Table 54-2A (Continued)

- (9) Side Slopes. Retention of the existing side slope shape of 2:1 or flatter will most often be acceptable. However, an existing fill slope of steeper than 4:1 should be evaluated for flattening. Section 54-3.03 provides additional information for side slope criteria for a project with freeway widening (i.e., lane and/or shoulder widening).
- (10) Structural Capacity (New or Reconstructed Bridge). Other loadings will apply to the Toll Road or an Extra Heavy Duty Highway. See Chapter Sixty for more information.
- (11) Width (New or Reconstructed Bridge). See Sections 49-5.0 and 59-1.0 for more information on bridge width.
- (12) Vertical Clearance (Freeway Under). The following will apply:
  - a. Vertical clearance applies from usable edge to usable edge of shoulders.
  - b. Table values include an additional 150-mm allowance for future overlays.
  - c. A 4.3-m clearance may be used in an urban area where an alternative freeway facility with a 4.9-m clearance is available; see Section 54-3.02.
- (13) Vertical Clearance (Freeway Over Railroad). See Chapter Sixty-nine for additional information on railroad clearance under a highway.
- (14) Existing Conditions. For these design elements, the existing conditions are generally satisfactory unless accident history dictates that a modification is necessary.
- (15) Superelevation Rate. The designer should review Sections 43-2.0 and 43-3.0 to determine if any improvements are necessary.
- (16) Shoulders (Surface Type). The pavement type selection will be determined by the Pavement Design Engineer. For a ramp with curve radii less than or equal to 100 m, the shoulders will have the same pavement design as the travelway.
- (17) Cross Slope (Shoulders). For a ramp with curve radii less than or equal to 100 m, the shoulder cross slope will be the same as the travelway.
- (18) Superelevation. The maximum superelevation rate will depend on site conditions. The highest rate practical should be used, especially for a descending ramp.

ARCHIVED