

PCCP SMOOTHNESS

The Standard Specifications are revised as follows:

SECTION 501, DELETE LINES 571 THROUGH 571aa.

SECTION 501, AFTER LINE 572, INSERT AS FOLLOWS:

| <i>SECTION PAY FACTORS FOR SMOOTHNESS (PI_{0.0}) ZERO BLANKING BAND</i> | |
|---|-------------------|
| <i>Design Speed Greater Than 45 mph (70 km/hr)</i> | |
| <i>Profile Index in./0.1 mi. (mm/0.16 km)</i> | <i>Pay Factor</i> |
| <i>Over 0.00 to 1.40 in. (Over 0 to 35 mm)</i> | <i>1.06</i> |
| <i>Over 1.40 to 1.60 in. (Over 35 to 40 mm)</i> | <i>1.05</i> |
| <i>Over 1.60 to 1.80 in. (Over 40 to 45 mm)</i> | <i>1.04</i> |
| <i>Over 1.80 to 2.00 in. (Over 45 to 50 mm)</i> | <i>1.03</i> |
| <i>Over 2.00 to 2.40 in. (Over 50 to 60 mm)</i> | <i>1.02</i> |
| <i>Over 2.40 to 2.80 in. (Over 60 to 70 mm)</i> | <i>1.01</i> |
| <i>Over 2.80 to 3.60 in. (Over 70 to 90 mm)</i> | <i>1.00</i> |
| <i>Over 3.60 to 3.80 in. (Over 90 to 95 mm)</i> | <i>0.96</i> |
| | |
| <i>All pavements with a Profile Index (PI_{0.0}) greater than 3.80 in. (95 mm) shall be corrected to 3.80 in. (95mm).</i> | |
