

801-T-163 TEMPORARY CONCRETE TRAFFIC BARRIERS

(Adopted 12-18-06)

The Standard Specifications are revised as follows:

SECTION 801, BEGIN LINE 320, DELETE AND INSERT AS FOLLOWS:

801.10 Temporary Traffic Barriers

Temporary traffic barrier shall be one of the following four types as shown on the plans.

Type 1

Type 1 temporary traffic barriers shall be used to separate two-way traffic and shall be precast concrete in accordance with applicable requirements of 707 and 602 and as shown on the plans. Type 1 barriers may also be used to separate traffic from the work zone. The surfaces of individual precast units shall vary no more than 0.25 in. (6 mm) in 10 ft (3 m) from the specified cross section, as measured from a longitudinal straightedge. The maximum variation in the vertical and horizontal alignment of adjacent units shall be 0.25 in. (6 mm) across the joint, as measured from a 10 ft (3 m) longitudinal straightedge. Sections that have obvious defects or visual cracks shall not be used. Sections that develop any of these conditions during the contract shall be repaired with concrete or replaced within a reasonable amount of time.

Type 1 barrier units precast prior to 2003 shall not be used after January 1, 2012. Units precast after March 1, 2003 shall be clearly marked with the name or trademark of the manufacturer, the year of manufacture, and "INDOT". The markings shall be indented on an end or on the top of each barrier section. ~~Units precast prior to 2003 shall not be used after January 1, 2012.~~ Units precast after January 1, 2007 shall be from the Department's list of Certified Precast Concrete Producers.
