

## 621-R-800 SEEDING AND SODDING

(Adopted 07-17-25)

The Standard Specifications are revised as follows:

SECTION 621, BEGIN LINE 30, DELETE AND INSERT AS FOLLOWS:

**621.03 Preparation of Ground Before Seeding**

The area to be seeded shall be made smooth and uniform and shall be in accordance with the finished grade and cross-section shown on the plans or as otherwise designated and shall be trimmed in accordance with 210. The seed bed, if not loose, shall be loosened to a minimum depth of 36 in. before fertilizer or seed is applied. ~~In areas of excessive vehicular traffic, such as parking of construction equipment near a bridge repair, the soil shall be loosened to a minimum depth of 6 in.~~

Areas to be covered with topsoil shall be milled or disked slightly before the topsoil is placed. A disk, spike-toothed harrow, or other similar device may be used for this purpose. Such loosening will be required to ensure ~~bond of~~ the topsoil *bonds* with the surface on which it is placed and to form a uniform surface. The topsoil shall then be spread to a sufficient depth to produce the ~~thickness~~ specified *thickness* after it has been compacted lightly with an approved roller, tamping device, or other method. *The topsoil shall be loose enough that the tread of a person's boot shows when walking on the soil but shall not be so loose as to allow more than 1/2 in. of total compaction.*

SECTION 621, BEGIN LINE 54, DELETE AND INSERT AS FOLLOWS:

**621.05 Applying Fertilizer, Seed, and Mulch****(a) Fertilizer**

Fertilizer as specified shall be spread uniformly over the area to be seeded. Fertilizer shall be spread at the rate of 800400 lb/ac unless otherwise specified.

**(b) Seed**

~~Seed may be drilled in or mixed with water. The mixture shall be sprayed over the area to be seeded. An approved mechanical method which shall place the seed in direct contact with the soil may be used. In places inaccessible to mechanical equipment, or where the area to be seeded is small, a hand operated cyclone seeder or other approved equipment may be used. Seed of warm season grasses, forbs, or aquatic species shall not be covered more than 1/8 in. All other seed shall not be covered more than 1/2 in.~~ *Seed shall be applied in a manner that results in uniform distribution of seed in which seed to soil contact at the optimal seed depth is attained necessary for the germination of the species being planted.*

---