

7/13
Crafts

ChemCAS

Expert MSDS Authoring

www.chsi.com

Don't have the time or expertise? Count on experienced professionals. A

[Ads by Google](#) [MSDS Sheets](#) [Glass Company](#) [Fire Glass](#) [Safety Glass](#)

Search



MSDS : GALLERY GLASS LI
QUID LEADING, MS-
15150S
CAS :
NAME : non-hazardous ients

Free NFPA Diamond Guide



Understand the NFPA Diamond at a glance. Use as a desk or wall chart.

Click Here

DuraLabel

Catalog of Chemical Suppliers, Buyers, Custom Synthesis Companies And Equipment Manufacturers
[GALLERY GLASS LIQUID LEADING, MS-15150S]

Suppliers:

Not Available

Buyers:

Not Available

WagginTails.com

WagginTails.com

Made in USA Pet Foods. New Customers Save 15% w/Code WT15!



AdChoices

=====
===== Product Identification =====
=====

MSDS NAME:GALLERY GLASS LIQUID LEADING, MS-15150S
NIIN:00N065360
MSDS Number: CBCWG
=== Responsible Party ===
Company:PLAID ENTERPRISES
Address:1649 INTERNATIONAL BLVD
City:NORCROSS
State:GA
ZIP:30091
Country:US
Info Phone Num:404-923-8200

Emergency Phone Num:404-923-8200

Preparer's Name:J. STANLEY

CAGE:0ACX4

=== Contractor Identification ===

Company:PLAID ENTERPRISES

Address:1649 INTERNATIONAL BLVD

Box:City:NORCROSS

State:GA

ZIP:30091

Country:US

Phone:404-923-8200

CAGE:0ACX4

=====
Composition/Information on Ingredients
=====

==

Name:NON-HAZARDOUS INGREDIENTS

OSHA PEL:N/K

ACGIH TLV:N/K

=====
Hazards Identification
=====

====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SKIN CONTACT:PROLONGED OR R
EPEATED

CONTACT MAY CAUSE LOCAL IRRITATION. EYE:DIRECT CONTACT
W/PRODUCT

MAY CAUSE IRRITATION. INHALATION/SKIN ABSORPTION/INGEST
ION: NOT

APPLICABLE.

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:SEE HEALTH HAZARDS.

=====
First Aid Measures
=====

====

First Aid:INGEST:CALL MD IMMEDIATELY . INHAL:REMOVE TO FRESH
AIR.

SUPPORT BREATHING (GIVE O²/ARTF RESP) . SKIN:WASH THOROUGHLY

W/SOAP & WATER FOR AT LEAST 15 MINUTES. EYE:PROMPTLY &
THOROUGHLY

FLUSH W/WATER FOR AT LEAST 15 MINUTES. CONSULT MD IF IRRITATION

PERSISTS.

=====
Fire Fighting Measures
=====

====

Extinguishing Media:MEDIA SUITABLE FOR SURROUNDING FIRE .

Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA & FULL
PROTECTIVE

EQUIPMENT . USE WATER SPRAY TO COOL CONTAINERS NOT ACTIVELY

INVOLVED IN FIRE.

Unusual Fire/Explosion Hazard:PROD IN LIQ STATE WILL NOT BURN, BUT MAY

SPLATTER IF TEMP EXCEEDS BOILING POINT. DRIED COPOLYMER IS CAPABLE

OF BURNING, GIVING OFF OXIDES OF CARBON & NITROGEN.

===== Accidental Release Measures =====
=====

Spill Release Procedures:KEEP UNNECESSARY PERSONNEL AWAY. D
IKE &

CONTAIN SPILL WITH INERT MATERIAL SUCH AS SAND OR EARTH. T
RANSFER

MATERIAL INTO CONTAINER FOR PROPER DISPOSAL. KEEP SPIL
L OUT OF

SEWERS & OPEN BODIES OF WATER. FLOORS MAY BECOME SLI
PPERY.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====
=====

Handling and Storage Precautions:DO NOT FREEZE. DO NOT STORE A
T

TEMPERATURES >130F.

===== Exposure Controls/Personal Protection =====
=

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATOR APPRO
PRIATE FOR

EXPOSURE OF CONCERN .

Eye Protection:ANSI APPROVED CHEM WORKERS GOGGS .

Work Hygienic Practices:AFTER USING PRODUCT, WASH HANDS BEF
ORE EATING,

DRINKING OR SMOKING.

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====
=====

Boiling Pt:B.P. Text:212F,100C

Spec Gravity:1 (H*20=1)

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:100% SOL/DISPERSABLE

Appearance and Odor:VISCIOUS LIQUID W/SLIGHT ODOR OF AMMONI
A.

===== Stability and Reactivity Data =====
=

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:DO NOT FREEZE.

Hazardous Decomposition Products:HAZARDOUS DECOMPOSITION WI
LL NOT

OCCUR.

===== Disposal Considerations =====
=====

Waste Disposal Methods:DISPOSE OF I/A/W ALL LOCAL, STATE & FED
ERAL

WASTE DISPOSAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.

*** END OF RECORD ***

Search More



ALL PAGES On Chemical Property IN THIS GROUP

NAME	CAS
<u>2-NITROPHTHALENE TECH, 85%, 18484-5</u>	581-89-5
<u>1-NITROPYRENE, 99%, N2295-9</u>	5522-43-0
<u>POWDER, UNIQUE, 0-626</u>	55-63-0 9004-70-0
<u>PRIMER MIX 955, E-899</u>	15345-44-0 109-27-3
<u>CARTRIDGE, DOOR BREACHING, 231906</u>	15345-44-0 109-27-3
<u>PRIMER, 410172</u>	7439-92-1
<u>2 DIESEL OIL STANDARD AR 2829</u>	68476-34-6
<u>HYDROCARBON STANDARD LUBE OIL AR2836</u>	8012-95-1
<u>A-301/5GL TRAFFIC YELLOW EXTERIOR</u>	21564-17-0 13463-67-7 8032-32-4 7758-97-6
<u>A-300/5GL TRAFFIC PAINT COLOR: WHITE EXTERIOR</u>	21564-17-0 13463-67-7 8032-32-4
<u>ZIRCONIUM HYDRIDE</u>	7704-99-6
<u>ZIRCONIUM METAL, POWDER</u>	7440-67-7
<u>MA-142</u>	108-88-3 110-54-3
<u>ACCELERATOR, AC-102</u>	63512-71-0 64-17-5
<u>CARTRIDGE CASE PRIMED, 531907</u>	15345-44-0 109-27-3 7439-92-1
<u>AQUANISM</u>	
<u>RESIN DIABRASIVE TOOLING</u>	7782-40-3
<u>AR-8000</u>	64742-34-3 64742-11-6 8052-42-4
<u>SC-800</u>	64742-34-3 64742-11-6 8052-42-4
<u>LAPPING COMPOUND</u>	409-21-2
<u>SF-880RD SILICONE OIL</u>	
<u>C 592</u>	7647-01-0
<u>VANISH-Q QTS</u>	111-76-2 67-63-0
<u>TRIFLUOROMONOBROMOMETHANE, MAT24070</u>	75-63-8
<u>SILANE, MAT20590</u>	7803-62-5
<u>AIR, COMPRESSED</u>	25635-88-5
<u>HEPTAFLUOROBUTYRIC ANHYDRIDE, H1006</u>	336-59-4
<u>705 HOT MELT ADHESIVE</u>	

<u>LIQUID CERTIZYME, 0317</u>	67-63-0
<u>CHECK-MARK RC-100, 0243</u>	1194-65-6
<u>P1404 NEUTRA PRIME, 1404</u>	67-63-0
	107-98-2
	1401-55-4
	75-45-6
<u>GALLERY GLASS LIQUID LEADING, MS-15150S</u>	
<u>ISOBUTYLENE</u>	115-11-7
<u>CREATIVE TOUCH GLASS STAIN</u>	7664-41-7
	34590-94-8
<u>CREATIVE TOUCH OVERGLAZES</u>	63231-67-4
<u>BLUE GREASE, 35001</u>	15890-25-2
	64742-52-5
	64742-53-6
	68411-15-4
	25038-37-3
<u>CONTAX NONFLAMMABLE, 91020</u>	1717-00-6
	124-38-9
<u>P-206 ZIP-CRETE</u>	1309-48-4
	14808-60-7
	7722-76-1
<u>P-204 HAND-TUFF</u>	65997-15-1
	14808-60-7
	25068-63-7
	7732-18-5
<u>CORROSEAL RUST CONVERTER & COPOLYMER METAL(SUPDAT)</u>	112-15-2
<u>EZE-FLO FUMELESS, ALKALINE LIQUID DRAIN (SUPDAT)</u>	1310-58-3
<u>CIP BLACK SATIN, 96</u>	64742-47-8
<u>PANASONIC KX-P4420</u>	25153-46-2
	1317-61-9
	1309-37-1
	9003-07-0
	1333-86-4
	31714-55-3
	7631-86-9
<u>FIBERED ROOF COATING, F100 BULK AF</u>	8031-18-3
	64742-88-7
<u>LN-604 WB PANEL & FOAM ADHESIVE, MMF 361</u>	1317-65-3
	1332-58-7
	67-56-1
	64742-47-8
	71302-83-5
	7732-18-5
	9003-55-8
<u>GENIE PAC PANTASTIC</u>	151-21-3
	497-19-8
<u>GREASECUTTER</u>	1310-73-2
	111-76-2
<u>BLACK FLUX</u>	12228-88-5
	10043-35-3
	1229-13-9
	7789-29-9
	151-21-3
	7440-42-8
<u>PR-500 PLATE CLEANER/SCRATCH REMOVER</u>	64742-88-7
	7664-38-2
<u>CONDUCTIVITY SOLUTION 5000 UMHOS, R-0868-5K</u>	7647-14-5
	7732-18-5

Free MSDS Search (Providing 250,000+ Material Properties)
Chemcas.com

Last modified: 02/06/2013 15:02:14