

SCM COATINGS AND RESINS DIVISION -- ULTRA-HIDE SANDING SEALER-CLEAR, Y5035E
 -- 8010-00F000574

=====
 Product Identification
 =====

Product ID:ULTRA-HIDE SANDING SEALER-CLEAR, Y5035E

MSDS Date:01/01/1985

FSC:8010

NIIN:00F000574

MSDS Number: BBGXV

=== Responsible Party ===

Company Name:SCM COATINGS AND RESINS DIVISION

Emergency Phone Num:216/ 826-5566

CAGE:82053

=== Contractor Identification ===

Company Name:SCM COATINGS AND RESINS DIVISION

CAGE:82053

=====
 Composition/Information on Ingredients
 =====

Ingred Name:MINERAL SPIRITS EXEMPT (TLV VALUE SHOWN IS TYPICALLY
 RECOMMENDED BY SUPPLIERS)

RTECS #:SE7550000

Fraction by Wt: 27%

ACGIH TLV:100PPM

Ingred Name:(SEE SUPPLEMENTAL SECTION FOR ADDITIONAL INGREDIENTS).

=====
 Hazards Identification
 =====

Effects of Overexposure:IRRITATION OF EYES, SKIN AND RESPIRATORY TRACT.
 HEADACHE AND DIZZINESS LIKELY W/VAPOR INHALATION.

=====
 First Aid Measures
 =====

First Aid:FUMES: MOVE PERSON TO WELL VENTILATED AREA. RESTORE
 BREATHING. GET MEDICAL ATTENTION. SKIN: WIPE WITH CLEAN CLOTH, WASH
 THOROUGHLY WITH SOAP AND WATER. EYES: FLUSH THOROUGHLY WITH WATER,
 GET MEDICAL ATTENTION.

=====
 Fire Fighting Measures
 =====

Flash Point:50F, T.C.C.

Lower Limits:0.9

Extinguishing Media:CO2, DRY CHEMICAL OR FOAM

Fire Fighting Procedures:WATER SPRAY MAY BE USED TO COOL CLOSED
 CONTAINERS.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN
 EXPOSED TO EXTREME HEAT OR FIRE. DO NOT APPLY TO HOT SURFACES.

=====
 Accidental Release Measures
 =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE
 AREA. MOP SPILLS WITH INERT ABSORBENT.

=====
 Handling and Storage
 =====

Handling and Storage Precautions:STORE BELOW 100 DEGREES F. KEEP
 CONTAINERS CLOSED AND AWAY FROM HEAT AND OPEN FLAME.

Other Precautions:AVOID PROLONGED CONTACT WITH SKIN AND BREATHING
VAPORS OR SPRAY MIST. DO NOT TAKE INTERNALLY. AVOID CONTAMINATION
WITH FOREI MATERIALS.

=====**Exposure Controls/Personal Protection**=====

Respiratory Protection:USE MASK, MECHANICAL FILTER/ MASK, CHEMICAL
MECHANICAL FILTER TYPE
Ventilation:DILUTION VENTILATION OR LOCAL EXHAUST
Protective Gloves:SOLVENT RESISTN
Eye Protection:SPLASH-PROOF GOGGLES
Other Protective Equipment:IN CONFINED AREAS USE AIR LINE RESPIRATOR OR
HOODS.
Supplemental Safety and Health
ALSO CONTAINS 37% SUPER VM&P NAPHTHA, TLV-300PPM.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:240-374F
Vapor Density:>AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:71

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE KNOWN
Hazardous Decomposition Products:CO, CO2 AND POSSISBLE NO FUMES ON
IGNITION

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH ALL APPLICABLE
REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.