

**PROPRIETARY-MATERIAL-USE
PUBLIC-INTEREST FINDING**

PROGRAMMATIC APPROVAL

PROGRAMMATIC APPROVAL PERIOD: July 1, 2015 – June 30, 2017

FHWA OVERSIGHT: YES NO

PROPRIETARY MATERIAL:

Global Traffic Technologies, LLC
Canoga™ 702 Non-invasive Microloop™ Sensor

ADDITIONAL PARTS:

The following parts are included with the programmatic approval for the Canoga™ 702 Non-invasive Microloop™ Sensor, as being necessary for a complete installation of a microloop vehicle detection system.

1. Canoga™ 702 Microloop™ Sensor Carrier
2. Canoga™ 702 Non-invasive Microloop™ Sensor Installation Kit
3. 3M™ Scotchcast™ 3832 Buried Service Wire Splice Installation Kit
4. Canoga™ C922, C924 Vehicle Detectors
5. Canoga™ 3003 Home Run Cable

Background

The Canoga™ 702 Non-invasive Microloop™ Sensor received programmatic approval on August 11, 2011 for a two year term that ends on June 30, 2013. The programmatic approval was renewed for another two year term that ended June 30, 2015.

Product Selection

Recurring special provision 805-T-191 contains specifications for a common alternative to inductive vehicle detection loops at signalized intersections. The Canoga™ 702 Non-invasive Microloop™ Sensor is a useful alternative to the conventional method in the following situations:

- if the pavement is in poor condition
- if a shorter lane closure is desired for maintaining traffic, as the Canoga™ 702 Non-invasive Microloop™ Sensor is bored underneath the pavement from the side of the road
- if the pavement is due to be resurfaced within the next few years

Product History

The desired product is also currently listed on INDOT's Approved Materials List for Traffic Signal Control Equipment under the non-counting loop amplifier section. Even though it is listed as a non-counting loop amplifier, it does have vehicle counting capabilities and is the only one of the three that currently has this capability. The ability to count vehicles and communicate

this data is important if a vehicle detection device is to be a true alternative to traditional inductive vehicle detection loops.

Project Compatibility.

The product desired would be compatible with many traffic signal installation and traffic signal modernization projects throughout the State. The product would be intended for use at all traffic signal projects when its advantages outweigh its disadvantages.

Product Availability

The product desired is the only product of its type that is currently available. A Google search for “vehicle detection microloop” will turn up only the Canoga™ Non-invasive Microloop™ Sensor within the first 30 relevant search results.

Product Cost

The 2013 and 2014 unit price summaries show a unit price of \$1,050 for a Microloop Detector (pay item 805-11540) out of 203 items.

Typically, the conventional inductive loops are paid for by the amount of saw cutting and cable installed, but an approximate unit price for an inductive loop is around \$250. So while the product desired is more expensive than conventional vehicle detection methods, it is the preferred detection method when the existing pavement is in poor condition (for example on local road approaches) or to minimize lane closures.

Product Alternatives – Summary Table

	Microloop Detectors	Video Detection Systems	Wireless Vehicle Detection Systems	Traditional Inductive Loops
Non-invasive to Pavement	Yes, system bored underneath pavement	Yes, system installed on traffic signal mast arms	No, requires 4 inch pavement cores	No, requires saw cutting for loops
High Accuracy Rate	Yes, meets <u>ITM 934</u>	No, see JTRP Report 2005-30	Yes, meets <u>ITM 934</u>	Yes, meets <u>ITM 934</u>
Minimizes Lane Closure During Installation	Yes, system can be installed with shoulder closure	No, requires short lane close to install camera over lanes	No, requires short lane closure for pavement cores	No, requires moderate lane closure for saw cutting
Capable of Providing Vehicle Counts	Yes, Canoga 702 Microloop	Yes	Yes, Type F Sensor	Yes
Proprietary Item	Yes, <u>Canoga</u> by GTT	No, multiple manufacturers	Yes, VDS 240 by Sensys Networks	No, multiple manufacturers

Maintenance

The product is easier to maintain than inductive loops because they are not as susceptible to being torn by the pavement (because they are bored underneath the pavement) and the sensors can be replaced without cutting the pavement.

PREPARED BY:

Date: 8/14/2015

Joseph E. Bruno
Traffic Administration Engineer
INDOT – Traffic Support Division
(317) 234-7949

Based upon the above finding, the use of the proprietary material listed is in the public interest and is hereby approved.

APPROVED:


Deputy Commissioner, Engineering
& Asset Management, INDOT


for Division Administrator, FHWA

Date: 9/16/2015

Date: 9/21/2015



Global Traffic
Technologies

Canoga™ Traffic Sensing System

Canoga™ 702 Non-invasive Microloop™ Sensors

A Matched Component of the Canoga™ Traffic Sensing System

October 2007

Description

Canoga™ 702 Non-invasive Microloop™ Sensors are a matched component of the Canoga™ Traffic Sensing System. These traffic sensors provide a unique alternative to other vehicle detection systems when connected to a suitably configured Canoga™ Traffic Monitoring Card or a Canoga™ C900 Series Vehicle Detector.

The Canoga 702 Microloop is a transducer that converts changes in the vertical component of the earth's magnetic field to changes in inductance. Vehicles containing vertical components of ferromagnetic material "focus" the earth's field, increasing the magnetic field at the sensor when vehicles move over the sensor. Changes in inductance can be sensed by a Canoga traffic monitoring card or Canoga C900 series vehicle detector suitably configured for the Canoga 702 Microloop.

The Canoga 702 Microloop sensor's small size permits its easy insertion into a 3-inch (7.6 cm) plastic conduit installed 18–24 inches (46–61 cm) below the road surface. Installing the sensors in a conduit leaves the road surface intact, bypasses the effects of poor pavement conditions and inclement weather, and virtually eliminates maintenance and service requirements.

Features

Canoga 702 Microloop offers superior value compared with other vehicle detection technology. It effectively replaces inductive loops for freeway, counting and intersection applications. When connected to Canoga traffic monitoring cards, Canoga 702 Microloop provides accurate, real-time mean speed, count and occupancy data, and vehicle speed and length classification. When performance and life cycle cost are important, Canoga 702 Microloop provides an industry leading advantage.



Canoga™ 702 Non-invasive Microloop™ Sensor

Superior Value

- Lower life cycle costs.
- No maintenance. Underground, protected from weather and traffic, highly durable Canoga 702 Microloop requires no maintenance.
- Lower service costs. Repair is virtually eliminated. Buried sensors and cables are not affected by environmental factors, pavement deterioration or other mechanical stresses. Sensors can be replaced from the roadside without affecting traffic.
- Lower pavement repair and maintenance costs; the road surface is not damaged.
- Better installation and efficiency; traffic lanes are not closed for long periods of time.
- Better road repair efficiency; resurfacing and surface repairs can occur without affecting detection performance.

A Matched Component of the Canoga™ Traffic Sensing System

Flexibility

The Canoga™ 702 Non-invasive Microloop™ Sensors can be easily repositioned or readjusted to improve vehicle sensing accuracy or to reflect changing traffic characteristics in permanent installations or work zones.

Easy to Install

Conventional, horizontal directional drilling techniques or open trenching are used for installation of the conduit.

Small Size

Canoga 702 Microloop sensors fit into specially designed carriers. Carriers can be inserted in less than an hour into a 3-inch (7.6 cm) Schedule 80 conduit installed 18–24 inches (46–61 cm) below the road surface.

Accurate

Canoga 702 Microloop sensors connected to a suitably configured Canoga™ Traffic Monitoring Card or Canoga™ C900 Series Vehicle Detector provide accurate and highly reliable measurements.

- Closely spaced vehicles can be resolved and adjacent lane vehicles rejected.
- Accurate detection is achieved in every lane and under all environmental conditions, unfazed by rain, snow, wind or fog.

Operating Parameters

- **Earth's Vertical Magnetic Field:** 0.2–0.8 oersted.
- **Inductance (Red to Green Wires):** 50–63 microhenries per sensor plus a nominal 16.5 microhenries per 100 feet (30 m) of lead-in cable.
- **DC Resistance (Red to Green Wires):** 1.2–1.8 ohm per sensor plus a nominal 3.04 ohm per 100 feet (30 m) of lead-in cable.
- **Transducer Gain (Sensitivity):** Typically 5.0 nH per millioersted per sensor at 0.4 oersted ambient vertical field intensity.
- **Canoga 702 Microloop Assemblies:** Available in single, double or triple sensor assemblies with standard sensor separations and connected in series to a lead-in cable which may be up to 1,000 feet (305 m) in length.

- **Home-run Cable:** Canoga™ 30003 Home-run Cable is used to connect lead-in cable to the cabinet. The combined length of home-run cable and lead-in cable may be as long as 2,500 feet (762 m).
- **Maximum Number of Sensors per Channel:** Up to three sensors are recommended per channel.
- **Microloop Peak-to-Peak Drive Current with Canoga Traffic Monitoring Cards or Canoga C900 Series Cards:** The cards must provide between 14 and 80 milliAmp-p.

Installation

Canoga 702 Microloop sensors are designed to be inserted into a 3-inch (7.6 cm) non-ferrous Schedule 80 conduit.

Conduit is installed 21 ± 3 inches (53.3 ± 7.6 cm) below the road surface using horizontal directional drilling or open trenching techniques.

See Canoga 702 Microloop installation instructions for more information.

Wiring

Multiple Canoga 702 Microloop sets can be wired in series to accommodate different applications. Two independent sensor sets can be connected to a single Canoga 30003. For reliable operation, all splices must be soldered, insulated and waterproofed. See Canoga 702 Microloop installation instructions for detailed wiring instructions.

Environmental

- **Temperature:** -30° F to +165° F (-34° C to +74° C).
- **Relative Humidity:** 100% (including submersion in solutions of chemicals typical of roadway runoff).

Physical Characteristics

- **Sensor:** Cylindrical, 2.25 inches (5.7 cm) high, fitting a .8125 inch (2 cm) hole in the carrier.
- **Lead-in Cable:** Polyurethane-jacketed cable with two PVC insulated AWG #22 conductors. Overall diameter 0.19 inches (0.48 cm).
- **Color:** Black sensor body and black jacketed lead-in cable with red and green insulated wires.

Related Products or Accessories

Canoga™ 702 Non-invasive Microloop™ Sensor Carriers hold Canoga 702 Microloop sensors in a fixed, vertical position as they are inserted into the previously installed, 3-inch (7.6 cm) conduit. The carriers' interlocking mechanism maintains the alignment of the sensors within $\pm 20^\circ$ from vertical.

- Physical characteristics of the carrier:
12 inches (30.5 cm) long PVC sensor carrier with an outer diameter of 2.6 inches (6.6 cm).

Canoga™ 702 Non-invasive Microloop™ Sensor Installation Kit is required for each conduit

(one kit per conduit). The kit contains all of the parts necessary to insert and remove the sensors, to label sensor cables and to close off the conduit ends.

- Physical characteristics of the end cap carrier: PVC tubing 13 inches (33 cm) long and 2.6 inches (6.6 cm) in diameter. The end cap carrier is the first piece to be inserted into the conduit. It has an attached rope that permits removal of the installed Canoga 702 Microloop assembly.

Consult the installation instructions to install the conduit and Canoga 702 Microloop sensors using Canoga 702 Microloop carriers.

3M™ Scotchcast™ 3832 Buried Service Wire Splice Installation Kit is recommended for splicing the lead-in cable with the home-run cable. This wire splice installation kit ensures a reliable connection in the environments encountered by the Canoga 702 Microloop.

Canoga™ 942 or 944 Traffic Monitoring Card for monitoring vehicle speeds, count and occupancy, and for classification of vehicle speeds and lengths.

Canoga™ C922 or C924 Vehicle Detectors for detection of vehicle presence and for traffic count applications.

Canoga™ 30003 Home-run Cable is recommended for all home-runs, especially those exceeding 500 feet.



Canoga™ 702 Non-invasive Microloop™ Sensor Carriers



Canoga™ 702 Non-invasive Microloop™ Sensor Installation Kit

Important Notice to Purchaser:

EXCEPT FOR THE LIMITED WARRANTIES SET FORTH IN THIS DOCUMENT, GLOBAL TRAFFIC TECHNOLOGIES (GTT) MAKES NO OTHER WARRANTIES AND EXPRESSLY DISCLAIMS ALL OTHER WARRANTIES, WHETHER EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY WARRANTY AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE.

GTT will, at its sole option, repair, replace or refund the purchase price of Canoga™ Traffic Sensing System components or Canoga™ Vehicle Detectors described herein found to be defective in materials or manufacture within seven (7) years from the date of shipment from GTT. This warranty shall not apply to Canoga traffic sensing system components or Canoga vehicle detectors which have been (1) repaired or modified

by persons not authorized by GTT; (2) subjected to misuse, neglect or accident; (3) damaged by extreme atmospheric or weather conditions; or (4) subjected to events or use outside the normal or anticipated course.

IN NO EVENT SHALL GTT BE LIABLE FOR ANY INJURY (INCLUDING, WITHOUT LIMITATION, PERSONAL INJURY), DEATH, LOSS, OR DAMAGE (INCLUDING, WITHOUT LIMITATION, PROPERTY DAMAGE), WHETHER DIRECT, INDIRECT, INCIDENTAL, SPECIAL, CONSEQUENTIAL OR OTHERWISE, ARISING OUT OF THE USE OR INABILITY TO USE, REPAIR OR FAILURE TO REPAIR, ANY GTT PRODUCT, REGARDLESS OF THE LEGAL THEORY ASSERTED. THE REMEDIES SET FORTH IN THIS DOCUMENT ARE EXCLUSIVE.



Global Traffic
Technologies

Global Traffic Technologies, LLC
7800 Third Street North
St. Paul, Minnesota 55128-5441
1-800-258-4610

Global Traffic Technologies Canada, Inc.

157 Adelaide Street West
Suite 448
Toronto, ON M5H 4E7
Canada
1-800-258-4610

Canoga and Microloop are trademarks of Global Traffic Technologies, LLC.

3M and Scotchcast are trademarks of 3M.
Used under license in Canada.

All rights reserved. Printed in U.S.A.

© Global Traffic Technologies, LLC 2007

75-0301-3689-1 (A)