TITLE 170 INDIANA UTILITY REGULATORY COMMISSION 170 IAC 4

[STRAWMAN] Proposed Rule LSA Document #24-XXX

DIGEST

Amends 170 IAC 4-4.3 to update definitions, to update performance standards and to incorporate batteries

Effective 30 days after filing with the Publisher.

Effective 30 days after filing with the Publisher.	
Rule 4.3. Customer-Generator Facility Interconnection Standards	Formatted: Strikethrough
170 IAC 4-4.3-1 Definitions	
Authority: IC 8-1-1-3; IC 8-1-2.4	
Affected: IC 8-1-2-1	
Sec. 1. (a) The definitions in this section apply throughout this rule.	
(b) "Area network" means a type of electric distribution system served by multiple transformers interconnected in an	
electrical network circuit that is generally used in large metropolitan areas, which are densely populated, in order to provide high	1
reliability of service. (c) "Commission" means the Indiana utility regulatory commission.	
(d) "Customer-generator facility" means an arrangement of equipment for the production of electricity, including	
batteries, that is owned and operated by:	Formatted: Strikethrough
(1) an eligible customer; or	Formatted: Font: Bold
(2) a third party at the eligible customer's site.	
(c) "Elipible customer" means any:	
(1) person;	
(2) firm;	
(3) corporation;	
(4) municipality; or	
(5) other government agency:	
that has agreed, orally or otherwise, to pay for electric service received from an investor-owned electric utility and is in good	
standing with that utility.	
(f) "Equipment package" means a group of components connecting an electric generator a customer-facility with an	Formatted: Strikethrough
electric distribution system and includes all interface equipment including any of the following:	
(1) Switchgear.	
(2) Inverters.	
(3) Other interface devices.	
The term includes an integrated generator or electric source.	
(g) "Interconnection" or "interconnected" means the physical, parallel connection of a customer-generator facility with	Formatted: Strikethrough
a distribution facility of an investor-owned electric utility.	
(h) "Investor-owned electric utility" or "utility" means a public utility, as defined in IC 8-1-2-1:	
(1) that provides electricity;	
(2) that is financed by the sale of securities; and	
 (3) whose business operations are overseen by a board representing the utility's shareholders. (i) "Nameplate capacity" means the full-load continuous rating of a generator customer-facility -under specified 	
(1) Nameptate capacity means the full-load continuous rating of a generator customer-facility -under specified conditions as designated by the manufacturer.	Formatted: Strikethrough
(j) "Parallel" means the designed operation of the:	
() A many means the designed operation of the.	

(1) customer- generator facility;	Formatted: Strikethrough
(2) interconnection equipment; and	Tomatted. Striketmough
(3) investor-owned electric utility's system;	
where the instantaneous flow of electrical energy may automatically occur in either direction across the interconnection point	
between the customer generator facility and the electrical utility's distribution system.	Formatted: Strikethrough
(k) "Spot network" means a type of electric distribution system that uses two (2) or more intertied transformers to	
supply an electrical network circuit. A spot network is generally used to supply power to a single customer or a small group of customers.	
(1) "System emergency" means a condition on a utility's system reasonably likely to result in any of the following:	
(1) A significant disruption of service to a customer.	
(2) A substantial deviation from a normal service standard.	
(3) An endangerment to life or property.	
(Indiana Utility Regulatory Commission; 170 IAC 4-4.3-1; filed Mar 6, 2006, 9:45 a.m.: 29 IR 2170; readopted filed Jul 12,	
2012, 2:12 p.m.: <u>20120808-IR-170120114RFA</u> ; readopted filed Aug 2, 2013, 2:16 p.m.: <u>20130828-IR-170130227RFA</u> ;	
readopted filed Apr 11, 2019, 9:04 a.m.: <u>20190508-IR-170190136RFA</u>)	
170 IAC 4-4.3-2 Applicability	
Authority: IC 8-1-1-3; IC 8-1-2.4	
Affected: IC 8-1-2	
Sec. 2. This rule shall apply to any investor-owned electric utility, subject to the jurisdiction of the commission, that	
may now or hereafter be engaged in the: (1) production;	
(2) transmission;	
(3) sale; or	
(4) distribution;	
of electric service and all customer-generator facilities that apply for interconnection with such utilities on or after the effective	Formatted: Strikethrough
date of this rule. (Indiana Utility Regulatory Commission; 170 IAC 4-4.3-2; filed Mar 6, 2006, 9:45 a.m.: 29 IR 2171; readopted	
filed Jul 12, 2012, 2:12 p.m.: <u>20120808-IR-170120114RFA</u> ; readopted filed Aug 2, 2013, 2:16 p.m.: <u>20130828-IR-</u>	
<u>170130227RFA;</u> readopted filed Apr 11, 2019, 9:04 a.m.: <u>20190508-IR-170190136RFA</u>)	
170 IAC 4-4.3-3 Exemptions	
Authority: IC 8-1-1-3; IC 8-1-2.4	
Affected: IC 8-1-2	
Sec. 3. (a) Customer-generator-facilities shall be exempt from revenue requirements and associated regulation under <u>IC</u>	Formatted: Strikethrough
<u>8-1-2</u> as administered by the commission, except that the commission shall have authority over rates charged by electric utilities to customer generator facilities.	Formatted: Strikethrough
(b) Upon agreement of an eligible customer and the utility, the customer generator facility interconnection may be	Formatted: Strikethrough
exempt from the requirements of this rule, except for the provisions of section 4(f) and 4(g) of this rule. (<i>Indiana Utility Regulatory Commission; 170 IAC 4-4.3-3; filed Mar 6, 2006, 9:45 a.m.: 29 IR 2171; readopted filed Jul 12, 2012, 2:12 p.m.:</i>	Formatted. Strikethough
20120808-IR-170120114RFA; readopted filed Aug 2, 2013, 2:16 p.m.: 20130828-IR-170130227RFA; readopted filed Apr 11,	
2019.9:04 a.m.: <u>20190508-IR-170190136RFA</u>)	
170 IAC 4-4.3-4 General interconnection provisions	
Authority: <u>IC 8-1-1-3; IC 8-1-2.4</u> Affected: IC 8-1-2	
Antono, <u>100-1-2</u>	
Sec. 4. (a) Each investor-owned electric utility shall provide each of the following three (3) procedures for applications	
for interconnection of customer generator facilities and use:	Formatted: Strikethrough
(1) The Level 1 review procedure described in section 6 of this rule for applications to connect inverter-based customer-generator facilities that:	
customet conclutor natifieds that.	Formatted: Strikethrough

I

I

l

I

|

(A) have a nameplate capacity of ten (10) kilowatts or less; and	
(B) meet the certification requirements of section 5 of this rule.	
(2) The Level 2 review procedure described in section 7 of this rule for applications to connect customer-generator facilities:	Formatted: Strikethrough
(A) with a nameplate capacity of two (2) megawatts or less; and	
(B) that meet the certification requirements of section 5 of this rule.	
(3) The Level 3 review procedure described in section 8 of this rule for applications to connect customer-generator	Formatted: Strikethrough
facilities to its distribution system that do not qualify for either Level 1 or Level 2 interconnection review procedures.	Formatted: Strikethrough
(b) Each utility shall designate a contact person or office from which an eligible customer can obtain basic application	
forms and information through an informal process.	
(c) Each utility shall use commission-approved interconnection application and interconnection agreement forms.	
(d) The utility may require the applicant to include a disconnect switch as a supplement to the equipment package.	
(e) Application and interconnection review fees shall be set as follows:	
(1) A utility shall not charge an application or other fee to an applicant that requests Level 1 interconnection review.	
However, if an application for Level 1 interconnection review is denied because the:	
(A) application does not meet the requirements for Level 1 interconnection review; and	
(B) applicant resubmits the application under another review procedure;	
the utility may impose a fee for the resubmitted application, consistent with this section. (2) For a Level 2 interconnection review, the utility may charge fees up to fifty dollars (\$50) plus one dollar (\$1) per	
kilowatt of the customer-generator facility's nameplate capacity, plus the cost of any minor modifications to the electric	
distribution system or additional review, if required under section 7(q)(3) of this rule. Costs for minor modifications or	Formatted: Strikethrough
additional review shall be:	
(A) based on utility estimates; and	
(B) subject to review by the commission or its designee.	
Costs for engineering work done as part of any additional review shall not exceed one hundred dollars (\$100) per hour.	
(3) For a Level 3 interconnection review, the utility may charge fees up to one hundred dollars (\$100) plus two dollars	
(\$2) per kilowatt of the customer-generator facility's nameplate capacity, as well as charges for actual time spent on any	Formatted: Strikethrough
impact or facilities studies required under section 8 of this rule. Costs for engineering work done as part of any impact	
or facilities study shall not exceed one hundred dollars (\$100) per hour. If the utility must install facilities in order to	
accommodate the interconnection of the customer generator facility, the cost of such facilities shall be the	Formatted: Strikethrough
responsibility of the applicant.	
(f) The interconnection and operation of any customer-generator facility is secondary to and shall not interfere with the	Formatted: Strikethrough
ability of the utility to meet its primary responsibility of furnishing reasonably adequate service to all customers.	
 (g) All the customer generator facility electrical installations shall conform to the following: (1) The requirements of local ordinances and inspection authorities. 	Formatted: Strikethrough
(1) The requirements of local ordinances and inspection autorities. (2) The applicable requirements of this rule.	
(Indiana Utility Regulatory Commission; 170 IAC 4-4.3-4; filed Mar 6, 2006, 9:45 a.m.: 29 IR 2171; readopted filed Jul 12,	
2012, 2:12 p.m.: <u>20120808-IR-170120114RFA</u> ; readopted filed Aug 2, 2013, 2:16 p.m.: <u>20130828-IR-170130227RFA</u> ;	
readopted filed Apr 11, 2019, 9:04 a.m.: 20190508-IR-170190136RFA)	Formatted: Strikethrough
	Formatted: Strikethrough
170 IAC 4-4.3-5 Certification of customer-generator facilities	
Authority: <u>IC 8-1-1-3; IC 8-1-2.4</u>	Formatted: Strikethrough
Affected: IC 8-1-2	Formatted: Font: Bold
	Formatted: Strikethrough
Sec. 5. (a) In order to qualify for the Level 1 and the Level 2 interconnection review procedures described in sections 6 and 7 of this rule, a customer-generator facility must be certified as complying with the following standards, as applicable:	Formatted: Strikethrough
(1) IEEE 1547-2018, Standard for Interconnecting Interconnection and Interoperability of Distributed Energy	Formatted: Strikethrough
Resources with <u>Associated</u> Electric Power Systems <u>Interfaces</u> , as amended and supplemented, which is incorporated	
by reference herein. IEEE 1547-2018 can be obtained through the IEEE at 445 Hoes Lane, P.O. Box 1331, Piscataway, New Jersey 08855 1331 or at www.standards.ieee.org.	Formatted: Strikethrough
 (2) Underwriters Laboratories (UL) Standard 1741: Standards on for Inverters, Converters, and Controllers and 	Formatted: Strikethrough
Interconnection System Equipment for Use in Independent Power Systems with Distributed Energy Resources	Formatted: Strikethrough
(January 2001), as amended and supplemented, which is incorporated by reference herein. UL Standards can be	
	Earmattad: Strikethrough

Formatted: Strikethrough

obtained through Underwriters Laboratories at 333 Pfingelen Road, Northbrook, Illinois 60062-2096 or at www all.com. (b) An equipment package shall be considered certified for interconnection operation if it has been tested and listed by anticularly recognized testing and certification holostory in compliance with subsection (1/1). (c) The equipment package shall be doemoid orthole, and (c) unitipating package shall be doemoid orthole, and (c) unity and certification is been tested and lists: bte- (d) If the equipment package includes only the interface components, an interconnection applicant must show that the generator of units of the interface components, an interconnection applicant must show that the generator of units of the interface components, an interconnection applicant must show that the generator of units of the interface components, an interconnection applicant must show that the generator of units of the company of the interface components, an interconnection specificant on units where the interface of the interface component package. (d) If the equipment package includes only the interface components, an interconnection specificant on units of the issel equipment package. (d) If the equipment package includes only the interface component package is an (d) If according the interface interface interface interface interface interface interface and the interface interface interface and the interface interf		
 We wail com. (b) An equipment package shall be considered earlifed tor interconnection operation if it has been tested and listed by a nationally recognized testing and certification laboratory in compliance with subsection (a/(1)). (c) If the equipment package shall be deemed earlifed; and (c) utility shall not require: (a) further design review; (d) The optipment package shall be deemed earlifed; and (e) The optipment package shall be deemed earlifed; and (f) earling or other design review; (g) The optipment package shall be deemed earlifed; and (g) The optipment package shall be deemed earlifed; and (g) The optipment package shall be deemed earlifed; and (g) The optipment package shall be deemed earlifed; and (g) The optipment package shall be deemed earlifed; and (g) The optipment package shall be deemed earlifed; and (g) The optipment package shall be deemed earlifed; and the components, an interconnection applicant must show that the generative ar absence components, an interconnection applicate testing and certification laboratory, the equipment package is: (f) romatted: Strikethrough (f) comatted: Strikethrough (f) (f) a constrained: Total (f) (f) (f) (f) (f) (f) (f) (f) (f) (f)		
 We wal com. (b) An equipment package shall be considered entified or interconnection operation if it has been tested and listed by a nationally recognized testing and certification laboratory in compliance with subsection (a/1). (c) If the equipment package shall be deemed certified, and (c) utility shall not require: (d) If the equipment package shall be deemed certified, and (e) If the equipment package shall be deemed certified, and (f) equipment package shall be deemed certified, and (g) there design review; (g) Eachdismad certification: (f) for autional certification: (f) for autional certification: (f) for autional certification: (f) for autional certification: (f) compatible with the equipment package: (g) The equipment package shall not require: (h) If the equipment package: (h) If		
 We wal com. (b) An equipment package shall be considered entified or interconnection operation if it has been tested and listed by a nationally recognized testing and certification laboratory in compliance with subsection (a/1). (c) If the equipment package shall be deemed certified, and (c) utility shall not require: (d) If the equipment package shall be deemed certified, and (e) If the equipment package shall be deemed certified, and (f) equipment package shall be deemed certified, and (g) there design review; (g) Eachdismad certification: (f) for autional certification: (f) for autional certification: (f) for autional certification: (f) for autional certification: (f) compatible with the equipment package: (g) The equipment package shall not require: (h) If the equipment package: (h) If		
(b) An equipment package shall be considered certified for interconnection operation if it has been tested and listed by a nationally recognized testing and extinctions agenerated callised by a nationally recognized testing and extinctions. Formatted: Strikethrough (c) If the quipment package shall be deemed certified; and (c) unity shall not require: (c) Strikethrough (d) Strike quipment package includes only the interface components, an interconnection applicant must show that the generative returner facility being unitzed with the quipment package is: Formatted: Strikethrough (e) Units quipment package, includes only the interface components, an interconnection applicant must show that the generative returner facility being unitzed with the quipment package is consistent with the testing and listing performed by the anationally recognized testing and certification laboratory. Formatted: Strikethrough (f) the generator or event events, setting, consistent with the testing and listing performed by the anationally recognized testing and certification laboratory. Formatted: Strikethrough (f) the generator or event events, setting, consistent with the testing and listing performed by the applicance facility being unitized with the quipment package. Inflamo things generative facility shall adopt a Level 1 interconnection review Formatted: Strikethrough (f) the vector or event events with section 5 of this rate. Formatted: Strikethrough Formatted: Strikethrough (g) consistent with the testing and listing bot on another generative facility shall adopt a Level 1 interconnection review procedure. The utility shall adopt a		Formatted: Strikethrough
a nationally recognized exciting and certification laboratory in compliance with subsection (a)(1). (c) If the quipment package shale how benet sted and listed in accordance with fully section as an integrated package that includes a generator or other electric source container. Chilly, the: (c) utility shall not require: (c) (a) further design review; (d) Itsing: or (c) (a) compatible with the equipment package is: (c) (a) further design review; (c) (b) for a conduct design des		
 (c) If the quipment package has been tested and listed in accordance with this section as an integrated package that includes a generator or other electric source (conserver, callity, the: (1) equipment package shall be deemed certified; and (2) utility shall not require. (A) further design review; (B) testing; or (C) additional certification: (I) compatible with the equipment package; includes only the interface components, an interconnection applicant must show that the generator or other electric source contempt. The interface components, an interconnection applicant must show that the generator end testing and listing performed by <u>the a</u> nationally recognized testing and certification liaboratory. (I) compatible with the equipment package; and (2) consistent with the testing and certification liaboratory. (I) compatible with the quipment package; and (2) consistent with the testing and certification liaboratory. (I) compatible with the quipment package; and (2) consistent with the selectric utility shall adors at the consistent with the testing and testing performed by <u>the an atomation</u>. <i>TD</i> AC 44 3-5, <i>Ticle</i> Mer 6, 2005, 9:45 a.m.; 2018/02/27, <i>Trainported filed</i> Apr 11, 2019, 9:04 a.m.; 2019/03/28. <i>He</i>:1701901/04/27, 2019/03/27, 216 p.m.; 2019/03/28. <i>He</i>:1701901/04/27, 2019/03/27, 216 p.m.; 2019/03/28. <i>He</i>:1701901/04/27, 2019/03/28. <i>He</i>:1701901/04/27, 2019/03/27, 216 p.m.; 2019/03/28. <i>He</i>:1701901/04/27, 2019/03/27, 216 p.m.; 2019/03/28. <i>He</i>:1701901/04/27, 2019/03/28. <i>He</i>:1701		
Includes a generator or other electric source customer_facility, the: (1) (equipment package hills be deemed certificit; and (2) utility shall not require: (A) Inther design review; (B) testing; or (C) and there a customer_facility is the quipment package includes only the interface components, an interconnection applicant must show that the generator or other electric source customer_facility with the equipment package; and (C) consistent with the testing and listing performed by the quipment package is consistent with the testing and listing performed by the quipment package is consistent with the testing and listing performed by the quipment package is consistent with the testing and listing performed by the quipment package is consistent with the testing and listing performed by the quipment package is consistent with the testing and listing performed by the quipment package is consistent with the testing and listing performed by the quipment package is consistent with the testing and listing performed by the quipment package. (<i>I</i> and <i>L</i> 2012): 12:16:17:10:11:16:17:17:11:16:17:17:17:17:17:17:17:17:17:17:17:17:17:		
 (i) cquipment package shall be deemed certified; and (2) unlike shall not require: (A) further design review; (B) testing; or (C) a classing and classing of the state deputy methods, and (C) consistent with the scatter source continue of the bits deputy methods, and (C) consistent with the scatter source continue of the bits deputy methods, and the cquipment package is: (D) compatible with the equipment package; and (C) consistent with the scatter source continue of the state deputy methods, and the cquipment package is: (D) compatible with the equipment package; and (C) consistent with the scatter source continue of the state deputy methods, and the cquipment package is: (D) compatible with the equipment package; and (C) consistent with the scatter source continue of the state deputy methods, and the scatter source of the state deputy methods and the scatter source of the state deputy methods and the scatter source of the state deputy methods and the scatter source of the state deputy methods and the scatter source of the state deputy methods and the scatter source of the state deputy methods and the scatter source of the state deputy methods and the scatter source of the state deputy methods and the scatter source of the state deputy methods and the scatter source of the state deputy methods and the scatter source of the state deputy methods and the scatter source of the state deputy methods and the scatter source of the state deputy of the scatter source of the scatter source of the state deputy of the scatter source of the scatter source of the scatter source of the scatter source of the scatter and source of the scatter source of the scatter so		
 (c) utility shall not require: (d) Intrude design review; (e) Desting: or (f) generator of the leader of t		Formatted: Strikethrough
 (A) further design review; (B) testing: or (C) setting: or (C) Setting: or (C) If the equipment package: includes only the interface components, an interconnection applicant must show that the guipment package is: (C) compatible with the equipment package: and (C) constant with the testing and listing performed by <u>the a</u> nationally recognized testing and certification laboratory. (F) compatible with the equipment package: include the application laboratory. (F) the guipment package: indicational controls, with the equipment package is consistent with the testing and listing performed by <u>the a</u> nationally recognized testing and certification alboratory. (F) the equipment package: indicational controls, with the equipment package is consistent with the testing and listing performed by <u>the anational control with the equipment package is consistent with the testing and listing performed by <u>the anational control with the equipment package is consistent with the testing and listing performed by <u>the anational control with the equipment package is consistent with the testing and listing performed by <u>the anational control with the equipment package is consistent with the testing and listing performed by <u>the anational control with the equipment package is consistent with the testing and listing performed by <u>the anational control with section 100 Is (C) II (C) II</u></u></u></u></u></u>		
 (B) lesting: or (C) additional certification; (a) If the equipment package includes only the interface components, an interconnection applicant must show that the generative source customer_Actific being utilized with the equipment package is: (b) or the equipment package; and (C) consistent with the testing and listing performed by the <u>a</u> nationally recognized testing and certification laboratory. If the generator electric owners customer_Actific being utilized with the equipment package is consistent with the testing and listing performed by the <u>a</u> nationally recognized testing and certification laboratory. He equipment package is consistent with the testing and listing performed by the <u>a</u> nationally recognized testing and certification laboratory. He equipment package is consistent with the testing and listing performed by the <u>a</u> nationally recognized testing and certification is the listed equipment package is consistent with the testing and listing performed by the <u>a</u> nationally recognized testing and certification is the listed equipment package is consistent with the testing and listing performed by the <u>a</u> nationally recognized testing and certification is the listed equipment package is consistent with the testing and listing performed by the <u>a</u> nationally recognized testing and certification is the listed equipment package is consistent. To NL 24.4.3.5 (Rec 12.4.1.2.102.1.2.1.2.1.2.1.2.1.2.1.2.1.2.1.2		
(C)2 additional certification; (d) If the equipment package: (a) Of the isade quipment package: (e) Of the isade quipment package: and (c) compatible with the equipment package; and (f) compatible with the equipment package; and (c) compatible with the equipment package; and (f) compatible with the equipment package; and (c) consistent with the testing and listing performed by the antionally recognized testing and certification laboratory. formatted: Strikethrough If the generator of electric source customer_facility being utilized with the equipment package is consistent with the testing and certification laboratory. formatted: Strikethrough Isting performed by the antionally recognized testing and certification laboratory. formatted: Strikethrough If the sequeption of the state quipment package is consistent with the testing and certification laboratory. formatted: Strikethrough If the sequeption of the state quipment package is consistent with the testing and certification aboratory. formatted: Strikethrough If the sequeption of the state quipment package is consistent with the testing and striket. formatted: Strikethrough If the sequeption of the striket quipment package is consistent with the section anneal package. formatted: Strikethrough If the sequeption of the striket quipment package is consistent with the section anneal pack application to interconnection review procedure. The utility shall formatted: Strikethrough <		
 of the fixed equipment package includes only the interface components, an interconnection applicant must show that the generator or other description package includes only the interface components, an interconnection applicant must show that the generator or other description sources customer_Actility being utilized with the equipment package is and (1) consistent with the testing and listing performed by <u>the a</u> nationally recognized testing and certification laboratory. If the generator customer_Actility being utilized with the equipment package is consistent with the testing and listing performed by <u>the a</u> nationally recognized testing and certification laboratory. He equipment package is consistent with the testing and listing performed by <u>the a</u> nationally recognized testing and certification is the listed equipment package is consistent with the testing and listing performed by <u>the a</u> nationally recognized testing and certification is the listed equipment package is consistent. <i>TO IMC 4-13-5</i>, <i>Tiled Mar 6, 2006, 9-45 a.m.; 2018 2172; readopted filed Jul 12, 2012, 221 m; 2013/08/28/18/17012014/18/47; readopted filed Agr 1, 2019, 9-04 a.m.; 2019/08/28/18/17012014/18/47; readopted filed Agr 2, 2013, 2:16 p.m.; 2013/08/28/18/17013/01/18/47; readopted filed Agr 1, 2019, 9-04 a.m.; 2019/08/28/18/17012014/18/47; readopted filed Agr 1, 2019, 9:04 a.m.; 2019/08/28/18/17012014/18/47; readopted filed Agr 1, 2019, 9:04 a.m.; 2019/08/28/18/17012014/18/47; readopted filed Agr 1, 2019/08/28/18/17013/01/18/47; readopted filed Agr 1, 2019/08/28/18/17012014/18/47; readopted filed Agr 2, 2013, 2:16 p.m.; 2013/08/28/18/17013/02/27/87/45;</i> (2) In a customer generator facility is to be incroanted exceed to percent (0%) to the size of the percent 		
 (d) If the equipment package includes only the interface components, an interconnection applicant must show that the generator continuer electric-aware customer_facility being utilized with the equipment package is: (a) compatible with the equipment package is: (b) compatible with the equipment package is: (c) consistent with the testing and itsing performed by the antionally recognized testing and certification laboratory. (f) the guipment package is: (f) the utility shall not require further design review, testing, or additional certification of the listed equipment package. (f) that 2, 2012, 21, pm.: 20120804. Its: 1700.01 (2014), 2, 2013, 2; 16 pm.: 20140023. Its: 1700.00227 Its: 120140023. Its: 1700.00227 Its: 120140000000000000000000000000000000000		
generator or other electric source customer_facility being utilized with the equipment package is: Formatted: Strikethrough (1) consistent with the testing and listing performed by <u>be a</u> nationally recognized testing and certification laboratory. Formatted: Strikethrough (1) the generator or electric source customer_facility being utilized with the equipment package is consistent with the testing and listing performed by <u>be a</u> nationally recognized testing and certification of the listed equipment package is consistent with the testing and listing performated by <u>be a</u> nationally recognized testing and certification of the listed equipment package is consistent with the testing and listing performated by <u>be a</u> nationally recognized testing and certification of the listed equipment package is consistent with the testing and listing performated by <u>be a</u> nationally recognized testing and certification of the listed equipment package is consistent with the testing and listing performated is the constance with the testing and listing performated is the constance with the design review, testing or additional certification of the listed equipment package is consistent with the testing and listing performated is the sector. (1) DIAC 4-4.3-6 Level 1 interconnection review Authority: IC 54-1-23 Sec. 6. (a) Each investor-owned electric utility shall adopt a Level 1 interconnection review procedure for an application to interconnect a customer <u>generator facility</u> with sections 10 (b) kilowatts or less; and Formatted: Strikethrough (1) bis a nameplate capacity of ten (10) kilowatts or less; and (3) is cerification and perfected authorized under this section. Formatted: Strikethrough (2) If a customer		
 (1) compatible with the equipment package; and (2) consistent with the testing and listing performed by <u>the a</u> nationally recognized testing and certification laboratory. (1) compatible with the testing and listing performed by <u>the a</u> nationally recognized testing and certification laboratory. (1) compatible with the testing and listing performed by <u>the a</u> nationally recognized testing and certification laboratory. (1) compatible with the testing and listing performed by <u>the a</u> nationally recognized testing and certification laboratory. The equipment package is consistent with the testing and listing performed by <u>the a</u> nationally recognized testing and certification laboratory. (1) Constitute: Junt2000000000000000000000000000000000000		
 (2) consistent with the testing and listing performed by the <u>a</u> nationally recognized using and certification laboratory. If the <u>generator electric source customer - Actually</u> is consistent with the testing and listing performed by <u>the a</u> nationally recognized testing and certification laboratory. the cupiment package shall be deemed listing performed by <u>the a</u> nationally recognized testing and certification laboratory. the cupiment package shall be deemed listing performed by <u>the a</u> nationally recognized testing and certification laboratory. The cupiment package shall be deemed listing performed by <u>the a</u> nationally recognized testing and certification laboratory. The cupiment package shall be deemed listing performed by <u>the a</u> nationally recognized testing and certification is the sized equipment lockage shall be deemed listing performed by <u>the a</u> nationally recognized testing and certification is the sized equipment lockage shall be deemed listing performed by <u>the a</u> nationally recognized listing performed by <u>the a</u> national received listing performed by <u>the a</u> national received method listing the recogned of the (10) kilowatts or less; and (2) is nertified in a nacondance with section 5 of this rule. (b) For a customer generator facility described in usbection (a), the utility shall approve interconnection under the Level 1 review if all of the applicable requirements in subsection (b) (b) are net. A utility shall not impose additional requirements in subsection (c) (b) are match as generator facility (c) shall not exc		Formatted: Strikethrough
If the generator or electric source customer_facility being utilized with the equipment package is consistent with the testing and listing performed by the a nationally recognized testing and certification laboratory, the equipment package shall be deemed certified, and the utility shall not require further design review, testing, or additional certification of the listed equipment package. (Indiana Utility Regulatory: Commission: 170 IAC 4-4.3-5; filed Mar 6, 2006, 9-45 a.m.: 2018 2172; readopted filed Jul 12, 2012, 2:12 p.m.: 20120008-IR-1701014REA: readopted filed May 2, 2013, 2:16 p.m.: 20130824:IR-170130227REA; readopted filed Apr 11, 2019, 9:04 a.m.: 20190508-IR-170193056REA) 170 IAC 4-4.3-6 Level 1 interconnection review Authority: IC 8-1-13; IC 8-1-24 Affected: IC 8-1-2 Sec. 6. (a) Each investor-owned electric utility shall adopt a Level 1 interconnection review procedure. The utility shall use the Level 1 review procedure for an application to interconnect a customer generator-facility that: (1) is inverter-based; (2) has a nameplate capacity of ten (10) kilowatts or less; and (3) is certified in accordance with section. (c) though (h) are met. A utility shall approve interconnection under the Level 1 review if all of the applicable requirements in subsection. (a) the utility shall approve interconnection under the Level 1 review reactore. with section. (c) If a customer generator facility to be connected to a radial distribution circuit. the aggregate generation nameplate capacity, shall not exceed the percent (5%) of the circuit annual peak load as most recently measured are substation; the aggregate generation nameplate capacity, shall not exceed the percent (10%) of the circuit 5 maximum fault current at the point on which the primary level that is nearest the proposed point of common coupling. (c) If a customer generator facility is to be interconnected on a center ta neutral of a two hander forty (20) VM service, the addition of the usstorer generator facility shall not create an imbalance betw		
 listing performed by <u>the a</u> nationally recognized testing and certification laboratory, the equipment package. (Indiana Utility Regulatory Commission; 170 IAC 4-4.3-5; filed Mar 6, 2006, 9-45 a.m.: 29 IR 2172; readopted filed that proceeding of the utility shall on trequire further design review, testing, or additional certification of the listed equipment package. (Indiana Utility Regulatory Commission; 170 IAC 4-4.3-5; filed Mar 6, 2006, 9-45 a.m.: 29 IR 2172; readopted filed Apr 11, 2019, 2019, 2014 a.m.: 2019088-IR: 1701901368FA. 170 IAC 4-4.3-6 Level 1 interconnection review Authority: IC 8-1-2.4 Affected: IC 8-1-2 Sec. 6, (a) Each investor-owned electric utility shall adopt a Level 1 interconnection review procedure. The utility shall use the Level 1 review procedure for an application to interconnect a customer generator-facility that: (1) is inverter-based; (2) has a nameplate capacity of the (10) kilowatts or less; and (3) is certified in accordance with sections (c) though (h) are met. A utility shall not impose additional requirements in subsections. (c) though (h) are met. A utility shall not impose additional requirements in subsections. (c) though (h) are met. A utility shall not impose additional requirements in subsections. (c) though (h) are met. A utility shall not impose additional entiple expacity connected to a line applicable requirement in subsections. (c) the argengate generation nameplate capacity onnected to a simst recently measured at the substation. (a) The augregate generation nameplate capacity, shall not exceed the percent (10%) of the circuit smaximum fault current at be point on which the prinary level that is nacest the proposed point of common coupling. (b) If a customer generator-facility is to be interconnected on a center tap neutral of at two hundred forty (240) volt service merator facility point of		Formatted: Strikethrough
Formatted: Strikethrough <td></td> <td>Exemption Striketbrough</td>		Exemption Striketbrough
 package. (Indiana Uritity Regulatory): Commission: 170 IAC 4-4.3-5; filed Mar 6, 2006, 9:45 a.m.: 29 IR 2172; readopted filed Jul 12, 2012, 2:12 p.m.: 20120828: IR-170120114REA; readopted filed Aug 2, 2013, 2:16 p.m.: 20130828-IR-170130227REA; readopted filed Apr 11, 2019, 9:04 a.m.: 20100508-IR-170190130REA TO IAC 4-4.3-6 Level 1 interconnection review Authority: IC 8-1-1-3; IC 8-1-2.4 Affected: IC 8-1-2 Sec. 6. (a) Each investor-owned electric utility shall adopt a Level 1 interconnection review procedure. The utility shall use the Level 1 review procedure for an application to interconnect a customer generator-facility that: (1) is inverter-based; (2) has a nameplate capacity of the (10) kilowatts or less; and (3) is certified in accordance with section 5 of this rule. (b) For a customer generator-facility described in subsection (a), the utility shall approve interconnection under the Level 1 review if all of the applicable requirements in subsections (c) though (h) are met. A utility shall not impose additional requirements not specifically authorized under this section. (c) If a customer generator-facility is to be connected to a radial distribution circuit, the aggregate generation nameplate capacity, shall not exceed five percent (5%) of the circuit annual peak load as most recently measured or stimated based on the most recently measured or stimated based on the most recently measured accordary, including the proposed nameplate capacity, shall not exceed five percent (5%) of the circuit smainum faek load as most recently measured accordary including the approaced point of common coupling. (e) If a customer generator-facility is to be connected to a nine generation nameplate capacity connected to the shard secondary, including the proposed point of common coupling. (f) If a customer generator-facility is to be co		Formatted. Striketinough
<i>Jul 12, 2012, 2:12 p.m: 20120808-IR-170120114RFA; readopted filed Aug 2, 2013, 2:16 p.m.: 20130828-IR-170130227RFA; readopted filed Apr 11, 2019, 9:04 a.m.: 20190508-IR-170190136RFA)</i> 170 IAC 4-4.3-6 Level 1 interconnection review Authority: IC 8-1-3; IC 8-1-2, Sec. 6. (a) Each investor-owned electric utility shall adopt a Level 1 interconnection review procedure. The utility shall use the Level 1 review procedure for an application to interconnect a customer-generator-facility that: (1) is inverter-based; (2) has a nameplate capacity of ten (10) kilowatts or less; and (3) is certified in accordance with section 5 of this rule. (b) For a customer-generator-facility described in subsection (a), the utility shall approve interconnection under the Level 1 review if all of the applicable requirements in subsections (c) though (h) are met. A utility shall not impose additional requirements not specifically undhorized under this section. (c) If a customer-generator-facility is to be connected to a criticuit, including the proposed nameplate capacity, shall not exceed five percent (5%) of the circuit amutal peak load as most recently measured at the substation; the aggregate generation nameplate capacity, shall not exceed five percent (10%) of the line section annual peak load as most recently measured or ethore than ten percent (10%) of the intervent facility will interconnect, including its nameplate capacity, shall not exceed the substation: (d) The aggregate generation nameplate capacity, shall not exceed the substation. (e) If a customer-generator-facility is to be connected to a single-phase shared secondary, the aggregate ageneration facility will interconnect including its nameplate capacity, shall not exceed the assert of twenty (20) kVA or the nameplate capacity sonnel cubit with the customer-generator-facility is to be interconnected on a nemplate capacity on the distribution circuit to assimute based to the shared secondary, hild proposed nameplate capacity, shall not exceed the lesser of twenty (20) kV		Formatted: Strikethrough
readopted filed Apr 11, 2019, 9:04 a.m.: 20190508-IR-170190136RFA) 170 IAC 4-4.3-6 Level 1 interconnection review Authority: [C 8-1-1-3; [C 8-1-24 Affectet: [C 8-1-2] Sec. 6. (a) Each investor-owned electric utility shall adopt a Level 1 interconnection review procedure. The utility shall use the Level 1 review procedure for an application to interconnect a customer generator facility that: (1) is inverter-based; (2) has a nameplate capacity of ten (10) kilowatts or less; and (3) is certified in accordance with section 5 of this rule. (b) For a customer generator facility described in subsection (a), the utility shall approve interconnection under the Level 1 review if all of the applicable requirements in subsection (a), the utility shall not impose additional requirements not specifically authorized under this section. (c) If a customer generator facility is to be connected to a radial distribution circuit, the aggregate generation nameplate capacity connected to the circuit, including the proposed nameplate capacity, shall not exceed five percent (5%) of the circuit annual peak load as most recently measured or estimated based on the most recently measured or estimated based contexp, including the proposed nameplate capacity, shall not contribute more than ten percent (10%) to the circuit's maximum fall current at the point on which the primary level that is nearest the proposed nameplate capacity, shall not exceed fite verse transformer. (f) If a customer generator facility is to be connected to a single-phase shared secondary, the aggregate generation maneplate capacity connected to the shared secondary, including the p	package. (Indiana Utility Regulatory Commission; 170 IAC 4-4.3-5; filed Mar 6, 2006, 9:45 a.m.: 29 IR 2172; readopted filed	
170 LAC 44.3-6 Level 1 interconnection review Authority: [C.8-1-3; [C.8-1-2] See, 6. (a) Each investor-owned electric utility shall adopt a Level 1 interconnection review procedure. The utility shall use the Level 1 review procedure for an application to interconnect a customer generator facility that: (1) is inverter-based; (2) has a nameplate capacity of ten (10) kilowatts or less; and (3) is certified in accordance with section 5 of this rule. (b) For a customer generator facility described in subsection (a), the utility shall approve interconnection under the Level 1 review if all of the applicable requirements in subsections (c) though (h) are met. A utility shall not impose additional requirements not specifically authorized under this section. (c) If a customer generator facility is to be connected to a radial distribution circuit, the aggregate generation nameplate capacity, shall not exceed fine percent (10%) of the section annual peak load as most recently measured or espacity, shall not exceed in percent (10%) of the section family is nomeplate capacity, shall not contribute more than the percent (10%) of the customer generator facility is to be connected to a single-phase shared secondary, the aggregate generation nameplate capacity connected to the shared secondary, the aggregate generation nameplate capacity, shall not exceed the percent (10%) of the accounter generator facility is to be connected to a single-phase shared secondary, the aggregate generation nameplate capacity connected to the shared secondary, the aggregate generation nameplate capacity, shall not exceed the percent (10%) of the accounter generatore facility with interconnected to the shared secondar		
Authority: <u>IC 8-1-1.3</u> ; <u>IC 8-1-2.4</u> Affected: <u>IC 8-1-2</u> Sec. 6. (a) Each investor-owned electric utility shall adopt a Level 1 interconnection review procedure. The utility shall use the Level 1 review procedure for an application to interconnect a customer-generator-facility that: (1) is inverter-based; (2) has a nameplate capacity of ten (10) kilowatts or less; and (3) is certified in accordance with section 5 of this rule. (b) For a customer-generator-facility described in subsection (a), the utility shall approve interconnection under the Level 1 review if all of the applicable requirements in subsections (c) though (h) are met. A utility shall not impose additional requirements not specifically authorized under this section. (c) If a customer-generator-facility is to be connected to a radial distribution circuit, the aggregate generation nameplate capacity connected to the circuit, including the proposed nameplate capacity, shall not exceed five percent (5%) of the circuit's maximum fauntal peak load as most recently measured at the substation; the aggregate generation nameplate capacity on the distribution circuit to which the customer-generator-facility will interconnect, including its nameplate capacity, shall not exceed ten percent (10%) of the line section annual peak load as most recently measured or the most recently measured circuit load at the substation. (d) The aggregate generation nameplate capacity, shall not contribute more than ten percent (10%) to the circuit's maximum fault current at the point on which the primary level that is nearest the proposed nameplate capacity, shall not exceed the lesser of twenty (20) kVA or the nameplate rating of the service transformer. (f) If a single-phase shared secondary, including the proposed nameplate capacity, shall not exceed the lesser of twenty (20) kVA or the nameplate capacity is to be interconnected on a center tap neutral of a two hundred forty (240) volt service more than twenty percent (20%) of the nameplate rating of th	readopted filed Apr 11, 2019, 9:04 a.m.: <u>20190508-IR-170190136RFA</u>)	
Authority: <u>IC 8-1-1.3</u> ; <u>IC 8-1-2.4</u> Affected: <u>IC 8-1-2</u> Sec. 6. (a) Each investor-owned electric utility shall adopt a Level 1 interconnection review procedure. The utility shall use the Level 1 review procedure for an application to interconnect a customer-generator-facility that: (1) is inverter-based; (2) has a nameplate capacity of ten (10) kilowatts or less; and (3) is certified in accordance with section 5 of this rule. (b) For a customer-generator-facility described in subsection (a), the utility shall approve interconnection under the Level 1 review if all of the applicable requirements in subsections (c) though (h) are met. A utility shall not impose additional requirements not specifically authorized under this section. (c) If a customer-generator-facility is to be connected to a radial distribution circuit, the aggregate generation nameplate capacity connected to the circuit, including the proposed nameplate capacity, shall not exceed five percent (5%) of the circuit's maximum fauntal peak load as most recently measured at the substation; the aggregate generation nameplate capacity on the distribution circuit to which the customer-generator-facility will interconnect, including its nameplate capacity, shall not exceed ten percent (10%) of the line section annual peak load as most recently measured or the most recently measured circuit load at the substation. (d) The aggregate generation nameplate capacity, shall not contribute more than ten percent (10%) to the circuit's maximum fault current at the point on which the primary level that is nearest the proposed nameplate capacity, shall not exceed the lesser of twenty (20) kVA or the nameplate rating of the service transformer. (f) If a single-phase shared secondary, including the proposed nameplate capacity, shall not exceed the lesser of twenty (20) kVA or the nameplate capacity is to be interconnected on a center tap neutral of a two hundred forty (240) volt service more than twenty percent (20%) of the nameplate rating of th		
Affected: <u>IC 8-1-2</u> Sec. 6. (a) Each investor-owned electric utility shall adopt a Level 1 interconnection review procedure. The utility shall use the Level 1 review procedure for an application to interconnect a customer <u>generator</u> facility that: (1) is inverter-based; (2) has a nameplate capacity of ten (10) kilowatts or less; and (3) is certified in accordance with section 5 of this rule. (b) For a customer <u>generator</u> facility is to be connected to a radial distribution circuit, the aggregate generation nameplate capacity connected to the applicable requirements in subsections (c) though (h) are met. A utility shall not impose additional requirements not specifically authorized under this section. (c) If a customer <u>generator</u> facility is to be connected to a radial distribution circuit, the aggregate generation nameplate capacity connected to the circuit, including the proposed nameplate capacity, shall not exceed five percent (5%) of the circuit annual peak load as most recently measured at the substation; the aggregate generation nameplate capacity, shall not crcue than ten percent (10%) of the line section annual peak load as most recently measured or estimated based on the most recently measured circuit load at the substation. (d) The aggregate generation nameplate capacity, shall not corribut more than ten percent (10%) to the circuit's maximum fault current at the point on which the primary level that is nearest the proposed point of common coupling. (e) If a customer <u>generator</u> facility is to be interconnected on a center tap neutral of a two hundred forty (240) volt service more than twenty percent (20%) of the nameplate capacity, shall not create an imbalance between the two (2) sides of the two hundred forty (240) volt service more than twenty percent (20%) of the nameplate rapacity of the customer <u>generator</u> facility is to be interconnected on a center tap neutral of a two hundred forty (240) volt service, he addition of the customer <u>generator</u> facility sind not create an		
Sec. 6. (a) Each investor-owned electric utility shall adopt a Level 1 interconnection review procedure. The utility shall use the Level 1 review procedure for an application to interconnect a customer <u>generator</u> facility that: (1) is inverter-based; (2) has a nameplate capacity of ten (10) kilowatts or less; and (3) is certified in accordance with section 5 of this rule. (b) For a customer <u>generator</u> facility described in subsections (a), the utility shall approve interconnection under the Level 1 review if all of the applicable requirements in subsections (c) though (h) are met. A utility shall not impose additional requirements not specifically authorized under this section. (c) If a customer <u>generator</u> facility is to be connected to a radial distribution circuit, the aggregate generation nameplate capacity connected to the circuit, including the proposed nameplate capacity, shall not exceed five percent (5%) of the circuit annual peak load as most recently measured at the substation, the distribution circuit to which the customer <u>generator</u> facility will interconnect, including its nameplate capacity, shall not contribute more than ten percent (10%) of the circuit's maximum fault current at the point on which the primary level that is nearest the proposed nameplate capacity, shall not exceed the lesser of twenty (20) kVA or the nameplate rating of the service transformer. (c) If a single-phase customer <u>generator</u> facility is to be interconnected to a single-phase shared secondary, the aggregate generation nameplate capacity connected to the shared secondary, including the proposed nameplate capacity, shall not exceed the lesser of twenty (20) kVA or the nameplate rating of the service transformer. (c) If a single-phase customer <u>generator</u> facility is that is nearest the proposed nameplate capacity, shall not exceed the lesser of twenty (20) kVA or the nameplate rating of the service transformer. (c) If a single-phase customer <u>generator</u> facility is that in orce ate an imbalance between the two (2) si		
use the Level 1 review procedure for an application to interconnect a customer generator facility that: (1) is inverter-based; (2) has a nameplate capacity of ten (10) kilowatts or less; and (3) is certified in accordance with section 5 of this rule. (b) For a customer generator facility described in subsection (a), the utility shall approve interconnection under the Level 1 review if all of the applicable requirements in subsections (c) though (h) are met. A utility shall not impose additional requirements not specifically authorized under this section. (c) If a customer generator facility is to be connected to a radial distribution circuit, the aggregate generation nameplate capacity, shall not exceed the percent (10%) of the line section annual peak load as most recently measured at the substation; the aggregate generation nameplate capacity onnected to the shared secondary, including the proposed nameplate capacity on the distribution circuit to which the customer generator facility is to be connected to a single-phase shared secondary, the aggregate generation nameplate capacity connected to the shared secondary, including the proposed nameplate rains of the service transformer. (b) If a customer generator facility is to be connected to a single-phase shared secondary, the aggregate generation nameplate capacity connected to the shared secondary, including the proposed nameplate rains of the service transformer. (c) If a single-phase customer generator facility is to be interconnected on a center tap neutral of a two hundred forty (240) volt service more than twenty percent (20%) of the nameplate raining of the service transformer. (g) The customer generator facility point of common coupling shall not exceed the service transformer. (g) The customer facility point of common coupling shall not be on: 	Affected: <u>IC 8-1-2</u>	
use the Level 1 review procedure for an application to interconnect a customer generator facility that: (1) is inverter-based; (2) has a nameplate capacity of ten (10) kilowatts or less; and (3) is certified in accordance with section 5 of this rule. (b) For a customer generator facility described in subsection (a), the utility shall approve interconnection under the Level 1 review if all of the applicable requirements in subsections (c) though (h) are met. A utility shall not impose additional requirements not specifically authorized under this section. (c) If a customer generator facility is to be connected to a radial distribution circuit, the aggregate generation nameplate capacity, shall not exceed the percent (10%) of the line section annual peak load as most recently measured at the substation; the aggregate generation dameplate capacity, shall not exceed the percent (10%) of the line section annual peak load as most recently measured capacity on the distribution circuit to which the customer generator facility is to be connected to a single-phase shared secondary, the aggregate generation nameplate capacity connected to the shared secondary, including the proposed nameplate rapacity, shall not common coupling. (e) If a customer generator facility is to be connected to a single-phase shared secondary, the aggregate generation nameplate capacity connected to the shared secondary, including the proposed nameplate rapacity, shall not exceed the applicable capacity connected to the shared secondary, including the proposed nameplate rapacity is to be interconnected on a center tap neutral of a two hundred forty (c) If a single-phase customer generator facility is to be interconnected on a center tap neutral of a two hundred forty (240) volt service more than twenty percent (20%) of the mameplate rapacity, shall not create an imbalance between the two (2) sides of the two hundred forty (240) volt service more than twenty pe		
 (1) is inverter-based; (2) has a nameplate capacity of ten (10) kilowatts or less; and (3) is certified in accordance with section 5 of this rule. (b) For a customer-generator-facility described in subsection (a), the utility shall approve interconnection under the Level 1 review if all of the applicable requirements in subsections (c) though (h) are met. A utility shall not impose additional requirements not specifically authorized under this section. (c) If a customer-generator-facility is to be connected to a radial distribution circuit, the aggregate generation nameplate capacity connected to the circuit, including the proposed nameplate capacity, shall not exceed the percent (10%) of the line section annual peak load as most recently measured at the substation; the aggregate generation nameplate capacity, shall not exceed the nearce transformer facility is to be connected to a single-phase shared secondary, the aggregate generation nameplate capacity connected to the shared secondary, including the proposed nameplate capacity, shall not create an imbalance between the two (2) sides of the formatted: Strikethrough Formatted: Strikethrough Format		
 (2) has a nameplate capacity of ten (10) kilowatts or less; and (3) is certified in accordance with section 5 of this rule. (b) For a customer-generator-facility described in subsection (a), the utility shall approve interconnection under the Level 1 review if all of the applicable requirements in subsections (c) though (h) are met. A utility shall not impose additional requirements not specifically authorized under this section. (c) If a customer-generator-facility is to be connected to a radial distribution circuit, the aggregate generation nameplate capacity connected to the circuit, including the proposed nameplate capacity, shall not exceed five percent (5%) of the circuit annual peak load as most recently measured at the substation; the aggregate generation nameplate capacity connected to a fire percent (10%) of the line section annual peak load as most recently measured circuit load at the substation. (d) The aggregate generation nameplate capacity, shall not exceed the percent (10%) of the circuit's maximum fault current at the point on which the primary level that is nearest the proposed point of common coupling. (e) If a customer-generator-facility is to be connected to a single-phase shared secondary, the aggregate generation nameplate capacity connected to the shared secondary, including the proposed nameplate rating of the service transformer. (f) If a single-phase customer-generator-facility is to be interconnected on a center tap neutral of a two hundred forty (200) volt service, the addition of the customer-generator-facility is to be interconnected on a center tap neutral of a two hundred forty (200) volt service, the addition of the customer-generator-facility is all not create an imbalance between the two (2) sides of the two hundred forty (200) volt service, the addition of the customer-generator-facility shall not create an imbalance between the two (2) sides of the forty (240) volt service more than tempepater tating o		Formatted: Strikethrough
 (3) is certified in accordance with section 5 of this rule. (b) For a customer <u>generator</u> facility described in subsection (a), the utility shall approve interconnection under the applicable requirements in subsections (c) though (h) are met. A utility shall not impose additional requirements not specifically authorized under this section. (c) If a customer <u>generator</u> facility is to be connected to a radial distribution circuit, the aggregate generation nameplate capacity connected to the circuit, including the proposed nameplate capacity, shall not exceed five percent (5%) of the circuit annual peak load as most recently measured at the substation; the aggregate generation nameplate capacity connected to a line section, including its nameplate capacity, shall not cortribute more than ten percent (10%) to the circuit's maximum fault current at the point on which the primary level that is nearest the proposed nameplate capacity, shall not cortribute more than ten percent (10%) to the circuit's maximum fault current at the point on which the primary level that is nearest the proposed nameplate capacity, shall not cortribute more than ten percent (10%) to the circuit's maximum fault current at the point on which the primary level that is nearest the proposed point of common coupling. (c) If a customer <u>generator</u> facility is to be connected to a single-phase shared secondary, the aggregate generation nameplate capacity connected to the shared secondary, including the proposed nameplate capacity, shall not exceed the lesser of twenty (20) kVA or the nameplate rating of the service transformer. (f) If a single-phase customer <u>generator</u> facility shall not create an imbalance between the two (2) sides of the two hundred forty (240) volt service, the addition of the customer <u>generator</u> facility shall not cortribute an imbalance between the two (2) sides of the two hundred forty (240) volt service than then the percent (20%) of the nameplate rating of the service transfor		
 (b) For a customer generator facility described in subsection (a), the utility shall approve interconnection under the Level 1 review if all of the applicable requirements in subsections (c) though (h) are met. A utility shall not impose additional requirements not specifically authorized under this section. (c) If a customer generator facility is to be connected to a radial distribution circuit, the aggregate generation nameplate capacity connected to the circuit, including the proposed nameplate capacity, shall not exceed five percent (5%) of the circuit annual peak load as most recently measured at the substation; the aggregate generation nameplate capacity connected to a memplate capacity, shall not exceed the percent (10%) of the line section annual peak load as most recently measured or estimated based on the most recently measured circuit load at the substation. (d) The aggregate generation nameplate capacity, shall not contribute more than ten percent (10%) to the circuit's maximum fault current at the point on which the primary level that is nearest the proposed point of common coupling. (e) If a customer generator facility is to be connected to a single-phase shared secondary, the aggregate generation nameplate capacity connected to the shared secondary, including the proposed nameplate capacity, shall not exceed the lesser of twenty (20) kVA or the nameplate rating of the service transformer. (f) If a single-phase customer generator facility is to be interconnected on a center tap neutral of a two hundred forty (240) volt service, the addition of the customer generator facility is to be interconnected on a center tap neutral of a two hundred forty (240) volt service more than twenty percent (20%) of the nameplate rating of the service transformer. (g) The customer generator facility point of common coupling shall not be on: 		
Level 1 review if all of the applicable requirements in subsections (c) though (h) are met. A utility shall not impose additional requirements not specifically authorized under this section. (c) If a customer generator facility is to be connected to a radial distribution circuit, the aggregate generation nameplate capacity connected to the circuit, including the proposed nameplate capacity, shall not exceed five percent (5%) of the circuit annual peak load as most recently measured at the substation; the aggregate generation nameplate capacity connected to a line section, including the proposed nameplate capacity on the distribution circuit load at the substation. (d) The aggregate generation nameplate capacity, shall not exceed the percent (10%) of the line section annual peak load as most recently measured circuit load at the substation. (d) The aggregate generation nameplate capacity, shall not cortribute more than the preme than the preme than the primary level that is nearest the proposed point of common coupling. (e) If a customer generator facility is to be connected to a single-phase shared secondary, the aggregate generation nameplate capacity connected to the shared secondary, including the proposed nameplate capacity, shall not exceed the lesser of twenty (20) kVA or the nameplate rating of the service transformer. (f) If a single-phase customer generator facility is to be interconnected on a center tap neutral of a two hundred forty (240) volt service more than twenty percent (20%) of the nameplate rating of the service transformer. (g) The customer generator facility point of common coupling shall not be on:		
requirements not specifically authorized under this section. (c) If a customer-generator-facility is to be connected to a radial distribution circuit, the aggregate generation nameplate capacity connected to the circuit, including the proposed nameplate capacity, shall not exceed five percent (5%) of the circuit annual peak load as most recently measured at the substation; the aggregate generation nameplate capacity connected to a line section, including the proposed nameplate capacity, shall not exceed the percent (10%) of the line section annual peak load as most recently measured or estimated based on the most recently measured circuit load at the substation. (d) The aggregate generation nameplate capacity, shall not contribute more than ten percent (10%) to the circuit's maximum fault current at the point on which the primary level that is nearest the proposed nameplate capacity, shall not contribute more than ten percent (10%) to the circuit's maximum fault current at the point on which the primary level that is nearest the proposed nameplate capacity, shall not contribute more than ten percent (10%) to the circuit's maximum fault current at the point on which the primary level that is nearest the proposed nameplate capacity, shall not exceed the lesser of twenty (20) kVA or the nameplate rating of the service transformer. (f) If a single-phase customer-generator-facility is to be connected on a center tap neutral of a two hundred forty (240) volt service, the addition of the customer-generator-facility shall not create an imbalance between the two (2) sides of the two hundred forty (240) volt service more than twenty percent (20%) of the nameplate rating of the service transformer. (g) The customer-generator-facility point of common coupling shall not be on:		Formatted: Strikethrough
 (c) If a customer generator facility is to be connected to a radial distribution circuit, the aggregate generation nameplate capacity connected to the circuit annual peak load as most recently measured at the substation; the aggregate generation nameplate capacity connected to a line section, including the proposed nameplate capacity, shall not exceed the percent (10%) of the line section annual peak load as most recently measured on the most recently measured circuit to which the new substation. (d) The aggregate generation nameplate capacity, shall not contribute more than ten percent (10%) to the circuit's maximum fault current at the point on which the primary level that is nearest the proposed point of common coupling. (e) If a customer generator facility is to be connected to a single-phase shared secondary, the aggregate generation nameplate capacity connected to the shared secondary, including the proposed nameplate capacity, shall not create an imbalance between the two (2) sides of the two hundred forty (240) volt service more than twenty percent (20%) of the nameplate rating of the service transformer. (g) The customer generator facility point of common coupling shall not be on: 		
capacity connected to the circuit, including the proposed nameplate capacity, shall not exceed five percent (5%) of the circuit annual peak load as most recently measured at the substation; the aggregate generation nameplate capacity connected to a line section, including the proposed nameplate capacity, shall not exceed ten percent (10%) of the line section annual peak load as most recently measured or estimated based on the most recently measured circuit load at the substation. (d) The aggregate generation nameplate capacity, shall not contribute more than ten percent (10%) to the circuit's maximum fault current at the point on which the primary level that is nearest the proposed point of common coupling. (e) If a customer generator facility is to be connected to a single-phase shared secondary, the aggregate generation nameplate capacity connected to the shared secondary, including the proposed nameplate capacity, shall not exceed the lesser of twenty (20) kVA or the nameplate rating of the service transformer. (f) If a single-phase customer generator facility is to be interconnected on a center tap neutral of a two hundred forty (240) volt service, the addition of the customer generator facility shall not create an imbalance between the two (2) sides of the two hundred forty (240) volt service more than twenty percent (20%) of the nameplate rating of the service transformer. (g) The customer generator facility point of common coupling shall not be on:		
annual peak load as most recently measured at the substation; the aggregate generation nameplate capacity connected to a line section, including the proposed nameplate capacity, shall not exceed ten percent (10%) of the line section annual peak load as most recently measured or estimated based on the most recently measured circuit load at the substation. (d) The aggregate generation nameplate capacity on the distribution circuit to which the customer <u>generator facility</u> will interconnect, including its nameplate capacity, shall not contribute more than ten percent (10%) to the circuit's maximun fault current at the point on which the primary level that is nearest the proposed point of common coupling. (e) If a customer <u>generator facility</u> is to be connected to a single-phase shared secondary, the aggregate generation nameplate capacity connected to the shared secondary, including the proposed nameplate capacity, shall not exceed the lesser of twenty (20) kVA or the nameplate rating of the service transformer. (f) If a single-phase customer <u>generator facility</u> is to be interconnected on a center tap neutral of a two hundred forty (240) volt service, the addition of the customer <u>generator facility</u> shall not create an imbalance between the two (2) sides of the two hundred forty (240) volt service more than twenty percent (20%) of the nameplate rating of the service transformer. (g) The customer <u>generator facility</u> point of common coupling shall not be on: (e) The customer <u>generator facility</u> point of common coupling shall not be on:		Formatted: Strikethrough
section, including the proposed nameplate capacity, shall not exceed ten percent (10%) of the line section annual peak load as most recently measured or estimated based on the most recently measured circuit load at the substation. (d) The aggregate generation nameplate capacity on the distribution circuit to which the customer <u>generator facility</u> will interconnect, including its nameplate capacity, shall not contribute more than ten percent (10%) to the circuit's maximum fault current at the point on which the primary level that is nearest the proposed point of common coupling. (e) If a customer <u>generator facility</u> is to be connected to a single-phase shared secondary, the aggregate generation nameplate capacity connected to the shared secondary, including the proposed nameplate capacity, shall not exceed the lesser of twenty (20) kVA or the nameplate rating of the service transformer. (f) If a single-phase customer <u>generator facility</u> is to be interconnected on a center tap neutral of a two hundred forty (240) volt service, the addition of the customer <u>generator facility</u> shall not create an imbalance between the two (2) sides of the two hundred forty (240) volt service more than twenty percent (20%) of the nameplate rating of the service transformer. (g) The customer <u>generator facility</u> point of common coupling shall not be on: (g) The customer <u>generator facility</u> point of common coupling shall not be on:		
most recently measured or estimated based on the most recently measured circuit load at the substation. (d) The aggregate generation nameplate capacity on the distribution circuit to which the customer generator facility will interconnect, including its nameplate capacity, shall not contribute more than ten percent (10%) to the circuit's maximum fault current at the point on which the primary level that is nearest the proposed point of common coupling. (e) If a customer generator facility is to be connected to a single-phase shared secondary, the aggregate generation nameplate capacity connected to the shared secondary, including the proposed nameplate capacity, shall not exceed the lesser of twenty (20) kVA or the nameplate rating of the service transformer. (f) If a single-phase customer generator facility is to be interconnected on a center tap neutral of a two hundred forty (240) volt service, the addition of the customer generator facility shall not create an imbalance between the two (2) sides of the two hundred forty (240) volt service more than twenty percent (20%) of the nameplate rating of the service transformer. (g) The customer generator facility point of common coupling shall not be on: (g) The customer generator facility point of common coupling shall not be on: (g) The customer generator facility point of common coupling shall not be on:		
 (d) The aggregate generation nameplate capacity on the distribution circuit to which the customer generator facility will interconnect, including its nameplate capacity, shall not contribute more than ten percent (10%) to the circuit's maximum fault current at the point on which the primary level that is nearest the proposed point of common coupling. (e) If a customer generator facility is to be connected to a single-phase shared secondary, the aggregate generation nameplate capacity connected to the shared secondary, including the proposed nameplate capacity, shall not exceed the lesser of twenty (20) kVA or the nameplate rating of the service transformer. (f) If a single-phase customer generator facility is to be interconnected on a center tap neutral of a two hundred forty (240) volt service, the addition of the customer generator facility shall not create an imbalance between the two (2) sides of the Formatted: Strikethrough Formatted: Strikethrough Formatted: Strikethrough 		
will interconnect, including its nameplate capacity, shall not contribute more than ten percent (10%) to the circuit's maximum fault current at the point on which the primary level that is nearest the proposed point of common coupling. (e) If a customer generator facility is to be connected to a single-phase shared secondary, the aggregate generation nameplate capacity connected to the shared secondary, including the proposed nameplate capacity, shall not exceed the lesser of twenty (20) kVA or the nameplate rating of the service transformer. (f) If a single-phase customer-generator facility is to be interconnected on a center tap neutral of a two hundred forty (240) volt service, the addition of the customer-generator-facility shall not create an imbalance between the two (2) sides of the two hundred forty (240) volt service more than twenty percent (20%) of the nameplate rating of the service transformer. (g) The customer-generator facility point of common coupling shall not be on: 		
fault current at the point on which the primary level that is nearest the proposed point of common coupling. (e) If a customer generator facility is to be connected to a single-phase shared secondary, the aggregate generation nameplate capacity connected to the shared secondary, including the proposed nameplate capacity, shall not exceed the lesser of twenty (20) kVA or the nameplate rating of the service transformer. (f) If a single-phase customer-generator facility is to be interconnected on a center tap neutral of a two hundred forty (240) volt service, the addition of the customer-generator facility shall not create an imbalance between the two (2) sides of the two hundred forty (240) volt service more than twenty percent (20%) of the nameplate rating of the service transformer. (g) The customer-generator facility point of common coupling shall not be on: (b) the customer-generator facility point of common coupling shall not be on: (c) the customer-generator facility point of common coupling shall not be on: (c) the customer-generator facility point of common coupling shall not be on: (c) the customer-generator facility point of common coupling shall not be on: (c) the customer-generator facility point of common coupling shall not be on: (c) the customer-generator facility point of common coupling shall not be on: (c) the customer-generator facility point of common coupling shall not be on: (c) the customer-generator facility point of common coupling shall not be on: (c) the customer-generator facility point of common coupling shall not be on: (c) the customer-generator facility point of common coupling shall not be on: (c) the customer-generator facility point of common coupling shall not be on: (c) the customer-generator facility point of common coupling shall not be on: (c) the customer-generator facility point of common coupling shall not be on: (c) the customer-generator facility point of common coupling shall not be on: (c) the customer-generator facility point of common coupling shall not be on: (c)		Formatted: Strikethrough
 (e) If a customer <u>generator</u> facility is to be connected to a single-phase shared secondary, the aggregate generation nameplate capacity connected to the shared secondary, including the proposed nameplate capacity, shall not exceed the lesser of twenty (20) kVA or the nameplate rating of the service transformer. (f) If a single-phase customer <u>generator</u> facility is to be interconnected on a center tap neutral of a two hundred forty (240) volt service, the addition of the customer <u>generator</u> facility shall not create an imbalance between the two (2) sides of the two hundred forty (240) volt service more than twenty percent (20%) of the nameplate rating of the service transformer. (g) The customer <u>generator</u> facility point of common coupling shall not be on: 		
nameplate capacity connected to the shared secondary, including the proposed nameplate capacity, shall not exceed the lesser of twenty (20) kVA or the nameplate rating of the service transformer. (f) If a single-phase customer-generator facility is to be interconnected on a center tap neutral of a two hundred forty (240) volt service, the addition of the customer-generator facility shall not create an imbalance between the two (2) sides of the two hundred forty (240) volt service more than twenty percent (20%) of the nameplate rating of the service transformer. (g) The customer-generator facility point of common coupling shall not be on: (g) The customer-generator facility point of common coupling shall not be on: (g) The customer-generator facility point of common coupling shall not be on:		
nameplate capacity connected to the shared secondary, including the proposed nameplate capacity, shall not exceed the lesser of twenty (20) kVA or the nameplate rating of the service transformer. (240) volt service, the addition of the customer-generator-facility shall not create an imbalance between the two (2) sides of the two hundred forty (240) volt service more than twenty percent (20%) of the nameplate rating of the service transformer. (g) The customer-generator-facility point of common coupling shall not be on: Formatted: Strikethrough Formatted: Strikethrough		Formatted: Strikethrough
(f) If a single-phase customer-generator facility is to be interconnected on a center tap neutral of a two hundred forty (240) volt service, the addition of the customer-generator facility shall not create an imbalance between the two (2) sides of the two hundred forty (240) volt service more than twenty percent (20%) of the nameplate rating of the service transformer. (g) The customer-generator facility point of common coupling shall not be on: Formatted: Strikethrough Formatted: Strikethrough		-
(240) volt service, the addition of the customer <u>generator</u> facility shall not create an imbalance between the two (2) sides of the two hundred forty (240) volt service more than twenty percent (20%) of the nameplate rating of the service transformer. (g) The customer <u>generator</u> facility point of common coupling shall not be on: Formatted: Strikethrough		
 (240) volt service, the addition of the customer-generator facility shall not create an imbalance between the two (2) sides of the two hundred forty (240) volt service more than twenty percent (20%) of the nameplate rating of the service transformer. (g) The customer-generator facility point of common coupling shall not be on: 		Formatted: Strikethrough
(g) The customer-generator facility point of common coupling shall not be on:		
		rormatted: Strikethrough
		Formatted: Strikethrough
(1) a transmission line;	(1) a transmission line:	

(2) a spot network; or(3) an area network.

1

I

1

l

I

1

I

I

(h) The customer-generator facility shall not violate any applicable provisions of IEEE 1547-2018, Standard for		Formatted: Strikethrough
Interconnecting Interconnection and Interoperability of Distributed Energy Resources with Associated Electric Power		Formatted: Strikethrough
Systems Interfaces, as identified by the utility.		Tomatted. Strikethough
(i) The utility shall notify the applicant within ten (10) business days after receiving an application for Level 1		
interconnection review as to whether the application is complete. If the application is incomplete, the notification shall include a		
list detailing the information needed to complete the application.		
(j) Within fifteen (15) business days after the utility notifies the applicant that the application is complete, the utility		
shall notify the applicant that the customer-generator facility: (1) meets all of the criteria in subsections (c) I through (h) that apply to the facility, and the interconnection will be		Formatted: Strikethrough
finally approved upon completion of the process set forth in subsections (k) though (m); or		
(2) has failed to meet one (1) or more of the applicable criteria in subsections (k) mough (h), and the interconnection		
application is denied.		
(k) If approved, the utility shall, within ten (10) business days after sending the notice of approval under subsection		
(j)(1), do the following:		
(1) Notify the applicant if the utility will require inspection of the customer-generator facility for compliance with this		
rule before starting operation of the facility.		Formatted: Strikethrough
(2) Execute and send to the applicant a Level 1 interconnection agreement.		
(1) An applicant that receives an interconnection agreement under subsection (k) shall do the following:		
(1) Execute the agreement.		
(2) Return the agreement to the utility at least ten (10) business days before starting operation of the customer-generator	_	Formatted: Strikethrough
facility.		Formatted: surkethrough
(3) Indicate the anticipated start date for operation of the customer-generator facility.		Formatted: Strikethrough
If the utility requires an inspection of the customer generator facility, the applicant shall not begin operating the facility until		Tomatted. Strikethough
completion of the inspection.		Formatted: Strikethrough
(m) Upon:		
(1) receipt of the executed interconnection agreement; and		
(2) satisfactory completion of any required inspection;		
the utility shall approve the interconnection, conditioned on approval by the electric code officials with jurisdiction over the		
interconnection.		
(n) If an application for Level 1 interconnection review is denied because it does not meet one (1) or more of the		
applicable requirements of this section, an applicant may resubmit the application under Level 2 or Level 3 interconnection		
review procedure as appropriate. (Indiana Utility Regulatory Commission; 170 IAC 4-4.3-6; filed Mar 6, 2006, 9:45 a.m.: 29 IR		
2172; readopted filed Jul 12, 2012, 2:12 p.m.: <u>20120808-IR-170120114RFA</u> ; readopted filed Aug 2, 2013, 2:16 p.m.:		
<u>20130828-IR-170130227RFA</u> ; readopted filed Apr 11, 2019, 9:04 a.m.: <u>20190508-IR-170190136RFA</u>)		
170 IAC 4-4.3-7 Level 2 interconnection review Error! Bookmark not defined.		Field Code Changed
Authority: <u>IC 8-1-1-3</u> ; <u>IC 8-1-2.4</u>		
Affected: <u>IC 8-1-2</u>		
Sec. 7. (a) Each investor-owned electric utility shall adopt a Level 2 interconnection review procedure. The utility shall use the Level 2 review procedure for an application to interconnect a customer-generator facility that:		
(1) has a nameplate capacity of two (2) megawatts or less; and		Formatted: Strikethrough
(2) is certified in accordance with section 5 of this rule.		
(b) For a customer- generator facility described in subsection (a), the utility shall approve interconnection under the		
Level 2 review if all of the applicable requirements in subsections (c) through (o) are met. A utility shall not impose additional		Formatted: Strikethrough
requirements not specifically authorized under this section.		
(c) If a customer generator facility is to be connected to a radial distribution circuit, the aggregate generation nameplate		Formattad Striketbrough
capacity connected to the circuit, including the proposed nameplate capacity, shall not exceed fifteen percent (15%) of the line		Formatted: Strikethrough
section annual peak load as most recently measured or estimated based on the most recently measured circuit load at the		
substation.		
(d) The aggregate generation capacity on the distribution circuit to which the customer-generator facility will		Formatted: Strikethrough
interconnect, including its capacity, shall not contribute more than ten percent (10%) to the circuit's maximum fault current at		- officiated. Strikethough
the point on which the primary level that is nearest the proposed point of common coupling.		

(e) If a customer-generator facility is to be connected to a single-phase shared secondary, the aggregate generation	 Formatted: Strikethrough
capacity connected to the shared secondary, including the proposed capacity, shall not exceed the lesser of twenty (20) kVA or	
the nameplate rating of the service transformer.	
(f) If a single-phase customer-generator facility is to be interconnected on a center tap neutral of a two hundred forty	 Formatted: Strikethrough
(240) volt service, its addition will not create an imbalance between the two (2) sides of the two hundred forty (240) volt service	
more than twenty percent (20%) of the nameplate rating of the service transformer.	
(g) The aggregate generation capacity on the distribution circuit to which the customer generator facility will	 Formatted: Strikethrough
interconnect, including its capacity, shall not cause any:	
(1) distribution protective equipment; or	
(2) customer equipment on the distribution system;	
to exceed ninety percent (90%) of the short circuit interrupting capability of the equipment. In addition, a customer generator	Formatted: Strikethrough
facility shall not be connected to a circuit that already exceeds ninety percent (90%) of the short circuit interrupting capability.	
(h) If there are known or posted transient stability limits to generating units located in the general electrical vicinity of	
the proposed point of common coupling, for example, three (3) or four (4) transmission voltage level busses, the aggregate	
generation capacity, including the proposed facility, connected to the distribution low voltage side of the substation transformer	
feeding the distribution circuit containing the point of common coupling shall not exceed ten (10) megawatts.	
(i) If a customer-generator facility is to be connected to three phase, three (3) wire primary utility distribution lines, a	 Formatted: Strikethrough
three-phase or single-phase generator shall be connected phase to phase.	l'omattea: striketnioùgin
(j) If a customer-generator facility is to be connected to three-phase, four (4) wire primary utility distribution lines, the	 Formatted: Strikethrough
generator shall appear to the primary utility distribution line as an effectively grounded source.	l'omattea: striketnioùgin
(k) The customer-generator facility point of common coupling shall not be on a transmission line.	 Formatted: Strikethrough
(1) If a customer generator facility is to be connected to the load side of spot network protectors, the proposed facility	
shall:	Formatted: Strikethrough
(1) utilize an inverter-based equipment package; and	
(2) together with the aggregated other inverter-based generation, not exceed the smaller of five percent (5%) of a s pot	
network's maximum load or fifty (50) kilowatts.	
(m) If a customer-generator facility is to be connected to any network, the proposed facility must utilize a protective	 Formatted: Strikethrough
scheme that will ensure that its current flow will not affect the network protective devices including reverse power relays or a	Tormatted. Strikethoogh
comparable function. Synchronous customer generator facilities shall not be interconnected to a secondary network.	 Formatted: Strikethrough
(n) If a customer- generator facility that:	Tomatted. Stilkethough
(1) is an induction generator; or	Formatted: Strikethrough
(2) utilizes inverter-based protective functions;	
both of which include reverse power relays functions, the proposed facility, in aggregate with other generation interconnected on	
the load side of the network protective devices, will not exceed the lesser of ten percent (10%) of the minimum load on the	
network or fifty (50) kilowatts.	
(o) The customer-generator facility shall not violate any applicable provisions of IEEE 1547,-2018 Standard for	 Formatted: Strikethrough
Interconnecting Interconnection and Interoperability of Distributed Energy Resources with Associated Electric Power	Tornatted. Strikethough
Systems Interfaces, as identified by the utility.	Formatted: Strikethrough
(p) The utility shall notify the applicant within ten (10) business days after receiving an application for Level 2	Formatted: Font: Bold
interconnection review as to whether the application is complete. If the application is incomplete, the notification shall include a	Tornatted. Font. Bold
list detailing all of the information needed to complete the application.	
(q) Within fifteen (15) business days after the utility notifies the applicant that the application is complete, the investor-	
owned electric utility shall perform an initial review to determine if the applicable requirements of subsections $\frac{(e)(c)}{(e)}$ through (o)	
are met. During the initial review the utility may, at its own expense, conduct any studies or tests it deems necessary to evaluate	
the proposed interconnection. The initial review shall result in one (1) of the following determinations:	
(1) The customer-generator facility meets the applicable requirements in subsections ns (c) through (o). In this case, the	 Formatted: Strikethrough
utility shall:	
(A) notify the applicant that the interconnection will be finally approved upon completion of the process set forth	
in subsections (r) through (t); and	
(B) within ten (10) business days after this notice, provide the applicant with an executable interconnection	
agreement.	
(2) The customer-generator facility has failed to meet one (1) or more of the applicable requirements in subseesections	 Formatted: Strikethrough

(c) through (o); however, the utility has determined that the customer-generator-facility can be interconnected

1

Formatted: Strikethrough

consistent with safety, reliability, and power quality. In this case, the utility shall: (A) notify the applicant that the interconnection will be finally approved upon completion of the process set forth in subsubsections (r) through (t); and (B) within ten (10) business days after this notice, provide the applicant with an executable interconnection agreement. (3) The customer generator facility has failed to meet one (1) or more of the applicable requirements in in subsections Formatted: Strikethrough (c) through (o); however, the initial review indicates that additional review may enable the utility to determine that the customer-generator facility can be interconnected consistent with safety, reliability, and power quality. In such a case, Formatted: Strikethrough the utility shall: (A) offer to perform additional review to determine whether minor modifications to the electrical distribution system would enable the interconnection to be made consistent with safety, reliability, and power quality; (B) provide to the applicant a nonbinding, good faith estimate of the costs of the additional review or the minor modificationson, or both; and (C) undertake the additional review or modifications in accordance with subsection (u). (4) The customer generator facility has failed to meet one (1) or more of the applicable requirements of subsections Formatted: Strikethrough (c) through (o), and the initial review indicates that additional review would not enable the utility to determine that the customer-generator facility can be interconnected consistent with safety, reliability, and power quality. In such a case, Formatted: Strikethrough the utility shall: (A) notify the applicant that the interconnection application has been denied; and (B) provide an explanation of the reason or reasons for the denial, including a list of additional information or modifications, or both, to' the customer-generator's facility that would be required in order to obtain an approval Formatted: Strikethrough under Level 2 interconnection procedures. (r) An applicant that receives an interconnection agreement under subsection (q)(1) or (q)(2) shall do the following: (1) Execute the agreement. (2) Return the agreement to the utility at least ten (10) business days before starting operation of the customer-generator Formatted: Strikethrough facility. (3) Indicate to the utility the anticipated start date for operation of the customer-generator-facility. Formatted: Strikethrough (s) The utility may: (1) require an inspection of a customer-generator facility for compliance with this section before operation; and Formatted: Strikethrough (2) require and arrange for witness of commissioning tests as set forth in IEEE 1547-2018, Standard for Interconnecting Formatted: Strikethrough Interconnection and Interoperability of Distributed Energy Resources with Associated Electric Power Systems Interfaces. Formatted: Font: Bold The utility shall schedule any inspections or tests under this section promptly and within a reasonable time after submittal of the Formatted: Font: Bold application. The applicant shall not begin operating the customer-generator facility until after the inspection and testing is completed. Formatted: Strikethrough (t) For an applicant that receives an interconnection agreement under subsection (q)(1) or (q)(2), approval of interconnected operation of the customer-generator facility shall be conditioned on all of the following: Formatted: Strikethrough (1) The interconnection has been approved by the electrical code official with jurisdiction over the interconnection. (2) Any utility inspection or witnessing of commissioning tests arranged under subsection (s) are successfully completed. (3) The planned start date provided by the applicant under subsection (r) (3) has passed. (u) For an applicant that pays for additional review under subsection (q)(3), within ten (10) business days from the receipt of payment, the utility shall perform any additional review and notify the applicant of the results. If the additional review determines that the customer-generator facility can be interconnected without adversely affecting safety, reliability, and power Formatted: Strikethrough quality upon the completion of utility system modifications, the utility shall provide a cost estimate of the modifications with the results. Within twenty (20) business days after receipt of the cost estimate, the applicant will either: (1) send payment to the utility for the estimated cost; or

(2) notify the utility in writing that it does not wish to proceed with the project.

Upon receipt of payment, the utility shall proceed to schedule and complete the required modifications or new construction. Within five (5) business days after the completion <u>fsie.</u>, <u>off</u> <u>of</u> the modifications or new construction, the utility shall provide the applicant with an executable interconnection agreement and notification that the interconnection will <u>finally</u> be approved upon completion of the process set forth in subsections (r) through (t).

(v) If an application for Level 2 interconnection review is denied because it does not meet one (1) or more of the

Formatted: Strikethrough
Formatted: Strikethrough

applicable requirements in this section, an applicant may resubmit the application under the Level 3 interconnection review procedure as appropriate. (*Indiana Utility Regulatory Commission; 170 IAC 4-4.3-7; filed Mar 6, 2006, 9:45 a.m.: 29 IR 2173; readopted filed Jul 12, 2012, 2:12 p.m.: 20120808-IR-170120114RFA; readopted filed Aug 2, 2013, 2:16 p.m.: 20130828-IR-170130227RFA; readopted filed Apr 11, 2019, 9:04 a.m.: 20190508-IR-170190136RFA*)

170 IAC 4-4.3-8 Level 3 interconnection review

Authority: <u>IC 8-1-1-3</u>; <u>IC 8-1-2.4</u>

Affected: IC 8-1-2

Sec. 8. (a) Each investor-owned electric utility shall adopt a Level 3 interconnection review procedure. The utility shall use the Level 3 review procedure for an application to interconnect a customer-<u>generator</u> facility that:

Formatted: Strikethrough

Formatted: Strikethrough

Formatted: Strikethrough

- (1) is connected to its distribution system; and
- (2) does not meet the requirements of section 6 or 7 of this rule.

(b) The utility shall do the following:

(1) Conduct an initial review of the application.

(2) Offer the applicant the opportunity to meet with utility staff to discuss the application.

(c) The utility shall provide an impact study agreement to the applicant, which shall include a good faith estimate of the cost for an impact study to be performed by the utility.

(d) If the proposed interconnection may affect electric transmission or delivery systems other than those controlled by the utility, operators of these systems may require additional studies to determine the impact of the interconnection on these systems. The utility shall coordinate the studies of other operators, but shall not be responsible for their timing. The applicant shall be responsible for the costs of any such additional studies required by other affected system operators. The studies shall be conducted only after the applicant has provided written authorization.

(e) After the applicant has executed the impact study agreement and has paid the utility the amount of the good faith estimate required under subsection (c), the utility shall conduct the impact study and notify the applicant of the results as follows:

(1) If the impact study indicates that only insubstantial modifications to the utility's electric distribution system are necessary to accommodate the proposed interconnection, the utility shall send the applicant an interconnection agreement that details the following:

(A) The scope of the necessary modifications.

(B) An estimate of their cost.

(2) If the impact study indicates that substantial modifications to the utility's electric distribution system are necessary to accommodate the proposed interconnection, the utility shall do the following:

(A) Provide a good faith estimate of the cost of the modifications.

(B) Offer to conduct a facilities study at the applicant's expense, which will identify the types and cost of equipment needed to safely interconnect the applicant's customer generator facility.

(f) If the applicant requests a facilities study under subsection (e)(2), the utility shall provide a facilities study agreement. The facilities study agreement shall describe the work to be undertaken in the facilities study and shall include a good faith estimate of the cost to the applicant for completion of the study. Upon execution by the applicant of the facilities study agreement, the utility shall conduct a facilities study, which shall identify the following:

(1) The facilities necessary to safely interconnect the customer-generator-facility with the utility's electric distribution Formatted: Strikethrough system.

(2) The cost of those facilities.

(3) The time required to build and install those facilities.

(g) Upon completion of the facilities study, the utility shall provide the applicant with the results of the study and an executable interconnection agreement. The agreement shall list the following:

(1) The conditions and facilities necessary to safely interconnect the customer-generator facility with the utility's

electric distribution system.

I

(2) The cost of those facilities.

(3) The time required to build and install those facilities.

(h) If the applicant wishes to interconnect, the applicant shall do the following:

(1) Execute the interconnection agreement.

(2) Provide a deposit of the cost of the facilities identified in the facilities study.

(3) Complete installation of the customer generator facility.	Formatted: Strikethrough
(4) Agree to pay the utility the amount required for the facilities needed to interconnect as identified in the facilities	
study.	
(i) Within fifteen (15) business days after notice from the applicant that the customer-generator-facility has been	Formatted: Strikethrough
installed, the utility shall do the following:	
(1) Inspect the customer generator facility.	Formatted: Strikethrough
(2) Arrange to witness any commissioning tests required under IEEE 1547-2018, Standard for Interconnecting	Formatted: Strikethrough
Interconnection and Interoperability of Distributed Energy Resources with Associated Electric Power Systems Interfaces.	
The utility and the applicant shall select a date by mutual agreement for the utility to witness commissioning tests.	
(j) Provided the customer-generator facility passes any required commissioning tests satisfactorily, the utility shall	
notify the applicant in writing, within five (5) business days after the tests, of one (1) of the following:	Formatted: Strikethrough
(1) The interconnection is approved and the customer-generator facility may begin operation.	
(2) The facilities study identified necessary construction that has not been completed, the date upon which the	Formatted: Strikethrough
construction will be completed, and the date when the customer-generator facility may begin operation.	En unsette di Ctaillathan unde
(k) If the commissioning tests are not satisfactory, the customer generator shall repair or replace the unsatisfactory	Formatted: Strikethrough
equipment and reschedule a commissioning test under subsection (i). (<i>Indiana Utility Regulatory Commission; 170 IAC 4-4.3-8;</i>	Formatted: Strikethrough
filed Mar 6, 2006, 9:45 a.m.: 29 IR 2175; readopted filed Jul 12, 2012, 2:12 p.m.: 20120808-IR-170120114RFA; readopted	
filed Aug 2, 2013, 2:16 p.m.: 20130828-IR-170130227RFA; readopted filed Apr 11, 2019, 9:04 a.m.: 20190508-IR-	
170190136RFA)	
170 IAC 4-4.3-9 Requirements for ongoing operation of customer-generator facilities	Formatted: Strikethrough
Authority: <u>IC 8-1-1-3</u> ; <u>IC 8-1-2.4</u>	Tomated. Strikethough
Authority: <u>IC 8-1-1-3; IC 8-1-2.4</u> Affected: <u>IC 8-1-2</u>	Tomateu. Sancanougn
Affected: IC 8-1-2	
Affected: IC 8-1-2 Sec. 9. (a) The investor-owned electric utility may perform reasonable on-site inspections to verify the proper	
Affected: <u>IC 8-1-2</u> Sec. 9. (a) The investor-owned electric utility may perform reasonable on-site inspections to verify the proper installation and continuing safe operation of the customer generator facility and interconnection facilities:	Formatted: Strikethrough
Affected: IC 8-1-2 Sec. 9. (a) The investor-owned electric utility may perform reasonable on-site inspections to verify the proper installation and continuing safe operation of the customer generator facility and interconnection facilities: (1) at reasonable times; and	
Affected: IC 8-1-2 Sec. 9. (a) The investor-owned electric utility may perform reasonable on-site inspections to verify the proper installation and continuing safe operation of the customer generator facility and interconnection facilities: (1) at reasonable times; and (2) upon reasonable advance notice to the customer.	
Affected: IC 8-1-2 Sec. 9. (a) The investor-owned electric utility may perform reasonable on-site inspections to verify the proper installation and continuing safe operation of the customer-generator-facility and interconnection facilities: (1) at reasonable times; and (2) upon reasonable advance notice to the customer. The cost of the inspection or inspections shall be at the utility's expense; however, the utility shall not be responsible for any	
Affected: IC 8-1-2 Sec. 9. (a) The investor-owned electric utility may perform reasonable on-site inspections to verify the proper installation and continuing safe operation of the customer generator facility and interconnection facilities: (1) at reasonable times; and (2) upon reasonable advance notice to the customer. The cost of the inspection or inspections shall be at the utility's expense; however, the utility shall not be responsible for any other cost the customer may incur as a result of the inspection or inspections.	Formatted: Strikethrough
Affected: <u>IC 8-1-2</u> Sec. 9. (a) The investor-owned electric utility may perform reasonable on-site inspections to verify the proper installation and continuing safe operation of the customer <u>generator</u> facility and interconnection facilities: (1) at reasonable times; and (2) upon reasonable advance notice to the customer. The cost of the inspection or inspections shall be at the utility's expense; however, the utility shall not be responsible for any other cost the customer may incur as a result of the inspection or inspections. (b) The customer shall install, operate, and maintain the customer <u>generator</u> facility in accordance with the	
Affected: <u>IC 8-1-2</u> Sec. 9. (a) The investor-owned electric utility may perform reasonable on-site inspections to verify the proper installation and continuing safe operation of the customer <u>generator</u> facility and interconnection facilities: (1) at reasonable times; and (2) upon reasonable advance notice to the customer. The cost of the inspection or inspections shall be at the utility's expense; however, the utility shall not be responsible for any other cost the customer may incur as a result of the inspection or inspections. (b) The customer shall install, operate, and maintain the customer <u>generator</u> facility in accordance with the manufacturer's suggested practices for safe, efficient, and reliable operation in parallel to the utility's system.	Formatted: Strikethrough Formatted: Strikethrough
Affected: IC 8-1-2 Sec. 9. (a) The investor-owned electric utility may perform reasonable on-site inspections to verify the proper installation and continuing safe operation of the customer <u>generator</u> facility and interconnection facilities: (1) at reasonable times; and (2) upon reasonable advance notice to the customer. The cost of the inspections shall be at the utility's expense; however, the utility shall not be responsible for any other cost the customer may incur as a result of the inspection or inspections. (b) The customer shall install, operate, and maintain the customer <u>generator</u> facility in accordance with the manufacturer's suggested practices for safe, efficient, and reliable operation in parallel to the utility's system. (c) The utility may isolate any customer <u>generator</u> facility if the utility believes continued interconnection with the	Formatted: Strikethrough
Affected: IC 8-1-2 Sec. 9. (a) The investor-owned electric utility may perform reasonable on-site inspections to verify the proper installation and continuing safe operation of the customer generator facility and interconnection facilities: (1) at reasonable times; and (2) upon reasonable advance notice to the customer. The cost of the inspection or inspections shall be at the utility's expense; however, the utility shall not be responsible for any other cost the customer may incur as a result of the inspection or inspections. (b) The customer shall install, operate, and maintain the customer generator facility in accordance with the manufacturer's suggested practices for safe, efficient, and reliable operation in parallel to the utility's system. (c) The utility may isolate any customer generator facility if the utility believes continued interconnection with the customer generator facility creates or contributes to a system emergency. System emergencies causing discontinuance of	Formatted: Strikethrough Formatted: Strikethrough Formatted: Strikethrough
Affected: IC 8-1-2 Sec. 9. (a) The investor-owned electric utility may perform reasonable on-site inspections to verify the proper installation and continuing safe operation of the customer generator facility and interconnection facilities: (1) at reasonable times; and (2) upon reasonable advance notice to the customer. The cost of the inspection or inspections shall be at the utility's expense; however, the utility shall not be responsible for any other cost the customer may incur as a result of the inspection or inspections. (b) The customer shall install, operate, and maintain the customer generator facility in accordance with the manufacturer's suggested practices for safe, efficient, and reliable operation in parallel to the utility's system. (c) The utility may isolate any customer generator facility if the utility believes continued interconnection with the customer generator facility creates or contributes to a system emergency. System emergencies causing discontinuance of interconnection shall be subject to verification by the commission upon a complaint made by the customer in accordance with	Formatted: Strikethrough Formatted: Strikethrough
Affected: IC 8-1-2 Sec. 9. (a) The investor-owned electric utility may perform reasonable on-site inspections to verify the proper installation and continuing safe operation of the customer generator facility and interconnection facilities: (1) at reasonable times; and (2) upon reasonable advance notice to the customer. The cost of the inspection or inspections shall be at the utility's expense; however, the utility shall not be responsible for any other cost the customer may incur as a result of the inspection or inspections. (b) The customer shall install, operate, and maintain the customer generator facility in accordance with the manufacturer's suggested practices for safe, efficient, and reliable operation in parallel to the utility's system. (c) The utility may isolate any customer generator facility if the utility believes continued interconnection with the customer generator facility creates or contributes to a system emergency. System emergencies causing discontinuance of interconnection shall be subject to verification by the commission upon a complaint made by the customer in accordance with the commission's consumer complaint rules.	Formatted: Strikethrough Formatted: Strikethrough Formatted: Strikethrough Formatted: Strikethrough
Affected: IC 8-1-2 Sec. 9. (a) The investor-owned electric utility may perform reasonable on-site inspections to verify the proper installation and continuing safe operation of the customer generator facility and interconnection facilities: (1) at reasonable times; and (2) upon reasonable advance notice to the customer. The cost of the inspection or inspections shall be at the utility's expense; however, the utility shall not be responsible for any other cost the customer may incur as a result of the inspection or inspections. (b) The customer shall install, operate, and maintain the customer generator facility in accordance with the manufacturer's suggested practices for safe, efficient, and reliable operation in parallel to the utility's system. (c) The utility may isolate any customer generator facility if the utility believes continued interconnection with the customer generator facility creates or contributes to a system emergency. System emergencies causing discontinuance of interconnection shall be subject to verification by the commission upon a complaint made by the customer in accordance with the cummission's consumer complaint rules. (d) If the utility finds that the customer generator's facility is not in compliance with the requirements of this rule, and	Formatted: Strikethrough Formatted: Strikethrough Formatted: Strikethrough
Affected: IC 8-1-2 Sec. 9. (a) The investor-owned electric utility may perform reasonable on-site inspections to verify the proper installation and continuing safe operation of the customer generator facility and interconnection facilities: (1) at reasonable times; and (2) upon reasonable advance notice to the customer. The cost of the inspection or inspections shall be at the utility's expense; however, the utility shall not be responsible for any other cost the customer may incur as a result of the inspection or inspections. (b) The customer shall install, operate, and maintain the customer generator facility in accordance with the manufacturer's suggested practices for safe, efficient, and reliable operation in parallel to the utility's system. (c) The utility may isolate any customer generator facility if the utility believes continued interconnection with the customer generator facility creates or contributes to a system emergency. System emergencies causing discontinuance of interconnection shall be subject to verification by the commission upon a complaint made by the customer in accordance with the commission's consumer complaint rules. (d) If the utility finds that the customer generator's facility is not in compliance with the requirements of this rule, and the noncompliance adversely affects the safety, reliability, or power quality of the electric distribution system, the utility may	Formatted: Strikethrough Formatted: Strikethrough Formatted: Strikethrough Formatted: Strikethrough Formatted: Strikethrough
Affected: IC 8-1-2 Sec. 9. (a) The investor-owned electric utility may perform reasonable on-site inspections to verify the proper installation and continuing safe operation of the customer generator facility and interconnection facilities: (1) at reasonable times; and (2) upon reasonable advance notice to the customer. The cost of the inspection or inspections shall be at the utility's expense; however, the utility shall not be responsible for any other cost the customer may incur as a result of the inspection or inspections. (b) The customer shall install, operate, and maintain the customer generator facility in accordance with the manufacturer's suggested practices for safe, efficient, and reliable operation in parallel to the utility's system. (c) The utility may isolate any customer generator facility if the utility believes continued interconnection with the customer generator facility creates or contributes to a system emergency. System emergencies causing discontinuance of interconnection shall be subject to verification by the commission upon a complaint made by the customer in accordance with the commission's consumer complaint rules. (d) If the utility finds that the customer generator's facility is not in compliance with the requirements of this rule, and the noncompliance adversely affects the safety, reliability, or power quality of the electric distribution system, the utility may require the customer generator facility until compliance is achieved. (Indiana Utility	Formatted: Strikethrough Formatted: Strikethrough Formatted: Strikethrough Formatted: Strikethrough
Affected: IC 8-1-2 Sec. 9. (a) The investor-owned electric utility may perform reasonable on-site inspections to verify the proper installation and continuing safe operation of the customer generator facility and interconnection facilities: (1) at reasonable times; and (2) upon reasonable advance notice to the customer. The cost of the inspection or inspections shall be at the utility's expense; however, the utility shall not be responsible for any other cost the customer may incur as a result of the inspection or inspections. (b) The customer shall install, operate, and maintain the customer generator facility in accordance with the manufacturer's suggested practices for safe, efficient, and reliable operation in parallel to the utility's system. (c) The utility may isolate any customer generator facility if the utility believes continued interconnection with the customer generator facility creates or contributes to a system emergency. System emergencies causing discontinuance of interconnection shall be subject to verification by the commission upon a complaint made by the customer in accordance with the commission's consumer complaint rules. (d) If the utility finds that the customer generator's facility is not in compliance with the requirements of this rule, and the noncompliance adversely affects the safety, reliability, or power quality of the electric distribution system, the utility may require the customer generator facility until compliance is achieved. (Indiana Utility Regulatory Commission; 170 IAC 4-4.3-9; filed Mar 6, 2006, 9:45 a.m.: 29 IR 2176; readopted filed Jul 12, 2012, 2:12 p.m.:	Formatted: Strikethrough Formatted: Strikethrough Formatted: Strikethrough Formatted: Strikethrough Formatted: Strikethrough
Affected: IC 8-1-2 Sec. 9. (a) The investor-owned electric utility may perform reasonable on-site inspections to verify the proper installation and continuing safe operation of the customer generator facility and interconnection facilities: (1) at reasonable times; and (2) upon reasonable advance notice to the customer. The cost of the inspection or inspections shall be at the utility's expense; however, the utility shall not be responsible for any other cost the customer may incur as a result of the inspection or inspections. (b) The customer may incur as a result of the inspection or inspections. (b) The customer shall install, operate, and maintain the customer generator facility in accordance with the manufacturer's suggested practices for safe, efficient, and reliable operation in parallel to the utility's system. (c) The utility may isolate any customer generator facility if the utility believes continued interconnection with the customer generator facility creates or contributes to a system emergency. System emergencies causing discontinuance of interconnection shall be subject to verification by the commission upon a complaint made by the customer in accordance with the commission's consumer complaint rules. (d) If the utility finds that the customer generator's facility is not in compliance with the requirements of this rule, and the noncompliance adversely affects the safety, reliability, or power quality of the electric distribution system, the utility may require the customer generator facility until compliance is achieved. (<i>Indiana Utility</i>	Formatted: Strikethrough Formatted: Strikethrough
Affected: IC 8-1-2 Sec. 9. (a) The investor-owned electric utility may perform reasonable on-site inspections to verify the proper installation and continuing safe operation of the customer generator facility and interconnection facilities: (1) at reasonable times; and (2) upon reasonable advance notice to the customer. The cost of the inspection or inspections shall be at the utility's expense; however, the utility shall not be responsible for any other cost the customer may incur as a result of the inspection or inspections. (b) The customer shall install, operate, and maintain the customer generator facility in accordance with the manufacturer's suggested practices for safe, efficient, and reliable operation in parallel to the utility's system. (c) The utility may isolate any customer generator facility if the utility believes continued interconnection with the customer generator facility creates or contributes to a system emergency. System emergencies causing discontinuance of interconnection shall be subject to verification by the commission upon a complaint made by the customer in accordance with the commission's consumer complaint rules. (d) If the utility finds that the customer generator's facility is not in compliance with the requirements of this rule, and the noncompliance adversely affects the safety, reliability, or power quality of the electric distribution system, the utility may require the customer generator to disconnect the customer generator facility until compliance is achieved. (Indiana Utility Regulatory Commission; 170 IAC 4-4.3-9; filed Mar 6, 2006, 9:45 a.m.: 29 IR 2176; readopted filed Jul 12, 2012, 2:12 p.m.: 20120808-IR-170120114RFA; readopted filed Aug 2, 2013, 2:16 p.m.: 20130828-IR-170130227RFA; readopted filed Apr 11, <td>Formatted: Strikethrough Formatted: Strikethrough</td>	Formatted: Strikethrough Formatted: Strikethrough
Affected: IC 8-1-2 Sec. 9. (a) The investor-owned electric utility may perform reasonable on-site inspections to verify the proper installation and continuing safe operation of the customer generator facility and interconnection facilities: (1) at reasonable times; and (2) upon reasonable advance notice to the customer. The cost of the inspection or inspections shall be at the utility's expense; however, the utility shall not be responsible for any other cost the customer may incur as a result of the inspection or inspections. (b) The customer shall install, operate, and maintain the customer generator facility in accordance with the manufacturer's suggested practices for safe, efficient, and reliable operation in parallel to the utility's system. (c) The utility may isolate any customer generator facility if the utility believes continued interconnection with the customer generator facility creates or contributes to a system emergency. System emergencies causing discontinuance of interconnection shall be subject to verification by the commission upon a complaint made by the customer in accordance with the commission's consumer complaint rules. (d) If the utility finds that the customer generator's facility is not in compliance with the requirements of this rule, and the noncompliance adversely affects the safety, reliability, or power quality of the electric distribution system, the utility may require the customer generator to disconnect the customer generator facility until compliance is achieved. (Indiana Utility Regulatory Commission; 170 IAC 4-4.3-9; filed Mar 6, 2006, 9:45 a.m.: 29 IR 2176; readopted filed Jul 12, 2012, 2:12 p.m.: 20120808-IR-170120114RFA; readopted filed Aug 2, 2013, 2:16 p.m.: 20130828-IR-170130227RFA; readopted filed Apr 11, <td>Formatted: Strikethrough Formatted: Strikethrough</td>	Formatted: Strikethrough Formatted: Strikethrough
Affected: IC 8-1-2 Sec. 9. (a) The investor-owned electric utility may perform reasonable on-site inspections to verify the proper installation and continuing safe operation of the customer generator facility and interconnection facilities: (1) at reasonable times; and (2) upon reasonable advance notice to the customer. The cost of the inspection or inspections shall be at the utility's expense; however, the utility shall not be responsible for any other cost the customer may incur as a result of the inspection or inspections. (b) The customer shall install, operate, and maintain the customer generator facility in accordance with the manufacturer's suggested practices for safe, efficient, and reliable operation in parallel to the utility's system. (c) The utility may isolate any customer generator facility if the utility believes continued interconnection with the customer generator facility creates or contributes to a system emergency. System emergencies causing discontinuance of interconnection shall be subject to verification by the commission upon a complaint made by the customer in accordance with the commission's consumer complaint rules. (d) If the utility finds that the customer generator's facility is not in compliance with the requirements of this rule, and the noncompliance adversely affects the safety, reliability, or power quality of the electric distribution system, the utility may require the customer generator facility until compliance is achieved. (Indiana Utility Regulatory Commission; 170 IAC 4-4.3-9; filed Mar 6, 2006, 9:45 a.m.: 29 IR 2176; readopted filed Jul 12, 2012, 2:12 p.m.: 20120808-IR-170120114RFA; readopted filed Aug 2, 2013, 2:16 p.m.: 20130828-IR-170130227RFA; readopted filed Apr 11, 2019, 9:04 a.m.: 20190508-IR-1701901	Formatted: Strikethrough Formatted: Strikethrough

Affected: IC 8-1-2-33; IC 8-1-2-34

Sec. 10. (a) The liability insurance and indemnification requirements of a customer-generator facility that is also a net (b) The liability insurance and indemnification requirements of a customer-generator facility that is not also a net (b) The liability insurance and indemnification requirements of a customer-generator facility that is not also a net (b) The liability insurance and indemnification requirements of a customer-generator facility that is not also a net (b) The liability insurance and indemnification requirements of a customer-generator facility that is not also a net (b) The liability insurance and indemnification requirements of a customer-generator facility that is not also a net (b) The liability insurance and indemnification requirements of a customer-generator facility that is not also a net (b) The liability insurance and indemnification requirements of a customer-generator facility that is not also a net (b) The liability insurance and indemnification requirements of a customer-generator facility that is not also a net (b) The liability insurance and indemnification requirements of a customer-generator facility that is not also a net (b) The liability insurance and indemnification requirements of a customer-generator facility that is not also a net (b) The liability insurance and indemnification requirements of a customer-generator facility that is not also a net (b) The liability insurance and indemnification requirements of a customer-generator facility that is not also a net (b) The liability insurance and indemnification requirements of a customer-generator facility and the liability insurance and indemnification requirements of a customer-generator facility that is not also a net (b) The liability insurance and indemnification requirements of a customer-generator facility and the liability insurance and the liability i

(1) Insurance provisions shall require a party to obtain only reasonable amounts of insurance against risks for which

there is a reasonable likelihood of occurrence.

(2) The utility and the customer shall indemnify and hold each other harmless from and against all claims, liability, damages, and expenses, including attorney's fees, based on any injury to any person, including loss of life or damage to any property, including loss of use thereof, arising out of, resulting from, or connected with, or that may be alleged to have arisen out of, resulted from, or connected with an act or omission by the other party or its:

(A) employees;

(B) agents:

(C) representatives;

(D) successors; or

(E) assigns;

in the construction, ownership, operation, or maintenance of the party's facilities. (Indiana Utility Regulatory Commission; 170 IAC 4-4.3-10; filed Mar 6, 2006, 9:45 a.m.: 29 IR 2177; readopted filed Jul 12, 2012, 2:12 p.m.: 20120808-IR-170120114RFA; readopted filed Aug 2, 2013, 2:16 p.m.: 20130828-IR-170130227RFA; readopted filed Apr 11, 2019, 9:04 a.m.: 20190508-IR-170190136RFA)

170 IAC 4-4.3-11 Tariff and reporting requirements

Authority: IC 8-1-1-3; IC 8-1-2.4 Affected: IC 8-1-2

Sec. 11. (a) Within sixty (60) days of the effective date of this rule, all investor-owned electric utilities shall submit for approval via the commission's thirty (30) day filing process generic interconnection application and interconnection agreement forms for each of the three (3) levels of review.

(b) To assist the commission in monitoring the effectiveness of this rule over time, each investor-owned utility shall file a report with the commission's electricity division before March 2 of each year following the effective date of this rule. The report shall contain the number, size, and type of the following:

(1) Customer-generator facilities detailed in all applications received during the pervious [sic.] previous calendar year and the resolution, for example, granted, denied, withdrawn, of the applications. The report shall include the following: (A) The application procedure (Level 1, 2, or 3) for all applications.

(B) The reason or reasons for any denied application or applications.

(2) The number, size, and type of customer-generator facilities interconnected, pursuant to Rule 4.3 as of December 31 of the previous calendar year.

(Indiana Utility Regulatory Commission; 170 IAC 4-4.3-11; filed Mar 6, 2006, 9:45 a.m.: 29 IR 2177; readopted filed Jul 12, 2012, 2:12 p.m.: 20120808-IR-170120114RFA; readopted filed Aug 2, 2013, 2:16 p.m.: 20130828-IR-170130227RFA; readopted filed Apr 11, 2019, 9:04 a.m.: 20190508-IR-170190136RFA)

170 IAC 4-4.3-12 Customer complaints

I

I

Authority: IC 8-1-1-3; IC 8-1-2.4 Affected: IC 8-1-2-34.5

Sec. 12. In the event an investor-owned electric utility and an eligible customer are unable to agree on matters relating to customer generator facility interconnection, either party may raise a customer complaint to the commission in accordance with the commission's consumer complaint rules. (Indiana Utility Regulatory Commission; 170 IAC 4-4.3-12; filed Mar 6, 2006, 9:45 a.m.: 29 IR 2177; readopted filed Jul 12, 2012, 2:12 p.m.: 20120808-IR-170120114RFA; readopted filed Aug 2, 2013, 2:16 p.m.: 20130828-IR-170130227RFA; readopted filed Apr 11, 2019, 9:04 a.m.: 20190508-IR-170190136RFA)

Formatted: Strikethrough

Formatted: Strikethrough

Formatted: Strikethrough

Formatted: Strikethrough